

# Utilization of Different Wireless Technologies' RSSI for Indoor Environment Classification Using Support Vector Machine

Zoren P. Mabunga  
*College of Engineering  
Southern Luzon State University  
Quezon, Philippines  
zmabunga@slsu.edu.ph*

Jennifer C. dela Cruz  
*School of EECE  
Mapua University  
Manila, Philippines  
jcdelacruz@mapua.edu.ph*

Angelica C. Samortin  
*School of Graduate Studies  
Mapua University  
Manila, Philippines  
acsamortin@mymail.mapua.edu.ph*

Renato R. Maaliw III  
*College of Engineering  
Southern Luzon State University  
Lucban, Quezon, Philippines  
rmaaliw@slsu.edu.ph*

**Abstract**—This paper presents the development of three indoor environment classifier model using support vector machine algorithm with Gaussian Kernel for three different wireless technology. The dataset that was used in this paper contained RSSI from three nodes for each wireless technology. Three different type of indoor environment was considered in this paper namely, small room with low interference, small room with high interference and large room with medium interference. Based on the results of the validation and testing for the three models, an overall accuracy of 57.1% was obtained for the classifier model using the RSSI of Zigbee technology while 84.8% was obtained for the model using the RSSI of BLE and 86.7% for the model using the RSSI of Wi-Fi technology. This corresponds to a conclusion that the model based on the RSSI of Wi-Fi technology is the best classifier model among the three for indoor environment classification. This paper can be used to further increase the accuracy of indoor localization using RSSI.

**Keywords**—support vector machine, Bluetooth, Wi-Fi, RSSI, Zigbee, localization

## I. INTRODUCTION

At present, wireless technology has become an essential part of our daily life. Different wireless technologies play a key role in today's communications, and it will become more important in the coming years due to its continuous development. Some of these wireless technologies are the 802.15.4/ZigBee, Bluetooth and Wi-Fi which can be used in networks with decentralized and centralized management [1]. These technologies can be used for solving various engineering task such as in building management, logistics, health care, entertainment, security, transportation and in industrial applications. One way to determine the performance of a certain wireless technology is by identifying its Received Signal Strength Indicator (RSSI).

RSSI provides the measurement of the power received by a certain receiving device. RSSI allows users to determine the quality of wireless communication system they are using.

Several studies were done over the past years in relations to these different wireless technologies' RSSI. In [2], a weighted trilateral localization method based on RSSI ranging for mine underground was proposed. In this study, a hybrid filtering algorithm was used that reduced the positioning error and improve the personnel positioning accuracy underground [2]. An investigation on the effects of RSSI in energy consumption was done in [3]. In [3], they used Monte-Carlo simulation to demonstrate the effectiveness of their proposed algorithm for energy saving using RSSI. Another localization application based on RSSI was developed in [4]. In their study, Extreme Ensemble Machine Learning and Principal Component Analysis (PCA) was used for floor localization of tall buildings. PCA was used in their study to reduce the dimensions of the training set while the ensemble ELM was used for the classification learning and to obtain the final classification function. Other indoor localization based on several wireless technologies' RSSI were also presented in [5]–[9].

The RSSI of different wireless technologies have been used mostly for indoor localization and range estimation. Using RSSI for indoor localization provides the advantages of simple and low-cost implementation. However, RSSI suffers from multiple interference mainly due to the dynamic indoor environment which results to inaccurate indoor localization [10]. The type of indoor environments was not considered in the previous studies which greatly affects the localization accuracy. It is therefore important to first identify the type of indoor environment before estimating the range and location of a person or object indoor. Several indoor environment classifier using machine

learning and ultrasonic sensors were already done by several researchers over the past years such as the paper in [11]–[13]. But their model focuses on a single wireless technology. The comparison of various wireless technologies RSSI for indoor environment classification were not yet done based on the available literature.

This paper aims to develop an accurate model that can classify indoor environment using RSSI of different wireless technologies. Specifically, the researchers aim: 1) to obtain a clean data from the raw dataset available in the literature; 2) to develop an indoor environment classification model using support vector machine algorithm for different wireless technologies; 2) to evaluate the models and select the best wireless technology for indoor environment classification.

The dataset that was used in this paper came from [14]. This dataset is composed of RSSI readings gathered from three different type of environment based on their interference level. The different scenarios/environment that was considered were: 1) a small meeting room with low interference; 2) a small meeting room with high interference; 3) large room with average interference. Three different type of wireless technology was utilized in gathering the RSSI dataset namely Wi-Fi (2.4 GHz band), Bluetooth Low Energy (BLE) and Zigbee. The training and testing of the developed model will be done using Matlab machine learning tools.

## II. RELATED LITERATURE

### A. Indoor Environment Classification

Indoor environment classification had been the focused of much research over the past years. In [15], a machine learning based indoor environment classification was developed using RF signatures. In their paper, a combination of RSS and channel transfer function (CTF) were used to classify indoor environment by utilizing different machine learning algorithms. Their developed model was able to achieve an accuracy of 83% in classifying the type of surrounding in an indoor environment setting. Another study was presented in [13] using a single ultrasonic sensor in classifying four different type of indoor environment. They use traditional statistical methods in classifying the indoor environment by utilizing the information from the received echo of the ultrasonic sensor. Lastly, in [11] classification of indoor environment was done by using UWB signals. Their paper proposed a novel feature extraction method based on mixed graph similarity. These features were then forwarded into a classifier model based on machine learning algorithm.

### B. Zigbee (IEEE 802.15.4)

Zigbee is typically use small, low-cost and low power radios for high-level communication. The operation of Zigbee is limited up to 10 meters of distance between the transmitter and receiver. ZigBee provides self-organized, multi-hop, and reliable mesh networking with long battery lifetime [16]. Several researches had been done over the years by utilizing Zigbee in different applications such as in [17]. In [17], a Zigbee transmitter was designed using Verilog for IoT applications. In [18], Zigbee technology was used for a

that utilizing Zigbee technology due to its low power consumption and low cost.

### C. Bluetooth Low Energy (BLE)

BLE is a modified version of the traditional Bluetooth, it is also known as Bluetooth 4.0. BLE main difference with the traditional Bluetooth technology is its low power consumption which makes it suitable wireless technology for wearable devices and IoT systems. BLE also operates in the 2.4 GHz band just like Zigbee and Wi-Fi. The major drawback of BLE is that it can't handle large amount of data for its transmission.

### D. Wi-Fi (IEEE 802.11n 2.4 GHz Band)

Wi-Fi is currently the most popular wireless technology mainly due to its faster data rate and farther range of coverage. Wi-Fi enables multiple users to connect to the internet at high speed through access points or in ad hoc mode. Several applications had been developed over the past years by utilizing Wi-Fi technology such as [19]–[21]. In [19], a Brute Force algorithm was used together with Wi-Fi signal quality to estimate the best placement of AP in an indoor environment. And in [20], a Wi-Fi ID system was developed that aims to identify persons within a certain location. While in [21], Wi-Fi was used in the transmission of data from sensors nodes to the cloud for their IoT application in sanitary landfills. These data were then used in the development of a model that detects groundwater contamination.

### E. Support Vector Machine

Support Vector Machine (SVM) is a very popular supervised machine learning algorithm that is being used for various classification and regression problems. SVM is a powerful way of solving complex non-linear functions. In each feature space, SVM learns by constructing a hyperplane that will separate training data according to their class labels. The hyperplane is obtained by several training iterations by using support vectors which intend to maximize the margin on each side of the plane. If there are instances that data are not linearly separable by a hyperplane, the data can be converted into a higher dimension of feature space where the dataset can be separated linearly. This process is accomplished by using kernel with SVM.

SVM linear classifier is given by equation 1.

$$f(x) = w^T x + b \quad (1)$$

Equation 1 is formulated as finding the solution for an optimization problem over  $w$  using equation 2.

$$\min_{w \in \mathbb{R}^d} \|w\|^2 + C \sum_i^N \max(0, 1 - y_i f(x_i)) \quad (2)$$

This quadratics optimization problem is also called as primal problem. However, SVM can also be formulated to obtain a linear classifier using equation 3 by solving an optimization problem over  $\alpha_i$ .

$$f(x) = \sum_i^N \alpha_i y_i (x_i^T x) + b \quad (3)$$

This is commonly known as dual problem which offers advantages compare with primal problem especially for non-linear datasets in which we can utilize different kernel

functions such as gaussian kernel, Laplace RBF kernel, polynomial kernel and Gaussian Radial Basis Function.

### III. METHODOLOGY

#### A. Dataset

The dataset is consisting of RSSI values from three transmitter nodes for each type of wireless technology namely Zigbee, BLE and Wi-Fi. These RSSI datasets were gathered from three different type of indoor environments. The datasets were collected in three rooms with different interference level and interference sizes. During the data gathering, Sadowski et al, used Gimbal Series 10 Beacons, Raspberry Pi 3 and Xbees together with Arduino Uno microcontroller [14].

#### B. Data Pre-Processing

The raw dataset from [14], was pre-processed by manual elimination of incomplete data. After the elimination of incomplete data, the researcher was able to obtain a total of 106 cleaned datasets. These data undergo data normalization as part of the data preparation stage. Thru data normalization, the dataset was able to have a common scale without altering the difference in span of values by having a value of 0 to 1. The normalization was done by using equation 1, wherein  $z_{\text{new}}$  is the normalized value,  $z$  is the actual value,  $z_{\min}$  is the minimum value among the parameter and  $z_{\max}$  is the maximum value of that parameter.

$$z_{\text{new}} = \frac{z - z_{\min}}{z_{\max} - z_{\min}} \quad (4)$$

#### C. Development of the Classifier Model

Three classifier model were developed using the machine learning app of Matlab software. The three model corresponds to the three different wireless technologies that were used in the determination of RSSI at different indoor environment type. The dataset was split into 70% for training and 30% as test data. These partition had been a common data splitting ration in many machine learning research papers. A study in [22], compare the performance of a developed models for various data partitioning ratio which results into a best performance for the 70/30 training/testing ratio. The 30% test data were used for the testing and validation of each classifier model.

Support vector machine algorithm will be used for the training of the classifier model. This algorithm was chosen due to its performance for data with non-linear relationship such as the relationship between the RSSI values and level of interference in an indoor environment. For this paper, we used Gaussian kernel since the input spaces is not fit for linear classification. Using Gaussian kernel allows to transform the original features spaces into a higher dimension feature spaces where each data point has  $N$  features for each support vector. The value of the  $i$ th feature is calculated by using the value of the kernel between the data point being classified and the  $i$ th support vector.

#### D. Testing and Evaluation of the Models

For the testing and evaluation of each model, hold out validations was used with 30% held out. In this technique, the data set was divided into two different sets, called training and test data. The training data was used solely for the training of the classifier model and the test set was used to test and evaluate the developed model. To compare the performance

of the three models that was developed for the three wireless technologies, their accuracy on the test set was used.

### IV. RESULTS AND DISCUSSION

This section presents the results obtained. Table I - III shows the raw dataset obtained from [14] for Zigbee technology, Bluetooth Low Energy (BLE) and Wi-Fi.

TABLE I.

SAMPLE RAW DATA FOR ZIGBEE TECHNOLOGY[11]

RSSI			Environment Type
Node A	Node B	Node C	
51	55	64	1
63	63	60	1
55	55	56	1
53	57	62	2
54	55	58	2
57	59	61	2
51	72	60	3
64	72	59	3
66	67	54	3

TABLE II.

SAMPLE RAW DATA FOR BLE TECHNOLOGY[11]

RSSI			Environment Type
Node A	Node B	Node C	
63	79	75	3
72	85	77	3
78	76	79	3
75	93	87	1
70	88	85	1
83	81	85	1
67	73	70	2
68	69	73	2
69	71	72	2

TABLE III.

SAMPLE RAW DATA FOR WI-FI TECHNOLOGY[11]

RSSI			Environment Type
Node A	Node B	Node C	
33	54	48	2
34	42	38	2
34	42	46	2
20	50	35	3
36	38	33	3
49	41	32	3
44	56	44	1
43	52	56	1
51	51	55	1

Table IV presents the cleaned and normalized data set after data pre-processing to ensure a more accurate classifier model. These are the normalized data for Wi-Fi Technology.

TABLE IV. SAMPLE CLEANED AND NORMALIZED DATA FOR WiFi TECHNOLOGY

RSSI			Environment Type
Node A	Node B	Node C	
0.2826	0.8333	0.6735	2
0.3043	0.4333	0.4694	2
0.3043	0.4333	0.6327	2
0.5000	0.7000	0.4082	3
0.3478	0.3000	0.3673	3
0.6304	0.4000	0.3469	3
0.5217	0.9000	0.5918	1
0.5000	0.7667	0.8367	1
0.6739	0.7333	0.8163	1

Figure 1 presents the confusion matrix for the classifier model based on support vector machine algorithm with Gaussian Kernel for the Zigbee technology. According to Figure 1, a true positive of 91.8% was obtained for the environment type 1, 0% true positive for environment type 2, and 37.5% true positive for environment type 3. This corresponds to overall accuracy of 57.1% for the SVM classifier model using Zigbee technology RSSI.




Fig. 1. Confusion Matrix for SVM Classifier Model Using Zigbee RSSI

Figure 2 also presents the confusion matrix for the SVM classifier using Bluetooth Low Energy RSSI. It was observed that the true positive for environment type 1 was 98%, true positive for environment type 2 was 37.5% and true positive for environment type 3 was 87.5%. This corresponds to an overall accuracy of 84.8% for the SVM classifier model using BLE RSSI.




Fig. 2. Confusion Matrix for SVM Classifier Model Using BLE RSSI

The confusion matrix for the SVM classifier model using Wi-Fi RSSI is presented in figure 3. This gives a true positive of 98% for environment type 1, a true positive of 31.2% for environment type 2 and a true positive of 95% for environment type 3. The overall accuracy for this classifier model is 86.7%.




Fig. 3. Confusion Matrix for SVM Classifier Model Using Wi-Fi RSSI

Table V displays the summary of the accuracy for the three SVM based classifier model using different wireless technology for indoor environment classification. Based on table V, zigbee technology is not suitable for indoor environment classification since it achieved the lowest accuracy of 57.1%. BLE and Wi-Fi can be used for indoor environment classification due to its high classification accuracy of 84.8% and 86.7% respectively.

TABLE V. SUMMARY OF THE ACCURACY FOR THE THREE CLASSIFIER MODEL

Wireless Technology	Accuracy
Zigbee	57.1%
Bluetooth Low Energy	84.8%
Wi-Fi	86.7%

## V. CONCLUSION

In this paper, the researcher created three classifier models using the received signal strength indicator of three different wireless technology namely, Zigbee, BLE and Wi-Fi. The three model is based on support vector machine algorithm. The dataset that was used in this paper was cleaned and normalized which result to an increase in the accuracy of the developed models. Based on the results obtained, there is a less true positive results for the environment 2 mainly due to the less data for this type of environment compare to the other two types of environments. The overall accuracy of the three-classifier model was compared which results to the classifier model using Wi-Fi RSSI as the best model since it obtained the highest overall accuracy of 86.7%.

For future study, this paper can be used to improve the existing research on indoor localization using RSSI. Since RSSI is dependent on the type of environment, it is therefore important to first identify the type of environment before making an approximation of the location of a certain object

in an indoor setting. More data points can also be consider to further improve the accuracy of the model.

#### ACKNOWLEDGEMENT

The authors would like to thank Sebastian Sadowski, Dr. Petros Spachos and Dr. Konstantinos N. Plataniotis for the dataset that was used in this paper. We also like to express our gratitude to Mapua University for providing the necessary funds for this paper publication and presentation.

#### REFERENCES

- [1] A. Proskochylo, A. Vorobyov, M. Zriakhov, A. Kravchuk, A. Akulyничев, and V. Lukin, "Overview of wireless technologies for organizing sensor networks," *2015 2nd Int. Sci. Conf. Probl. Infocommunications Sci. Technol. PIC S T 2015 - Conf. Proc.*, pp. 39–41, 2015, doi: 10.1109/INFOCOMMST.2015.7357263.
- [2] L. Yi, L. Tao, and S. Jun, "RSSI localization method for mine underground based on RSSI hybrid filtering algorithm," *2017 9th IEEE Int. Conf. Commun. Softw. Networks, ICCSN 2017*, vol. 2017-Janua, pp. 327–332, 2017, doi: 10.1109/ICCSN.2017.8230129.
- [3] H. Li and L. Chen, "RSSI-aware energy saving for large file downloading on smartphones," *IEEE Embed. Syst. Lett.*, vol. 7, no. 2, pp. 63–66, 2015, doi: 10.1109/LES.2015.2426195.
- [4] G. Qi, Y. Jin, and J. Yan, "RSSI-based Floor Localization Using Principal Component Analysis and Ensemble Extreme Learning Machine Technique," *Int. Conf. Digit. Signal Process. DSP*, vol. 2018-Novem, 2019, doi: 10.1109/ICDSP.2018.8631549.
- [5] A. K. Paul, M. Arifuzzaman, K. Yu, and T. Sato, "Detour Path Angular Information based Range Free Localization with Last Hop RSSI Measurement based Distance Calculation," *2019 12th Int. Conf. Mob. Comput. Ubiquitous Network, ICMU 2019*, pp. 2–5, 2019, doi: 10.23919/ICMU48249.2019.9006644.
- [6] C. Zhao and B. Wang, "A MLE-PSO indoor localization algorithm based on RSSI," *Chinese Control Conf. CCC*, no. 2, pp. 6011–6015, 2017, doi: 10.23919/ChiCC.2017.8028312.
- [7] J. Xiong, Q. Qin, and K. Zeng, "A Distance Measurement Wireless Localization Correction Algorithm Based on RSSI," *Proc. - 2014 7th Int. Symp. Comput. Intell. Des. Isc. 2014*, vol. 2, no. 2, pp. 276–278, 2015, doi: 10.1109/ISCID.2014.246.
- [8] F. Wu, J. Xing, and B. Dong, "An indoor localization method based on RSSI of adjustable power WiFi router," *Proc. - 5th Int. Conf. Instrum. Meas. Comput. Commun. Control. IMCCC 2015*, no. 2, pp. 1481–1484, 2016, doi: 10.1109/IMCCC.2015.313.
- [9] J. C. D. Cruz and T. M. Amado, "Development of Machine Learning-based Predictive Models for Wireless Indoor Localization Application with Feature Ranking via Recursive Feature Elimination Algorithm," *ICSPCC 2020 - IEEE Int. Conf. Signal Process. Commun. Comput. Proc.*, pp. 2–7, 2020, doi: 10.1109/ICSPCC50002.2020.9259526.
- [10] S. Barai, D. Biswas, and B. Sau, "Improved RSSI based Angle Localization using Rotational Object," *2020 IEEE Int. Conf. Power Electron. Renew. Energy Appl. PEREA 2020*, pp. 0–4, 2020, doi: 10.1109/PEREA51218.2020.9339773.
- [11] G. Zhu, F. Dong, and N. Pang, "Classification of Indoor Environments Based on Mixed Graph Similarity using UWB Signals," *2020 IEEE Symp. Ser. Comput. Intell. SSCI 2020*, pp. 197–201, 2020, doi: 10.1109/SSCI47803.2020.9308294.
- [12] M. I. Alhajri, N. T. Ali, and R. M. Shubair, "Classification of Indoor Environments for IoT Applications: A Machine Learning Approach," *IEEE Antennas Wirel. Propag. Lett.*, vol. 17, no. 12, pp. 2164–2168, 2018, doi: 10.1109/LAWP.2018.2869548.
- [13] C. Barat and N. Ait Oufroukh, "Classification of indoor environment using only one ultrasonic sensor," *Conf. Rec. - IEEE Instrum. Meas. Technol. Conf.*, vol. 3, pp. 1750–1755, 2001, doi: 10.1109/imtc.2001.929501.
- [14] S. Sadowski, P. Spachos, and K. N. Plataniotis, "Memoryless Techniques and Wireless Technologies for Indoor Localization with the Internet of Things," *IEEE Internet Things J.*, vol. 7, no. 11, pp. 10996–11005, 2020, doi: 10.1109/JIOT.2020.2992651.
- [15] M. I. Alhajri, N. T. Ali, and R. M. Shubair, "A machine learning approach for the classification of indoor environments using RF signatures," *2018 IEEE Glob. Conf. Signal Inf. Process. Glob. 2018 - Proc.*, no. 1, pp. 1060–1062, 2019, doi: 10.1109/GlobalsIP.2018.8646600.
- [16] S. Shukla and N. W. Bergmann, "Single bit error correction implementation in CRC-16 on FPGA," *Proc. - 2004 IEEE Int. Conf. Field-Programmable Technol. FPT '04*, pp. 319–322, 2004, doi: 10.1109/fpt.2004.1393289.
- [17] T. Elarabi, V. Deep, and C. K. Rai, "Design and simulation of state-of-art ZigBee transmitter for IoT wireless devices," *2015 IEEE Int. Symp. Signal Process. Inf. Technol. ISSPIT 2015*, pp. 297–300, 2016, doi: 10.1109/ISSPIT.2015.7394347.
- [18] X. Li and X. Lu, "Design of a ZigBee wireless sensor network node for aquaculture monitoring," *2016 2nd IEEE Int. Conf. Comput. Commun. ICCC 2016 - Proc.*, pp. 2179–2182, 2017, doi: 10.1109/CompComm.2016.7925086.
- [19] W. N. Fatihah Wan Mustapha, M. A. Abdul Aziz, M. Masrie, R. Sam, and M. N. M. Tan, "WiFi Approximated Strength Measurement Method with Brute Force Algorithm for a Minimum Number of AP and Maximum WiFi Coverage," *ISCAIE 2020 - IEEE 10th Symp. Comput. Appl. Ind. Electron.*, pp. 180–185, 2020, doi: 10.1109/ISCAIE47305.2020.9108833.
- [20] J. Zhang, B. Wei, W. Hu, and S. S. Kanhere, "WiFi-ID: Human identification using WiFi signal," *Proc. - 12th Annu. Int. Conf. Distrib. Comput. Sens. Syst. DCOS 2016*, pp. 75–82, 2016, doi: 10.1109/DCOSS.2016.30.
- [21] Z. Mabunga, J. C. Dela Cruz, G. Magwili, and A. Samartin, "Development of Sanitary Landfill's Groundwater Contamination Detection Model Based on Machine Learning Algorithms," in *2020 IEEE 12th International Conference on Humanoid, Nanotechnology, Information Technology, Communication and Control, Environment, and Management (HNICEM)*, 2020, pp. 1–6, doi: 10.1109/HNICEM51456.2020.9400140.
- [22] Q. H. Nguyen *et al.*, "Influence of Data Splitting on Performance of Machine Learning Models in Prediction of Shear Strength of Soil," *Math. Probl. Eng.*, vol. 2021, p. 4832864, 2021, doi: 10.1155/2021/4832864.

# Certification of Author Contribution

We hereby certify that the following statement outlines the contributions made by each author to the creation of this work. This certification serves to acknowledge and authenticate the individual contributions, ensuring transparency and proper recognition of each author's involvement in the research/project.

**Article Title:** "Utilization of different wireless technologies' RSSI for indoor environment classification using support vector machine"

**Publisher:** Institute of Electrical and Electronics Engineers (IEEE)

**Published In:** IEEE Xplore

**Date of Publication:** August 7, 2021

**Publication Link:** <https://ieeexplore.ieee.org/abstract/document/9515242>


**DOI:** [10.1109/ICSGRC53186.2021.9515242](https://doi.org/10.1109/ICSGRC53186.2021.9515242)

**Scopus-Indexed (SCI):** Yes

**Web of Science Indexed (WOS):** YES (Inspect Accession Number: 21103216)

CRediT (Contributor Roles Taxonomy) *			
Author Name	Role/s	Percentage Contribution	Signature
Zoren P. Mabunga (Lead Author)	Conceptualization, Methodology, Software, Validation, Data Curation, Writing – Original Draft, Visualization, Supervision	60%	
Jennifer C. dela Cruz	Conceptualization, Methodology, Formal Analysis, Investigation, Writing – Original Draft, Project Administration	20%	
Angelica C. Samortin	Writing- Review & Editing, Resources	10%	
Renato R. Maaliw	Writing, Review and Editing	10%	
TOTAL		100.00%	

**Certified by:**

  
Zoren P. Mabunga (Lead Author)  
Faculty, College of Engineering  
Southern Luzon State University

  
Renato R. Maaliw III, DIT  
Dean, College of Engineering  
Southern Luzon State University



## Author Feedback Wizard

[← Back to author profile](#)[Review profile details for](#)[About the Author Feedback Wizard](#) ⓘ**Maaliw, Renato R.****Author details**[Documents](#)[Preprints](#)[Awarded grants](#)**Author details****Preferred Name**  
Maaliw, Renato R.**Current affiliation**  
Southern Luzon State University**37 Documents**

Review and remove any documents that do not belong to this profile

Sort by [Year \(oldest\)](#)

Document title	Authors	Source	Year
<a href="#">Classification of learning styles in virtual learning environment using J48 decision tree</a>	Maaliw, R.R., Ballera, M.A.	14th International Conference on Cognition and Exploratory Learning in the Digital Age, CELDA 2017	2017 pp. 149-156
<a href="#">X Remove from profile</a>			
<a href="#">A Personalized Virtual Learning Environment Using Multiple Modeling Techniques</a>	Maaliw, R.R.	2021 IEEE 12th Annual Ubiquitous Computing, Electronics and Mobile Communication Conference, UEMCON 2021	2021 pp. 8-15
<a href="#">X Remove from profile</a>			
<a href="#">An Ensemble Machine Learning Approach for Time Series Forecasting of COVID-19 Cases</a>	Maaliw, R.R., Ballera, M.A., Mabunga, Z.P., ...Dejelo, D.A., Seno, M.P.	2021 IEEE 12th Annual Information Technology, Electronics and Mobile Communication Conference, IEMCON 2021	2021 pp. 633-640
<a href="#">X Remove from profile</a>			
<a href="#">A Circuit Design of a Sensor Amplifier for Improving Blood Pressure Measurement in Telehealth System</a>	Maaliw, R.R., Panergo, M.C., Cruz, F.R.G.	2021 IEEE 12th Annual Information Technology, Electronics and Mobile Communication Conference, IEMCON 2021	2021 pp. 783-788
<a href="#">X Remove from profile</a>			
<a href="#">Early Prediction of Electronics Engineering Licensure Examination Performance using Random Forest</a>	Maaliw, R.R.	2021 IEEE World AI IoT Congress, AlloT 2021	2021 pp. 41-47
<a href="#">X Remove from profile</a>			
<a href="#">Utilization of Different Wireless Technologies' RSSI for Indoor Environment Classification Using Support Vector Machine</a>	Maaliw, R.R., Mabunga, Z.P., Cruz, J.C.D., ...Samortin, A.C.	2021 IEEE 12th Control and System Graduate Research Colloquium, ICSGRC 2021 - Proceedings	2021 pp. 233-237
<a href="#">X Remove from profile</a>			

Time-Series Forecasting of COVID-19 Cases Using Stacked Long Short-Term Memory Networks

[X Remove from profile](#)

Maaliw, R.R.,  
Mabunga, Z.P.,  
Villa, F.T.

2021 International Conference on Innovation and Intelligence for Informatics, Computing, and Technologies, 3ICT 2021  
pp. 435-441

2021

Golden Apple Snail Kuhol Eggs Detection Using MATLAB Image Processing

[X Remove from profile](#)

Maaliw, R.R.,  
Carreon, B.I.A.,  
Dequito, C.Y.,  
...Esmerna, C.J.M.,  
Ballado, A.H.

2022 IEEE 14th International Conference on Humanoid, Nanotechnology, Information Technology, Communication and Control, Environment, and Management, HNICEM 2022

2022

I-Respond: Mobile Application for Emergency Response Using Dijkstra's Algorithm Shortest Path

[X Remove from profile](#)

Maaliw, R.R.,  
Lagman, A.C., De Angel, R., ...Ramos, R.F., Perez, M.R.L.

2022 IEEE 14th International Conference on Humanoid, Nanotechnology, Information Technology, Communication and Control, Environment, and Management, HNICEM 2022

2022

Virtual Dietitian as a Precision Nutrition Application for Gym and Fitness Enthusiasts: A Quality Improvement Initiative

[X Remove from profile](#)

Garcia, M.B.,  
Revano, T.F.,  
Loresco, P.J.M.,  
...Oducado, R.M.F.,  
Uludag, K.

2022 IEEE 14th International Conference on Humanoid, Nanotechnology, Information Technology, Communication and Control, Environment, and Management, HNICEM 2022

2022

[◀ Previous](#) [1](#) [2](#) [3](#) [4](#) [Next ▶](#)

Display [10 results](#) [▼](#)



Are any documents missing? [Search for missing documents on Scopus](#)

2 Preprints

0 Awarded grants

## About Scopus

[What is Scopus](#)

[Content coverage](#)

[Scopus blog](#)

[Scopus API](#)

[Privacy matters](#)

## Language

[日本語版を表示する](#)

[查看简体中文版本](#)

[查看繁體中文版本](#)

[Просмотр версии на русском языке](#)

## Customer Service

[Help](#)

[Tutorials](#)

[Contact us](#)

All



ADVANCED SEARCH

Conferences &gt; 2021 IEEE 12th Control and Sy... ?

# Utilization of Different Wireless Technologies' RSSI for Indoor Environment Classification Using Support Vector Machine

Publisher: IEEE

Cite This

PDF

Zoren P. Mabunga ; Jennifer C. dela Cruz ; Angelica C. Samortin ; Renato R. Maaliw All Authors

2  
Paper  
Citations133  
Full  
Text Views

Back to Results | Next &gt;



## Abstract

**Abstract:**

This paper presents the development of three indoor environment classifier model using support vector machine algorithm with Gaussian Kernel for three different wireless technology. The dataset that was used in this paper contained RSSI from three nodes for each wireless technology. Three different type of indoor environment was considered in this paper namely, small room with low interference, small room with high interference and large room with medium interference. Based on the results of the validation and testing for the three models, an overall accuracy of 57.1% was obtained for the classifier model using the RSSI of Zigbee technology while 84.8% was obtained for the model using the RSSI of BLE and 86.7% for the model using the RSSI of Wi-Fi technology. This corresponds to a conclusion that the model based on the RSSI of Wi-Fi technology is the best classifier model among the three for indoor environment classification. This paper can be used to further increase the accuracy of indoor localization using RSSI.

## Document Sections

- I. Introduction
- II. Related Literature
- III. Methodology
- IV. Results and Discussion
- V. Conclusion

## Authors

## Figures

Published in: 2021 IEEE 12th Control and System Graduate Research Colloquium (ICSGRC)

## References

Date of Conference: 07-07 August 2021      INSPEC Accession Number: 21103216

## Citations

Date Added to IEEE Xplore: 20 August 2021      DOI: 10.1109/ICSGRC53186.2021.9515242

## Keywords

ISBN Information:

Publisher: IEEE

## Metrics

Conference Location: Shah Alam, Malaysia

## I. Introduction

At present, wireless technology has become an essential part of our daily life. Different wireless technologies play a key role in today's communications, and it will become more important in the coming years due to its continuous development. Some of these wireless technologies are the 802.15.4/ZigBee, Bluetooth and Wi-Fi which can be used in networks with decentralized and centralized management [1]. These technologies have been widely used in solving various engineering task such as in building management, transportation, environment, security, and industrial applications. One way to determine the performance of a certain wireless technology is by identifying its Received Signal Strength Indicator (RSSI). RSSI provides the measurement of the power received by a certain receiving device. RSSI allows

Sign in to Continue Reading

## More Like This

Twin Support Vector Machines for Pattern Classification

IEEE Transactions on Pattern Analysis and Machine Intelligence  
Published: 2007Weighted Linear Loss Projection  
Twin Support Vector Machine for Pattern ClassificationIEEE Access  
Published: 2019

Show More



## Authors

Zoren P. Mabunga

School of Graduate Studies, College of Engineering Mapua University, Southern Luzon State University, Manila, Philippines

Jennifer C. dela Cruz

Angelica C. Samortin

School of Graduate Studies, Mapua University, Manila, Philippines

Renato R. Maaliw

College of Engineering, Southern Luzon State University, Lucban, Philippines

Figures



References



Citations



Keywords



Metrics



**IEEE Personal Account**

CHANGE USERNAME/PASSWORD

**Purchase Details**

PAYMENT OPTIONS

**Profile Information**

COMMUNICATIONS PREFERENCES

**Need Help?**

US & CANADA: +1 800 678 4333



VIEW PURCHASED DOCUMENTS

PROFESSION AND EDUCATION

WORLDWIDE: +1 732 981 0060

TECHNICAL INTERESTS

CONTACT & SUPPORT

[About IEEE Xplore](#) | [Contact Us](#) | [Help](#) | [Accessibility](#) | [Terms of Use](#) | [Nondiscrimination Policy](#) | [IEEE Ethics Reporting](#) | [Sitemap](#) | [IEEE Privacy Policy](#)  
A not-for-profit organization, IEEE is the world's largest technical professional organization dedicated to advancing technology for the benefit of humanity.

© Copyright 2023 IEEE - All rights reserved.

Feedback

# IEEE COPYRIGHT AND CONSENT FORM

To ensure uniformity of treatment among all contributors, other forms may not be substituted for this form, nor may any wording of the form be changed. This form is intended for original material submitted to the IEEE and must accompany any such material in order to be published by the IEEE. Please read the form carefully and keep a copy for your files.

## **Utilization of Different Wireless Technologies' RSSI for Indoor Environment Classification Using Support Vector Machine**

**Zoren P. Mabunga, Jennifer Dela Cruz, Angelica C. Samortin, Renato R. Maaliw III**

**2021 IEEE Control System Graduate Research Colloquium (ICSGRC)**

## **COPYRIGHT TRANSFER**

The undersigned hereby assigns to The Institute of Electrical and Electronics Engineers, Incorporated (the "IEEE") all rights under copyright that may exist in and to: (a) the Work, including any revised or expanded derivative works submitted to the IEEE by the undersigned based on the Work; and (b) any associated written or multimedia components or other enhancements accompanying the Work.

## **GENERAL TERMS**

1. The undersigned represents that he/she has the power and authority to make and execute this form.
  2. The undersigned agrees to indemnify and hold harmless the IEEE from any damage or expense that may arise in the event of a breach of any of the warranties set forth above.
  3. The undersigned agrees that publication with IEEE is subject to the policies and procedures of the [IEEE PSPB Operations Manual](#).
  4. In the event the above work is not accepted and published by the IEEE or is withdrawn by the author(s) before acceptance by the IEEE, the foregoing copyright transfer shall be null and void. In this case, IEEE will retain a copy of
  5. the manuscript for internal administrative/record-keeping purposes.
- For jointly authored Works, all joint authors should sign, or one of the authors should sign as authorized agent for the others.

The author hereby warrants that the Work and Presentation (collectively, the "Materials") are original and that he/she is the author of the Materials. To the extent the Materials incorporate text passages, figures, data or other material from the works of others, the author has obtained any necessary permissions. Where necessary, the author has obtained all third party permissions and consents to grant the license above and has provided copies of such permissions and consents to IEEE

**You have indicated that you DO wish to have video/audio recordings made of your conference presentation under terms and conditions set forth in "Consent and Release."**

## **CONSENT AND RELEASE**

In the event the author makes a presentation based upon the Work at a conference hosted or sponsored in whole or in

1. part by the IEEE, the author, in consideration for his/her participation in the conference, hereby grants the IEEE the unlimited, worldwide, irrevocable permission to use, distribute, publish, license, exhibit, record, digitize, broadcast, reproduce and archive, in any format or medium, whether now known or hereafter developed: (a) his/her presentation and comments at the conference; (b) any written materials or multimedia files used in connection with his/her presentation; and (c) any recorded interviews of him/her (collectively, the "Presentation"). The permission granted includes the transcription and reproduction of the Presentation for inclusion in products sold or distributed by IEEE and live or recorded broadcast of the Presentation during or after the conference.

In connection with the permission granted in Section 1, the author hereby grants IEEE the unlimited, worldwide,

2. irrevocable right to use his/her name, picture, likeness, voice and biographical information as part of the advertisement, distribution and sale of products incorporating the Work or Presentation, and releases IEEE from any claim based on right of privacy or publicity.

BY TYPING IN YOUR FULL NAME BELOW AND CLICKING THE SUBMIT BUTTON, YOU CERTIFY THAT SUCH ACTION CONSTITUTES YOUR ELECTRONIC SIGNATURE TO THIS FORM IN ACCORDANCE WITH UNITED STATES LAW, WHICH AUTHORIZES ELECTRONIC SIGNATURE BY AUTHENTICATED REQUEST FROM A USER OVER THE INTERNET AS A VALID SUBSTITUTE FOR A WRITTEN SIGNATURE.

  
Renato Maaliw III  
Signature

07-13-2021

Date (dd-mm-yyyy)

## Information for Authors

### AUTHOR RESPONSIBILITIES

The IEEE distributes its technical publications throughout the world and wants to ensure that the material submitted to its publications is properly available to the readership of those publications. Authors must ensure that their Work meets the requirements as stated in section 8.2.1 of the IEEE PSPB Operations Manual, including provisions covering originality, authorship, author responsibilities and author misconduct. More information on IEEE's publishing policies may be found at [http://www.ieee.org/publications\\_standards/publications/rights/authorrightsresponsibilities.html](http://www.ieee.org/publications_standards/publications/rights/authorrightsresponsibilities.html). Authors are advised especially of IEEE PSPB Operations Manual section 8.2.1.B12: "It is the responsibility of the authors, not the IEEE, to determine whether disclosure of their material requires the prior consent of other parties and, if so, to obtain it." Authors are also advised of IEEE PSPB Operations Manual section 8.1.1B: "Statements and opinions given in work published by the IEEE are the expression of the authors."

### RETAINED RIGHTS/TERMS AND CONDITIONS

- Authors/employers retain all proprietary rights in any process, procedure, or article of manufacture described in the Work.
- Authors/employers may reproduce or authorize others to reproduce the Work, material extracted verbatim from the Work, or derivative works for the author's personal use or for company use, provided that the source and the IEEE copyright notice are indicated, the copies are not used in any way that implies IEEE endorsement of a product or service of any employer, and the copies themselves are not offered for sale.
- Although authors are permitted to re-use all or portions of the Work in other works, this does not include granting third-party requests for reprinting, republishing, or other types of re-use. The IEEE Intellectual Property Rights office must handle all such third-party requests.
- Authors whose work was performed under a grant from a government funding agency are free to fulfill any deposit mandates from that funding agency.

### AUTHOR ONLINE USE

- **Personal Servers.** Authors and/or their employers shall have the right to post the accepted version of IEEE-copyrighted articles on their own personal servers or the servers of their institutions or employers without permission from IEEE, provided that the posted version includes a prominently displayed IEEE copyright notice and, when published, a full citation to the original IEEE publication, including a link to the article abstract in IEEE Xplore. Authors shall not post the final, published versions of their papers.
- **Classroom or Internal Training Use.** An author is expressly permitted to post any portion of the accepted version of his/her own IEEE-copyrighted articles on the author's personal web site or the servers of the author's institution or company in connection with the author's teaching, training, or work responsibilities, provided that the appropriate copyright, credit, and reuse notices appear prominently with the posted material. Examples of permitted uses are lecture materials, course packs, e-reserves, conference presentations, or in-house training courses.
- **Electronic Preprints.** Before submitting an article to an IEEE publication, authors frequently post their manuscripts to their own web site, their employer's site, or to another server that invites constructive comment from colleagues. Upon submission of an article to IEEE, an author is required to transfer copyright in the article to IEEE, and the author must update any previously posted version of the article with a prominently displayed IEEE copyright notice. Upon publication of an article by the IEEE, the author must replace any previously posted electronic versions of the article with either (1) the full citation to the

IEEE work with a Digital Object Identifier (DOI) or link to the article abstract in IEEE Xplore, or (2) the accepted version only (not the IEEE-published version), including the IEEE copyright notice and full citation, with a link to the final, published article in IEEE Xplore.

**Questions about the submission of the form or manuscript must be sent to the publication's editor.**

**Please direct all questions about IEEE copyright policy to:**

**IEEE Intellectual Property Rights Office, [copyrights@ieee.org](mailto:copyrights@ieee.org), +1-732-562-3966**



# Evidence of Peer-Review

Until December 31



- [Compose](#)
- [Inbox](#)
- [Starred](#)
- [Snoozed](#)
- [Sent](#)
- [Drafts](#)
- [Less](#)
- [Important](#)
- [Scheduled](#)
- [All Mail](#)
- [Spam](#)
- [Trash](#)
- [Categories](#)
  - [Social](#)
  - [Updates](#)


36 of 37 < >   

[ICSGRC2021] Your Submission has been Accepted!  

ICSGRC2021 <asprg.net@gmail.com>  
to me

Thu, Jul 8, 2021, 1:49 PM   

**Be careful with this message**  
The sender hasn't authenticated this message so SLSU Mail can't verify that it actually came from them. Avoid clicking links, downloading attachments, or replying with personal information.

\*Please ignore this email if you have already completed your registration\*

Dear Renato,

Congratulations!

On behalf of the 2021 12th IEEE Control & System Graduate Research Colloquium (ICSGRC 2021), I am pleased to inform you that your submission titled: "Utilization of Different Wireless Technologies' RSSI for Indoor Environment Classification Using Support Vector Machine" has been ACCEPTED for Virtual Presentation.

**Reviewers' Feedback/Comment**  
-----  
We have included the reviewers' feedback at the end of this message. Please read comments from reviewers and make the necessary corrections and amendments prior to final camera-ready submission. Please address these comments while preparing your camera-ready version. Your paper may still be rejected if this is not followed.

**Registration and Payment:**  
-----  
Please complete the registration and payment latest by 1st July 2021 at this registration link:  
[http://www.asprg.net/icsgrc2021\\_reg](http://www.asprg.net/icsgrc2021_reg)

**IEEE No Show Policy**  
-----  
Please take note that IEEE has a strict policy on "NO-SHOW" status. The IEEE has implemented policies to exclude authors that do not present their accepted submission from further distribution of their publication, such as exclusion from IEEE Xplore. Therefore, one of the authors or their representatives MUST submit the video presentation and upload it. Please take note of IEEE Terms & Conditions here:  
<https://sites.google.com/view/icsgrc2021/ieee-no-show-policy?authuser=0>

Once again, Congratulations and Stay Safe. Take Care.

Regards,  
Technical Program Chair  
ICSGRC 2021  
[asprg.net@gmail.com](mailto:asprg.net@gmail.com)

**Reviewers' Comment:**  
\*\*\*\*\*  
The paper is well written but it can be improved with the following comments  
1. Add citation [11] in this statement "... Sadowski et al, used Gimbal Series 10 Beacons, Raspberry Pi 3 and Xbees together with Arduino Uno microcontroller"  
2. Change word 'thru' to 'through'  
3. Add a bracket in equation (4)  
4. Please center align Figure 1 and Figure 2  
5. The title of Table IV is confusing. these data belong to which technology.  
\*\*\*\*\*  
1. Figures & tables should be cited in the text & the insertion of the same should be very near to where it is cited.  
2. Nomenclature has to be put at the end along with the acknowledgement.  
3. The existing work is not compared with some standard technique, if this point is implemented, then the proposed work would be authenticated that it is a better concept than the others, if not done, so, please do it & add it so that it will be a full-fledged paper which can be cited by many.  
4. The future work in this field is not mentioned.  
5. Literature survey is inadequate; incorporate the recent works of the authors.  
6. The disadvantages, drawbacks of the works in the other author's papers in the relevant field are not put.  
7. Authors are encouraged to provide details of preprocessing of images.  
8. There is no results and discussion in the paper. All the algorithms/techniques are explained very nicely. But the quantification of results are to be provided by the authors.  
9. Need to refer to new references.  
10. Paper contains the content, but it has to be revised in a standard way.  
\*\*\*\*\*

No novelty is found

- ```
*****
```
- 1.Paper is well written. Use quantitative approach in all the places of the paper.
  - 2.More recent models can be used for analysis purpose.
  - 3.Some more visualization other than confusion matrix may be appreciated.
- ```
*****
```

Would you please give an explanation or justification for why use SVM? Not another classifier? or compared some classifier.  
Why the splitting used a 70:30 ratio? Give an explanation or justification.

 Reply

 Forward

 Forums