

# Integration Manual

for S32K1\_S32M24X MEM\_43\_EEP Driver

Document Number: IM2MEM\_43\_EEPASRR21-11 Rev0000R2.0.0 Rev. 1.0

<b>1 Revision History</b>	<b>2</b>
<b>2 Introduction</b>	<b>3</b>
2.1 Supported Derivatives . . . . .	3
2.2 Overview . . . . .	4
2.3 About This Manual . . . . .	5
2.4 Acronyms and Definitions . . . . .	6
2.5 Reference List . . . . .	6
<b>3 Building the driver</b>	<b>7</b>
3.1 Build Options . . . . .	7
3.1.1 GCC Compiler/Assembler/Linker Options . . . . .	7
3.1.2 IAR Compiler/Assembler/Linker Options . . . . .	11
3.1.3 GHS Compiler/Assembler/Linker Options . . . . .	13
3.2 Files required for compilation . . . . .	15
3.2.1 Other includes files: . . . . .	16
3.3 Setting up the plugins . . . . .	17
<b>4 Function calls to module</b>	<b>19</b>
4.1 Function Calls during Start-up . . . . .	19
4.2 Function Calls during Shutdown . . . . .	19
4.3 Function Calls during Wake-up . . . . .	19
<b>5 Module requirements</b>	<b>20</b>
5.1 Exclusive areas to be defined in BSW scheduler . . . . .	20
5.1.1 Critical Region Exclusive Matrix . . . . .	23
5.2 Exclusive areas not available on this platform . . . . .	23
5.3 Peripheral Hardware Requirements . . . . .	23
5.4 ISR to configure within AutosarOS - dependencies . . . . .	23
5.5 ISR Macro . . . . .	24
5.5.1 Without an Operating System . . . . .	24
5.5.2 With an Operating System . . . . .	24
5.6 Other AUTOSAR modules - dependencies . . . . .	24
5.7 Data Cache Restrictions . . . . .	25
5.8 User Mode support . . . . .	25
5.8.1 User Mode configuration in AutosarOS . . . . .	25
5.9 Multicore support . . . . .	26
<b>6 Main API Requirements</b>	<b>27</b>
6.1 Main function calls within BSW scheduler . . . . .	27
6.2 API Requirements . . . . .	27
6.3 Calls to Notification Functions, Callbacks, Callouts . . . . .	27

<b>7 Memory allocation</b>	<b>28</b>
7.1 Sections to be defined in Mem_43_EEP_MemMap.h . . . . .	28
7.2 Linker command file . . . . .	29
<b>8 Integration Steps</b>	<b>30</b>
<b>9 External assumptions for driver</b>	<b>31</b>

## Chapter 1

### Revision History

Revision	Date	Author	Description
1.0	04.08.2023	NXP RTD Team	S32K1_S32M24X Real-Time Drivers AUTOSAR 4.4 & R21-11 Version 2.0.0

## Chapter 2

### Introduction

- [Supported Derivatives](#)
- [Overview](#)
- [About This Manual](#)
- [Acronyms and Definitions](#)
- [Reference List](#)

This integration manual describes the integration requirements for MEM\_EEP Driver for S32K1\_S32M24X micro-controllers.

### 2.1 Supported Derivatives

The software described in this document is intended to be used with the following microcontroller devices of NXP Semiconductors:

- s32k116\_qfn32
- s32k116\_lqfp48
- s32k118\_lqfp48
- s32k118\_lqfp64
- s32k142\_lqfp48
- s32k142\_lqfp64
- s32k142\_lqfp100
- s32k142w\_lqfp48
- s32k142w\_lqfp64
- s32k144\_lqfp48
- s32k144\_lqfp64 / MWCT1014S\_lqfp64

- s32k144\_lqfp100 / MWCT1014S\_lqfp100
- s32k144\_mapbga100
- s32k144w\_lqfp48
- s32k144w\_lqfp64
- s32k146\_lqfp64
- s32k146\_lqfp100 / MWCT1015S\_lqfp100
- s32k146\_mapbga100 / MWCT1015S\_mapbga100
- s32k146\_lqfp144
- s32k148\_lqfp100
- s32k148\_mapbga100 / MWCT1016S\_mapbga100
- s32k148\_lqfp144
- s32k148\_lqfp176
- s32m241\_lqfp64
- s32m242\_lqfp64
- s32m243\_lqfp64
- s32m244\_lqfp64

All of the above microcontroller devices are collectively named as S32K1\_S32M24X. Note: MWCT part numbers contain NXP confidential IP for Qi Wireless Power

## 2.2 Overview

**AUTOSAR (AUTomotive Open System ARchitecture)** is an industry partnership working to establish standards for software interfaces and software modules for automobile electronic control systems.

AUTOSAR:

- paves the way for innovative electronic systems that further improve performance, safety and environmental friendliness.
- is a strong global partnership that creates one common standard: "Cooperate on standards, compete on implementation".
- is a key enabling technology to manage the growing electrics/electronics complexity. It aims to be prepared for the upcoming technologies and to improve cost-efficiency without making any compromise with respect to quality.
- facilitates the exchange and update of software and hardware over the service life of the vehicle.

## 2.3 About This Manual

This Technical Reference employs the following typographical conventions:

- **Boldface** style: Used for important terms, notes and warnings.
- *Italic* style: Used for code snippets in the text. Note that C language modifiers such "const" or "volatile" are sometimes omitted to improve readability of the presented code.

Notes and warnings are shown as below:

Note

This is a note.

Warning

This is a warning

## 2.4 Acronyms and Definitions

Term	Definition
API	Application Programming Interface
AUTOSAR	Automotive Open System Architecture
DET	Default Error Tracer
DEM	Diagnostic Event Manager
ECC	Error Correcting Code
VLE	Variable Length Encoding
N/A	Not Available
MCU	Microcontroller Unit
ECU	Electronic Control Unit
EEPROM	Electrically Erasable Programmable Read-Only Memory
EA	EEPROM Abstraction
MEM_EEP	Memory EEPROM driver
XML	Extensible Markup Language

## 2.5 Reference List

#	Title	Version
1	Specification of MEM Driver	AUTOSAR Release R21-11
2	Reference Manual	S32K1xx Series Reference Manual, Rev. 14, 09/2021
		S32M24x Reference Manual, Rev. 2 Draft A, 05/2023
3	Errata	S32K116_0N96V Rev. 22/OCT/2021
		S32K118_0N97V Rev. 22/OCT/2021
		S32K142_0N33V Rev. 22/OCT/2021
		S32K144_0N57U Rev. 22/OCT/2021
		S32K144W_0P64A Rev. 22/OCT/2021
		S32K146_0N73V Rev. 22/OCT/2021
		S32K148_0N20V Rev. 22/OCT/2021
		S32M244_P64A+P73G, Rev. 0
		S32M242_N33V+P73G, Rev. 0, 6/2023
4	Data Sheet	S32K1xx Data Sheet, Rev. 14, 08/2021
		S32M2xx Data Sheet, Supports S32M24x and S32M27x, Rev. 3 Draft A, 05/2023



## Chapter 3

### Building the driver

- [Build Options](#)
- [Files required for compilation](#)
- [Setting up the plugins](#)

This section describes the source files and various compilers, linker options used for building the driver. It also explains the EB Tresos Studio plugin setup procedure.

#### 3.1 Build Options

- [GCC Compiler/Assembler/Linker Options](#)
- [IAR Compiler/Assembler/Linker Options](#)
- [GHS Compiler/Assembler/Linker Options](#)

The RTD driver files are compiled using:

- NXP GCC 10.2.0 20200723 (Build 1728 Revision g5963bc8)
- IAR ANSI C/C++ Compiler V8.40.3.228/W32 for ARM Functional Safety
- Green Hills Multi 7.1.6d / Compiler 2020.1.4

The compiler, assembler, and linker flags used for building the driver are explained below.

The TS\_T40D2M20I0R0 part of the plugin name is composed as follows:

- T = Target\_Id (e.g. T40 identifies Cortex-M architecture)
- D = Derivative\_Id (e.g. D2 identifies S32K1 platform)
- M = SW\_Version\_Major and SW\_Version\_Minor
- I = SW\_Version\_Patch
- R = Reserved

##### 3.1.1 GCC Compiler/Assembler/Linker Options

###### 3.1.1.1 GCC Compiler Options

Compiler Option	Description
-mcpu=cortex-m4	Targeted ARM processor for which GCC should tune the performance of the code (for S32K14x or S32M24x devices)
-mcpu=cortex-m0plus	Targeted ARM processor for which GCC should tune the performance of the code (for S32K11x devices)
-mthumb	Generates code that executes in Thumb state
-mlittle-endian	Generate code for a processor running in little-endian mode
-mfpv4-sp-d16	Specifies the floating-point hardware available on the target (for S32K14x or S32M24x devices)
-mfloat-abi=hard	Specifies the floating-point ABI to use. "hard" allows generation of floating-point instructions and uses FPU-specific calling conventions (for S32K14x or S32M24x devices)
-mfpv4-sp-d16	Specifies the floating-point hardware available on the target (for S32K11x devices)
-mfloat-abi=soft	Specifies the floating-point ABI to use. Specifying "soft" causes GCC to generate output containing library calls for floating-point operations (for S32K11x devices)
-std=c99	Specifies the ISO C99 base standard
-Os	Optimize for size. Enables all -O2 optimizations except those that often increase code size
-ggdb3	Produce debugging information for use by GDB using the most expressive format available, including GDB extensions if at all possible. Level 3 includes extra information, such as all the macro definitions present in the program
-Wall	Enables all the warnings about constructions that some users consider questionable, and that are easy to avoid (or modify to prevent the warning), even in conjunction with macros
-Wextra	This enables some extra warning flags that are not enabled by -Wall
-pedantic	Issue all the warnings demanded by strict ISO C. Reject all programs that use forbidden extensions. Follows the version of the ISO C standard specified by the aforementioned -std option
-Wstrict-prototypes	Warn if a function is declared or defined without specifying the argument types
-Wundef	Warn if an undefined identifier is evaluated in an #if directive. Such identifiers are replaced with zero
-Wunused	Warn whenever a function, variable, label, value, macro is unused
-Werror=implicit-function-declaration	Make the specified warning into an error. This option throws an error when a function is used before being declared
-Wsign-compare	Warn when a comparison between signed and unsigned values could produce an incorrect result when the signed value is converted to unsigned.
-Wdouble-promotion	Give a warning when a value of type float is implicitly promoted to double
-fno-short-enums	Specifies that the size of an enumeration type is at least 32 bits regardless of the size of the enumerator values.

Compiler Option	Description
-funsigned-char	Let the type char be unsigned by default, when the declaration does not use either signed or unsigned
-funsigned-bitfields	Let a bit-field be unsigned by default, when the declaration does not use either signed or unsigned
-fomit-frame-pointer	Omit the frame pointer in functions that don't need one. This avoids the instructions to save, set up and restore the frame pointer; on many targets it also makes an extra register available.
-fno-common	Makes the compiler place uninitialized global variables in the BSS section of the object file. This inhibits the merging of tentative definitions by the linker so you get a multiple-definition error if the same variable is accidentally defined in more than one compilation unit
-fstack-usage	This option is only used to build test for generation Ram/↔ Stack size report. Makes the compiler output stack usage information for the program, on a per-function basis
-fdump-ipa-all	This option is only used to build test for generation Ram/↔ Stack size report. Enables all inter-procedural analysis dumps
-c	Stop after assembly and produce an object file for each source file
-DS32K1XX	Predefine S32K1XX as a macro, with definition 1
-DS32K148	Predefine S32K148 as a macro, with definition 1. S32↔K148 can be replaced according to derivatives name S32K116,S32K118,S32K142,S32K142W,S32K144,S32↔K144W,S32K146,S32K148,S32M244,S32M242.
-DGCC	Predefine GCC as a macro, with definition 1
-DUSE_SW_VECTOR_MODE	Predefine USE_SW_VECTOR_MODE as a macro, with definition 1. By default, the drivers are compiled to handle interrupts in Software Vector Mode
-DI_CACHE_ENABLE	Predefine I_CACHE_ENABLE as a macro, with definition 1. Enables instruction cache initialization in source file system.c under the Platform driver (for S32K14x or S32↔M24x devices)
-DENABLE_FPU	Predefine ENABLE_FPU as a macro, with definition 1. Enables FPU initialization in source file system.c under the Platform driver (for S32K14x or S32M24x devices)
-DMCAL_ENABLE_USER_MODE_SUPPORT	Predefine MCAL_ENABLE_USER_MODE_SUPPO↔RT as a macro, with definition 1. Allows drivers to be configured in user mode.
-sysroot=	Specifies the path to the sysroot, for Cortex-M7 it is /arm-none-eabi/newlib
-specs=nano.specs	Use Newlib nano specs
-specs=nosys.specs	Do not use printf/scanf

### 3.1.1.2 GCC Assembler Options

Assembler Option	Description
-Xassembler-with-cpp	Specifies the language for the following input files (rather than letting the compiler choose a default based on the file name suffix)
-mcpu=cortex-m4	Targeted ARM processor for which GCC should tune the performance of the code (for S32K14x or S32M24x devices)
-mcpu=cortex-m0plus	Targeted ARM processor for which GCC should tune the performance of the code (for S32K11x devices)
-mfpu=fpv4-sp-d16	Specifies the floating-point hardware available on the target (for S32K14x devices)
-mfloat-abi=hard	Specifies the floating-point ABI to use. "hard" allows generation of floating-point instructions and uses FPU-specific calling conventions (for S32K14x devices)
-mfpu=auto	Specifies the floating-point hardware available on the target (for S32K11x devices)
-mfloat-abi=soft	Specifies the floating-point ABI to use. Specifying "soft" causes GCC to generate output containing library calls for floating-point operations (for S32K11x devices)
-mthumb	Generates code that executes in Thumb state
-c	Stop after assembly and produce an object file for each source file

### 3.1.1.3 GCC Linker Options

Linker Option	Description
-Wl,-Map,filename	Produces a map file
-T linkerfile	Use linkerfile as the linker script. This script replaces the default linker script (rather than adding to it)
-entry=Reset_Handler	Specifies that the program entry point is Reset_Handler
-nostartfiles	Do not use the standard system startup files when linking
-mcpu=cortex-m4	Targeted ARM processor for which GCC should tune the performance of the code (for S32K14x or S32M24x devices)
-mcpu=cortex-m0plus	Targeted ARM processor for which GCC should tune the performance of the code (for S32K11x devices)
-mthumb	Generates code that executes in Thumb state
-mfpu=fpv4-sp-d16	Specifies the floating-point hardware available on the target (for S32K14x or S32M24x devices)
-mfloat-abi=hard	Specifies the floating-point ABI to use. "hard" allows generation of floating-point instructions and uses FPU-specific calling conventions (for S32K14x or S32M24x devices)
-mfpu=auto	Specifies the floating-point hardware available on the target (for S32K11x devices)
-mfloat-abi=soft	Specifies the floating-point ABI to use. Specifying "soft" causes GCC to generate output containing library calls for floating-point operations (for S32K11x devices)
-mlittle-endian	Generate code for a processor running in little-endian mode
-ggdb3	Produce debugging information for use by GDB using the most expressive format available, including GDB extensions if at all possible. Level 3 includes extra information, such as all the macro definitions present in the program
-lc	Link with the C library
-lm	Link with the Math library
-lgcc	Link with the GCC library
-n	Turn off page alignment of sections, and disable linking against shared libraries
-sysroot=	Specifies the path to the sysroot, for Cortex-M7 it is /arm-none-eabi/newlib

Linker Option	Description
-specs=nano.specs	Use Newlib nano specs
-specs=nosys.specs	Do not use printf/scanf

### 3.1.2 IAR Compiler/Assembler/Linker Options

#### 3.1.2.1 IAR Compiler Options

Compiler Option	Description
-cpu=Cortex-M4	Targeted ARM processor for which IAR should tune the performance of the code (for S32K14x or S32M24x devices)
-cpu=Cortex-M0+	Targeted ARM processor for which IAR should tune the performance of the code (for S32K11x devices)
-cpu_mode=thumb	Generates code that executes in Thumb state
-endian=little	Generate code for a processor running in little-endian mode
-fpu=FPv4-SP	Use this option to generate code that performs floating-point operations using a Floating Point Unit (FPU). Single-precision variant. (for S32K14x or S32M24x devices)
-fpu=none	Use this option to generate code that performs floating-point operations using a Floating Point Unit (FPU). No FPU. (for S32K11x devices)
-e	Enables all IAR C language extensions
-Ohz	Optimize for size. the compiler will emit AEABI attributes indicating the requested optimization goal. This information can be used by the linker to select smaller or faster variants of DLIB library functions
-debug	Makes the compiler include debugging information in the object modules. Including debug information will make the object files larger
-no_clustering	Disables static clustering optimizations. Static and global variables defined within the same module will not be arranged so that variables that are accessed in the same function are close to each other
-no_mem_idioms	Makes the compiler not optimize certain memory access patterns
-no_explicit_zero_opt	Do not treat explicit initializations to zero of static variables as zero initializations
-require_prototypes	Force the compiler to verify that all functions have proper prototypes. Generates an error otherwise
-no_wrap_diagnostics	Does not wrap long lines in diagnostic messages
-diag_suppress=Pa050	Suppresses diagnostic message Pa050
-DS32K1XX	Predefine S32K1XX as a macro, with definition 1
-DS32K148	Predefine S32K148 as a macro, with definition 1. S32K148 can be replaced according to derivatives name S32K116,S32K118,S32K142,S32K142W,S32K144,S32K144W,S32K146,S32K148,S32M244,S32M242.
-DIAR	Predefine IAR as a macro, with definition 1

Compiler Option	Description
-DUSE_SW_VECTOR_MODE	Predefine USE_SW_VECTOR_MODE as a macro, with definition 1. By default, the drivers are compiled to handle interrupts in Software Vector Mode.
-DI_CACHE_ENABLE	Predefine I_CACHE_ENABLE as a macro, with definition 1. Enables instruction cache initialization in source file system.c under the Platform driver (for S32K14x or S32M24x devices)
-DENABLE_FPU	Predefine ENABLE_FPU as a macro, with definition 1. Enables FPU initialization in source file system.c under the Platform driver (for S32K14x or S32M24x devices)
-DMCAL_ENABLE_USER_MODE_SUPPORT	Predefine MCAL_ENABLE_USER_MODE_SUPPORT as a macro, with definition 1. Allows drivers to be configured in user mode.

### 3.1.2.2 IAR Assembler Options

Assembler Option	Description
-cpu=Cortex-M4	Targeted ARM processor for which IAR should tune the performance of the code (for S32K14x or S32M24x devices)
-cpu=Cortex-M0+	Targeted ARM processor for which IAR should tune the performance of the code (for S32K11x devices)
-fpu=FPv4-SP	Use this option to generate code that performs floating-point operations using a Floating Point Unit (FPU). Single-precision variant. (for S32K14x devices)
-fpu=none	Use this option to generate code that performs floating-point operations using a Floating Point Unit (FPU). No FPU. (for S32K11x devices)
-cpu_mode thumb	Selects the thumb mode for the assembler directive CODE
-g	Disables the automatic search for system include files
-r	Generates debug information

### 3.1.2.3 IAR Linker Options

Linker Option	Description
-map filename	Produces a map file
-config linkerfile	Use linkerfile as the linker script. This script replaces the default linker script (rather than adding to it)
-cpu=Cortex-M4	Targeted ARM processor for which IAR should tune the performance of the code (for S32K14x or S32M24x devices)
-cpu=Cortex-M0+	Targeted ARM processor for which IAR should tune the performance of the code (for S32K11x devices)
-fpu=FPv4-SP	Use this option to generate code that performs floating-point operations using a Floating Point Unit (FPU). Single-precision variant. (for S32K14x or S32M24x devices)
-fpu=none	Use this option to generate code that performs floating-point operations using a Floating Point Unit (FPU). No FPU. (for S32K11x devices)

Linker Option	Description
-entry _start	Treats _start as a root symbol and start label
-enable_stack_usage	Enables stack usage analysis. If a linker map file is produced, a stack usage chapter is included in the map file
-skip_dynamic_initialization	Dynamic initialization (typically initialization of C++ objects with static storage duration) will not be performed automatically during application startup
-no_wrap_diagnostics	Does not wrap long lines in diagnostic messages

### 3.1.3 GHS Compiler/Assembler/Linker Options

#### 3.1.3.1 GHS Compiler Options

Compiler Option	Description
-cpu=cortexm4	Selects target processor: Arm Cortex M4 (for S32K14x or S32M24x devices)
-cpu=cortexm0plus	Selects target processor: Arm Cortex M0+ (for S32K11x devices)
-thumb	Selects generating code that executes in Thumb state
-fpu=vfpv4_d16	Specifies hardware floating-point using the v4 version of the VFP instruction set, with 16 double-precision floating-point registers (for S32K14x or S32M24x devices)
-fsingle	Use hardware single-precision, software double-precision FP instructions (for S32K14x or S32M24x devices)
-fsoft	Specifies software floating-point (SFP) mode. This setting causes your target to use integer registers to hold floating-point data and use library subroutine calls to emulate floating-point operations (for S32K11x devices)
-C99	Use (strict ISO) C99 standard (without extensions)
-ghstd=last	Use the most recent version of Green Hills Standard mode (which enables warnings and errors that enforce a stricter coding standard than regular C and C++)
-Osize	Optimize for size
-gnu_asm	Enables GNU extended asm syntax support
-dual_debug	Generate DWARF 2.0 debug information
-G	Generate debug information
-keeptempfiles	Prevents the deletion of temporary files after they are used. If an assembly language file is created by the compiler, this option will place it in the current directory instead of the temporary directory
-Wimplicit-int	Produce warnings if functions are assumed to return int
-Wshadow	Produce warnings if variables are shadowed
-Wtrigraphs	Produce warnings if trigraphs are detected
-Wundef	Produce a warning if undefined identifiers are used in #if preprocessor statements
-unsigned_chars	Let the type char be unsigned, like unsigned char

Compiler Option	Description
-unsigned_fields	Bitfields declared with an integer type are unsigned
-no_commons	Allocates uninitialized global variables to a section and initializes them to zero at program startup
-no_exceptions	Disables C++ support for exception handling
-no_slash_comment	C++ style // comments are not accepted and generate errors
-prototype_errors	Controls the treatment of functions referenced or called when no prototype has been provided
-incorrect_pragma_warnings	Controls the treatment of valid #pragma directives that use the wrong syntax
-c	Stop after assembly and produce an object file for each source file
-DS32K1XX	Predefine S32K1XX as a macro, with definition 1
-DS32K148	Predefine S32K148 as a macro, with definition 1. S32K148 can be replaced according to derivatives name S32K116, S32K118, S32K142, S32K142W, S32K144, S32K144W, S32K146, S32K148, S32M244, S32M242.
-DGHS	Predefine GHS as a macro, with definition 1
-DUSE_SW_VECTOR_MODE	Predefine USE_SW_VECTOR_MODE as a macro, with definition 1. By default, the drivers are compiled to handle interrupts in Software Vector Mode
-DI_CACHE_ENABLE	Predefine I_CACHE_ENABLE as a macro, with definition 1. Enables instruction cache initialization in source file system.c under the Platform driver (for S32K14x or S32M24x devices)
-DENABLE_FPU	Predefine ENABLE_FPU as a macro, with definition 1. Enables FPU initialization in source file system.c under the Platform driver (for S32K14x or S32M24x devices)
-DMCAL_ENABLE_USER_MODE_SUPPORT	Predefine MCAL_ENABLE_USER_MODE_SUPPORT as a macro, with definition 1. Allows drivers to be configured in user mode

### 3.1.3.2 GHS Assembler Options

Assembler Option	Description
-cpu=cortexm4	Selects target processor: Arm Cortex M4 (for S32K14x or S32M24x devices)
-cpu=cortexm0plus	Selects target processor: Arm Cortex M0+ (for S32K11x devices)
-fpu=vfpv4_d16	Specifies hardware floating-point using the v4 version of the VFP instruction set, with 16 double-precision floating-point registers (for S32K14x devices)
-fsingle	Use hardware single-precision, software double-precision FP instructions (for S32K14x devices)
-fsoft	Specifies software floating-point (SFP) mode. This setting causes your target to use integer registers to hold floating-point data and use library subroutine calls to emulate floating-point operations (for S32K11x devices)
-preprocess_assembly_files	Controls whether assembly files with standard extensions such as .s and .asm are preprocessed
-list	Creates a listing by using the name and directory of the object file with the .lst extension



Assembler Option	Description
-c	Stop after assembly and produce an object file for each source file

### 3.1.3.3 GHS Linker Options

Linker Option	Description
-e Reset_Handler	Make the symbol Reset_Handler be treated as a root symbol and the start label of the application
-T linker_script_file.ld	Use linker_script_file.ld as the linker script. This script replaces the default linker script (rather than adding to it)
-map	Produce a map file
-keepmap	Controls the retention of the map file in the event of a link error
-Mn	Generates a listing of symbols sorted alphabetically/numerically by address
-delete	Instructs the linker to remove functions that are not referenced in the final executable. The linker iterates to find functions that do not have relocations pointing to them and eliminates them
-ignore_debug_references	Ignores relocations from DWARF debug sections when using -delete. DWARF debug information will contain references to deleted functions that may break some third-party debuggers
-Llibrary_path	Points to library_path (the libraries location) for thumb2 to be used for linking
-larch	Link architecture specific library
-lstartup	Link run-time environment startup routines. The source code for the modules in this library is provided in the src/libstartup directory
-lind_sd	Link language-independent library, containing support routines for features such as software floating point, run-time error checking, C99 complex numbers, and some general purpose routines of the ANSI C library (for S32K14x or S32M24x devices)
-lind_sf	Link language-independent library, containing support routines for features such as software floating point, run-time error checking, C99 complex numbers, and some general purpose routines of the ANSI C library (for S32K11x devices)
-v	Prints verbose information about the activities of the linker, including the libraries it searches to resolve undefined symbols
-keep=C40_Ip_AccessCode	Avoid linker remove function C40_Ip_AccessCode from Fls module because it is not referenced explicitly
-nostartfiles	Controls the start files to be linked into the executable

## 3.2 Files required for compilation

This section describes the include files required to compile, assemble (if assembler code) and link the MEM\_EEP driver for S32K1\_S32M24X microcontrollers. To avoid integration of incompatible files, all the include files from other modules shall have the same AR\_MAJOR\_VERSION and AR\_MINOR\_VERSION, i.e. only files with the same AUTOSAR major and minor versions can be compiled.

#MEM\_EEP files:

- Include file:

- Mem\_43\_EEP\_TS\_T40D2M20I0R0\include\Mem\_43\_EEP.h
  - Mem\_43\_EEP\_TS\_T40D2M20I0R0\include\Mem\_43\_EEP\_InternalTypes.h
  - Mem\_43\_EEP\_TS\_T40D2M20I0R0\include\Mem\_43\_EEP\_IPW.h
  - Mem\_43\_EEP\_TS\_T40D2M20I0R0\include\Mem\_43\_EEP\_Types.h
  - Mem\_43\_EEP\_TS\_T40D2M20I0R0\include\Ftfc\_Mem\_Eep\_Ip.h
- Source file:
    - Mem\_43\_EEP\_TS\_T40D2M20I0R0\src\Mem\_43\_EEP.c
    - Mem\_43\_EEP\_TS\_T40D2M20I0R0\src\Mem\_43\_EEP\_IPW.c
    - Mem\_43\_EEP\_TS\_T40D2M20I0R0\src\Ftfc\_Mem\_Eep\_Ip.c

### Note

- Mem\_43\_EEP\_Cfg.h - this file should be generated by the user using a configuration/generation tool
- Mem\_43\_EEP\_CfgDefines.h - this file should be generated by the user using a configuration/generation tool
- Mem\_43\_EEP\_Cfg.c - this file should be generated by the user using a configuration/generation tool
- Ftfc\_Mem\_Eep\_Ip\_Cfg.c - this file should be generated by the user using a configuration/generation tool
- Ftfc\_Mem\_Eep\_Ip\_Cfg.h - this file should be generated by the user using a configuration/generation tool
- Ftfc\_Mem\_Eep\_Ip\_Types.h - this file should be generated by the user using a configuration/generation tool

## 3.2.1 Other includes files:

### 3.2.1.1 Files from Base common folder

- BaseNXP\_TS\_T40D2M20I0R0\include\Compiler.h
- BaseNXP\_TS\_T40D2M20I0R0\include\Compiler\_Cfg.h
- BaseNXP\_TS\_T40D2M20I0R0\include\ComStack\_Types.h
- BaseNXP\_TS\_T40D2M20I0R0\include\Fls\_MemMap.h
- BaseNXP\_TS\_T40D2M20I0R0\include\Mcal.h
- BaseNXP\_TS\_T40D2M20I0R0\include\Platform\_Types.h
- BaseNXP\_TS\_T40D2M20I0R0\include\Std\_Types.h
- BaseNXP\_TS\_T40D2M20I0R0\include\Reg\_eSys.h
- BaseNXP\_TS\_T40D2M20I0R0\include\Soc\_Ips.h
- BaseNXP\_TS\_T40D2M20I0R0\include\Reg\_Macros.h
- BaseNXP\_TS\_T40D2M20I0R0\include\SilRegMacros.h
- BaseNXP\_TS\_T40D2M20I0R0\header\S32K148.h

**3.2.1.2 Files from Det folder:**

- Det\_TS\_T40D2M20I0R0\include\Det.h

**3.2.1.3 Files from Dem folder:**

- Dem\_TS\_T40D2M20I0R0\include\Dem.h

**3.2.1.4 Files from Platform folder:**

- Platform\_TS\_T40D2M20I0R0\include\Platform.h

**3.2.1.5 Files from Rte folder:**

- Rte\_TS\_T40D2M20I0R0\include\SchM\_Mem\_43\_EEP.h

**3.2.1.6 Files from Os folder:**

- Os\_TS\_T40D2M20I0R0\include\Os.h

**3.3 Setting up the plugins**

The MEM\_EEP Driver was designed to be configured by using the EB Tresos Studio (version EB tresos Studio 29.0.0 or later)

**3.3.0.0.1 Steps to generate the configuration:**

1. Copy the module folders:
  - BaseNXP\_TS\_T40D2M20I0R0
  - Det\_TS\_T40D2M20I0R0
  - Dem\_TS\_T40D2M20I0R0
  - EcuC\_TS\_T40D2M20I0R0
  - Mem\_43\_EEP\_TS\_T40D2M20I0R0
  - Os\_TS\_T40D2M20I0R0
  - Platform\_TS\_T40D2M20I0R0
  - Resource\_TS\_T40D2M20I0R0
  - Rte\_TS\_T40D2M20I0R0 into the Tresos plugins folder.
2. Set the desired Tresos Output location folder for the generated sources and header files.
3. Use the EB tresos Studio GUI to modify ECU configuration parameters values.
4. Generate the configuration files.

### 3.3.0.0.2 Location of various files inside the EEP module folder:

- VSMD (Vendor Specific Module Definition) file in EB Tresos Studio XDM format:
  - Mem\_43\_EEP\_TS\_T40D2M20I0R0\config\Mem\_43\_EEP.xdm
- VSMD (Vendor Specific Module Definition) file(s) in AUTOSAR compliant EPD format:
  - Mem\_43\_EEP\_TS\_T40D2M20I0R0\autosar\Mem\_43\_EEP\_<subderivative\_name>.epd

## Chapter 4

### Function calls to module

- [Function Calls during Start-up](#)
- [Function Calls during Shutdown](#)
- [Function Calls during Wake-up](#)

#### 4.1 Function Calls during Start-up

MEM\_EEP shall be initialized during STARTUP phase of EcuM initialization. The API to be called for this is Mem\_43\_EEP\_Init(). The MCU module should be initialized before the MEM\_EEP is initialized.

#### 4.2 Function Calls during Shutdown

None.

#### 4.3 Function Calls during Wake-up

None.

## Chapter 5

### Module requirements

- Exclusive areas to be defined in BSW scheduler
- Exclusive areas not available on this platform
- Peripheral Hardware Requirements
- ISR to configure within AutosarOS - dependencies
- ISR Macro
- Other AUTOSAR modules - dependencies
- Data Cache Restrictions
- User Mode support
- Multicore support

#### 5.1 Exclusive areas to be defined in BSW scheduler

- In the current implementation, MEM\_EEP is using the services of Run-Time Environment (RTE) for entering and exiting the critical regions.
- RTE implementation is done by the integrators of the RTD using OS or non-OS services.
- For testing the MEM\_EEP, stubs are used for RTE.
- MEM\_EEP driver has five exclusive areas.
- The purpose of these exclusive areas is to make the functions Mem\_43\_EEP\_Erase, Mem\_43\_EEP\_Write and Mem\_43\_EEP\_Read thread safe and thus protect MEM\_43\_EEP internal job variables.

**MEM\_43\_EEP\_MEM\_EXCLUSIVE\_AREA\_01** is used in function Mem\_43\_EEP\_Erase. It protects the variables:

- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32EepromAddrIt
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32RemainingLength

- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJob
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJobResult

**MEM\_43\_EEP\_MEM\_EXCLUSIVE\_AREA\_02** is used in function Mem\_43\_EEP\_Write. It protects the variables:

- Mem\_43\_EEP\_pJobSrcAddrPtr
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32EepromAddrIt
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_pJobSrcAddrPtr
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32RemainingLength
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJob
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJobResult

**MEM\_43\_EEP\_MEM\_EXCLUSIVE\_AREA\_03** is used in function Mem\_43\_EEP\_Read. It protects the variables:

- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32EepromAddrIt
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_pJobDataDestPtr
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32RemainingLength
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJob
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJobResult

**MEM\_43\_EEP\_MEM\_EXCLUSIVE\_AREA\_04** is used in function Mem\_43\_EEP\_Erase. It protects the variables:

- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32EepromAddrIt
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32RemainingLength
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJob
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJobResult

**MEM\_43\_EEP\_MEM\_EXCLUSIVE\_AREA\_05** is used in function Mem\_43\_EEP\_HwSpecificService. It protects the variables:

- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32HwServiceIdJob
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32EepromAddrIt
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_pJobDataDestPtr
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32RemainingLength
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJob

## Module requirements

- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJobResult

**MEM\_43\_EEP\_MEM\_EXCLUSIVE\_AREA\_06** is used in function Mem\_43\_EEP\_Erase. It protects the variables:

- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32EepromAddrIt
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32RemainingLength
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJob
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJobResult

**MEM\_43\_EEP\_MEM\_EXCLUSIVE\_AREA\_07** is used in function Mem\_43\_EEP\_Erase. It protects the variables:

- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32EepromAddrIt
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32RemainingLength
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJob
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJobResult

**MEM\_43\_EEP\_MEM\_EXCLUSIVE\_AREA\_08** is used in function Mem\_43\_EEP\_Erase. It protects the variables:

- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32EepromAddrIt
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32RemainingLength
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJob
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJobResult

**MEM\_43\_EEP\_MEM\_EXCLUSIVE\_AREA\_10** is used in function Mem\_43\_EEP\_Erase. It protects the variables:

- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32EepromAddrIt
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_u32RemainingLength
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJob
- Mem\_43\_EEP\_eJobRuntimeInfo[InstanceIndex].Mem\_43\_EEP\_eJobResult



### 5.1.1 Critical Region Exclusive Matrix

- Below is the table depicting the exclusivity between different critical region IDs from the MEM\_43\_EEP driver.
- If there is an “X” in a table, it means that those 2 critical regions cannot interrupt each other.

Exclusive Area ID	EEP_EXCLUSIVE_AREA_01 (Eep_Erase)	EEP_EXCLUSIVE_AREA_02 (Eep_Write)	EEP_EXCLUSIVE_AREA_03 (Eep_Read)	EEP_EXCLUSIVE_AREA_04 (Eep_Compare)	EEP_EXCLUSIVE_AREA_05 (Eep_QuickWrite)	EEP_EXCLUSIVE_AREA_07 protect write from FLS and CSEC (Ptfc_Eep_Ip_Write)	EEP_EXCLUSIVE_AREA_08 protect write from FLS and CSEC (Ptfc_Eep_Ip_CmdSetLexramFunction)	EEP_EXCLUSIVE_AREA_10 (Ptfc_Eep_Ip_Write)	EEP_EXCLUSIVE_AREA_11 (Ptfc_Eep_Ip_GetJobResult)
EEP_EXCLUSIVE_AREA_01 (Eep_Erase)		x	x	x	x				
EEP_EXCLUSIVE_AREA_02 (Eep_Write)	x		x	x	x				
EEP_EXCLUSIVE_AREA_03 (Eep_Read)	x	x		x	x				
EEP_EXCLUSIVE_AREA_04 (Eep_Compare)	x	x	x		x				
EEP_EXCLUSIVE_AREA_05 (Eep_QuickWrite)	x	x	x	x					
EEP_EXCLUSIVE_AREA_07 protect write from FLS and CSEC (Ptfc_Eep_Ip_Write)									
EEP_EXCLUSIVE_AREA_08 protect read from FLS and CSEC (Ptfc_Eep_Ip_CmdSetLexramFunction)									
EEP_EXCLUSIVE_AREA_10 (Ptfc_Eep_Ip_Write)									x
EEP_EXCLUSIVE_AREA_11 (Ptfc_Eep_Ip_GetJobResult)								x	

## 5.2 Exclusive areas not available on this platform

List of exclusive areas which are not available on this platform (or blank if they're all available).

- MEM\_43\_EEP\_MEM\_EXCLUSIVE\_AREA\_00
- MEM\_43\_EEP\_MEM\_EXCLUSIVE\_AREA\_11
- MEM\_43\_EEP\_MEM\_EXCLUSIVE\_AREA\_12
- MEM\_43\_EEP\_MEM\_EXCLUSIVE\_AREA\_13
- MEM\_43\_EEP\_MEM\_EXCLUSIVE\_AREA\_14

## 5.3 Peripheral Hardware Requirements

The MEM\_EEP driver uses/controls the "FTFC" MCU peripheral. For more details about peripheral and its structure refers to MCU reference manual.

## 5.4 ISR to configure within AutosarOS - dependencies

None.

## 5.5 ISR Macro

RTD drivers use the ISR macro to define the functions that will process hardware interrupts. Depending on whether the OS is used or not, this macro can have different definitions.

**5.5.1 Without an Operating System** The macro `USING_OS_AUTOSAROS` must not be defined.

### 5.5.1.1 Using Software Vector Mode

The macro `USE_SW_VECTOR_MODE` must be defined and the ISR macro is defined as:

```
#define ISR(IsrName) void IsrName(void)
```

In this case, the drivers' interrupt handlers are normal C functions and their prologue/epilogue will handle the context save and restore.

### 5.5.1.2 Using Hardware Vector Mode

The macro `USE_SW_VECTOR_MODE` must not be defined and the ISR macro is defined as:

```
#define ISR(IsrName) INTERRUPT_FUNC void IsrName(void)
```

In this case, the drivers' interrupt handlers must also handle the context save and restore.

**5.5.2 With an Operating System** Please refer to your OS documentation for description of the ISR macro.

## 5.6 Other AUTOSAR modules - dependencies

- **BaseNXP:** This module provides basic data types and auxiliary macros or functions commonly used by other AUTOSAR modules.
- **Dem:** This module is necessary for enabling reporting of production relevant error status. The API function used is `Dem_ReportErrorStatus()`.
- **Det** This module is necessary for enabling Development error detection. The API function used is `Det_ReportError()`. The activation/deactivation of Development error detection is configurable using 'EepDevErrorDetect' configuration parameter.
- **EcuC:** The ECUC module is used for ECU configuration. RTD modules need ECUC to retrieve the variant information.
- **Rte:** Exclusive areas implementations.

## 5.7 Data Cache Restrictions

In the DMA transfer mode, DMA transfers may issue cache coherency problems. To avoid possible coherency issues when D-CACHE is enabled, the user shall ensure that the buffers used as TCD source and destination are allocated in the NON-CACHEABLE area (by means of Mem\_43\_EEP\_Memmap).

## 5.8 User Mode support

- user\_mode\_config\_in\_module
- [User Mode configuration in AutosarOS](#)

No special measures need to be taken to run MEM\_EEP module from user mode. The MEM\_EEP driver code can be executed at any time from both supervisor and user mode.

### 5.8.1 User Mode configuration in AutosarOS

When User mode is enabled, the driver may have the functions that need to be called as trusted functions in AutosarOS context. Those functions are already defined in driver and declared in the header `<IpName>_Ip TrustedFunctions.h`. This header also included all headers files that contains all types definition used by parameters or return types of those functions. Refer the chapter `user_mode_config_in_module` for more detail about those functions and the name of header files they are declared inside. Those functions will be called indirectly with the naming convention below in order to AutosarOS can call them as trusted functions.

```
Call_<Function_Name>_TRUSTED(parameter1,parameter2,...)
```

That is the result of macro expansion `OsIf_Trusted_Call` in driver code:

```
#define OsIf_Trusted_Call[1-6params](name,param1,...,param6) Call_##name##_TRUSTED(param1,...,param6)
```

So, the following steps need to be done in AutosarOS:

- Ensure `MCAL_ENABLE_USER_MODE_SUPPORT` macro is defined in the build system or somewhere global.
- Define and declare all functions that need to call as trusted functions follow the naming convention above in Integration/User code. They need to visible in `Os.h` for the driver to call them. They will do the marshalling of the parameters and call `CallTrustedFunction()` in OS specific manner.
- `CallTrustedFunction()` will switch to privileged mode and call `TRUSTED_<Function_Name>()`.
- `TRUSTED_<Function_Name>()` function is also defined and declared in Integration/User code. It will un-marshalling of the parameters to call `<Function_Name>()` of driver. The `<Function_Name>()` functions are already defined in driver and declared in `<IpName>_Ip TrustedFunctions.h`. This header should be included in OS for OS call and indexing these functions.

## Module requirements

See the sequence chart below for an example calling `Linflexd_Uart_Ip_Init_Privileged()` as a trusted function.




Figure 5.1 Example sequence chart for calling `Linflexd_Uart_Ip_Init_Privileged` as trusted function

## 5.9 Multicore support

The Mem\_43\_EEP driver does not support multicore feature.

## Chapter 6

### Main API Requirements

- [Main function calls within BSW scheduler](#)
- [API Requirements](#)
- [Calls to Notification Functions, Callbacks, Callouts](#)

#### 6.1 Main function calls within BSW scheduler

Mem\_43\_EEP\_MainFunction (call rate depends on target application, i.e. how fast the data needs to be read/written/compare in FTFC memory)

#### 6.2 API Requirements

None.

#### 6.3 Calls to Notification Functions, Callbacks, Callouts

The MEM\_EEP driver provides notifications that are user configurable:

- StartEepromAccessNotif (usually routed to EA module)
- FinishedEepromAccessNotif (usually routed to EA module)

## Chapter 7

### Memory allocation

- [Sections to be defined in Mem\\_43\\_EEP\\_MemMap.h](#)
- [Linker command file](#)

#### 7.1 Sections to be defined in Mem\_43\_EEP\_MemMap.h

Section name	Type of section	Description
MEM_43_EEP_START_SEC_CONFIG_DATA_UNSPECIFIED↔	Configuration Data	Start of Memory Section for Config Data. Used for variables, constants, structure, array and unions when SIZE (alignment) does not fit the criteria of 8,16 or 32 bit. For instance used for variables of unknown size.
MEM_43_EEP_STOP_SEC_CONFIG_DATA_UNSPECIFIED↔	Configuration Data	End of above section
MEM_43_EEP_START_SEC_CODE	Code	Start of memory Section for Code.
MEM_43_EEP_STOP_SEC_CODE	Code	End of above section
MEM_43_EEP_START_SEC_RAMCODE	Code	Start of memory section for code placed and executed from RAM.
MEM_43_EEP_STOP_SEC_RAMCODE	Code	End of above section
MEM_43_EEP_START_SEC_VARIABLES_CLEARED_UNSPECIFIED↔	Variables	Start of memory Section for Variables. Used for variables, constants, structure, array and unions when SIZE (alignment) does not fit the criteria of 8, 16 or 32 bit. For instance used for variables of unknown size. These variables are cleared to zero by start-up code.
MEM_43_EEP_STOP_SEC_VARIABLES_CLEARED_UNSPECIFIED↔	Variables	End of above section
MEM_43_EEP_START_SEC_VARIABLES_CLEARED_8↔	Variables	Start of Memory Section for Variable 8 bits. These variables are cleared to zero by start-up code.
MEM_43_EEP_STOP_SEC_VARIABLES_CLEARED_8↔	Variables	End of above section

Section name	Type of section	Description
MEM_43_EEP_START_SEC_VAR_C↵ CLEARED_16	Variables	Start of Memory Section for Variable 16 bits. These variables are cleared to zero by start-up code.
MEM_43_EEP_STOP_SEC_VAR_C↵ LEARED_16	Variables	End of above section
MEM_43_EEP_START_SEC_VAR_C↵ CLEARED_32	Variables	Start of Memory Section for Variable 32 bits. These variables are cleared to zero by start-up code.
MEM_43_EEP_STOP_SEC_VAR_C↵ LEARED_32	Variables	End of above section

## 7.2 Linker command file

Memory shall be allocated for every section defined in the driver's "<Module>\_\_MemMap.h.



## Chapter 8

### Integration Steps

This section gives a brief overview of the steps needed for integrating this module:

1. Generate the required module configuration(s). For more details refer to section [Files Required for Compilation](#)
2. Allocate the proper memory sections in the driver's memory map header file ("`<Module>_MemMap.h`") and linker command file. For more details refer to section [Sections to be defined in `<Module>\_MemMap.h`](#)
3. Compile & build the module with all the dependent modules. For more details refer to section [Building the Driver](#)



## Chapter 9

### External assumptions for driver

The section presents requirements that must be complied with when integrating the MEM\_EEP driver into the application.

External Assumption Req ID	External Assumption Text
SWS_Mem_00039	If built as a separate image, the Mem driver shall be completely self contained, i.e. it must not call any library or any other external functions. Note: Image feature
SWS_Mem_00038	The Mem driver shall provide two ways for the service function invocation: - Direct service invocation - Indirect service invocation by a function pointer table Note: Image feature
SWS_Mem_00040	Since Mem drivers are always hardware/CPU specific, the byte order of data fields and address information within the Mem driver binary shall follow the standard CPU byte order. Note: Image feature
SWS_Mem_00041	Offset [bytes]: Size [bytes]: Name: Description 0: 8: Unique ID: Mem driver unique identifier - used to validate Mem driver version information, etc. 8: 8: Flags: Flags used for additional development error detection. 16: 4/8: Header address: Start address of Mem driver image header - used to verify consistency of Mem driver RAM buffer/ROM image location. 20/24: 4/8: Delimiter address: Address of Mem driver binary image delimiter pattern - used to validate if the binary is complete. Note: Image feature
SWS_Mem_00042	Offset [bytes]: Size [bytes]: Name: Description 0: 2: ABI version: BCD-encoded Mem driver binary interface version. Any change of the interface version will also require an update of the MemAcc module. 2: 2: Vendor ID: Standard AUTOSAR vendor identification. 4: 4: Driver ID: Vendor specific driver identification. Note: Image feature
SWS_Mem_00043	The ABI version of a Mem driver following this specification shall be 0001. Note: Image feature
SWS_Mem_00044	The header address is used for development error checks to verify the consistency of the linked Mem driver binary image with the location of the RAM buffer which is used for execution of the Mem driver. In case of a relocatable/position independent Mem driver binary, the header address shall be set to zero, otherwise, the header address shall hold the physical start address of the Mem driver binary. Note: Image feature

External Assumption Req ID	External Assumption Text
SWS_Mem_00045	The flag part of the Mem driver header is a bit-field which holds additional information for develop error checks. Offset [bits]: Size [bits]: Name: Description 0: 1: Relocatable binary: If this bit is set, the Mem driver binary is relocatable and no address consistency checks can be done. 1↵ : 31: Reserved: Reserved by this specification - shall be 0. 32: 32: Vendor specific: Vendor specific flags. Note: Image feature
SWS_Mem_00046	The delimiter address part of the Mem driver header is used for development error checks to verify that the Mem driver binary is complete by checking the delimiter pattern linked to the end of the Mem driver binary. In case of a relocatable/position independent Mem driver binary, the delimiter address shall be set to zero, otherwise, the delimiter address shall hold the physical address of the delimiter pattern. Note: Image feature
SWS_Mem_00073	The function pointer table is a standardized structure used to reference the Mem driver service functions. Entry: Name: Description 1: Init service pointer: Function pointer to Mem driver Init service. 2: DeInit service pointer: Function pointer to Mem driver DeInit service. 3: MainFunction service pointer: Function pointer to Mem driver MainFunction service. 4: GetJobResult service pointer: Function pointer to Mem driver GetJob↵ Result service. 5: Read service pointer: Function pointer to Mem driver Read service. 6: Write service pointer: Function pointer to Mem driver Write service. 7: Erase service pointer: Function pointer to Mem driver Erase service. 8: PropagateError service pointer: Function pointer to Mem driver PropagateError service. 9: BlankCheck service pointer: Function pointer to Mem driver BlankCheck service. 10: Suspend service pointer↵ : Function pointer to Mem driver Suspend service. 11: Resume service pointer: Function pointer to Mem driver Resume service. 12: HwSpecific↵ Service service pointer: Function pointer to Mem driver HwSpecificService service. Note: Image feature
SWS_Mem_00048	The size of the Mem driver function pointers shall be machine/CPU specific. Note: Image feature
SWS_Mem_00051	The value of the delimiter field shall be the ones' complement of the unique identifier value. Note: Image feature
EA_RTD_00071	If interrupts are locked, a centralized function pair to lock and unlock interrupts shall be used.
EA_RTD_00081	The integrator shall assure that <MSN>_Init() and <MSN>_DeInit() functions do not interrupt each other.
EA_RTD_00082	When caches are enabled and data buffers are allocated in cacheable memory regions the buffers involved in DMA transfer shall be aligned with both start and end to cache line size. Note: <b>Rationale:</b> This ensures that no other buffers/variables compete for the same cache lines.
EA_RTD_00106	Standalone IP configuration and HL configuration of the same driver shall be done in the same project
EA_RTD_00107	The integrator shall use the IP interface only for hardware resources that were configured for standalone IP usage. Note: The integrator shall not directly use the IP interface for hardware resources that were allocated to be used in HL context.
EA_RTD_00108	The integrator shall use the IP interface to a build a CDD, therefore the BSWMD will not contain reference to the IP interface

External Assumption Req ID	External Assumption Text
EA_RTD_00113	When RTD drivers are integrated with AutosarOS and User mode support is enabled, the integrator shall assure that the definition and declaration of all RTD functions needed to be called as trusted functions follow the naming convention Call<Function_Name>TRUSTED(parameter1,parameter2,...) in Integration/User code. They need to be visible in Os.h for the driver to call them. They will call RTD <Function_Name>() as trusted functions in OS specific manner.

**How to Reach Us:**

**Home Page:**

[nxp.com](http://nxp.com)

**Web Support:**

[nxp.com/support](http://nxp.com/support)

Information in this document is provided solely to enable system and software implementers to use NXP products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits based on the information in this document. NXP reserves the right to make changes without further notice to any products herein.

NXP makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does NXP assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in NXP data sheets and/or specifications can and do vary in different applications, and actual performance may vary over time. All operating parameters, including "typicals," must be validated for each customer application by customer's technical experts. NXP does not convey any license under its patent rights nor the rights of others. NXP sells products pursuant to standard terms and conditions of sale, which can be found at the following address: [nxp.com/SalesTermsandConditions](http://nxp.com/SalesTermsandConditions).

NXP, the NXP logo, NXP SECURE CONNECTIONS FOR A SMARTER WORLD, COOLFLUX, EMBRACE, GREENCHIP, HITAG, I2C BUS, ICODE, JCOP, LIFE VIBES, MIFARE, MIFARE CLASSIC, MIFARE DESFire, MIFARE PLUS, MIFARE FLEX, MANTIS, MIFARE ULTRALIGHT, MIFARE4MOBILE, MIGLO, NTAG, ROADLINK, SMARTLX, SMARTMX, STARPLUG, TOPFET, TRENCHMOS, UCODE, Freescale, the Freescale logo, Altivec, C-5, CodeTEST, CodeWarrior, ColdFire, ColdFire+, C-Ware, the Energy Efficient Solutions logo, Kinetis, Layerscape, MagniV, mobileGT, PEG, PowerQUICC, Processor Expert, QorIQ, QorIQ Qonverge, Ready Play, SafeAssure, the SafeAssure logo, StarCore, Symphony, VortiQa, Vybrid, Airfast, BeeKit, BeeStack, CoreNet, Flexis, MXC, Platform in a Package, QUICC Engine, SMARTMOS, Tower, TurboLink, and UMEMS are trademarks of NXP B.V. All other product or service names are the property of their respective owners. ARM, AMBA, ARM Powered, Artisan, Cortex, Jazelle, Keil, SecurCore, Thumb, TrustZone, and Vision are registered trademarks of ARM Limited (or its subsidiaries) in the EU and/or elsewhere. ARM7, ARM9, ARM11, big.LITTLE, CoreLink, CoreSight, DesignStart, Mali, mbed, NEON, POP, Sensinode, Socrates, ULINK and Versatile are trademarks of ARM Limited (or its subsidiaries) in the EU and/or elsewhere. All rights reserved. Oracle and Java are registered trademarks of Oracle and/or its affiliates. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org.

© 2023 NXP B.V.

