

Task 1: Reference points

a

i




Figure 1:

ii

We first need to translate to the backwheel to the frame reference point, then do rotation, and then move it back to its place.

$$\text{BackWheelRotate}(30^\circ) = \text{Translate}(-7, 4)\text{Rotate}(30^\circ)\text{Translate}(7, -4) \quad (1)$$

Transforming the wheel from right to left with the above equation should result in a rotation about the back wheel reference point.

Task 2: Getting started

a

In order to make the character visible, I added a camera and a perspective projection. By moving the camera around I captured this image. I also modified the buffer from task 1 to add support for the mesh colors.




Figure 2: Task 2 a

b

i

The w-component of the homogeneous coordinates gives an elegant way to perform translations. Vertices are represented in homogeneous coordinates as $(x, y, z, 1)$. Since the w-component is 1 we can use it to translate in x,y, and z by using the transformation matrix

$$\text{Translate}(dx, dy, dz) = \begin{bmatrix} 1 & 0 & 0 & dx \\ 0 & 1 & 0 & dy \\ 0 & 0 & 1 & dz \\ 0 & 0 & 0 & 1 \end{bmatrix}. \quad (2)$$

ii

Perspective transformation is not an affine transformation, but since we always map a point (x, y, z, w) to $(x/w, y/w, z/w, 1)$, we can perform perspective transformations quite easily.

To do emulate perspective, we want to shrink coordinates toward the center of the screen based on the z-coordinate. The formula for x is roughly this

$$x' = -x/z$$

. This is not affine but due to the above mentioned convention, we can do it if we get the z-coordinate to the w-coordinate using an affine transformation. That is if we can make the coordinate look like $(x, y, z, -z)$, then we will have performed perspective division.

A simple affine transform that does this is

$$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & -1 & 0 \end{bmatrix}. \quad (3)$$

iii

The viewport transform is the transformation that takes vertices from the normalized device coordinate space to the window space. Usually this means mapping object from in the cube $-1 \leq x, y, z \leq 1$, into a space parametrized by screen size and near/far z-clipping values.

Task 4

f

I could figure out how to make the character rotate correctly when moving on path, so it looks a bit wonky.