

PeakAndPack Playwright Test Strategy

This README explains the tagging convention enforced by `playwright.config.ts` . Read this before adding new tests.

The flow, tag to report

write test	tag it	run it	see it
test('...', ...) →	@critical →	npx playwright test →	playwright-report/
	@high	--grep @critical	(HTML, pass/fail,
	@regression		screenshots on fail)

The tag you choose at write time decides which command picks the test up later. Get the tag wrong and a critical test might only run in the regression sweep, days after it should have blocked a release.

Tag meanings

Tag	Meaning	When to use
@critical	Failure here means real money lost or a data leak	Checkout discount logic, orders visibility, auth boundaries
@high	Failure here breaks a core user flow but isn't a money/data risk	Cart totals, stock checks
@regression	Lower-stakes, but worth re-checking after any change	Sort order, product listing display

These match the risk ranking in `test-strategy-manual.md` and `test-strategy-ai-assisted.md` . The ranking decided what matters; these tags enforce that ranking in code.

Running by tag

```
# Run only the critical suite before a release
npx playwright test --grep @critical

# Run everything except regression (faster local feedback loop)
npx playwright test --grep-invert @regression
```

Self-healing pattern

All locators in this suite use role-based selectors or `data-testid` , not CSS classes:

```
// Avoid
page.locator('.btn-checkout-submit')

// Use
page.getByRole('button', { name: 'Place order' })
page.getByTestId('checkout-submit-btn')
```

This means a UI redesign that changes class names or layout doesn't break the test suite, only a change to the actual button text or test ID would.

Retry behavior

`retries: process.env.CI ? 2 : 1` means a flaky test gets one extra attempt locally, two in CI, before being reported as a real failure. This is configured in `playwright.config.ts` , not per-test, so it applies consistently across the whole suite.