AOBP - Centralized SSO, Authentication and Authorization

API contract: AOBP API URL and HTTP standard. Application-owned endpoints in this edition use that convention; OAuth/OIDC and private vendor integration endpoints retain their documented protocol contracts. Local-only logout uses `DELETE /bff/api/v1/session` (204); SSO logout orchestration uses `POST /bff/api/v1/logout-requests` (200 result, optional approved redirect).

BFF-based target architecture | AWS EKS | Proposed design | 2 November 2026

1. Objective and introduction

Establish one clear, secure authentication and authorization architecture for AOBP. BAC SSO owns authentication and user lifecycle. AOBP keeps OAuth tokens on the server and applies business permissions consistently across Microservice 1, Microservice 2 and future services.

The decision in plain language

The React application is the screen the user operates. The Backend for Frontend (BFF) is its trusted server-side companion: it signs the user in through BAC SSO, keeps their tokens safe, and calls backend APIs for them. The browser receives a random session reference, like a claim ticket, rather than an API access token. The BFF calls the selected private microservice directly. Each microservice enforces operation permissions and resource policies using centrally governed authorization data.

Scope and source alignment

This rewrite is based on the supplied 10-page AOBP Centralized SSO, Authentication and Authorization PDF. It retains its Objective, High-level architecture, Implementation Approach, Authentication Runtime, Service RBAC, Central Authorization Management, Resource-Level ABAC and Authorization Database topics. The referenced Markdown attachment was unavailable, so its exact contents and formatting have not been verified.

What changes from the reviewed design

Reviewed PDF	Revised design
SPA registered as OAuth client	BFF registered as confidential OIDC client
SPA receives and retains access tokens	BFF receives tokens; browser holds opaque cookie
Browser sends bearer token to gateway	Browser calls BFF; BFF relays token privately
Browser-led token handling	Shared server-side session and controlled refresh
Gateway-centric business decisions	Central administration with service-local RBAC and ABAC

No local user accounts: AOBP does not create passwords or become a second identity directory. Minimal session claims and issuer/subject references are permitted for runtime security and audit. Authorization configuration and access-scope grants remain AOBP responsibilities.

2. High-level architecture

Decision: place the BFF behind the AWS Application Load Balancer (ALB) and optional public edge gateway. The BFF calls microservices directly over the private network. Each service evaluates RBAC and ABAC; an internal gateway is optional for separately justified traffic controls. The UI remains a separately deployed React microfrontend application, exposed through the same origin as its BFF.

Figure 1. Browser business traffic passes through the BFF directly to a private microservice. Central policy distribution is separate from the business request path.




Figure 1. Browser business traffic passes through the BFF directly to a private microservice. Central policy distribution is separate from the business request path.

The ALB is the first network entry point. The BFF is the first application component that handles browser authentication and protected API calls. An optional public edge gateway may route to the BFF. An internal gateway is not required for business authorization. These are distinct responsibilities, so the answer depends on which boundary is being discussed.

2.1 Components, responsibilities and benefits

Component	Responsibility
React SPA / MFE	Render screens; check session; submit same-origin requests and CSRF header. No OAuth library token cache.
BAC SSO / IdP	Authenticate users, MFA, identity attributes and group lifecycle. Either direct BAC IdP integration or approved Keycloak federation.
AWS WAF + ALB	Filter and balance HTTPS traffic; route static files, BFF routes and OIDC callbacks. No business RBAC.
BFF replicas	Confidential OIDC client, session lifecycle, token refresh, allowlisted proxy and token relay.
Redis	Shared sessions, login transaction state, authorized-client tokens, refresh coordination and logout state.
Optional gateway	Edge routing, rate limits and optional coarse token/scope checks; not authoritative business RBAC.
Authorization Management Service	Manage and distribute approved role mappings, permissions, policies and scope grants to service-local evaluators.
Microservices	Validate tokens independently; enforce both operation RBAC and resource ABAC plus business rules before reads/writes.
Authorization Database	Persist roles, permissions, mappings, policies, scope grants and change audit.

Architecture principles

Identity-centric security: BAC authenticates; AOBP authorizes. Least privilege: deny unless a role and resource policy permit the action. Defense in depth: edge, BFF, gateway and services enforce different controls. Separation of concerns: UI, OAuth handling, routing and business logic evolve independently. Secure by default: private services, no browser tokens and no bypass route. Deployment-independent policy: the same decisions apply with or without Istio.

Benefits and trade-offs

A compromised browser script cannot directly read server-held OAuth tokens. Shared Redis state lets any healthy BFF replica serve a session. Direct BFF-to-service calls avoid a mandatory private-gateway hop and synchronous policy dependency. Costs include consistent local policy evaluation, bounded policy/entitlement freshness, Redis dependency, CSRF protection and careful distributed refresh. The BFF reduces token theft exposure; it does not stop malicious JavaScript from performing actions through an active user session.

2.2 AWS EKS placement and routing

Figure 5. ALB balances to private pod IP targets. Gateway and business services remain private. Cross-zone service routing is allowed; replicas are not paired by zone.




Figure 5. ALB balances to private pod IP targets. Gateway and business services remain private. Cross-zone service routing is allowed; replicas are not paired by zone.

Layer	Deployment specification
Edge	Route 53 DNS, WAF-associated ALB, ACM certificate and HTTPS 443. Use an internal ALB for private-only BAC access; otherwise an internet-facing ALB in public subnets.

Layer	Deployment specification
EKS ingress	AWS Load Balancer Controller reconciles Kubernetes Ingress into ALB listeners and target groups. Use target-type ip. The controller is not a request proxy.
Private compute	UI, BFF, any optional edge gateway, authorization management and microservices use Deployments and ClusterIP Services. No public NodePorts or service LoadBalancers for internal APIs.
Private data	Managed Redis and RDS in private data subnets; security groups permit only necessary callers.
Encryption	TLS to ALB and HTTPS ALB targets. Use workload TLS/mTLS with certificate validation for internal calls; ALB HTTPS target encryption alone is not pod identity verification.

2.3 Public URLs and exact request routes

Example origin: https://aobp.example.com. This is an illustrative hostname, to be replaced with BAC DNS. Separate UI and BFF deployments do not require separate browser origins. Same-origin ingress avoids cross-origin cookie and CORS complexity.

Browser URL / method	ALB target / behavior
GET / and /assets/*	UI static host. SPA fallback applies only to UI paths.
GET/DELETE /bff/api/v1/session	BFF. GET: display identity/capabilities or 401. DELETE: end local session, 204; CSRF for active sessions. Never return tokens.
GET /bff/api/v1/csrf-token	BFF. Return session-bound CSRF token; Cache-Control: no-store.
GET /oauth2/authorization/bac	BFF. Begin login via top-level navigation.
GET /login/oauth2/code/bac	BFF. OIDC query-mode callback with code and state.
GET/POST/PATCH/PUT/DELETE /bff/api/v1/microservice-1/**	BFF. Session and CSRF checks, then allowlisted internal API proxy.
POST /bff/api/v1/logout-requests	BFF. CSRF-protected logout, invalidate session and server tokens.
GET /bff/ws/v1/events	BFF WebSocket upgrade with session and exact Origin check.

Route transformation example

```
Browser: GET https://aobp.example.com/bff/api/v1/microservice-1/resources/resource-123
BFF:     GET https://microservice-1.aobp.svc.cluster.local/api/v1/resources/resource-123
Service: JWT validation -> local RBAC -> resource ABAC -> transaction
```

Ingress sends BFF and OIDC paths to the BFF with higher priority than the UI catch-all. The BFF uses an explicit method/resource route table and chooses a fixed configured destination; it does not expose a catch-all proxy. Browser-supplied URLs, arbitrary hosts and arbitrary proxy paths are rejected. Private service DNS is resolvable only on the controlled backend network.

Why a private gateway is optional

The BFF owns browser OAuth and sessions; services own business authorization. A gateway before the BFF may provide enterprise routing/traffic controls. An internal gateway may serve justified API-management requirements, but adding one solely to enforce RBAC duplicates service responsibilities. The selected default route is ALB -> optional edge gateway -> BFF -> private service.

3. Implementation Approach

Step 1 - Register the BFF as the OIDC client

Register a confidential web client named aobp-bff with BAC SSO. Use Authorization Code flow with PKCE S256, even though the BFF also authenticates as a client. Keep the client secret or private key in Secrets Manager with controlled workload access. Never embed a secret in React assets.

Property	Proposed value / rule
Client ID	aobp-bff
Redirect URI	https://aobp.example.com/login/oauth2/code/bac; exact match, no wildcard
Post-logout redirect	https://aobp.example.com/; explicitly registered
Scopes	openid plus only necessary profile/API scopes; request offline access only if required by provider policy
Client authentication	Prefer private_key_jwt where supported; otherwise managed and rotated client secret
PKCE / state / nonce	S256 challenge; one-time state and OIDC nonce; verifier stored server-side
Login response mode	Authorization code via query-mode GET callback; redact callback query logs

Step 2 - Register the protected API

Represent the AOBP protected API as a logical audience, for example aobp-api. The exact issuer, audience and scope syntax are IdP-specific. For Entra ID, use the resource application ID/identifier and exposed delegated scopes; Keycloak requires appropriate client scopes/audience mapping. Do not assume the literal sample value is accepted by every provider.

Microservices sharing this audience form one trust domain. Each still validates issuer, audience, signature, permitted algorithm, expiry and required claims. If service boundaries require distinct audiences, use separate resources and provider-supported token exchange/on-behalf-of flow; forwarding an unchanged token to a different audience is invalid.

Step 3 - Configure IdP groups and attributes

BAC owns external group membership and user lifecycle. Use stable entitlement IDs scoped by issuer, rather than mutable display names. Where token group claims are incomplete, resolve through an approved server-side IdP API, with least-privilege access and explicit caching. Missing or unresolvable required claims must deny access.

3.1 Roles, permissions and scope

Step 4 - Define AOBP roles

Role	Meaning
ADMIN	Manage approved platform configuration, subject to segregation of duties
MANAGER	Perform management actions
OPERATOR	Perform permitted operational updates
VIEWER	Read approved operational information

Step 5 - Map external entitlements to roles

IdP entitlement example	AOBP role
AOBP_OPERATIONS	OPERATOR
AOBP_MANAGERS	MANAGER
AOBP_VIEWERS	VIEWER
AOBP_ADMINISTRATORS	ADMIN

Persist issuer, entitlement type and stable external entitlement ID. Display names above are examples only. Multiple matching groups can grant multiple roles; explicit deny policy and separation-of-duty rules take precedence where configured.

Step 6 - Define business permissions

Use stable permissions such as DATA.READ, DATA.UPDATE, APPROVAL.SUBMIT and APPROVAL.APPROVE. They describe business actions independently of microservice names. Each service obtains the required permission from its controlled operation mapping, never a browser header.

Step 7 - Assign role permissions (RBAC)

An OPERATOR may receive DATA.READ and DATA.UPDATE. A VIEWER receives DATA.READ. An ADMIN does not automatically bypass terminal restrictions or approval separation. API scopes represent coarse delegated access; they do not replace AOBP business permissions.

Step 8 - Apply resource scope (ABAC)

User	Role	Trusted permitted terminals
User A	OPERATOR	T1
User B	OPERATOR	T2
User C	OPERATOR	T1, T2

The role answers what the user may do. Scope answers where or to which records they may do it. Store scope grants as authorization data or obtain them from approved BAC attributes. Every final decision

combines the permission and the authoritative resource context.

4. Authentication Runtime

Figure 2. SSO activity sequence. Network redirects carry the authorization code; tokens are exchanged directly between the BFF and IdP.




Figure 2. SSO activity sequence. Network redirects carry the authorization code; tokens are exchanged directly between the BFF and IdP.

Step-by-step login

1. React loads from its static host and calls /bff/api/v1/session. A missing session returns 401 JSON. 2. The UI navigates to the BFF login endpoint. 3. The BFF stores a one-time login transaction in Redis and redirects to BAC SSO. 4. BAC authenticates the user with existing SSO/MFA rules. 5. The browser carries the authorization code to the BFF callback. 6. The BFF checks state, exchanges the code using the PKCE verifier and client authentication, and validates the ID token including issuer, audience and nonce. 7. It rotates the session identifier, stores tokens server-side and sets the session cookie. 8. It redirects to a validated local return path; React reloads session display information.

BAC credentials are entered at BAC SSO, not the BFF. If Keycloak brokers BAC, AOBP trusts Keycloak as the configured issuer; federation and logout behavior must be tested. Do not treat tokens from two issuers as interchangeable.

4.1 Cookies, tokens and browser protections

Credential / data	Where it lives and where it travels
Session cookie	Browser cookie jar and BFF only. Contains opaque random session reference, never OAuth tokens.
Access token	Encrypted server-side authorized-client store; sent in Authorization header directly from BFF to the configured service.
Refresh token	Server-side store; sent only from BFF to IdP token endpoint.
ID token	BFF authentication context. Not used as an API bearer token.
CSRF token	Session-bound value available to React and sent as X-CSRF-TOKEN on unsafe requests. Not an OAuth token.
Display user / capabilities	Minimal /bff/api/v1/session response. UI hints only; server authorization remains authoritative.

```
Set-Cookie: __Host-AOBPSESSION=<opaque>; Path=/; Secure; HttpOnly; SameSite=Lax
Cache-Control: no-store
```

Do not set Domain on the __Host- cookie. Lax supports a normal top-level GET redirect from the IdP. If a provider requires cross-site POST callbacks, assess the cookie/transaction correlation design separately; do not simply remove SameSite protection. Rotate the session ID after login and sensitive privilege changes.

CSRF and XSS controls


BFF checks a session-bound CSRF token on POST, PUT, PATCH, DELETE and logout. It also checks the expected Origin/Referer and Fetch Metadata as layered controls. GET requests must not change state. SameSite is an additional control, not the sole CSRF defense. The CSRF token endpoint and authenticated responses are never cached.

Serve a restrictive Content Security Policy, safe output encoding and approved script sources. Limit MFE remote origins and publish immutable versioned assets. Independently deployed MFEs execute with the shell privileges when same-origin, so treat their supply chain as part of the security boundary. HttpOnly prevents script access to the session cookie but does not prevent injected code from sending authenticated requests.

Same-origin requests need no permissive CORS policy. If cross-origin deployment becomes necessary, explicitly allow approved origins with credentials, never wildcard origin plus credentials, and re-evaluate cookie behavior. Keep bearer tokens out of browser storage, URLs, HTML, postMessage and logs.

5. Service Level RBAC Authorization

Figure 3. Each microservice validates identity and evaluates RBAC plus ABAC before business work.



Business path: public edge -> BFF -> private service. Policy distribution is a separate control-plane flow.

Request processing in order

1. The BFF validates session, CSRF and the fixed route/destination.

2. It obtains a usable authorized-client access token, refreshing server-side if necessary.

3. It constructs a new private TLS request directly to the selected service, stripping browser Cookie, Authorization and spoofable identity metadata.

4. The service validates signature, issuer, audience, algorithm, expiry and required claims.

5. The service checks policy/entitlement freshness and evaluates the operation's required business permission locally.

6. It reads authoritative resource attributes and checks scope/ownership/state policies.

7. On allow, it validates input and commits with concurrency and audit controls. Deny is 403; missing/expired mandatory policy data is 503 with no mutation.

5.1 Central Authorization Management

Central administration with local enforcement

The Authorization Management Service owns versioned role definitions, issuer-scoped entitlement mappings, permissions, named policies and scope grants. It authenticates service workloads and publishes approved, signed/versioned policy bundles or authenticated snapshots. It is a control-plane component, not a required synchronous hop for every business request. Each service validates the configured publisher/signature and schema, enforces version/validity bounds, and evaluates both RBAC and ABAC locally. Spring services may use shared policy classes; polyglot services may use a local policy evaluator with the same versioned contract. Domain services own their resource-specific rules.

Policies use stable permission names, independent of service deployment names. A service selects the required permission from its controlled operation mapping. It supplies the verified issuer/subject, trusted entitlements and authoritative resource attributes; the browser cannot select its actor, policy, permission or scope grant. Query, bulk and export paths enforce the same rules.

Policy distribution uses change notifications plus periodic reconciliation and a bounded maximum age. A service may continue using a last-known-good snapshot only while it remains explicitly valid and permitted by policy. Missing, invalid or expired mandatory policy/entitlement data causes a controlled 503 with no business mutation; a valid policy denial is 403. Sensitive operations can require a fresh entitlement check through an authenticated central endpoint under a documented availability contract.

Log policy version, entitlement source/freshness and a safe decision reason. Revocation targets must cover token claim age, policy/grant caches and notification delay. Refreshing a policy bundle does not remove stale group claims from an existing JWT; meeting a tighter SLA requires token revocation, fresh entitlement resolution or reauthentication. Never silently extend validity during an outage.

Token relay and enforcement details

Token relay forwards the current user's **access token** in `Authorization: Bearer ...`; it does not grant permission by itself. Each service acts as an OAuth resource server and validates the configured issuer, signature/allowed algorithm, intended audience and time claims. An ID token authenticates the BFF login; it is not an API credential. A refresh token is sent only to the provider token endpoint.

For Spring services, enable method authorization explicitly with `@EnableMethodSecurity`; adding the security starter alone does not enable it. Apply operation authorization at the application/service layer, with a trusted permission resolver or `AuthorizationManager`. Map provider groups/roles through the governed entitlement contract; default `SCOPE_` authorities do not automatically become AOBP business permissions. Resource authorization loads authoritative data inside the protected use case, with transaction/version

checks before mutation. Account for proxy/self-invocation boundaries when using annotation-based enforcement.

Every path must follow the same rules: REST controllers, service-to-service requests, background workload identities, list/export queries and WebSocket subscriptions/messages. Authenticate long-lived connection establishment and re-evaluate applicable session, permission and resource constraints for subsequent operations. Enforce query scope before pagination/count/export, not by hiding records in the UI.

These are implementation requirements and design choices, not a claim that one framework annotation or an API gateway automatically provides complete authorization. Verify behaviour against the supported framework/IdP versions selected for deployment. Reviewed primary references on 2 November 2026: Spring method security, JWT resource server, and OWASP authorization.

Status contract

401 means no valid authentication; 403 means a valid identity lacks permission or scope; 503 means mandatory security data is unavailable/expired or another required dependency failed. Normal policy-management outages need not stop requests while a last-known-good snapshot remains explicitly valid. Sensitive operations follow their stricter freshness contract. Never extend policy validity silently.

6. Resource-Level ABAC Authorization

Example: identical role, different terminal

User A is an OPERATOR permitted for Terminal T1. They request an update to resource 123. Microservice 1 locally confirms DATA.UPDATE using its valid policy snapshot. Microservice 1 loads resource 123 from its database and discovers that it belongs to Terminal T2. The security policy denies access because T2 is outside the user scope. Final result: 403; no business change occurs.

Check	Example outcome
Valid authenticated identity	ALLOW
RBAC: OPERATOR grants DATA.UPDATE	ALLOW
Authoritative resource terminal	T2, read from business data
Trusted user scope	T1
ABAC: T2 in permitted terminals?	DENY
Final decision	DENY; no operation executed

Where enforcement belongs

The gateway cannot reliably make the final object-level decision because it does not own current resource data. Each service must enforce access before returning records or committing changes. The service constructs resource attributes from trusted business data and evaluates the governed policy locally. It never trusts a terminal field supplied only by the browser.

For lists and searches, apply scope filters in the query before pagination and aggregation. For exports and bulk changes, authorize the whole selection and every affected resource; enforce volume/rate limits. For creates, validate the target terminal against user scope before insert. For moves between terminals, require

access to the source and destination plus the specific transfer permission.

Prevent time-of-check/time-of-use errors

A resource can change terminal between checking access and updating it. Combine authorization with an optimistic version condition or appropriate transaction/locking strategy. If the version or scope changes, reload and re-evaluate. For approval workflows, enforce maker/checker separation in the same transaction boundary as approval state changes.

Service-to-service calls

Where a backend acts for the user within the same API audience, relay the access token over a trusted channel and enforce policy again at the receiving service. For independent background work use a workload identity and least-privilege client credentials. Record the initiating user as audit context rather than pretending an expired user token is still valid.

7. Distributed BFF, Redis and token refresh

Figure 4. Shared state makes BFF replicas interchangeable; explicit refresh coordination prevents reuse of a rotated refresh token.




Figure 4. Shared state makes BFF replicas interchangeable; explicit refresh coordination prevents reuse of a rotated refresh token.

Shared state is an implementation requirement

Store Spring Session security context, authorization-request state and authorized-client data in shared storage. Spring Session Redis alone does not prove that OAuth authorized clients are persisted correctly: configure an explicit shared repository/service or a session-backed repository with its full token state serialized safely. Default in-memory token storage is unsuitable across replicas.

Key token state by a strong server session identifier and client registration. Suggested fields: issuer, subject, registrationId, token expiry, encrypted access/refresh token, tokenVersion, sessionGeneration and status. Protect Redis with TLS, ACLs, private network access and encryption at rest; use application-level token encryption where required by the threat model. Restrict serializer types and never enable unsafe polymorphic deserialization.

Any replica may handle login callback or later requests because transaction and token state are shared. Sticky sessions are unnecessary for correctness. Existing WebSocket connections remain attached to the handling pod until reconnect; reconnect may reach any healthy replica.

7.1 Refresh algorithm and expiry while processing

Before relaying an API request

Use a proposed refresh safety window of 60 seconds, subject to clock skew and measured request latency. If the token remains valid beyond the window, relay it. Otherwise acquire a bounded per-session/per-client refresh lease with a unique owner ID. Reload token state after acquisition: another pod may already have refreshed it. Only the owner calls the IdP with the current refresh token.

After refresh, atomically replace access token, refresh token if rotated, expiry and version only if the session is still active and the expected session generation/tokenVersion matches. Release the lease using compare-owner-and-delete. Other pods wait for a bounded interval and reread, then return a retryable error or require reauthentication. They must not refresh using a stale snapshot.

Race and failure cases

Condition	Required behavior
invalid_grant / detected token reuse	Invalidate authorized client and session; clear cookie; return 401. Do not loop refresh.
Temporary IdP failure	Return 503 if no usable token remains. Never bypass expiry or authorization.
Refresh timeout after possible rotation	Outcome may be ambiguous. Quarantine refresh state and require login rather than blindly reusing an old refresh token.
Lease expires while owner is running	Use renewal within strict limits and guarded writes. If ownership/outcome is uncertain, stop refresh and reauthenticate.
Redis unavailable	Fail closed for protected BFF requests. Do not fall back to pod-local tokens.
Logout races with refresh	Session tombstone/generation prevents writeback and session recreation. Retain it for the bounded in-flight refresh lifetime.

If the token expires during a downstream request

A resource server normally checks token validity when authenticating the request. Passing expiry later does not automatically cancel an already authenticated operation. A later call to another service validates the token again and may reject it. Long-running workflows must use durable jobs and appropriate workload credentials rather than keeping user tokens valid indefinitely.

A clear invalid_token response may trigger one controlled refresh and retry only when replay is safe. Read-only requests can normally be retried. A state-changing request requires a server-enforced idempotency key or proof it was rejected before execution. Never blindly retry a POST after a timeout, never retry 403 as token expiry, and never refresh in the gateway or microservices.

8. Logout, revocation and session policy

Logout sequence

1. React sends POST /bff/api/v1/logout-requests with CSRF. 2. BFF marks the session inactive and increments its generation/tombstone before clearing token data. 3. Remove shared session and authorized-client state; close tracked WebSocket sessions. 4. Revoke the refresh token at the IdP where supported. 5. Expire the browser cookie with the same name/path. 6. If global SSO logout is required, use the provider-supported RP-initiated logout flow and approved return URI. Record success/failure without tokens.

Deleting the BFF session stops browser access through that BFF immediately. It does not automatically invalidate an already issued self-contained JWT at every service. Provider revocation semantics vary. For strict rapid revocation, enforce a distributed jti/sid/session-generation deny state at every enforcement point or use supported introspection/reference tokens. Set an explicit maximum propagation delay and test it.

Starting policy values - subject to BAC approval

Setting	Proposed initial value / rule
Access-token lifetime	5 minutes; align with IdP capabilities and operational risk
Refresh safety window	60 seconds plus tested clock-skew policy
Browser idle timeout	15 minutes, tuned for operational usability
Absolute session lifetime	8 hours; force reauthentication at limit
Refresh-token lifetime	Bound by approved IdP policy; session may not outlive it
Sensitive operations	Step-up / recent authentication where supported; fresh authorization
Revocation target	At most 30 seconds where rapid revocation is required; otherwise bound residual access by token expiry
Session identifier	Cryptographically random, at least 128 bits entropy

Idle, absolute and token limits must be enforced server-side, not only by Redis TTL. Prevent sliding TTL from extending the absolute session limit. On account disable or role change, use provider events/back-channel logout where supported plus policy-cache invalidation. Keycloak and Entra group-change, token and logout semantics require provider-specific verification.

9. Third-party REST and WebSocket access

Machine-to-machine REST does not use browser sessions

A third-party system uses its own registered confidential client. It obtains an access token from the approved IdP using client credentials, and calls a dedicated integration hostname through a restricted integration ALB/ingress to the gateway. This path does not go through the browser BFF because no browser session exists.

```
Partner -> IdP token endpoint (client authentication)
Partner -> HTTPS integration.aobp.example.com/partner-api/v1/resources
```

```
Restricted integration ALB -> Gateway integration listener -> Microservice
```

Expose only a narrow route set and distinct machine scopes/roles on the integration listener or a separate gateway deployment. Use IP restrictions/private connectivity, quotas and mTLS where required. Authorize the application identity, not a fictitious user. Browser cookie authentication is rejected on this path. The browser BFF path must not be bypassable through broad partner routes; require appropriate client/application identity and grants.

Delegated user integration

If an integration truly acts for a user, use an approved delegated/OBO/token-exchange mechanism with the correct audience and consent. Do not use stored usernames/passwords or pass the browser session to a partner. Outbound integrations receive destination-specific credentials, never arbitrary AOBP bearer tokens.

WebSocket behavior

The browser opens wss://aobp.example.com/bff/ws/v1/events. BFF authenticates the session cookie and validates the exact Origin before upgrade. It opens a controlled direct backend connection with a server-added Authorization header. The browser WebSocket API cannot set arbitrary Authorization headers, so do not put OAuth tokens in query parameters.

A connection upgrade is authenticated once; every subscription/message still needs authorization. Cap connection lifetime, periodically recheck session/revocation and close connections on logout/expiry. Token refresh does not automatically reauthenticate an existing backend WebSocket. Define a reconnect/re-authentication protocol before token or session expiry. Configure ALB idle timeout, heartbeats, connection draining and gateway upgrade routing, then test reconnect across replicas.

10. Security risks and attack-point mitigations

Figure 6. Defense in depth across browser, login, session store and private API boundaries.



Figure 6. Defense in depth across browser, login, session store and private API boundaries.

Risk	Specific mitigation and residual exposure
XSS / MFE compromise	No browser OAuth tokens; CSP, encoding and dependency control. Malicious script can still use the active session.
Cookie theft / CSRF	TLS, HttpOnly/Secure cookie, session rotation, CSRF token and Origin validation. Browser/device compromise remains a risk.
Login substitution / redirect abuse	State, nonce, PKCE, exact redirect and allowlisted local return paths.

Risk	Specific mitigation and residual exposure
SSRF / token exfiltration	Fixed BFF proxy allowlist, blocked arbitrary destinations, restricted egress and sanitized redirects.
IDOR / excessive exports	Service resource ABAC, query scope, transactional recheck and bulk limits.
Refresh-token race / Redis compromise	Single refresh owner, versioned updates, private TLS Redis and encrypted token state.
Gateway bypass / forged headers	Private services, network restrictions and independent JWT validation; reject client identity headers.

10.1 Deployment hardening and operations

Kubernetes controls

Run UI, BFF, optional edge gateway and Authorization Management Service with at least two replicas spread over Availability Zones. Use topology spread constraints, readiness/startup/liveness probes, PodDisruptionBudgets and graceful termination. Start BFF at 2 replicas, optional gateway at 2 and Authorization Management Service at 2; these are availability baselines, not capacity sizing. Set CPU/memory requests and limits using measured load, and scale with HPA including latency/connection metrics where useful.

Use default-deny ingress and egress NetworkPolicies with an enforcing CNI configuration. Explicitly allow ALB target traffic, edge-to-BFF where used, BFF-to-service, service-to-policy-distribution, BFF-to-Redis, service-to-DB, DNS and approved IdP/telemetry egress. Native NetworkPolicy cannot generally express an IdP FQDN; use supported egress controls/proxy and account for changing provider addresses. Security groups constrain ALB targets and data stores.

Apply non-root containers, read-only root filesystems where feasible, dropped Linux capabilities, seccomp and restricted Pod Security admission. Use EKS Pod Identity/IRSA rather than static AWS keys. Restrict control-plane access, Kubernetes RBAC and secret access. Pin supported image versions, scan dependencies and containers, sign artifacts, and promote identical images through environments. If Istio is used, enforce strict mTLS and workload authorization policies; JWT and business authorization remain required.

Monitoring without leaking credentials

Propagate W3C trace context through BFF, gateway, services and policy distribution and optional explicit fresh-entitlement calls. Log UTC time, traceId, service, route template, operation, outcome, latency, policyVersion and decisionId. Audit role/policy changes, auth outcomes, denied access, refresh failure, logout, exports and administrative actions. Minimize or pseudonymize issuer/subject according to retention policy.

Never log Authorization, Cookie, Set-Cookie, tokens, PKCE verifier, client secret or OIDC code/state query values. Redact at ALB/edge access-log handling as well as application instrumentation. Restrict access to unavoidable sensitive edge logs and set retention. Alert on 401/403 spikes, reuse detection, refresh contention, Redis latency, policy timeouts and unexpected routes.

Failure and DR behavior

Redis Multi-AZ failover is not lossless; a recently rotated token/session write may be lost, requiring re-login. Do not promise zero RPO for sessions. RDS backups/PITR protect authorization configuration. For on-prem primary and AWS DR, reproduce the same trust boundaries and issuer configuration, promote policy/business data under the DR plan, and prefer fresh SSO sessions after failover. Never assume active Redis sessions can be transparently moved across sites.

11. Authorization Database

Retain the source design principle: authorization storage is independent of application/microservice registration tables. One AOBP application can share business permissions across services. Endpoint/permission mappings remain version-controlled configuration, or governed policy data when dynamic changes are required.

Entity	Key fields and constraints
AOBP_ROLE	role_code PK, description, enabled, policy_version
PERMISSION	permission_code PK, description, enabled
ROLE_PERMISSION	role_code FK + permission_code FK; composite PK
IDP_ROLE_MAPPING	mapping_id PK, issuer, entitlement_type, entitlement_id, role_code FK; unique mapping tuple
ACCESS_SCOPE_GRANT	issuer + subject_id or entitlement reference, scope_type, scope_value, enabled; explicit uniqueness
POLICY	policy_id PK, policy_version, action, resource_type, rule, enabled, approval metadata
POLICY_AUDIT	audit_id PK, actor issuer/subject, operation, before/after reference, timestamp, trace_id
SESSION_REVOCATION (if required)	issuer + sid/jti or session generation, expires_at, reason; shared enforcement state

Boundary between identity and authorization

ACCESS_SCOPE_GRANT is not a local user account. It records who is entitled to which resource scope using an external issuer/subject reference. Prefer BAC-managed attributes/groups when they provide the necessary scope. Do not add passwords, duplicate user lifecycle or treat copied profile attributes as an authoritative directory.

Foreign keys and unique constraints prevent duplicate role assignments. Require controlled administration and audit for permission/mapping changes. Enforce segregation of duties for privileged policy changes. Use safe parameterized SQL, bounded queries and least-privilege database roles. Cache invalidation follows the committed policy version, rather than uncommitted administration events.

Keep transient credentials separate

OAuth sessions and refresh tokens are transient security state in the protected BFF store. They are not columns in the role/permission schema. Audit records retain safe identity references and outcomes, never token values. Encryption-key access is separated from normal database administration where practical.

12. Implementation acceptance and rollout

Acceptance test	Pass condition
Browser token inspection	No OAuth token in browser storage, app responses or URLs; OIDC callback contains code only
SSO callback / replica switch	Login initiated on pod A and callback on B succeeds using shared state; wrong state/nonce fails
Route enforcement	Browser cannot reach gateway/services directly or exploit UI catch-all to bypass BFF
CSRF / fixation	Unsafe request without valid CSRF fails; session ID changes after login
JWT validation	Wrong issuer/audience/signature, expired token and ID token as bearer are rejected
RBAC / ABAC	Missing permission denied; T1 user cannot read/update T2 record or export it
Distributed refresh	Concurrent calls across pods cause one refresh; no stale token overwrite or repeated rotation
Refresh + logout race	Late refresh cannot recreate logged-out session; revocation reaches all required points
Retry safety	POST timeout does not cause duplicate update; idempotency contract verified
Dependency failure	Redis/IdP/policy outage follows documented 401/503 behavior with no fail-open
WebSocket / third party	Origin/session rejection, revoke/reconnect behavior and isolated machine scopes verified
Resilience / tracing	Pod/AZ failover tested; complete trace without credential leakage

Delivery sequence

Phase 1: agree BAC IdP, origin, client/audience registration, session limits and revocation target. Phase 2: implement BFF login/session/CSRF and shared authorized-client persistence. Phase 3: enforce direct private service routes, policy distribution and service-local RBAC/ABAC, then distributed refresh and logout. Phase 4: add integration/WebSocket controls, perform attack-path tests and load/failover tests. Phase 5: pilot, monitor, then retire the SPA token path and its public OAuth registration if no longer used.

This document is a proposed target architecture and implementation specification. It does not claim that the current application or EKS cluster already implements or passes these controls. Final pod resources, throughput targets and DR objectives require measured workload and BAC service requirements.

13. Decision record and technical references

Decision	Reason and consequence
BFF owns browser OAuth	Avoid browser bearer-token exposure; adds session/CSRF responsibilities
ALB -> optional edge gateway -> BFF -> private services	Clear session boundary with no mandatory internal authorization proxy
Separate UI deployment, same origin	Independent releases with simpler cookies and routing
Shared Redis + explicit token repository	Replica independence; state-store outage requires controlled failure
RBAC and ABAC at each service	One authoritative resource-owning enforcement point; centrally managed policy prevents drift
Separate machine API entry	Client credentials and scopes without browser cookies
Re-login after uncertain refresh / DR	Prioritize credential consistency over invisible session continuity

Verified primary references - 2 November 2026

The architecture choices above are AOBP design decisions informed by the references below; they are not claims of automatic compliance. Product behavior must be verified for the selected supported Spring, EKS and IdP versions.

R1. IETF RFC 10017, OAuth 2.0 for Browser-Based Applications, section 6.1 | https://datatracker.ietf.org/doc/html/rfc10017

R2. IETF RFC 9700, Best Current Practice for OAuth 2.0 Security | https://www.rfc-editor.org/info/rfc9700/

R3. AWS EKS: Route application traffic with Application Load Balancers | https://docs.aws.amazon.com/eks/latest/userguide/alb-ingress.html

R4. AWS EKS: Network security best practices | https://docs.aws.amazon.com/eks/latest/best-practices/network-security.html

R5. Spring Security: Authorized Client Features | https://docs.spring.io/spring-security/reference/servlet/oauth2/client/authorized-clients.html

R6. Spring Cloud Gateway: TokenRelay filter and storage note | https://docs.spring.io/spring-cloud-gateway/reference/spring-cloud-gateway-server-webmvc/filters/tokenrelay.html

R7. Spring Session: Integration with Spring Security | https://docs.spring.io/spring-session/reference/guides/java-security.html

R8. OWASP: Cross-Site Request Forgery Prevention Cheat Sheet | https://cheatsheetseries.owasp.org/cheatsheets/Cross-Site_Request_Forgery_Prevention_Cheat_Sheet.html

Reference mapping: BFF responsibilities and separate static hosting: R1. OAuth protections and refresh policies: R2. ALB placement: R3. Network isolation: R4. Client token refresh/relay implementation: R5-R7. Browser CSRF safeguards: R8. Distributed refresh locking, topology, session limits and gateway ordering are explicit project design decisions requiring implementation and tests.