

dable manual

Henrik Renlund

October 9, 2025

Contents

1	Introduction	3
2	Types	4
2.1	The guide	7
2.2	Variable and survival tables	9
3	Simple descriptive tables	12
3.1	Table stratification	14
3.1.1	Other descriptive functions	16
3.1.2	Change default functions	16
3.2	An emphasis on weight	17
3.3	Table comparisons	17
3.4	Table tests	20
3.5	Custom made functions	21
3.5.1	Custom made describers	21
3.5.2	The 'meta' attribute	22
3.5.3	Custom made describers for surv	22
3.5.4	Custom made comparers/testers	23
3.5.5	Custom made comparers/testers for surv	23
3.6	The information functions are privy to	24
3.7	Some notes on formatting	25
4	Baseline tables	26
4.1	Baseline theme 0 (default)	27
4.1.1	Baseline theme 1 ≈ 0	28
4.2	Baseline theme 2	29
4.3	Adjusting the baseline table	30
4.4	Behind the scenes of baseline tables	31
A	Loose ends	34
B	Testing	35
B.1	Default describers	35
B.2	Default comparers	36
B.3	Default testers	37
B.4	Default baseline	38

List of Figures

1	Possible mappings.	5
---	----------------------------	---

List of Tables

1	The basic mapping idea.	4
2	Default baseline table	11
3	Default L ^A T _E X output for descriptive table.	15
4	Descriptive table using less meta data.	15
5	Descriptive table with comparison.	18
6	Descriptive table with comparison order changed.	18
7	Comparison <i>across</i> the groups.	19
8	Comparison between <i>adjacent</i> groups.	19
9	Comparison between chosen groups.	20
10	Descriptive table with test.	20
11	Descriptive table with selected testing.	21
12	Baseline table theme 0 (default)	27
13	Baseline table theme 1.	28
14	Baseline table theme 2.	29
15	Adjusted baseline table	30
16	Table with info added in the foot.	32
17	Table with info added as footnotes.	32

1 Introduction

A *dable*, i.e. a *descriptive table*, has up to 3 (optional) parts consisting of

- descriptions (`desc`),

and if a stratification (grouping) is given, also

- comparisons (`comp`), as well as
- tests (`test`).

The table-creating functions will respond to a `part` argument which specifies which parts are wanted, with only the descriptive part being returned by default.

Each variable is given a type (Section 2), and each type is associated with its own set of functions to create the parts (Section 3.1.1). One must always choose one of these (or accept the default) to e.g. create the description part, but it is also possible to provide user defined functions (Section 3.5.1).

It is also possible to provide a *variable table* (`vtab`, Section 2.2) that provides a label and a group for each variable. The grouping can be used to group the rows of the output tables (if generated in e.g. \LaTeX).

The package initially tried to strictly separate table creation into

- (1) generate the statistics/numbers that go into the table
- (2) format for a desired output generating program/language

This aim has not quite been achieved, but almost. It works pretty well for default versions of *simple descriptive tables* (Section 3), but is harder to do for *baseline tables* (Section 4). The compromise reached is that one can set package parameters pointing to the desired output. As an example, this document is generated in \LaTeX so we could begin by restoring all defaults with that output¹ in mind - although this is superfluous since this currently is the default.

```
dpset_defaults(overwrite = TRUE, style = "latex") ## already the default
```

¹Currently, this actually does very little - it's main purpose is to set the `output` parameter to "latex". The most obvious problem in this context is the fact that '%' has a special meaning, but that is easy to substitute just before translating to \LaTeX code.

2 Types

To determine how to deal with a variable we classify it as

- numeric (**real**),
- categorical (**catg**),
- date (**date**), or
- time-to-event (**surv**).

Of course, a time-to-event variable will actually consist of a pair of variables - more on that later. There are also subcategories of **catg**:

- *binary* variables (**bnry**) are dichotomous variables where it should be completely obvious what the two levels are if you are only given one. The idea is that for these variables, it typically suffices to describe (e.g. by a count and/or percentage) one of the levels.
- *lavish categorical* variables (**lcat**) are those where there are too many unique values to routinely include value-level information in a table (e.g. an id-variable of some sort).

There is a non-surprising general idea of a mapping from the class (in R), of a variable, to the dable *type*, given by Table 1.

Table 1: The basic mapping idea.

R class	→	dable type
numeric, integer		real
factor, character, logical		catg (or bnry / lcat)
Date		date

But the types can be changed, manually or through parameters, so that e.g. integer variables with a small number of unique values can be describes as if it was categorical. See Figure 1 for a the full set of possible automatic mappings.

The parameters one can set that will alter the general mapping are given by:

- **real.tol** is an integer n and, if set, re-types a **real** variable to a **catg** variable *if* the number of unique values is $\leq n$. Why? **real** types typically describe variables measured on a continuous scale and if the number of unique values is low, it is probably a coding for something else *or* something you want described as a **catg**.
- **catg.tol** is an integer n and, if set, re-types a **catg** variable to a **lcat** variable *if* the number of unique values is $> n$. Why? Some categorical data just have too many levels to include in a descriptive table, the **lcat** type is meant to provide alternative descriptions for these.
- **bnry.list** is a list of length 2 vectors specifying, respectively, what the set of unique values can be in order for a variable to end up with the **bnry** type. Why? The **bnry** variables will generally only show descriptiv measures for the reference level, thus it must be clear from that level alone what the non-showing level is.




Figure 1: Possible mappings. For both numeric/integer and factor/character/logical, if there are exactly 2 unique values corresponding to one of the elements of `bnry.list`, they get type `bnry`. If number of unique values of a numeric/integer variable is `real.tol` or less, the type is `catg`. If number of unique values of a factor/character variable is strictly greater than `catg.tol`, the type is `lcat`. The `surv` type is determined through given names or pattern matching.

We can inspect the default values thus

```
dpget("real.tol")
## [1] 5

dpget("catg.tol")
## [1] 50

dpget("bnry.list")
## [[1]]
## [1] 0 1
##
## [[2]]
## [1] FALSE TRUE
##
## [[3]]
## [1] "No" "Yes"
##
## [[4]]
## [1] "no" "yes"
```

The time-to-event variable pairs need to be specified with a *survival table* (**stab**), an example of which is given in the package

```
test_stab()
## label time event
## 1 Foo t.foo ev.foo
## 2 Bar t.bar ev.bar
```

But - if one utilizes a naming scheme where the time- and status component of a time-to-event variable differs only by a consistent use of a prefix or suffix, these variables can be identified automatically!

The default is to use a prefix **t.** and **ev.** for the time- and event/status component, respectively.

```
dpget("surv.prefix") ## is prefix used? (else suffix)
## [1] TRUE

dpget("surv.affix") ## what is the affix used?

## time event
## "t." "ev."
```

2.1 The guide

The packages provides a test data set

```
d <- test_data()
str(d)

## 'data.frame': 1000 obs. of 24 variables:
## $ id      : int  1 2 3 4 5 6 7 8 9 10 ...
## $ pid     : chr  "id1" "id2" "id3" "id4" ...
## $ status  : chr  "included" "included" "included" "included" ...
## $ country : Factor w/ 3 levels "SW","NO","DE": 1 3 1 2 1 3 3 2 2 3 ...
## $ area    : chr  "urban" "rural" "urban" "urban" ...
## $ offspring : logi  TRUE TRUE FALSE TRUE FALSE FALSE ...
## $ age     : num  50 54 44 75 37 64 36 42 67 56 ...
## $ male    : int  1 0 0 0 1 0 0 0 0 1 ...
## $ measA   : num  10.9 42.4 91.1 16 77.4 ...
## $ measNA  : num  NA NA NA NA NA NA NA NA NA NA ...
## $ forgotten : num  -0.899 -0.433 0.753 0.905 -0.803 ...
## $ importance: num  2.7 2 3.3 4.4 4.3 3.6 5.2 6 5.1 4.6 ...
## $ index   : Date, format: "2017-08-14" "2017-08-25" ...
## $ posix   : POSIXct, format: "2017-04-04 23:51:11" "2017-05-15 15:28:34" ...
## $ ev.foo  : int  1 1 1 0 0 1 1 0 0 0 ...
## $ ev.bar  : int  0 0 0 1 0 0 0 0 0 0 ...
## $ t.bar   : num  365 365 365 157 365 ...
## $ t.foo   : num  130.5 21.5 16.3 365 365 ...
## $ end     : Date, format: "2018-08-14" "2018-08-25" ...
## $ measB   : num  58.5 13.3 26.8 NA 29.4 ...
## $ measM   : num  2.99 NA NA NA 84.5 ...
## $ gender  : Factor w/ 2 levels "male","female": 1 2 2 2 1 2 2 2 2 1 ...
## $ kids    : int  1 2 0 3 0 0 2 0 0 0 ...
## $ region  : chr  "A" "E" "B" "C" ...
```

We can use this data set to illustrate the *data guide* (`dguide`).

```
(g <- dguide(d))

## data guide:
##           term      type      class      label      group
## 1           id      real      integer      id      Covariates
## 2          pid      lcat      character      pid      Covariates
## 3        status      catg      character      status      Covariates
## 4        country      catg      factor      country      Covariates
## 5          area      catg      character      area      Covariates
## 6    offspring      bnry      logical  offspring      Covariates
## 7           age      real      numeric      age      Covariates
## 8          male      bnry      integer      male      Covariates
## 9        measA      real      numeric      measA      Covariates
## 10       measNA missing      numeric      measNA      Covariates
## 11   forgotten      real      numeric  forgotten      Covariates
## 12  importance      real      numeric  importance      Covariates
## 13         index      date      Date      index      Covariates
## 14        posix unknown      POSIXct      posix      Covariates
## 17          end      date      Date      end      Covariates
## 18        measB      real      numeric      measB      Covariates
## 19        measM      real      numeric      measM      Covariates
## 20        gender      catg      factor      gender      Covariates
## 21          kids      real      integer      kids      Covariates
## 22        region      catg      character      region      Covariates
## 16 ev.bar / t.bar      surv integer / numeric      bar Time-to-event
## 15 ev.foo / t.foo      surv integer / numeric      foo Time-to-event
## with stab:
##   label time event      group
## 1   bar t.bar ev.bar Time-to-event
## 2   foo t.foo ev.foo Time-to-event
```

Note that the guide provides an automatically generated survival table based on the naming of variables. Also, a default grouping of variables is always created with the value

```
dpget("vtab.group.name")

## [1] "Covariates"
```

for all but the time-to-event variables which are grouped as

```
dpget("stab.group.name")

## [1] "Time-to-event"
```


One can manually update the guide

```
g$type[g$term == "id"] <- "lcat"
```

or provide some parameters to influence the types.

The arguments for `dguide`:

- `data` the data (duh!)
- `id` a character vector of the terms that are id variables; these will be typed as `lcat`. (Also, the first entry will be singled out as the "unit id" and hidden from tables unless you set the dable option `unit.id.rm` to `FALSE`.)
- `elim.set` a character vector of variables to ignore
- `vtab` a "variable table", i.e. a `data.frame` with columns `term`, `label`, an optionally `group`. This table informs the `label` and `group` column of the guide.
- `stab` a "survival table", i.e. a `data.frame` with columns `label`, `time`, `event`, an optionally `group`.
- ... arguments passed to `term_type`.

2.2 Variable and survival tables

There are examples of `vtab` and `stab` in the package

```
(vt <- test_vtab())

##      term      label      group
## 1      id  ID (integer)  Meta data
## 2     pid         ID      Meta data
## 3   status  A constant  Meta data
## 4    index      Index  Meta data
## 5   posix  Unkown format  Meta data
## 6     end         End  Meta data
## 7     age         Age  Demographics
## 8    male         Male  Demographics
## 9   gender      Gender  Demographics
## 10  country      Country  Demographics
## 11    area         Area  Demographics
## 12  region      Region  Demographics
## 13 offspring  Offspring  Measures etc.
## 14    kids      Kid count  Measures etc.
## 15   measA      A measure  Measures etc.
## 16   measB  Another measure  Measures etc.
## 17   measM  Manly measure  Measures etc.
## 18  measNA  Missing measure  Measures etc.

(st <- test_stab())

##  label time event
## 1   Foo t.foo ev.foo
## 2   Bar t.bar ev.bar
```

The survival table has no grouping, so we can provide one

```
st$group <- "Outcomes"
```

We can see what the guide looks like, if we add some additional arguments:

```
(g <- dguide(d, id = c("id", "pid"), vtab = vt, stab = st))

## data guide:
##      term      type      class      label      group
## 1      id unit.id    integer    ID (integer)  Meta data
## 2      pid      lcat    character    ID        Meta data
## 3      status   catg    character    A constant  Meta data
## 13     index    date     Date        Index      Meta data
## 14     posix   unknown   POSIXct    Unkown format  Meta data
## 17     end      date     Date        End        Meta data
## 7      age      real     numeric    Age        Demographics
## 8      male     bnry     integer    Male       Demographics
## 20     gender   catg     factor     Gender     Demographics
## 4      country  catg     factor     Country    Demographics
## 5      area     catg     character    Area       Demographics
## 22     region   catg     character    Region     Demographics
## 6      offspring bnry     logical    Offspring  Measures etc.
## 21     kids     real     integer    Kid count  Measures etc.
## 9      measA    real     numeric    A measure  Measures etc.
## 18     measB    real     numeric    Another measure  Measures etc.
## 19     measM    real     numeric    Manly measure  Measures etc.
## 10     measNA   missing  numeric    Missing measure  Measures etc.
## 15     ev.foo / t.foo  surv integer / numeric    Foo        Outcomes
## 16     ev.bar / t.bar  surv integer / numeric    Bar        Outcomes
## 11     forgotten    real     numeric    forgotten    Covariates
## 12     importance    real     numeric    importance    Covariates
## with stab:
##   label time event  group
## 1   Foo t.foo ev.foo Outcomes
## 2   Bar t.bar ev.bar Outcomes
```

Note that the variables not specified by the variable table gets the default grouping and are placed at the end.

To see the usefulness of setting up a "variable table", notice that with these preparations the following code generates Table 2:

```
b <- baseline(d, guide = g, gtab = "gender", part = c(T,T,T))
blatex(b, where = "!ht", caption = "Default baseline table",
       label = "tab:default-bsl", size = "small")
```

Table 2: Default baseline table

	male n = 489	female n = 511	Compare male/female	Test male/female
Meta data				
ID	=489=	=511=		
A constant: included	489 (100.0%)	511 (100.0%)		
Index	170101/181229 [1]	170102/181225	-0.035	0.58 [∇]
End	180101/191229 [1]	180102/191225	-0.035	0.58 [∇]
Demographics				
Age	55.0 (48.0 - 55.0)	56.0 (49.0 - 56.0)	-0.069	0.28 ^b
Male: 1	489 (100.0%)	0 (0%)	Inf	<0.0001 [⊥]
Country: SW	173 (35.4%)	178 (34.8%)	0.031	0.88 [⊥]
NO	168 (34.4%)	171 (33.5%)		
DE	148 (30.3%)	162 (31.7%)		
Area: rural	101 (20.7%) [2]	103 (20.3%) [3]	0.011	0.92 [⊥]
urban	386 (79.3%)	405 (79.7%)		
Region: A	147 (30.1%)	157 (30.7%)	0.044	0.97 [⊥]
B	105 (21.5%)	108 (21.1%)		
C	65 (13.3%)	61 (11.9%)		
D	86 (17.6%)	93 (18.2%)		
E	86 (17.6%)	92 (18.0%)		
Measures etc.				
Offspring: TRUE	358 (73.2%)	382 (74.8%)	0.035	0.63 [⊥]
Kid count	1.00 (0 - 1.00)	1.00 (0 - 1.00)	-0.019	0.76 ^b
A measure	26.9 (11.5 - 26.9) [5]	30.3 (12.6 - 30.3) [2]	-0.14	0.029 ^b
Another measure	38.7 (18.4 - 38.7) [168]	46.7 (20.3 - 46.7) [171]	-0.13	0.088 ^b
Manly measure	33.6 (14.3 - 33.6)	- [511]		
Outcomes				
Foo	92; 0.00057	109; 0.00066	-0.0036	0.31 [#]
Bar	140; 0.00091	160; 0.0010	-0.0031	0.38 [#]
Covariates				
forgotten	0.025 (-0.47 - 0.025)	-0.023 (-0.50 - -0.023)	0.022	0.72 ^b
importance	3.10 (1.60 - 3.10)	3.30 (1.70 - 3.30)	-0.091	0.15 ^b

Rows: 1000 (male:489, female:511). No duplicate subjects. [⊥] Chi-square. [∇] Wilcoxon. ^b t-test. [#] Log rank. Categorical variable: =unique values=. [n] is missing count (if applicable). Categorical variable: Count (Percent). Date variables: min/max. Numeric variable: Median (Q1-Q3). Time-to-event variable: events; rate

3 Simple descriptive tables

A *simple descriptive table* describes only 1 type. Tables describing *all* variables will be referred to as *baseline tables* - so we will cut the "simple" and just refer to the tables in this section as *descriptive*. The workhorse for all tables is the `dable` function. To create the default descriptive table for the real type we use

```
dable(d, type = "real", guide = g)

##           term           Mean      SD
## 1          age 55.332000000 10.072399
## 2         kids  1.472000000  1.206097
## 3        measA 41.058453071 42.242859
## 4        measB 61.475041370 58.837329
## 5        measM 47.721624171 44.726907
## 6   forgotten  0.001249743  0.577495
## 7 importance  3.168900000  1.739416
```

where the output is ordered as the guide since we supply the guide as an argument.

There is a shorthand for each type, and some .

```
dreal(d, guide = g)

##           term           Mean      SD
## 1          age 55.332000000 10.072399
## 2         kids  1.472000000  1.206097
## 3        measA 41.058453071 42.242859
## 4        measB 61.475041370 58.837329
## 5        measM 47.721624171 44.726907
## 6   forgotten  0.001249743  0.577495
## 7 importance  3.168900000  1.739416
```

```
dcatg(d, guide = g)

##           term   Level Count Proportion
## 1   status included   1000  1.0000000
## 2   gender      male    489  0.4890000
## 3   gender      female  511  0.5110000
## 4   country      SW    351  0.3510000
## 5   country      NO    339  0.3390000
## 6   country      DE    310  0.3100000
## 7    area      rural   204  0.2050251
## 8    area      urban   791  0.7949749
## 9   region      A    304  0.3040000
## 10  region      B    213  0.2130000
## 11  region      C    126  0.1260000
## 12  region      D    179  0.1790000
## 13  region      E    178  0.1780000
```

```
dbnry(d, guide = g)
```

```
##      term Level Count Proportion
## 1    male      1   489      0.489
## 2 offspring TRUE   740      0.740

dlcat(d, guide = g)

##      term Unique
## 1  pid    1000

ddate(d, guide = g)

##      term      min      max
## 1 index 170101 181229
## 2   end 180101 191229

dsurv(d, guide = g)

##      term      Time Events      Rate
## 1  Foo 325923.1    201 0.0006167099
## 2  Bar 311600.9    300 0.0009627700
```

Some of these accept type specific extra arguments, which can be of interest

```
ddate(d, guide = g, date.format = "%Y-%m-%d")

##      term      min      max
## 1 index 2017-01-01 2018-12-29
## 2   end 2018-01-01 2019-12-29

dsurv(d, guide = g, time.unit = 365.25)

##      term      Time Events      Rate
## 1  Foo 892.3288    201 0.2252533
## 2  Bar 853.1167    300 0.3516518
```

Also, `dcatg` has the option to include the subtypes `bnry` and `lcat`, respectively.

```
dcatg(d, guide = g, bnry = TRUE, lcat = FALSE)

##      term      Level Count Proportion
## 1    status included  1000 1.0000000
## 2     male          0   511 0.5110000
## 3     male          1   489 0.4890000
## 4   gender      male  489 0.4890000
## 5   gender    female  511 0.5110000
## 6  country      SW   351 0.3510000
## 7  country      NO   339 0.3390000
## 8  country      DE   310 0.3100000
## 9    area      rural  204 0.2050251
## 10   area      urban  791 0.7949749
## 11  region        A   304 0.3040000
## 12  region        B   213 0.2130000
```

```
## 13    region      C    126  0.1260000
## 14    region      D    179  0.1790000
## 15    region      E    178  0.1780000
## 16 offspring FALSE  260  0.2600000
## 17 offspring  TRUE  740  0.7400000
```

3.1 Table stratification

Tables can be stratified using a *grouping table* (`gtab`). We are slightly overloading the "group" terminology here; the groups use to stratify a table have nothing to do with `group` column of the guide - those can be used to group rows of the output table created in e.g. \LaTeX , whereas the `gtab` group columns of the descriptive table.

The simplest way to create a stratification is to point to a grouping variable

```
(dt <- dreal(d, guide = g, gtab = "gender"))

##      term      Mean      SD      Mean      SD
## 1    age 54.977505112 10.3251198 55.671232877 9.8226197
## 2   kids  1.460122699  1.1886350  1.483365949  1.2236306
## 3 measA 38.059724024 38.8539428 43.909896801 45.0839527
## 4 measB 57.459770884 55.8057254 65.265929095 61.4038813
## 5 measM 47.721624171 44.7269066      NaN      NA
## 6 forgotten 0.007871068 0.5604131 -0.005086515 0.5938614
## 7 importance 3.088343558 1.7199192  3.245988258 1.7560926
```

Note that column names become duplicated, but there is "meta data" in the attributes that keeps track of which columns belong to which grouping.

```
attr(dt, "part")

## [1] "meta"      "desc:male" "desc:male" "desc:female" "desc:female"
```

In, fact there is even more meta data behind the scene; if we pass this object to `datex`, it generates the \LaTeX code for a table, using some of this additional information as can be seen in Table 3.

```
datex(dt, label = "tab:datex",
      caption = "Default \\LaTeX\\, output for descriptive table.")
```

The package assumes utilization of meta data is wanted. If not, one typically have to turn these features off, see Table 4.

```
datex(dt, row.group = FALSE, lab = FALSE, label = "tab:datex-less",
      caption = "Descriptive table using less meta data.")
```

Table 3: Default \LaTeX output for descriptive table.

	male		female	
	Mean	SD	Mean	SD
Demographics				
Age	55.0	10.3	55.7	9.82
Measures etc.				
Kid count	1.46	1.19	1.48	1.22
A measure	38.1	38.9	43.9	45.1
Another measure	57.5	55.8	65.3	61.4
Manly measure	47.7	44.7		
Covariates				
forgotten	0.0079	0.56	-0.0051	0.59
importance	3.09	1.72	3.25	1.76

Rows: 1000 (male:489, female:511). No duplicate subjects

Table 4: Descriptive table using less meta data.

	male		female	
	Mean	SD	Mean	SD
Age	55.0	10.3	55.7	9.82
Kid count	1.46	1.19	1.48	1.22
A measure	38.1	38.9	43.9	45.1
Another measure	57.5	55.8	65.3	61.4
Manly measure	47.7	44.7		
forgotten	0.0079	0.56	-0.0051	0.59
importance	3.09	1.72	3.25	1.76

Rows: 1000 (male:489, female:511). No duplicate subjects

But we are digressing. Another way to create a grouping is to use `gtab_maker`, or create one manually - it is simply a data frame with logical columns of length equal to the data set.

```
gt <- gtab_maker("area", data = d, all = TRUE)
head(gt)

##   rural urban All
## 1 FALSE  TRUE TRUE
## 2  TRUE FALSE TRUE
## 3 FALSE  TRUE TRUE
## 4 FALSE  TRUE TRUE
## 5 FALSE  TRUE TRUE
## 6 FALSE  TRUE TRUE
```

Lets use a less frequent type (`lcat`) to illustrate the next point; although the presentation defaults to the order of the `gtab`,

```
(dt <- dlcat(d, guide = g, gtab = gt))

##   term Unique Unique Unique
## 1  pid      204      791    1000

attr(dt, "part") ## ordered as gtab

## [1] "meta"          "desc:rural" "desc:urban" "desc:All"
```

it is possible to change it within the `part` argument.

```
dt <- dlcat(d, guide = g, gtab = gt, part = list("desc" = c(3,1,2)))
attr(dt, "part") ## order now permuted

## [1] "meta"          "desc:All"     "desc:rural"  "desc:urban"
```

It is also possible to specify `desc` as one of "all" (default), "first" or "last" ("none" is also accepted).

```
dt <- dlcat(d, guide = g, gtab = gt, part = "last")
attr(dt, "part") ## now only last group included

## [1] "meta"          "desc:All"
```

3.1.1 Other descriptive functions

If you are not happy with the default description, there are other describer functions to choose from, use `?desc-real` to see all build-in describers for the `real` type, and similar help pages exists for other types and the other parts (`comp/test`). In section 3.5 you can see how to define your own functions. The name of the new function must be supplied to the `fnc` argument. As an example, `min_max` is a built-in function that one can choose

```
dreal(d, fnc = list(desc = "min_max"))

##           term           Min           Max
## 1           id 1.000000000 1000.0000000
## 2           age 25.000000000   85.0000000
## 3          measA  0.018912588 367.3780576
## 4   forgotten -0.999758688   0.9965274
## 5 importance  0.100000000   6.0000000
## 6          measB  0.004979325 362.1742406
## 7          measM  0.195807952 306.1464719
## 8           kids 0.000000000   5.0000000
```

3.1.2 Change default functions

The default values can be viewed with `dpget`, e.g. the default describer, compararer and tester for `real`.


```

dpget("real.desc")
## [1] "mean_sd"
dpget("real.comp")
## [1] "real.std"
dpget("real.test")
## [1] "param"

```

New values can be set with `dpset`.

```
dpset("real.desc", "name_of_new_function") ## no eval
```

You can view *all* package parameters with `dpget_all()`.

3.2 An emphasis on weight

Most built-in describers and comparers has a `weight` argument (when it makes sense) - at the time of writing this is not implemented for the testers. This parameter is explicit in the higher order `dable` function so always exists (even if null), as can be seen in Section 3.6.

Currently, weights can only be specified as a variable in data.

```
dreal(d, guide = g, weight = "importance")
```

3.3 Table comparisons

The comparison part of a descriptive table is accessed by the `part` argument. This can be given either a logical vector of length up to 3 - if shorter, it fills in the missing values with `FALSE`. The position of the elements is associated with the parts: first *descriptions*, second *comparisons* and third *tests*.

```

dt <- dreal(d, guide = g, gtab = "gender", part = c(TRUE, TRUE))
datex(dt, label = "tab:desc-n-comp", row.group = FALSE,
      caption = "Descriptive table with comparison.")

```

But, as we've seen in Section 3.1, one can manipulate the order of the descriptive presentation, and one can change the "order" of the comparison as well. To do so, one provides a list to `part` instead. The first list entry corresponds to descriptions and is `TRUE/FALSE` or a vector of the wanted ordering. The second list entry corresponds to comparison and can be

- `TRUE/FALSE`
- A list of length 2 vectors for the comparison pairs
- A single character value "across" (Table 7) or "adjacent" (Table 8), "none" is also accepted.

So, to change to order of the comparison in Table 5 you use

Table 5: Descriptive table with comparison.

	male		female		Std. diff.
	Mean	SD	Mean	SD	male/female
Age	55.0	10.3	55.7	9.82	-0.069
Kid count	1.46	1.19	1.48	1.22	-0.019
A measure	38.1	38.9	43.9	45.1	-0.14
Another measure	57.5	55.8	65.3	61.4	-0.13
Manly measure	47.7	44.7			
forgotten	0.0079	0.56	-0.0051	0.59	0.022
importance	3.09	1.72	3.25	1.76	-0.091

Rows: 1000 (male:489, female:511). No duplicate subjects

```
dt <- dreal(d, guide = g, gtab = "gender",
  part = list(TRUE, list(c(2,1))))
datex(dt, label = "tab:desc-n-comp-2", row.group = FALSE,
  caption = "Descriptive table with comparison order changed.")
```

Table 6: Descriptive table with comparison order changed.

	male		female		Std. diff.
	Mean	SD	Mean	SD	female/male
Age	55.0	10.3	55.7	9.82	0.069
Kid count	1.46	1.19	1.48	1.22	0.019
A measure	38.1	38.9	43.9	45.1	0.14
Another measure	57.5	55.8	65.3	61.4	0.13
Manly measure	47.7	44.7			
forgotten	0.0079	0.56	-0.0051	0.59	-0.022
importance	3.09	1.72	3.25	1.76	0.091

Rows: 1000 (male:489, female:511). No duplicate subjects

to get Table 6.

To make comparisons "across":

```
dt <- dbnry(d, guide = g, gtab = "region",
            part = list(FALSE, "across"))
datex(dt, label = "tab:across", row.group = FALSE,
       caption = "Comparison \\emph{across} the groups.")
```

Table 7: Comparison *across* the groups.

	Std. diff.			
	A/B	A/C	A/D	A/E
Male	0.019	0.065	0.0062	0.00081
Offspring	0.15	0.13	0.099	0.14

Rows: 1000. No duplicate subjects

To make comparisons "adjacent":

```
dt <- dbnry(d, guide = g, gtab = "region",
            part = list(FALSE, "adjacent"))
datex(dt, label = "tab:adjacent", row.group = FALSE,
       caption = "Comparison between \\emph{adjacent} groups.")
```

Table 8: Comparison between *adjacent* groups.

	Std. diff.			
	A/B	B/C	C/D	D/E
Male	0.019	0.046	0.071	0.0054
Offspring	0.15	0.019	0.034	0.041

Rows: 1000. No duplicate subjects

To make your own comparison:

```
dt <- dbnry(d, guide = g, gtab = "region",
            part = list(FALSE, list(c(1,3), c(5,2))))
datex(dt, label = "tab:comp-list", row.group = FALSE,
      caption = "Comparison between chosen groups.")
```

Table 9: Comparison between chosen groups.

	Std. diff.	
	A/C	E/B
Male	0.065	0.020
Offspring	0.13	0.012

Rows: 1000. No duplicate subjects

3.4 Table tests

The testing part of the `part` argument can be given as `TRUE/FALSE`, with `TRUE` meaning to test all groups

```
dt <- drealm(d, guide = g, gtab = "country", part = c(TRUE,FALSE,TRUE))
datex(dt, label = "tab:desc-test", row.group = FALSE,
      caption = "Descriptive table with test.")
```

Table 10: Descriptive table with test.

	SW		NO		DE		F-test
	Mean	SD	Mean	SD	Mean	SD	SW/NO/DE
Age	55.5	9.78	55.4	10.0	55.1	10.5	0.88
Kid count	1.46	1.16	1.56	1.28	1.38	1.18	0.17
A measure	38.2	39.8	41.9	45.6	43.4	40.9	0.26
Another measure	63.3	62.8			59.4	54.1	0.4
Manly measure	50.8	49.4	46.1	43.2	45.9	40.6	0.53
forgotten	-0.038	0.59	0.022	0.59	0.023	0.55	0.29
importance	3.30	1.67	3.10	1.76	3.09	1.79	0.2

Rows: 1000 (SW:351, NO:339, DE:310). No duplicate subjects

One can also specify wich groups to include in the test

```
dt <- drealm(d, guide = g, gtab = "country", part = list(TRUE,FALSE,c(2,3)))
datex(dt, label = "tab:desc-test-2", row.group = FALSE,
      caption = "Descriptive table with selected testing.")
```

Table 11: Descriptive table with selected testing.

	SW		NO		DE		t-test
	Mean	SD	Mean	SD	Mean	SD	NO/DE
Age	55.5	9.78	55.4	10.0	55.1	10.5	0.71
Kid count	1.46	1.16	1.56	1.28	1.38	1.18	0.068
A measure	38.2	39.8	41.9	45.6	43.4	40.9	0.66
Another measure	63.3	62.8			59.4	54.1	
Manly measure	50.8	49.4	46.1	43.2	45.9	40.6	0.97
forgotten	-0.038	0.59	0.022	0.59	0.023	0.55	0.97
importance	3.30	1.67	3.10	1.76	3.09	1.79	0.95

Rows: 1000 (SW:351, NO:339, DE:310). No duplicate subjects

3.5 Custom made functions

In general, all custom made functions must take a `...` argument - since specific function arguments will be passed on through higher order functions, these additional arguments will be supplied to all describer, comparers, and testers. Therefore, they must tolerate being overfed arguments.

3.5.1 Custom made describers

The recommended way is to define a function that returns a `data.frame`, even if a single value is wanted. This function can be pointed to in the `fnc` argument.

Describers need only take an `x` argument (as well as `...`)

```
IQR <- function(x, ...){
  x <- quantile(x, probs = c(.25, .75), na.rm = TRUE)
  data.frame(IQR = x[2] - x[1])
}
dreal(d, fnc = list(desc = "IQR")) |> head(n = 3)

##      term      IQR
## 1    id 499.50000
## 2   age  14.25000
## 3 measA 43.98454
```

You can point to non-`data.frame`-returning functions as well (as long as they accept `...`), but they will not get great column names

```
dreal(d, fnc = list(desc = "mean"), na.rm = TRUE) |> head(n = 3)

##      term      r
## 1    id 500.50000
## 2   age  55.33200
## 3 measA 41.05845
```

unless you give them a label

```
myMean <- function(x, ...) mean(x, na.rm = TRUE, ...)
attr(myMean, "label") <- "The Mean Value"
dreal(d, fnc = list(desc = "myMean")) |> head(n = 3)

##      term The Mean Value
## 1    id      500.50000
## 2   age      55.33200
## 3 measA      41.05845
```

3.5.2 The 'meta' attribute

Some things a describer returns might be of a meta data character, e.g. the levels of a categorical variable - these are wasteful to repeat in each strata. To that end, there is a 'meta' attribute that can be set (on the function) to tell the program which columns not to repeat across a stratification.

```
myBnry <- function(x, ...){
  if(!is.factor(x)) x <- factor(x)
  data.frame(Level = levels(x),
             Count = as.integer(table(x)))
}
attr(myBnry, "meta") <- "Level"
dbnry(d, gtab = "gender", fnc = list(desc = "myBnry"))

##      term Level Count Count
## 1 offspring FALSE   131   129
## 2 offspring  TRUE   358   382
## 3      male     0     0   511
## 4      male     1   489     0
```

3.5.3 Custom made describers for surv

Decribers for the **surv** type must take a **time** and **event** argument. Note that all functions *can* take extra arguments, and that these can be passed from the higher order functions.

```
Foo <- function(time, event, my.unit.of.time = 'time units', ... ){
  data.frame(Info = sprintf(paste0("%s events in %.2f ", my.unit.of.time),
                             sum(event), sum(time)))
}
dsurv(d, fnc = list(desc = "Foo"))

##      term                               Info
## 1  bar 300 events in 311600.89 time units
## 2  foo 201 events in 325923.10 time units

dsurv(d, fnc = list(desc = "Foo"), my.unit.of.time = "days")

##      term                               Info
## 1  bar 300 events in 311600.89 days
## 2  foo 201 events in 325923.10 days
```

3.5.4 Custom made comparers/testers

Comparers, and testers, must take an `x` and `g` argument. Conceptually, comparers always deal with 2 groups, whereas a tester can deal with any number of groups.

```
Delta <- function(x, g, ...){
  if(!is.factor(g)) g <- factor(g)
  x_i <- g == levels(g)[1]
  y_i <- g == levels(g)[2]
  data.frame(MinDelta = min(x[x_i], na.rm = TRUE) - min(x[y_i], na.rm = TRUE),
             MaxDelta = max(x[x_i], na.rm = TRUE) - max(x[y_i], na.rm = TRUE))
}
dreal(d, gtab = "gender", part = c(F,T), fnc = list(desc=NULL, comp = "Delta"))

##           term      MinDelta      MaxDelta
## 1          id -1.000000000 -1.000000000
## 2         age  3.000000000  0.000000000
## 3      measA -0.043488640 -97.310299769
## 4 forgotten  0.003472922 -0.006842324
## 5 importance  0.000000000  0.000000000
## 6      measB  0.054081002 -7.272849083
## 7      measM        -Inf          Inf
## 8       kids  0.000000000  0.000000000
```

This function could also be supplied as a tester (although it is not testing anything); here is an example where we keep the default comparer:

```
(dt <- dreal(d, gtab = "gender", part = c(F,T,T),
             fnc = list(desc=NULL, comp = NULL, test = "Delta"))

##           term Std. diff.      MinDelta      MaxDelta
## 1          id -0.03630706 -1.000000000 -1.000000000
## 2         age -0.06884267  3.000000000  0.000000000
## 3      measA -0.13901052 -0.043488640 -97.310299769
## 4 forgotten  0.02244206  0.003472922 -0.006842324
## 5 importance -0.09069944  0.000000000  0.000000000
## 6      measB -0.13304830  0.054081002 -7.272849083
## 7      measM      NaN        -Inf          Inf
## 8       kids -0.01926886  0.000000000  0.000000000
```

Recall that what is set as tester or comparer is remembered by the `part` attribute.

```
attr(dt, "part")

## [1] "meta"          "comp:male/female" "test:male/female" "test:male/female"
```

3.5.5 Custom made comparers/testers for surv

Comparers, and testers, for `surv` must take a `time`, `event`, and `g` argument.

```
HR <- function(time, event, g, weight = NULL, ...){
  if(!is.factor(g)) g <- factor(g)
  mod <- survival::coxph(survival::Surv(time, event) ~ g, weight = weight)
  data.frame(HR = as.numeric(exp(mod$coefficients)[1]))
}
dsurv(d, gtab = "gender", part = c(F,T), fnc = list(desc=NULL, comp = "HR"))

##   term      HR
## 1  bar 1.107036
## 2  foo 1.155531
```

3.6 The information functions are privy to

Internally, what is passed to each function is not only what the user supplies in the "...” of the higher order functions, but also some additional stuff; e.g. the name of the current variable (`.term`), the label (`.label`), if the variable has any missing values (`.missing`), etc.

```
theDots <- function(x, ...){
  dots <- list(...)
  foo <- function(z) if(is.null(z)) "NULL" else z
  data.frame(name = names(dots),
             value = unlist(lapply(dots, foo)))
}
dlcat(d, guide = g, fnc = list(desc = "theDots"),
      pass_this_along = "this was passed by the user")

##   term      name      value
## 1  pid      weight      NULL
## 2  pid pass_this_along this was passed by the user
## 3  pid   .table.type      lcat
## 4  pid     .term      pid
## 5  pid    .label      ID
## 6  pid    .type      lcat
## 7  pid    .group  Meta data
## 8  pid   .missing     FALSE
```

This allows for silly functions

```
silly <- function(x, ...){
  dots <- list(...)
  r <- paste0("'I'm %s (a %s type) but I prefer my to use my label: %s'")
  data.frame(Presentation = sprintf(r, dots$.term, dots$.type, dots$.label))
}
dlcat(d, guide = g, fnc = list(desc = "silly"))

##   term      Presentation
## 1  pid 'I'm pid (a lcat type) but I prefer my to use my label: ID'
```


3.7 Some notes on formatting

To appear.

4 Baseline tables

Baseline tables describe several types in one table - the name is chosen from the world of clinical trials where the various traits of the study population are often described by the characteristics collected at the start of the study, at baseline.

Combining various types adds a layer of complexity for the functions that generate the parts of the table. For one, they have to return the same number of columns (per part). This typically means mixing numbers and text, and so formatting of numbers has to be done already at the table-generating phase. In contrast, the default simple descriptive tables could be populated with all numbers without the need for formatting.

Another problem is how to know what the presented numbers are. In a simple descriptive table, we name the columns to indicate what is in them; e.g. "Mean" and "SD" when we present the mean values and standard deviations for the variables. But in a baseline table, we mix the types - so the column names are not sufficient for that end.

A third problem in the context of this package, is that it becomes much more involved to pass user defined functions to baseline tables (so much so that it is currently not possible) - we need at least a function per type.

The current approach is that there is a set of default functions for baseline tables that is distinct from the set of default functions for simple descriptive tables. To "manually" implement a completely new set of baseline functions is somewhat cumbersome. However, the aim is to put together a number of baseline *themes* that the user easily can choose between without having to reset any default values - and if a new theme is needed, it would be best to implement it *within* the package.

Before going further into the details, let's look at the two (actually three, but really just two) themes that exist currently.

4.1 Baseline theme 0 (default)

The distinct feature of the default theme is that it tries to be compact.

The default baseline table was shown in Table 2, but we'll do a version of it again. We reuse the "variable table" stored in `vt` and we will also trim down the data so that the table becomes a bit smaller, see Table 12.

```
sel <- subset(g, !group %in% c("Measures etc.", "Outcomes", "Covariates"))$term
d2 <- d[, sel]
g2 <- dguide(d2, id = c("id", "pid"), vtab = vt,
             elim.set = c("end", "region", "area"))
b <- baseline(d2, theme = 0, guide = g2, gtab = "gender", part = c(T,T,T))
blatex(b, caption = "Baseline table theme 0 (default)",
       label = "tab:bsl-0", size = "small")
```

Table 12: Baseline table theme 0 (default)

	male	female	Compare	Test
	n = 489	n = 511	male/female	male/female
Meta data				
ID	=489=	=511=		
A constant: included	489 (100.0%)	511 (100.0%)		
Index	170101/181229 [1]	170102/181225	-0.035	0.58 [✓]
Demographics				
Age	55.0 (48.0 - 55.0)	56.0 (49.0 - 56.0)	-0.069	0.28 ^b
Male: 1	489 (100.0%)	0 (0%)	Inf	<0.0001 [⊥]
Country: SW	173 (35.4%)	178 (34.8%)	0.031	0.88 [⊥]
NO	168 (34.4%)	171 (33.5%)		
DE	148 (30.3%)	162 (31.7%)		

Rows: 1000 (male:489, female:511). No duplicate subjects. [⊥] Chi-square. [✓] Wilcoxon. ^b t-test.
Categorical variable: =unique values=. [n] is missing count (if applicable). Categorical variable:
Count (Percent). Date variables: min/max. Numeric variable: Median (Q1-Q3)

Notice that each type has a unique form of the numbers presented in the descriptive part of the table. This allows for the explanation of those numbers to be in the "foot" of the table. The comparison part only contain 1 kind of numbers (the standardized differences - but this is actually not clear). The test part contains different kinds of test, all of which are explained through footnotes.

Also, notice that baseline tables have their own L^AT_EX-code-generating function `blatex`.

4.1.1 Baseline theme 1 \approx 0

The only difference between theme 0 and 1 is that the `real` type is described as "Median (Q1-Q3)" in 0 and "Mean (SD)" in 1, see Table 13.

```
b <- baseline(d2, theme = 1, guide = g2, gtab = "gender", part = c(T,T,T))
blatex(b, caption = "Baseline table theme 1.",
       label = "tab:bsl-1", size = "small")
```

Table 13: Baseline table theme 1.

	male	female	Compare	Test
	n = 489	n = 511	male/female	male/female
Meta data				
ID	=489=	=511=		
A constant: included	489 (100.0%)	511 (100.0%)		
Index	170101/181229 [1]	170102/181225	-0.035	0.58 [∇]
Demographics				
Age	55.0 (10.3)	55.7 (9.82)	-0.069	0.28 ^b
Male: 1	489 (100.0%)	0 (0%)	Inf	<0.0001 [⊥]
Country: SW	173 (35.4%)	178 (34.8%)	0.031	0.88 [⊥]
NO	168 (34.4%)	171 (33.5%)		
DE	148 (30.3%)	162 (31.7%)		

Rows: 1000 (male:489, female:511). No duplicate subjects. [⊥] Chi-square. [∇] Wilcoxon. ^b t-test.
 Categorical variable: =unique values=. [n] is missing count (if applicable). Categorical variable:
 Count (Percent). Date variables: min/max. Numeric variable: Mean (SD)

4.2 Baseline theme 2

The baseline theme 2 takes more space, but is perhaps simpler to parse.

```
b <- baseline(d2, theme = 2, guide = g2, gtab = "gender", part = c(T,T,T))
blatex(b, caption = "Baseline table theme 2.",
        label = "tab:bsl-2", size = "small")
```

Table 14: Baseline table theme 2.

	male	female	Compare	Test
	n = 489	n = 511	male/female	male/female
Meta data				
ID ; Unique	489	511		
A constant , n (%): included	489 (100.0%)	511 (100.0%)		
Index ; Min	2017-01-01	2017-01-02	-0.035	0.58 [∇]
Max	2018-12-29	2018-12-25		
Missing	1	0		
Demographics				
Age ; Mean (SD)	55.0 (10.3)	55.7 (9.82)	-0.069	0.28 ^b
Median (Q1,Q3)	55.0 (48.0, 63.0)	56.0 (49.0, 62.0)		
Min, Max	28.0, 85.0	25.0, 85.0		
Male , n (%): 0	0 (0%)	511 (100.0%)	Inf	<0.0001 [⊥]
1	489 (100.0%)	0 (0%)		
Country , n (%): SW	173 (35.4%)	178 (34.8%)	0.031	0.88 [⊥]
NO	168 (34.4%)	171 (33.5%)		
DE	148 (30.3%)	162 (31.7%)		

Rows: 1000 (male:489, female:511). No duplicate subjects. [⊥] Chi-square. [∇] Wilcoxon. ^b t-test

4.3 Adjusting the baseline table

This section is just a reminder of some of the features that were presented for simple descriptive tables. E.g. suppose you want a default baseline table by `gender` but also a column showing the data for everyone, as well as a test - but, of course, the test should only contrast the gender levels. Then you can use `gtab_maker` and supply the correct input for the `part` argument.

```
gt <- gtab_maker("gender", data = d2, all = TRUE, all.first = TRUE)
b <- baseline(d2, theme = 0, guide = g2, gtab = gt,
              part = list(T, F, c(2,3)))
blatex(b, label = "tab:adj-bsl", caption = "Adjusted baseline table")
```

Table 15: Adjusted baseline table

	All	male	female	Test
	n = 1000	n = 489	n = 511	male/female
Meta data				
ID	=1000=	=489=	=511=	
A constant: included	1000 (100.0%)	489 (100.0%)	511 (100.0%)	
Index	170101/181229 [1]	170101/181229 [1]	170102/181225	0.58 [∇]
Demographics				
Age	55.0 (48.8 - 55.0)	55.0 (48.0 - 55.0)	56.0 (49.0 - 56.0)	0.28 ^b
Male: 1	489 (48.9%)	489 (100.0%)	0 (0%)	<0.0001 [⊥]
Gender: male	489 (48.9%)	489 (100.0%)	0 (0%)	<0.0001 [⊥]
female	511 (51.1%)	0 (0%)	511 (100.0%)	
Country: SW	351 (35.1%)	173 (35.4%)	178 (34.8%)	0.88 [⊥]
NO	339 (33.9%)	168 (34.4%)	171 (33.5%)	
DE	310 (31.0%)	148 (30.3%)	162 (31.7%)	

Rows: 1000 (All:1000, male:489, female:511). No duplicate subjects. [⊥] Chi-square. [∇] Wilcoxon.

^b t-test. Categorical variable: =unique values=. [n] is missing count (if applicable). Categorical variable: Count (Percent). Date variables: min/max. Numeric variable: Median (Q1-Q3)

4.4 Behind the scenes of baseline tables

We will use `dcatg` in a nonsense example to illustrate a few tools.

```
foo <- function(x, ...){
  dots <- list(...)
  z <- length(unique(x[!is.na(x)]))
  data.frame(mode = d.mode(x),
             someInfo = paste("Info ", LETTERS[z]))
}
(dt <- dcatg(d, guide = g, fnc = list(desc = "foo")))
```

```
##      term      mode someInfo
## 1 status included  Info  A
## 2 gender   female  Info  B
## 3 country      SW   Info  C
## 4 area      urban  Info  B
## 5 region      A    Info  E
```

```
attr(dt, "part")
```

```
## [1] "meta"      "desc:All" "desc:All"
```

We need to know that there is a function that collects some of the meta data.

```
attr2text(dt)
```

```
## [1] "Rows: 1000. No duplicate subjects"
```

Also, we can store things in an 'info' attribute in the, which can be part of the information collected by `attr2text`.

```
attr(dt, "info") <- "Something important."
attr2text(dt)
```

```
## [1] "Rows: 1000. No duplicate subjects. Something important."
```

To proceed with our example, suppose we are not interested in displaying the 'someInfo' column. In order to not destroy the meta data, columns should be removed with `dable.prune`.

```
(dt2 <- dable_prune(dt, rm = "someInfo"))
```

```
##      term      mode
## 1 status included
## 2 gender   female
## 3 country      SW
## 4 area      urban
## 5 region      A
```

```
attr(dt2, "part") ## sane meta data
```

```
## [1] "meta"      "desc:All"
```

```
attr(dt2, "info") ## unchanged
```

```
## [1] "Something important."
```

But if the stuff in 'someInfo' is pertinent to the data, there are a couple of options. One, we can store the information in the 'info' attribute

```
dt2 <- dable_prune(dt, rm = "someInfo", info = TRUE)
attr(dt2, "info")

## [1] "Something important." "Info A"          "Info B"
## [4] "Info C"              "Info E"
```

```
datex(dt2, label = "tab:info-added", row.group = FALSE,
      caption = "Table with info added in the foot.")
```

Table 16: Table with info added in the foot.

All	
	mode
A constant	included
Gender	female
Country	SW
Area	urban
Region	A

Rows: 1000. No duplicate subjects. Something important.. Info A. Info B. Info C. Info E

By default, only unique information is kept, i.e. duplicates are removed.

Another option for L^AT_EX output is to put the information in a footnote

```
dt2 <- dable_fnote(dt, info = "someInfo", fn.var = "mode")
datex(dt2, label = "tab:fnote-added", row.group = FALSE,
      caption = "Table with info added as footnotes.")
```

Table 17: Table with info added as footnotes.

All	
	mode
A constant	included [⊥]
Gender	female [∀]
Country	SW [ⓑ]
Area	urban [∀]
Region	A [#]

Rows: 1000. No duplicate subjects. Something important.. [⊥]Info A. [∀]Info B. [ⓑ]Info C. [#]Info E

The true nature of the baseline tables are that they are very *tidy*.


```

b <- baseline(d, theme = 0, guide = g, gtab = "gender", part = c(T,T,T))
str(subset(b))

## 'data.frame': 25 obs. of  8 variables:
## $ term      : chr  "pid" "status" "index" "end" ...
## $ Variable   : chr  "ID" "A constant: included" "Index" "End" ...
## $ Summary.info: chr  "Categorical variable: =unique values=. [n] is missing count (if applicab
## $ p.info     : chr  NA "Chi-square" "Wilcoxon" "Wilcoxon" ...
## $ Summary    : chr  "=489=" "489 (100.0%)" "170101/181229 [1]" "180101/191229 [1]" ...
## $ Summary.1  : chr  "=511=" "511 (100.0%)" "170102/181225" "180102/191225" ...
## $ Std. diff. : num  NA NA -0.0349 -0.0349 -0.0688 ...
## $ p          : num  NA NA 0.583 0.583 0.276 ...

```

For the summary and p-values there are separate columns containing the information on the contents thereof. These are added as info in the foot, and as footnotes.

A Loose ends

- Most testing functions do not use weighting - should a warning be issued from the built-in testers when being passed a non-null weight?
- Baseline theme 0: the 'Comparison' is never identified as having standardized differences. Should the name of 'Comparison' and 'Test' perhaps be carried in the object until presentation?

B Testing

This section is for testing all the defaults, to see that the code goes through.

B.1 Default describers

```
dable(d, type = "real", guide = g)

##           term           Mean          SD
## 1          age 55.332000000 10.072399
## 2         kids  1.472000000  1.206097
## 3        measA 41.058453071 42.242859
## 4        measB 61.475041370 58.837329
## 5        measM 47.721624171 44.726907
## 6   forgotten  0.001249743  0.577495
## 7   importance  3.168900000  1.739416

dable(d, type = "catg", guide = g)

##           term   Level Count Proportion
## 1   status included   1000  1.0000000
## 2   gender      male    489  0.4890000
## 3   gender      female  511  0.5110000
## 4   country      SW    351  0.3510000
## 5   country      NO    339  0.3390000
## 6   country      DE    310  0.3100000
## 7     area      rural   204  0.2050251
## 8     area      urban   791  0.7949749
## 9   region      A     304  0.3040000
## 10  region      B     213  0.2130000
## 11  region      C     126  0.1260000
## 12  region      D     179  0.1790000
## 13  region      E     178  0.1780000

dable(d, type = "bnry", guide = g)

##           term Level Count Proportion
## 1         male      1    489      0.489
## 2 offspring TRUE    740      0.740

dable(d, type = "date", guide = g)

##           term    min    max
## 1   index 170101 181229
## 2     end 180101 191229

dable(d, type = "surv", guide = g)

##           term   Time Events      Rate
## 1   Foo 325923.1    201 0.0006167099
## 2   Bar 311600.9    300 0.0009627700

dable(d, type = "lcat", guide = g)

##           term Unique
## 1   pid    1000
```

B.2 Default comparers

```
dable(d, type = "real", guide = g, gtab = "gender", part = c(F,T))

##      term Std. diff.
## 1      age -0.06884267
## 2      kids -0.01926886
## 3      measA -0.13901052
## 4      measB -0.13304830
## 5      measM      NaN
## 6 forgotten  0.02244206
## 7 importance -0.09069944

dable(d, type = "catg", guide = g, gtab = "gender", part = c(F,T))

##      term Std. diff.
## 1 status      NA
## 2 country 0.03139396
## 3 area 0.01148310
## 4 region 0.04429413

dable(d, type = "bnry", guide = g, gtab = "gender", part = c(F,T))

##      term Std. diff.
## 1      male      Inf
## 2 offspring 0.03521521

dable(d, type = "date", guide = g, gtab = "gender", part = c(F,T))

##      term Std. diff.
## 1 index -0.03490307
## 2 end -0.03490307

dable(d, type = "surv", guide = g, gtab = "gender", part = c(F,T))

##      term Std. diff.
## 1 Foo -0.003611166
## 2 Bar -0.003116198

dable(d, type = "lcat", guide = g, gtab = "gender", part = c(F,T))

##      term Std. diff.
## 1 pid      NA
```

B.3 Default testers

```
dable(d, type = "real", guide = g, gtab = "gender", part = c(F,F,T))

## [META_param] testing 'measM' against 'gender' does not compute; with error:
## Error in 'contrasts<-'(*tmp*', value = contr.funs[1 + isOF[nn]]): contrasts
## can be applied only to factors with 2 or more levels

##      term      t-test
## 1      age 0.27649031
## 2     kids 0.76081326
## 3    measA 0.02908696
## 4    measB 0.08824107
## 5    measM      NA
## 6 forgotten 0.72301814
## 7 importance 0.15205441

dable(d, type = "catg", guide = g, gtab = "gender", part = c(F,F,T))

## [META_chisq] testing 'status' against 'gender' does not compute; with error:
## Error in stats::chisq.test(x, g): 'x' and 'y' must have at least 2 levels

##      term      p
## 1 status      NA
## 2 country 0.8841969
## 3 area 0.9183285
## 4 region 0.9744276

dable(d, type = "bnry", guide = g, gtab = "gender", part = c(F,F,T))

##      term      p
## 1      male 1.328233e-218
## 2 offspring 6.279693e-01

dable(d, type = "date", guide = g, gtab = "gender", part = c(F,F,T))

##      term Wilcoxon
## 1 index 0.5834804
## 2 end 0.5834804

dable(d, type = "surv", guide = g, gtab = "gender", part = c(F,F,T))

##      term Logrank
## 1 Foo 0.3068142
## 2 Bar 0.3793844

dable(d, type = "lcat", guide = g, gtab = "gender", part = c(F,F,T))

##      term no.test
## 1 pid      NA
```

B.4 Default baseline

```
baseline(d, guide = g, gtab = "gender", part = c(F,F,F))

## no table produced

## data frame with 0 columns and 0 rows

baseline(d, guide = g, gtab = "gender", part = c(T,F,F))

##          term          Variable
## 21      pid             ID
## 10    status A constant: included
## 24      index           Index
## 25      end             End
## 1      age             Age
## 8      male            Male: 1
## 11    country         Country: SW
## 12    country          \t NO
## 13    country          \t DE
## 14      area          Area: rural
## 15      area          \t urban
## 16    region          Region: A
## 17    region          \t B
## 18    region          \t C
## 19    region          \t D
## 20    region          \t E
## 9    offspring Offspring: TRUE
## 2      kids           Kid count
## 3      measA           A measure
## 4      measB           Another measure
## 5      measM           Manly measure
## 6    forgotten         forgotten
## 7    importance         importance
## 22      Foo            Foo
## 23      Bar            Bar
##
##                                     Summary.info
## 21 Categorical variable: =unique values=. [n] is missing count (if applicable)
## 10 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 24      Date variables: min/max. [n] is missing count (if applicable)
## 25      Date variables: min/max. [n] is missing count (if applicable)
## 1      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 8      Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 11 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 12 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 13 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 14 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 15 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 16 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 17 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 18 Categorical variable: Count (Percent). [n] is missing count (if applicable)
```

```

## 19 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 20 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 9 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 2 Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 3 Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 4 Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 5 Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 6 Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 7 Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 22 Time-to-event variable: events; rate. [n] is missing count (if applicable)
## 23 Time-to-event variable: events; rate. [n] is missing count (if applicable)
## Summary Summary
## 21 =489= =511=
## 10 489 (100.0%) 511 (100.0%)
## 24 170101/181229 [1] 170102/181225
## 25 180101/191229 [1] 180102/191225
## 1 55.0 (48.0 - 55.0) 56.0 (49.0 - 56.0)
## 8 489 (100.0%) 0 (0%)
## 11 173 (35.4%) 178 (34.8%)
## 12 168 (34.4%) 171 (33.5%)
## 13 148 (30.3%) 162 (31.7%)
## 14 101 (20.7%) [2] 103 (20.3%) [3]
## 15 386 (79.3%) 405 (79.7%)
## 16 147 (30.1%) 157 (30.7%)
## 17 105 (21.5%) 108 (21.1%)
## 18 65 (13.3%) 61 (11.9%)
## 19 86 (17.6%) 93 (18.2%)
## 20 86 (17.6%) 92 (18.0%)
## 9 358 (73.2%) 382 (74.8%)
## 2 1.00 (0 - 1.00) 1.00 (0 - 1.00)
## 3 26.9 (11.5 - 26.9) [5] 30.3 (12.6 - 30.3) [2]
## 4 38.7 (18.4 - 38.7) [168] 46.7 (20.3 - 46.7) [171]
## 5 33.6 (14.3 - 33.6) - [511]
## 6 0.025 (-0.47 - 0.025) -0.023 (-0.50 - -0.023)
## 7 3.10 (1.60 - 3.10) 3.30 (1.70 - 3.30)
## 22 92; 0.00057 109; 0.00066
## 23 140; 0.00091 160; 0.0010

baseline(d, guide = g, gtab = "gender", part = c(F,T,F))

## term Std. diff.
## 14 pid NA
## 10 status NA
## 17 index -0.034903068
## 18 end -0.034903068
## 1 age -0.068842671
## 8 male Inf
## 11 country 0.031393958
## 12 area 0.011483102
## 13 region 0.044294127
## 9 offspring 0.035215213

```

```

## 2      kids -0.019268860
## 3      measA -0.139010518
## 4      measB -0.133048304
## 5      measM      NaN
## 6  forgotten 0.022442056
## 7  importance -0.090699441
## 15      Foo -0.003611166
## 16      Bar -0.003116198

baseline(d, guide = g, gtab = "gender", part = c(F,F,T))

## [META_param] testing 'measM' against 'gender' does not compute; with error:
## Error in 'contrasts<-'('(*tmp*-', value = contr.funs[1 + isOF[nn]]): contrasts
## can be applied only to factors with 2 or more levels
## [META_chisq] testing 'status' against 'gender' does not compute; with error:
## Error in stats::chisq.test(x, g): 'x' and 'y' must have at least 2 levels

##      term      p.info      p
## 14      pid      <NA>      NA
## 10      status Chi-square      NA
## 17      index  Wilcoxon 5.834804e-01
## 18      end    Wilcoxon 5.834804e-01
## 1      age     t-test 2.764903e-01
## 8      male    Chi-square 1.328233e-218
## 11      country Chi-square 8.841969e-01
## 12      area    Chi-square 9.183285e-01
## 13      region  Chi-square 9.744276e-01
## 9      offspring Chi-square 6.279693e-01
## 2      kids     t-test 7.608133e-01
## 3      measA     t-test 2.908696e-02
## 4      measB     t-test 8.824107e-02
## 5      measM     t-test      NA
## 6  forgotten     t-test 7.230181e-01
## 7  importance     t-test 1.520544e-01
## 15      Foo      Log rank 3.068142e-01
## 16      Bar      Log rank 3.793844e-01

baseline(d, guide = g, gtab = "gender", part = c(T,T,F))

##      term      Variable
## 21      pid      ID
## 10      status A constant: included
## 24      index      Index
## 25      end      End
## 1      age      Age
## 8      male      Male: 1
## 11      country      Country: SW
## 12      country      \t NO
## 13      country      \t DE
## 14      area      Area: rural
## 15      area      \t urban

```



```

## 16      region      Region: A
## 17      region      \t B
## 18      region      \t C
## 19      region      \t D
## 20      region      \t E
## 9      offspring    Offspring: TRUE
## 2      kids         Kid count
## 3      measA        A measure
## 4      measB        Another measure
## 5      measM        Manly measure
## 6      forgotten    forgotten
## 7      importance    importance
## 22      Foo         Foo
## 23      Bar         Bar
##
##                                     Summary.info
## 21 Categorical variable: =unique values=. [n] is missing count (if applicable)
## 10 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 24      Date variables: min/max. [n] is missing count (if applicable)
## 25      Date variables: min/max. [n] is missing count (if applicable)
## 1      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 8      Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 11     Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 12     Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 13     Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 14     Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 15     Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 16     Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 17     Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 18     Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 19     Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 20     Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 9      Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 2      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 3      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 4      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 5      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 6      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 7      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 22     Time-to-event variable: events; rate. [n] is missing count (if applicable)
## 23     Time-to-event variable: events; rate. [n] is missing count (if applicable)
##
##          Summary          Summary  Std. diff.
## 21          =489=          =511=          NA
## 10          489 (100.0%)          511 (100.0%)          NA
## 24          170101/181229 [1]          170102/181225 -0.034903068
## 25          180101/191229 [1]          180102/191225 -0.034903068
## 1           55.0 (48.0 - 55.0)          56.0 (49.0 - 56.0) -0.068842671
## 8           489 (100.0%)              0 (0%)              Inf
## 11          173 (35.4%)              178 (34.8%)  0.031393958
## 12          168 (34.4%)              171 (33.5%)          NA
## 13          148 (30.3%)              162 (31.7%)          NA

```

```

## 14      101 (20.7%) [2]      103 (20.3%) [3] 0.011483102
## 15      386 (79.3%)      405 (79.7%) NA
## 16      147 (30.1%)      157 (30.7%) 0.044294127
## 17      105 (21.5%)      108 (21.1%) NA
## 18       65 (13.3%)       61 (11.9%) NA
## 19       86 (17.6%)       93 (18.2%) NA
## 20       86 (17.6%)       92 (18.0%) NA
## 9       358 (73.2%)      382 (74.8%) 0.035215213
## 2       1.00 (0 - 1.00)    1.00 (0 - 1.00) -0.019268860
## 3      26.9 (11.5 - 26.9) [5] 30.3 (12.6 - 30.3) [2] -0.139010518
## 4      38.7 (18.4 - 38.7) [168] 46.7 (20.3 - 46.7) [171] -0.133048304
## 5       33.6 (14.3 - 33.6)      - [511] NA
## 6       0.025 (-0.47 - 0.025) -0.023 (-0.50 - -0.023) 0.022442056
## 7       3.10 (1.60 - 3.10)    3.30 (1.70 - 3.30) -0.090699441
## 22      92; 0.00057      109; 0.00066 -0.003611166
## 23     140; 0.00091     160; 0.0010 -0.003116198

baseline(d, guide = g, gtab = "gender", part = c(T,F,T))

## [META_param] testing 'measM' against 'gender' does not compute; with error:
## Error in 'contrasts<-'('tmp*', value = contr.funs[1 + isOF[nn]]): contrasts
## can be applied only to factors with 2 or more levels
##
## [META_chisq] testing 'status' against 'gender' does not compute; with error:
## Error in stats::chisq.test(x, g): 'x' and 'y' must have at least 2 levels

##      term      Variable
## 21      pid      ID
## 10      status A constant: included
## 24      index      Index
## 25      end      End
## 1      age      Age
## 8      male      Male: 1
## 11      country      Country: SW
## 12      country      \t NO
## 13      country      \t DE
## 14      area      Area: rural
## 15      area      \t urban
## 16      region      Region: A
## 17      region      \t B
## 18      region      \t C
## 19      region      \t D
## 20      region      \t E
## 9      offspring      Offspring: TRUE
## 2      kids      Kid count
## 3      measA      A measure
## 4      measB      Another measure
## 5      measM      Manly measure
## 6      forgotten      forgotten
## 7      importance      importance
## 22      Foo      Foo

```

##	23	Bar	Bar		Summary.info
##	21	Categorical variable: =unique values=.	[n]	is missing count	(if applicable)
##	10	Categorical variable: Count (Percent).	[n]	is missing count	(if applicable)
##	24	Date variables: min/max.	[n]	is missing count	(if applicable)
##	25	Date variables: min/max.	[n]	is missing count	(if applicable)
##	1	Numeric variable: Median (Q1-Q3).	[n]	is missing count	(if applicable)
##	8	Categorical variable: Count (Percent).	[n]	is missing count	(if applicable)
##	11	Categorical variable: Count (Percent).	[n]	is missing count	(if applicable)
##	12	Categorical variable: Count (Percent).	[n]	is missing count	(if applicable)
##	13	Categorical variable: Count (Percent).	[n]	is missing count	(if applicable)
##	14	Categorical variable: Count (Percent).	[n]	is missing count	(if applicable)
##	15	Categorical variable: Count (Percent).	[n]	is missing count	(if applicable)
##	16	Categorical variable: Count (Percent).	[n]	is missing count	(if applicable)
##	17	Categorical variable: Count (Percent).	[n]	is missing count	(if applicable)
##	18	Categorical variable: Count (Percent).	[n]	is missing count	(if applicable)
##	19	Categorical variable: Count (Percent).	[n]	is missing count	(if applicable)
##	20	Categorical variable: Count (Percent).	[n]	is missing count	(if applicable)
##	9	Categorical variable: Count (Percent).	[n]	is missing count	(if applicable)
##	2	Numeric variable: Median (Q1-Q3).	[n]	is missing count	(if applicable)
##	3	Numeric variable: Median (Q1-Q3).	[n]	is missing count	(if applicable)
##	4	Numeric variable: Median (Q1-Q3).	[n]	is missing count	(if applicable)
##	5	Numeric variable: Median (Q1-Q3).	[n]	is missing count	(if applicable)
##	6	Numeric variable: Median (Q1-Q3).	[n]	is missing count	(if applicable)
##	7	Numeric variable: Median (Q1-Q3).	[n]	is missing count	(if applicable)
##	22	Time-to-event variable: events; rate.	[n]	is missing count	(if applicable)
##	23	Time-to-event variable: events; rate.	[n]	is missing count	(if applicable)
##		p.info	Summary	Summary	p
##	21	<NA>	=489=	=511=	NA
##	10	Chi-square	489 (100.0%)	511 (100.0%)	NA
##	24	Wilcoxon	170101/181229 [1]	170102/181225	5.834804e-01
##	25	Wilcoxon	180101/191229 [1]	180102/191225	5.834804e-01
##	1	t-test	55.0 (48.0 - 55.0)	56.0 (49.0 - 56.0)	2.764903e-01
##	8	Chi-square	489 (100.0%)	0 (0%)	1.328233e-218
##	11	Chi-square	173 (35.4%)	178 (34.8%)	8.841969e-01
##	12	<NA>	168 (34.4%)	171 (33.5%)	NA
##	13	<NA>	148 (30.3%)	162 (31.7%)	NA
##	14	Chi-square	101 (20.7%) [2]	103 (20.3%) [3]	9.183285e-01
##	15	<NA>	386 (79.3%)	405 (79.7%)	NA
##	16	Chi-square	147 (30.1%)	157 (30.7%)	9.744276e-01
##	17	<NA>	105 (21.5%)	108 (21.1%)	NA
##	18	<NA>	65 (13.3%)	61 (11.9%)	NA
##	19	<NA>	86 (17.6%)	93 (18.2%)	NA
##	20	<NA>	86 (17.6%)	92 (18.0%)	NA
##	9	Chi-square	358 (73.2%)	382 (74.8%)	6.279693e-01
##	2	t-test	1.00 (0 - 1.00)	1.00 (0 - 1.00)	7.608133e-01
##	3	t-test	26.9 (11.5 - 26.9) [5]	30.3 (12.6 - 30.3) [2]	2.908696e-02
##	4	t-test	38.7 (18.4 - 38.7) [168]	46.7 (20.3 - 46.7) [171]	8.824107e-02
##	5	t-test	33.6 (14.3 - 33.6)	- [511]	NA
##	6	t-test	0.025 (-0.47 - 0.025)	-0.023 (-0.50 - -0.023)	7.230181e-01

```
## 7      t-test      3.10 (1.60 - 3.10)      3.30 (1.70 - 3.30) 1.520544e-01
## 22    Log rank      92; 0.00057      109; 0.00066 3.068142e-01
## 23    Log rank     140; 0.00091     160; 0.0010 3.793844e-01

baseline(d, guide = g, gtab = "gender", part = c(F,T,T))

## [META_param] testing 'measM' against 'gender' does not compute; with error:
## Error in 'contrasts<-'('*tmp*', value = contr.funs[1 + isOF[nn]]): contrasts
## can be applied only to factors with 2 or more levels
##
## [META_chisq] testing 'status' against 'gender' does not compute; with error:
## Error in stats::chisq.test(x, g): 'x' and 'y' must have at least 2 levels
##
##      term      p.info      Std. diff.      p
## 14      pid      <NA>      NA      NA
## 10     status Chi-square      NA      NA
## 17      index Wilcoxon -0.034903068 5.834804e-01
## 18      end   Wilcoxon -0.034903068 5.834804e-01
## 1      age     t-test -0.068842671 2.764903e-01
## 8       male Chi-square      Inf 1.328233e-218
## 11     country Chi-square 0.031393958 8.841969e-01
## 12      area Chi-square 0.011483102 9.183285e-01
## 13     region Chi-square 0.044294127 9.744276e-01
## 9     offspring Chi-square 0.035215213 6.279693e-01
## 2      kids     t-test -0.019268860 7.608133e-01
## 3      measA     t-test -0.139010518 2.908696e-02
## 4      measB     t-test -0.133048304 8.824107e-02
## 5      measM     t-test      NaN      NA
## 6   forgotten     t-test 0.022442056 7.230181e-01
## 7   importance     t-test -0.090699441 1.520544e-01
## 15      Foo     Log rank -0.003611166 3.068142e-01
## 16      Bar     Log rank -0.003116198 3.793844e-01

baseline(d, guide = g, gtab = "gender", part = c(T,T,T))

## [META_param] testing 'measM' against 'gender' does not compute; with error:
## Error in 'contrasts<-'('*tmp*', value = contr.funs[1 + isOF[nn]]): contrasts
## can be applied only to factors with 2 or more levels
##
## [META_chisq] testing 'status' against 'gender' does not compute; with error:
## Error in stats::chisq.test(x, g): 'x' and 'y' must have at least 2 levels
##
##      term      Variable
## 21      pid      ID
## 10     status A constant: included
## 24      index      Index
## 25      end      End
## 1      age      Age
## 8       male      Male: 1
## 11     country      Country: SW
## 12     country      \t NO
## 13     country      \t DE
```

```

## 14      area      Area: rural
## 15      area      \t urban
## 16      region    Region: A
## 17      region    \t B
## 18      region    \t C
## 19      region    \t D
## 20      region    \t E
## 9  offspring      Offspring: TRUE
## 2      kids        Kid count
## 3      measA       A measure
## 4      measB       Another measure
## 5      measM       Manly measure
## 6      forgotten   forgotten
## 7      importance  importance
## 22      Foo        Foo
## 23      Bar        Bar
##
##                                     Summary.info
## 21 Categorical variable: =unique values=. [n] is missing count (if applicable)
## 10 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 24      Date variables: min/max. [n] is missing count (if applicable)
## 25      Date variables: min/max. [n] is missing count (if applicable)
## 1      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 8  Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 11 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 12 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 13 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 14 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 15 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 16 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 17 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 18 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 19 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 20 Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 9  Categorical variable: Count (Percent). [n] is missing count (if applicable)
## 2      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 3      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 4      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 5      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 6      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 7      Numeric variable: Median (Q1-Q3). [n] is missing count (if applicable)
## 22 Time-to-event variable: events; rate. [n] is missing count (if applicable)
## 23 Time-to-event variable: events; rate. [n] is missing count (if applicable)
##      p.info      Summary      Summary      Std. diff.
## 21      <NA>      =489=      =511=      NA
## 10 Chi-square      489 (100.0%)      511 (100.0%)      NA
## 24 Wilcoxon      170101/181229 [1]      170102/181225 -0.034903068
## 25 Wilcoxon      180101/191229 [1]      180102/191225 -0.034903068
## 1      t-test      55.0 (48.0 - 55.0)      56.0 (49.0 - 56.0) -0.068842671
## 8  Chi-square      489 (100.0%)      0 (0%)      Inf
## 11 Chi-square      173 (35.4%)      178 (34.8%)      0.031393958

```

## 12	<NA>	168 (34.4%)	171 (33.5%)	NA
## 13	<NA>	148 (30.3%)	162 (31.7%)	NA
## 14	Chi-square	101 (20.7%) [2]	103 (20.3%) [3]	0.011483102
## 15	<NA>	386 (79.3%)	405 (79.7%)	NA
## 16	Chi-square	147 (30.1%)	157 (30.7%)	0.044294127
## 17	<NA>	105 (21.5%)	108 (21.1%)	NA
## 18	<NA>	65 (13.3%)	61 (11.9%)	NA
## 19	<NA>	86 (17.6%)	93 (18.2%)	NA
## 20	<NA>	86 (17.6%)	92 (18.0%)	NA
## 9	Chi-square	358 (73.2%)	382 (74.8%)	0.035215213
## 2	t-test	1.00 (0 - 1.00)	1.00 (0 - 1.00)	-0.019268860
## 3	t-test	26.9 (11.5 - 26.9) [5]	30.3 (12.6 - 30.3) [2]	-0.139010518
## 4	t-test	38.7 (18.4 - 38.7) [168]	46.7 (20.3 - 46.7) [171]	-0.133048304
## 5	t-test	33.6 (14.3 - 33.6)	- [511]	NaN
## 6	t-test	0.025 (-0.47 - 0.025)	-0.023 (-0.50 - -0.023)	0.022442056
## 7	t-test	3.10 (1.60 - 3.10)	3.30 (1.70 - 3.30)	-0.090699441
## 22	Log rank	92; 0.00057	109; 0.00066	-0.003611166
## 23	Log rank	140; 0.00091	160; 0.0010	-0.003116198
##	p			
## 21	NA			
## 10	NA			
## 24	5.834804e-01			
## 25	5.834804e-01			
## 1	2.764903e-01			
## 8	1.328233e-218			
## 11	8.841969e-01			
## 12	NA			
## 13	NA			
## 14	9.183285e-01			
## 15	NA			
## 16	9.744276e-01			
## 17	NA			
## 18	NA			
## 19	NA			
## 20	NA			
## 9	6.279693e-01			
## 2	7.608133e-01			
## 3	2.908696e-02			
## 4	8.824107e-02			
## 5	NA			
## 6	7.230181e-01			
## 7	1.520544e-01			
## 22	3.068142e-01			
## 23	3.793844e-01			