

TECHNICAL PARAMETERS Vibration exciter S 51110

Rated peak force Sine _{pk} /Random _{RMS} ¹	100/70 N
Frequency range	2 - 7000 Hz
Main resonance frequency	>6500 Hz
Max. displacement Peak-Peak ²	13 mm
Max. velocity	1.5 m/s
Max. acceleration Sine/Random	45/30 g
Suspension stiffness	8 N/mm
Effective moving mass	0.23 kg
Total mass	12 kg
Armature diameter	60 mm

1) Random force according to ISO 5344:2004

2) Payload has an impact on the possible maximum displacement



SCOPE OF DELIVERY, OPTIONS AND FEATURES OF THE SYSTEM

Scope of delivery:

Vibration exciter
Trunnion mount
Power amplifier
Connection cable (3 m)
Power cable (1.5 m)
for amplifier (CEE 7/7 connector)

Options:

Cable extension
Modal adapter M6
Stinger (see Modal brochure for details)
Factory acceptance test

Features:

Vibration isolation
High cross-axial stiffness
Light weight construction by using rare earth magnet
Minimum maintenance effort
Made in Germany
Service hotline

TECHNICAL PARAMETERS Power Amplifier BDA 120

Continuous sine output power, max.	120 VA
Frequency range (small signal / full power)	DC - 100 kHz / 40 Hz - 20 kHz
Voltage-Current mode	yes/no
Voltage _{RMS} ¹ , max.	22 V
Current _{RMS} ¹ , max.	5.5 A
Signal input voltage _{pk} (at 1 kHz sine for max. power)	3.5 V
Distortion THD (frequency range 40 Hz to 20 kHz)	< 0.1 %
Signal to noise ratio	> 100 dB(A)
Total mass	2 kg
Dimensions (W x H x D)	240 x 48 x 226 mm
Power supply	1 ~ / N / PE 100..230 V ± 5% 50/60 Hz CEE 7/7

Recommended fuse protection

Max. power consumption

Interlocks:

16 A slow

180 VA

Overcurrent, Temperature

Features:

- High Signal to noise ratio of > 100 dB(A)
- Low Distortion factor (THD) of < 0.1 %



S 51110 (Example drawing) (mm)

