

## Vibration Test System TV 52110

### TECHNICAL PARAMETERS Vibration exciter S 52110

|                                                                         |             |
|-------------------------------------------------------------------------|-------------|
| Rated peak force Sine <sub>pk</sub> /Random <sub>RMS</sub> <sup>1</sup> | 100/50 N    |
| Frequency range                                                         | 2 - 7000 Hz |
| Main resonance frequency                                                | >5700 Hz    |
| Max. displacement Peak-Peak <sup>2</sup>                                | 15 mm       |
| Max. velocity                                                           | 1.5 m/s     |
| Max. acceleration Sine/Random                                           | 50/25 g     |
| Suspension stiffness                                                    | 13.1 N/mm   |
| Effective moving mass                                                   | 0.25 kg     |
| Total mass                                                              | 36 kg       |
| Armature diameter                                                       | 60 mm       |

1) Random force according to ISO 5344:2004

2) Payload has an impact on the possible maximum displacement



### SCOPE OF DELIVERY, OPTIONS AND FEATURES OF THE SYSTEM

#### Scope of delivery:

Vibration exciter  
Trunnion mount  
Power amplifier  
Connection cable (3 m)  
Power cable (1.5 m)  
for amplifier (CEE 7/7 connector)

#### Options:

Cable extension  
Modal adapter M6  
Stinger (see Modal brochure for details)  
Factory acceptance test

#### Features:

Vibration isolation  
High cross-axial stiffness  
Minimum maintenance effort  
Made in Germany  
Service hotline

### TECHNICAL PARAMETERS Power Amplifier BDA 120

|                                                                   |                                                  |
|-------------------------------------------------------------------|--------------------------------------------------|
| Continuous sine output power, max.                                | 120 VA                                           |
| Frequency range (small signal / full power)                       | DC - 100 kHz / 40 Hz - 20 kHz                    |
| Voltage-/Current mode                                             | yes/no                                           |
| Voltage <sub>RMS</sub> <sup>1</sup> , max.                        | 22 V                                             |
| Current <sub>RMS</sub> <sup>1</sup> , max.                        | 5.5 A                                            |
| Signal input voltage <sub>pk</sub> (at 1 kHz sine for max. power) | 3.5 V                                            |
| Distortion THD (frequency range 40 Hz to 20 kHz)                  | < 0.1 %                                          |
| Signal to noise ratio                                             | > 100 dB(A)                                      |
| Total mass                                                        | 2 kg                                             |
| Dimensions (W x H x D)                                            | 240 x 48 x 226 mm                                |
| Power supply                                                      | 1 ~ / N / PE 100..230 V ± 5% 50/60 Hz<br>CEE 7/7 |

#### Recommended fuse protection

Max. power consumption

Interlocks:

16 A slow

180 VA

Overcurrent, Temperature

#### Features:

- High Signal to noise ratio of > 100 dB(A)
- Low Distortion factor (THD) of < 0.1 %



S 52110 (Example drawing) (mm)

