

# Application of Formal Framework to Spiking Neural P System Variants: A Proposal

Ren Tristan A. de la Cruz

November 4, 2020

## 1 Introduction

*Membrane computing* is a field of computer science that studies models of computation known as *P systems*. *P systems* refer to a family of models of computation that are inspired by different biological processes. P systems use biological concepts like cells, cell membranes, neurons, tissues, etc. Rules (computation operations) in P systems are inspired by biological processes like chemical reactions in cells, ion transport between regions divided by membranes, membrane creation, division and dissolution, spiking of neurons, neurogenesis, and synaptogenesis.

There is no single formal definition for the term ‘P system’ but there are certain characteristics that apply to most P systems. Most P systems use multiset of symbols as computing elements. One can think of these symbols as molecules or ions. The multiset of symbols are compartmentalized into regions and these regions are defined by membranes that enclose them. i.e. Region 1 is the space enclosed by membrane 1. This is the reason why the field is known as ‘membrane’ computing. Regions can be connected to each other. For example, in cell-like P system, membranes in the cell can be nested. If there are two membranes in a cell, membrane 0 and membrane 1, and membrane 1 is inside membrane 0 then the region enclosed by membrane 0 that is outside membrane 1 is ‘connected’ to the region enclosed by membrane 1. In tissue-like P system, membranes represent cells and a cell enclosed one region. Cells (and hence regions) are connected to each other via channels. Tissue P systems form networks of cells. In general, the *configuration* of a P system refers to the network of cells/membranes with each cell/membrane

containing a multiset of objects (the multiset can be empty). In some P systems, a cell/membrane has an internal state/status that is different from its content (multiset of symbols). For example, in some cell-like P system, a membrane has a state known as *polarity* or *charge* which can either be negative, positive, or neutral.

[2] [1] [3] [4]  
hello world

## 2 Proposal

## References

- [1] Rudolf Freund, Ignacio Pérez-Hurtado, Agustín Riscos-Núñez, and Sergey Verlan. A formalization of membrane systems with dynamically evolving structures. *International Journal of Computer Mathematics*, 90(4):801–815, 2013.
- [2] Rudolf Freund and Sergey Verlan. A formal framework for static (tissue) p systems. In George Eleftherakis, Petros Kefalas, Gheorghe Păun, Grzegorz Rozenberg, and Arto Salomaa, editors, *Membrane Computing*, pages 271–284, Berlin, Heidelberg, 2007. Springer Berlin Heidelberg.
- [3] Sergey Verlan. Using the formal framework for p systems. In Artiom Alhazov, Svetlana Cojocaru, Marian Gheorghe, Yurii Rogozhin, Grzegorz Rozenberg, and Arto Salomaa, editors, *Membrane Computing*, pages 56–79, Berlin, Heidelberg, 2014. Springer Berlin Heidelberg.
- [4] Sergey Verlan, Rudolf Freund, Artiom Alhazov, Sergiu Ivanov, and Linqiang Pan. A formal framework for spiking neural p systems. *Journal of Membrane Computing*, Oct 2020.