Select a definition v1

# Renty API v1 OAS 3.0

/swagger/v1/swagger.json

Renty - Rental Marketplace API

Servers
https://renty.runasp.net

Authorize

## Auth

POST /api/v1/auth/register

Parameters Try it out

No parameters

## Request body

application/json

**Example Value** Schema


```
{
  "email": "string",
  "password": "string",
  "confirmPassword": "string",
  "firstName": "string",
  "lastName": "string",
  "phoneNumber": "string",
  "userType": 1,
  "address": "string",
  "city": "string",
  "country": "string",
  "bio": "string"
}
```


## Responses

| Code | Description | Links |
|---|---|---|
| 201 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "message": "string",
    "userId": 0
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
```

| Code | Description | Links |
| --- | --- | --- |


```
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400

*No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## POST /api/v1/auth/verify-email

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema

```
{
  "email": "string",
  "code": "string"
}
```


## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br><br>**Example Value** Schema<br>`{ "data": { "message": "string" }, "error": true, "errorCode": [ 0 ], "messages": [ "string" ], "total": 0, "page": 0, "pages": 0, "successCode": 0 }` | *No links* |
| 400 | Media type<br>application/json<br><br>**Example Value** Schema | *No links* |

| Code | Description | Links |
| --- | --- | --- |


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**POST** `/api/v1/auth/send-verification`

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema


```
{
  "email": "string"
}
```


**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema<br>{<br>"data": "string",<br>"error": true,<br>"errorCode": [<br>0<br>],<br>"messages": [<br>"string"<br>],<br>"total": 0,<br>"page": 0,<br>"pages": 0,<br>"successCode": 0<br>} | *No links* |
| 400 | Media type<br>application/json<br>**Example Value** Schema<br>{<br>"data": "string",<br>"error": true,<br>"errorCode": [<br>0<br>],<br>"messages": [<br>"string"<br>],<br>"total": 0,<br>"page": 0,<br>"pages": 0,<br>"successCode": 0<br>} | *No links* |

POST /api/v1/auth/forgot-password

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema

```
{
  "email": "string"
}
```

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema<br>{<br>"data": "string",<br>"error": true,<br>"errorCode": [<br>0<br>],<br>"messages": [<br>"string" | *No links* |

| Code | Description | Links |
| --- | --- | --- |


```
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400

*No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**POST** `/api/v1/auth/reset-password`

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema

```
{
  "email": "string",
  "token": "string",
  "newPassword": "string"
}
```


## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br><br>**Example Value** Schema<br>`{ "data": "string", "error": true, "errorCode": [ 0 ], "messages": [ "string" ], "total": 0, "page": 0, "pages": 0, "successCode": 0 }` | *No links* |
| 400 | Media type<br>application/json<br><br>**Example Value** Schema<br>`{ "data": "string",` | *No links* |

| Code | Description | Links |
| --- | --- | --- |


```
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**POST** `/api/v1/auth/verify-reset-code`

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema


```
{
  "email": "string",
  "token": "string"
}
```


**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema<br>{<br>"data": "string",<br>"error": true,<br>"errorCode": [<br>0<br>],<br>"messages": [<br>"string"<br>],<br>"total": 0,<br>"page": 0,<br>"pages": 0,<br>"successCode": 0<br>} | *No links* |
| 400 | Media type<br>application/json<br>**Example Value** Schema<br>{<br>"data": "string",<br>"error": true,<br>"errorCode": [<br>0<br>],<br>"messages": [<br>"string"<br>],<br>"total": 0,<br>"page": 0,<br>"pages": 0,<br>"successCode": 0<br>} | *No links* |

POST /api/v1/auth/login

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema


```
{
  "email": "string",
  "password": "string"
}
```


**Responses**

| Code | Description | Links |
|---|---|---|
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "accessToken": "string",
    "refreshToken": "string",
    "refreshTokenExpiresAt": "2026-04-19T19:53:53.028Z",
    "user": {
      "id": 0,
      "firstName": "string",
```

| Code | Description | Links |
| --- | --- | --- |


```
      "lastName": "string",
      "email": "string",
      "role": "string",
      "profileImageUrl": "string"
    }
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


401 *No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**POST** `/api/v1/auth/refresh`

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema


```
{
  "accessToken": "string",
  "refreshToken": "string"
}
```


**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "accessToken": "string",
    "refreshToken": "string"
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
```

| Code | Description | Links |
| --- | --- | --- |


```
  "pages": 0,
  "successCode": 0
}
```


401

*No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**GET** `/api/v1/auth/me`

**Parameters** Try it out

No parameters

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "id": 0,
    "firstName": "string",
    "lastName": "string",
    "email": "string",
    "phone": "string",
    "city": "string",
    "role": "string",
    "profileImageUrl": "string",
    "isVerified": true,
    "createdAt": "2026-04-19T19:53:53.041Z"
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


PUT /api/v1/auth/me

**Parameters** Try it out

No parameters

## Request body

application/json

**Example Value** Schema


```
{
  "firstName": "string",
  "lastName": "string",
  "phoneNumber": "string",
  "address": "string",
  "city": "string",
  "country": "string",
  "bio": "string",
  "profilePictureUrl": "string"
}
```


## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
```

| Code | Description | Links |
| --- | --- | --- |
| | <pre>{<br>  "successCode": 0<br>}</pre> | |
| 400 | Media type<br>application/json<br>**Example Value** Schema<br><pre>{<br>  "data": "string",<br>  "error": true,<br>  "errorCode": [<br>  0<br>  ],<br>  "messages": [<br>  "string"<br>  ],<br>  "total": 0,<br>  "page": 0,<br>  "pages": 0,<br>  "successCode": 0<br>}</pre> | *No links* |

## Items

**GET** `/api/v1/items`

**Parameters** Try it out

| Name | Description |
| --- | --- |
| **page** * <br>`integer($int32)` <br>*(query)* | page |

| Name | Description |
| --- | --- |
| **limit** * <br> `integer($int32)` <br> *(query)* | limit |
| categoryId <br> `integer($int32)` <br> *(query)* | categoryId |
| subcategoryId <br> `integer($int32)` <br> *(query)* | subcategoryId |
| city <br> `string` <br> *(query)* | city |
| minPrice <br> `number($decimal)` <br> *(query)* | minPrice |
| maxPrice <br> `number($decimal)` <br> *(query)* | maxPrice |
| type <br> `string` <br> *(query)* | type |
| condition <br> `string` <br> *(query)* | condition |
| sort <br> `string` <br> *(query)* | sort |

| Name | Description |
| --- | --- |
| sortOrder<br>**string**<br>*(query)* | sortOrder |
| owner<br>**string**<br>*(query)* | owner |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": [
    {
      "id": "string",
      "titleAr": "string",
      "titleEn": "string",
      "dailyPrice": 0,
      "city": "string",
      "primaryImage": "string",
      "avgRating": 0,
      "reviewCount": 0,
      "type": "string",
      "condition": "string",
      "category": {
        "id": 0,
        "nameAr": "string",
        "nameEn": "string"
```

| Code | Description | Links |
| --- | --- | --- |


```
    },
    "subcategory": {
      "id": 0,
      "nameAr": "string",
      "nameEn": "string"
    },
    "brand": {
      "id": 0,
      "nameAr": "string",
      "nameEn": "string"
```


**POST** `/api/v1/items`

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema


```
{
  "titleAr": "string",
  "titleEn": "string",
  "descAr": "string",
  "descEn": "string",
  "type": "string",
  "condition": "string",
  "defaultDeposit": 0,
  "location": "string",
  "city": "string",
  "lat": 0,
  "lng": 0,
  "categoryId": 0,
  "subcategoryId": 0,
  "brandId": 0,
  "pricing": [
    {
      "price": 0,
      "pricingType": "string"
```

```
    }
  ],
  "images": [
    {
      "imageId": "string",
      "isPrimary": true
    }
  ]
}
```

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 201 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema<br>`{ "data": { "id": "string" }, "error": true, "errorCode": [ 0 ], "messages": [ "string" ], "total": 0, "page": 0, "pages": 0, "successCode": 0 }` | *No link* |
| 400 | Media type<br>application/json | *No links* |

| Code | Description | Links |
| --- | --- | --- |

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## GET /api/v1/items/{id}

### Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

### Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |
| 404 | Media type<br>application/json<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "id": "string",
    "titleAr": "string",
    "titleEn": "string",
    "descAr": "string",
    "descEn": "string",
    "type": "string",
    "status": "string",
    "condition": "string",
    "defaultDeposit": 0,
    "location": "string",
    "city": "string",
    "lat": 0,
    "lng": 0,
    "createdAt": "2026-04-19T19:53:53.084Z",
    "owner": {
      "firstName": "string",
      "city": "string",
      "profileImageUrl": "string"
    },
    "pricing": [
      {
        "pricingType": "string",
        "price": 0
      }
    ],
    "images": [
```

```
{
  "data": "string",
```

| Code | Description | Links |
|---|---|---|


```
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**PUT** `/api/v1/items/{id}`

**Parameters** Try it out

| Name | Description |
|---|---|
| **id** * <br> `string($guid)` <br> *(path)* | id |

**Request body** application/json

**Example Value** Schema


```
{
  "itemId": "string",
  "titleAr": "string",
  "titleEn": "string",
  "descAr": "string",
  "descEn": "string",
  "type": "string",
  "condition": "string",
  "defaultDeposit": 0,
  "location": "string",
```

```
  "city": "string",
  "lat": 0,
  "lng": 0,
  "categoryId": 0,
  "subcategoryId": 0,
  "brandId": 0,
  "pricing": [
    {
      "price": 0,
      "pricingType": "string"
    }
  ],
  "images": [
    {
      "imageId": "string",
      "isPrimary": true
    }
  ]
```


## Responses

| Code | Description | Links |
|---|---|---|
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "id": "string",
    "titleAr": "string",
    "titleEn": "string",
    "descAr": "string",
    "descEn": "string",
    "type": "string",
    "status": "string",
    "condition": "string",
    "defaultDeposit": 0,
    "location": "string",
    "city": "string",
```

| Code | Description | Links |
| --- | --- | --- |
| | <pre>"lat": 0,<br>"lng": 0,<br>"createdAt": "2026-04-19T19:53:53.096Z",<br>"owner": {<br>"firstName": "string",<br>"city": "string",<br>"profileImageUrl": "string"<br>},<br>"pricing": [<br>{<br>"pricingType": "string",<br>"price": 0<br>}<br>],<br>"images": [</pre> | |
| 400 | Media type<br>application/json<br>**Example Value** Schema<br><pre>{<br>"data": "string",<br>"error": true,<br>"errorCode": [<br>0<br>],<br>"messages": [<br>"string"<br>],<br>"total": 0,<br>"page": 0,<br>"pages": 0,<br>"successCode": 0<br>}</pre> | *No links* |

**DELETE** `/api/v1/items/{id}`

**Parameters** Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema <br> { "data": "string", "error": true, "errorCode": [ 0 ], "messages": [ "string" ], "total": 0, "page": 0, "pages": 0, "successCode": 0 } | *No links* |
| 400 | Media type <br> application/json <br> **Example Value** Schema | *No links* |

| Code | Description | Links |
| --- | --- | --- |


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## Search

GET /api/v1/search

Parameters

Try it out

| Name | Description |
| --- | --- |
| **q** * <br> `string` <br> *(query)* | q |
| categoryId <br> `integer($int32)` <br> *(query)* | categoryId |
| city <br> `string` <br> *(query)* | city |

| Name | Description |
| --- | --- |
| **page** * <br> integer($int32) <br> *(query)* | page |
| **limit** * <br> integer($int32) <br> *(query)* | limit |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls Accept header. <br> **Example Value** Schema <br> { "data": { "items": [ { "id": "string", "titleAr": "string", "titleEn": "string", "dailyPrice": 0, "city": "string", "primaryImage": "string", "avgRating": 0, "reviewCount": 0, "type": "string", "condition": "string", "category": { "id": 0, "nameAr": "string", | *No links* |

| Code | Description | Links |
| --- | --- | --- |
| 400 | Media type<br>application/json<br>**Example Value** Schema | *No links* |


```
        "nameEn": "string"
      },
      "subcategory": {
        "id": 0,
        "nameAr": "string",
        "nameEn": "string"
      },
      "brand": {
        "id": 0,
        "nameAr": "string",
```



```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## Favorites

POST /api/v1/items/{id}/favorite

Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 201 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema <br> { "data": "string", "error": true, "errorCode": [ 0 ], "messages": [ "string" ], "total": 0, "page": 0, "pages": 0, "successCode": 0 } | *No links* |
| 400 | Media type <br> application/json <br> **Example Value** Schema | *No links* |

| Code | Description | Links |
|---|---|---|


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**DELETE** `/api/v1/items/{id}/favorite`

### Parameters

Try it out

| Name | Description |
|---|---|
| **id** * <br> `string($guid)` <br> *(path)* | id |

### Responses

| Code | Description | Links |
|---|---|---|
| 200 | Media type | *No links* |

| Code | Description | Links |
| --- | --- | --- |

application/json

Controls `Accept` header.

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


404 *No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


GET /api/v1/users/me/favorites

## Parameters

Try it out

No parameters

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "success": true,
    "items": [
      {
        "id": "string",
        "title": "string",
        "dailyPrice": 0,
        "primaryImage": "string",
        "city": "string"
      }
    ],
    "error": "string"
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
```

| Code | Description | Links |
| --- | --- | --- |

```
  "successCode": 0
}
```

## Delivery

**GET** `/api/v1/orders/{id}/delivery`

### Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

### Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema | *No links* |

```
{
  "data": [
    {
```

| Code | Description | Links |
| --- | --- | --- |


```
      "status": "string",
      "location": "string",
      "updatedAt": "2026-04-19T19:53:53.137Z"
    }
  ],
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


404 *No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**PUT** `/api/v1/orders/{id}/delivery`

**Parameters** Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

**Request body** application/json

**Example Value** Schema

```
{
  "orderId": "string",
  "status": "string",
  "location": "string"
}
```

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema <br> `{ "data": "string", "error": true, "errorCode": [ 0 ], "messages": [` | *No links* |

| Code | Description | Links |
| --- | --- | --- |


```
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400

*No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## Reviews

**POST** `/api/v1/rentals/{id}/review`

**Parameters** Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

**Request body** application/json

**Example Value** Schema

```
{
  "rentalId": "string",
  "rating": 0,
  "comment": "string"
}
```

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 201 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema <br> `{ "data": { "reviewId": "string", "rating": 0, "comment": "string" }, "error": true,` | *No links* |

| Code | Description | Links |
| --- | --- | --- |


```
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400

*No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


GET `/api/v1/items/{id}/reviews`

**Parameters** Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema | *No links* |


```
{
  "data": {
    "reviews": [
      {
        "id": "string",
        "rating": 0,
        "comment": "string",
        "reviewer": {
          "firstName": "string",
          "profileImageUrl": "string"
        },
        "createdAt": "2026-04-19T19:53:53.166Z"
      }
    ],
    "avgRating": 0,
    "totalReviews": 0
  },
  "error": true,
  "errorCode": [
    0
  ],
```

| Code | Description | Links |
| --- | --- | --- |


```
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
```


## Verifications

**POST** `/api/v1/items/{id}/verify`

**Parameters** Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

**Request body** application/json

**Example Value** Schema


```
{
  "itemId": "string",
  "rentalId": "string",
  "checkType": "string",
  "status": "string",
  "notes": "string"
}
```

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 201 | Media type<br>application/json<br>Controls `Accept` header.<br><br>**Example Value** Schema<br><br>{<br>"data": {<br>"verificationId": "string",<br>"status": "string"<br>},<br>"error": true,<br>"errorCode": [<br>0<br>],<br>"messages": [<br>"string"<br>],<br>"total": 0,<br>"page": 0,<br>"pages": 0,<br>"successCode": 0<br>} | *No links* |
| 400 | Media type<br>application/json<br><br>**Example Value** Schema<br><br>{<br>"data": "string",<br>"error": true,<br>"errorCode": [<br>0<br>],<br>"messages": [<br>"string"<br>],<br>"total": 0, | *No links* |

| Code | Description | Links |
| --- | --- | --- |


```
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## GET /api/v1/items/{id}/verifications

### Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

### Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema | *No links* |


```
{
  "data": {
    "success": true,
    "error": "string",
    "verifications": [
```

| Code | Description | Links |
| --- | --- | --- |


```
      {
        "id": "string",
        "checkType": "string",
        "status": "string",
        "notes": "string",
        "expertFirstName": "string",
        "createdAt": "2026-04-19T19:53:53.182Z"
      }
    ]
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


404 *No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```

GET /api/v1/expert/assigned

**Parameters** Try it out

No parameters

**Responses**

| Code | Description | Links |
|---|---|---|
| 200 | Media type<br>application/json<br>Controls Accept header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "assignments": [
      {
        "verificationId": "string",
        "itemTitleAr": "string",
        "itemTitleEn": "string",
        "itemImage": "string",
        "rentalStartDate": "2026-04-19T19:53:53.187Z",
        "rentalEndDate": "2026-04-19T19:53:53.187Z",
        "checkType": "string",
        "createdAt": "2026-04-19T19:53:53.187Z"
      }
    ]
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
```

| Code | Description | Links |
| --- | --- | --- |


```
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## Admin

**GET** `/api/v1/admin/fraud`

**Parameters** Try it out

| Name | Description |
| --- | --- |
| decision<br>`string`<br>*(query)* | decision |
| minRisk<br>`number($double)`<br>*(query)* | minRisk |
| **page** *<br>`integer($int32)`<br>*(query)* | page |
| **limit** *<br>`integer($int32)`<br>*(query)* | limit |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |

```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```

GET /api/v1/admin/users

### Parameters

Try it out

| Name | Description |
| --- | --- |
| **page** * <br>`integer($int32)` <br>*(query)* | page |
| **limit** * <br>`integer($int32)` | limit |

| Name | Description |
| --- | --- |
| *(query)* | |

### Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## PUT /api/v1/admin/users/{id}/status

### Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> integer($int64) <br> *(path)* | id |

**Request body** application/json

**Example Value** Schema

```
{
  "userId": 0,
  "isActive": true
}
```

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema | *No links* |

```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
```

| Code | Description | Links |
| --- | --- | --- |


```
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


404

*No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


GET /api/v1/admin/kpis

**Parameters** Try it out

| Name | Description |
| --- | --- |
| period<br>**string**<br>*(query)* | period |

| Name | Description |
| --- | --- |
| from<br>**string**($date-time)<br>*(query)* | from |
| to<br>**string**($date-time)<br>*(query)* | to |

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**GET** `/api/v1/admin/kpis/latest`

**Parameters** Try it out

No parameters

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema<br>{<br>"data": "string",<br>"error": true,<br>"errorCode": [<br>0<br>],<br>"messages": [<br>"string"<br>],<br>"total": 0,<br>"page": 0,<br>"pages": 0,<br>"successCode": 0<br>} | *No links* |
| 404 | Media type<br>application/json<br>**Example Value** Schema<br>{<br>"data": "string",<br>"error": true,<br>"errorCode": [<br>0<br>],<br>"messages": [<br>"string"<br>],<br>"total": 0,<br>"page": 0,<br>"pages": 0,<br>"successCode": 0<br>} | *No links* |

GET /api/v1/admin/gap

## Parameters

Try it out

| Name | Description |
| --- | --- |
| period<br>string<br>*(query)* | period |
| **limit** *<br>integer($int32)<br>*(query)* | limit |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls Accept header.<br>**Example Value** Schema | *No links* |

```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
```

| Code | Description | Links |
| --- | --- | --- |


```
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## Subcategories

**GET** `/api/v1/categories/{categoryId}/subcategories`

**Parameters** Try it out

| Name | Description |
| --- | --- |
| **categoryId** * <br> `integer($int32)` <br> *(path)* | categoryId |
| **page** * <br> `integer($int32)` <br> *(query)* | page |
| **limit** * <br> `integer($int32)` <br> *(query)* | limit |
| sortBy <br> `string` <br> *(query)* | sortBy |

| Name | Description |
| --- | --- |
| sortOrder<br>**string**<br>*(query)* | sortOrder |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": [
    {
      "id": 0,
      "nameAr": "string",
      "nameEn": "string",
      "descAr": "string",
      "descEn": "string",
      "logoId": "string",
      "logoUrl": "string",
      "categoryId": 0,
      "categoryNameAr": "string",
      "categoryNameEn": "string",
      "productCount": 0,
      "created": "2026-04-19T19:53:53.252Z",
      "lastModified": "2026-04-19T19:53:53.252Z"
    }
  ],
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
```

| Code | Description | Links |
| --- | --- | --- |


```
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
```


GET /api/v1/subcategories

Parameters

Try it out

| Name | Description |
| --- | --- |
| categoryId<br>integer($int32)<br>*(query)* | categoryId |
| search<br>string<br>*(query)* | search |
| **page** *<br>integer($int32)<br>*(query)* | page |
| **limit** *<br>integer($int32)<br>*(query)* | limit |
| sortBy<br>string<br>*(query)* | sortBy |

| Name | Description |
| --- | --- |
| sortOrder<br>**string**<br>*(query)* | sortOrder |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": [
    {
      "id": 0,
      "nameAr": "string",
      "nameEn": "string",
      "descAr": "string",
      "descEn": "string",
      "logoId": "string",
      "logoUrl": "string",
      "categoryId": 0,
      "categoryNameAr": "string",
      "categoryNameEn": "string",
      "productCount": 0,
      "created": "2026-04-19T19:53:53.265Z",
      "lastModified": "2026-04-19T19:53:53.265Z"
    }
  ],
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
```

Code


```
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
```


Links

**POST** `/api/v1/subcategories`

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema


```
{
  "nameAr": "string",
  "nameEn": "string",
  "descAr": "string",
  "descEn": "string",
  "categoryId": 0,
  "logoId": "string"
}
```


**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 201 | Media type | *No links* |

| Code | Description | Links |
| --- | --- | --- |

application/json

Controls `Accept` header.

**Example Value** Schema


```
{
  "data": {
    "id": 0,
    "nameAr": "string",
    "nameEn": "string",
    "descAr": "string",
    "descEn": "string",
    "logoId": "string",
    "logoUrl": "string",
    "categoryId": 0,
    "categoryNameAr": "string",
    "categoryNameEn": "string",
    "productCount": 0,
    "created": "2026-04-19T19:53:53.274Z",
    "lastModified": "2026-04-19T19:53:53.274Z"
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400 *No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
```

| Code | Description | Links |
| --- | --- | --- |


```
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


GET /api/v1/subcategories/{id}

Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `integer($int32)` <br> *(path)* | id |

Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema | *No links* |

| Code | Description | Links |
| --- | --- | --- |


```
{
  "data": {
    "id": 0,
    "nameAr": "string",
    "nameEn": "string",
    "descAr": "string",
    "descEn": "string",
    "logoId": "string",
    "logoUrl": "string",
    "categoryId": 0,
    "categoryNameAr": "string",
    "categoryNameEn": "string",
    "productCount": 0,
    "created": "2026-04-19T19:53:53.281Z",
    "lastModified": "2026-04-19T19:53:53.281Z"
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


404 *No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
```

| Code | Description | Links |
| --- | --- | --- |


```
  "successCode": 0
}
```


**PUT** `/api/v1/subcategories/{id}`

**Parameters** Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `integer($int32)` <br> *(path)* | id |

**Request body** application/json

**Example Value** Schema


```
{
  "id": 0,
  "nameAr": "string",
  "nameEn": "string",
  "descAr": "string",
  "descEn": "string",
  "categoryId": 0,
  "logoId": "string"
}
```


**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "id": 0,
    "nameAr": "string",
    "nameEn": "string",
    "descAr": "string",
    "descEn": "string",
    "logoId": "string",
    "logoUrl": "string",
    "categoryId": 0,
    "categoryNameAr": "string",
    "categoryNameEn": "string",
    "productCount": 0,
    "created": "2026-04-19T19:53:53.294Z",
    "lastModified": "2026-04-19T19:53:53.294Z"
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


| | | |
| --- | --- | --- |
| 400 | Media type<br>application/json<br>**Example Value** Schema | *No links* |


```
{
  "data": "string",
```

| Code | Description | Links |
| --- | --- | --- |


```
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**DELETE** `/api/v1/subcategories/{id}`

### Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `integer($int32)` <br> *(path)* | id |

### Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. | *No links* |

| Code | Description | Links |
| --- | --- | --- |

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400 *No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## Rentals

POST /api/v1/rentals

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema


```
{
  "itemId": "string",
  "startDate": "2026-04-19T19:53:53.308Z",
  "endDate": "2026-04-19T19:53:53.308Z",
  "pricingType": "string"
}
```


**Responses**

| Code | Description | Links |
|---|---|---|
| 201 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "rentalId": "string",
    "orderId": "string",
    "rentalPrice": 0,
    "depositAmount": 0,
    "status": "string"
  },
  "error": true,
  "errorCode": [
```

| Code | Description | Links |
| --- | --- | --- |


```
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400

*No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


GET /api/v1/rentals

**Parameters** Try it out

| Name | Description |
| --- | --- |
| status<br>`string`<br>*(query)* | status |
| **page** *<br>`integer($int32)`<br>*(query)* | page |
| **limit** *<br>`integer($int32)`<br>*(query)* | limit |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "rentals": [
      {
        "id": "string",
        "itemTitle": "string",
        "itemImage": "string",
        "startDate": "2026-04-19T19:53:53.318Z",
        "endDate": "2026-04-19T19:53:53.318Z",
        "rentalPrice": 0,
```

| Code | Description | Links |
| --- | --- | --- |


```
        "status": "string",
        "depositStatus": "string"
      }
    ],
    "total": 0,
    "page": 0,
    "pages": 0
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
```


## GET /api/v1/rentals/{id}

### Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

### Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "id": "string",
    "itemId": "string",
    "itemTitle": "string",
    "itemImage": "string",
    "ownerFirstName": "string",
    "ownerCity": "string",
    "startDate": "2026-04-19T19:53:53.323Z",
    "endDate": "2026-04-19T19:53:53.323Z",
    "actualReturnDate": "2026-04-19T19:53:53.323Z",
    "rentalPrice": 0,
    "depositAmount": 0,
    "lateFee": 0,
    "status": "string",
    "depositStatus": "string",
    "notes": "string",
    "createdAt": "2026-04-19T19:53:53.323Z",
    "hasReview": true
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
```


| | | |
| --- | --- | --- |
| 404 | Media type<br>application/json<br>**Example Value** Schema | *No links* |


```
{
  "data": "string",
```

| Code | Description | Links |
| --- | --- | --- |


```
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**PUT** `/api/v1/rentals/{id}/confirm`

### Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

### Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. | *No links* |

| Code | Description | Links |
| --- | --- | --- |

**Example Value** Schema


```
{
  "data": {
    "status": "string"
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400 *No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


PUT `/api/v1/rentals/{id}/activate`

**Parameters**

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema <br> { "data": { "status": "string" }, "error": true, "errorCode": [ 0 ], "messages": [ "string" ], "total": 0, "page": 0, "pages": 0, "successCode": 0 } | *No links* |
| 400 | | *No links* |

| Code | Description | Links |
|---|---|---|

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**PUT** `/api/v1/rentals/{id}/complete`

**Parameters** Try it out

| Name | Description |
|---|---|
| **id** * <br> `string($guid)` <br> *(path)* | id |
| **damaged** * <br> `boolean` <br> *(query)* | -- |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |
| 400 | Media type<br>application/json<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "rentalId": "string",
    "status": "string",
    "lateFee": 0,
    "depositStatus": "string"
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```



```
{
  "data": "string",
  "error": true,
  "errorCode": [
```

| Code | Description | Links |
| --- | --- | --- |


```
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**PUT** `/api/v1/rentals/{id}/cancel`

### Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

### Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema | *No links* |

| Code | Description | Links |
| --- | --- | --- |
| | {<br>"data": {<br>"status": "string"<br>},<br>"error": true,<br>"errorCode": [<br>0<br>],<br>"messages": [<br>"string"<br>],<br>"total": 0,<br>"page": 0,<br>"pages": 0,<br>"successCode": 0<br>} | |
| 400 | Media type<br>application/json<br>**Example Value** Schema<br>{<br>"data": "string",<br>"error": true,<br>"errorCode": [<br>0<br>],<br>"messages": [<br>"string"<br>],<br>"total": 0,<br>"page": 0,<br>"pages": 0,<br>"successCode": 0<br>} | *No links* |

## Orders

POST /api/v1/orders

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema

```
{
  "items": [
    {
      "itemId": "string",
      "quantity": 0
    }
  ]
}
```

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 201 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema<br>`{ "data": { "orderId": "string", "totalAmount": 0, "status": "string" }, "error": true, "errorCode": [` | *No links* |

| Code | Description | Links |
| --- | --- | --- |


```
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400

*No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


GET `/api/v1/orders`

**Parameters** Try it out

No parameters

## Responses

| Code | Description | Links |
|---|---|---|
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "orders": [
      {
        "id": "string",
        "totalAmount": 0,
        "status": "string",
        "createdAt": "2026-04-19T19:53:53.363Z",
        "itemCount": 0
      }
    ]
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


GET /api/v1/orders/{id}

Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema | *No links* |


```
{
  "data": {
    "id": "string",
    "totalAmount": 0,
    "status": "string",
    "createdAt": "2026-04-19T19:53:53.367Z",
    "items": [
      {
        "itemId": "string",
        "title": "string",
        "quantity": 0,
        "priceAtTime": 0,
        "primaryImage": "string"
      }
    ],
    "paymentStatus": "string",
    "deliveryStatus": "string"
  },
  "error": true,
  "errorCode": [
    0
```

| Code | Description | Links |
| --- | --- | --- |
| 404 | Media type<br>application/json<br>**Example Value** Schema | *No links* |


```
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
```



```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## Payments

**POST** `/api/v1/payments`

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema


```
{
  "orderId": "string",
  "method": "string",
  "transactionRef": "string"
}
```


## Responses

| Code | Description | Links |
| --- | --- | --- |
| 201 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |
| 400 | Media type | *No links* |


```
{
  "data": {
    "paymentId": "string",
    "status": "string",
    "transactionRef": "string"
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```

| Code | Description | Links |
| --- | --- | --- |

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**GET** `/api/v1/payments/{orderId}`

**Parameters** Try it out

| Name | Description |
| --- | --- |
| **orderId** * <br> `string($guid)` <br> *(path)* | orderId |

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |
| 404 | Media type<br>application/json<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "id": "string",
    "amount": 0,
    "method": "string",
    "status": "string",
    "createdAt": "2026-04-19T19:53:53.383Z"
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```

```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
```

| Code | Description | Links |
| --- | --- | --- |


```
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## Support

POST /api/v1/support/tickets

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema


```
{
  "type": "string",
  "message": "string"
}
```


**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 201 | Media type | *No links* |

| Code | Description | Links |
| --- | --- | --- |
| | application/json<br>Controls `Accept` header.<br><br>**Example Value** Schema<br><br>`{ "data": { "ticketId": "string", "status": "string" }, "error": true, "errorCode": [ 0 ], "messages": [ "string" ], "total": 0, "page": 0, "pages": 0, "successCode": 0 }` | |
| 400 | Media type<br>application/json<br><br>**Example Value** Schema<br><br>`{ "data": "string", "error": true, "errorCode": [ 0 ], "messages": [ "string" ], "total": 0, "page": 0, "pages": 0, "successCode": 0 }` | *No links* |

GET /api/v1/support/tickets

**Parameters** Try it out

No parameters

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "tickets": [
      {
        "id": "string",
        "type": "string",
        "status": "string",
        "createdAt": "2026-04-19T19:53:53.398Z",
        "lastMessage": "string"
      }
    ]
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
```

| Code | Description | Links |
| --- | --- | --- |

```
  "successCode": 0
}
```

**POST** `/api/v1/support/tickets/{id}/messages`

### Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

### Request body

application/json

**Example Value** Schema

```
{
  "ticketId": "string",
  "message": "string"
}
```

### Responses

| Code | Description | Links |
| --- | --- | --- |
| 201 | Media type | *No links* |

| Code | Description | Links |
| --- | --- | --- |

application/json

Controls `Accept` header.

**Example Value** Schema


```
{
  "data": {
    "messageId": "string",
    "message": "string",
    "createdAt": "2026-04-19T19:53:53.408Z"
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400 *No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```

PUT /api/v1/support/tickets/{id}/status

## Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

## Request body

application/json

**Example Value** Schema

```
{
  "ticketId": "string",
  "status": "string"
}
```

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema | *No links* |

| Code | Description | Links |
| --- | --- | --- |
| | <pre>{<br>  "data": {<br>  "ticketId": "string",<br>  "status": "string"<br>  },<br>  "error": true,<br>  "errorCode": [<br>  0<br>  ],<br>  "messages": [<br>  "string"<br>  ],<br>  "total": 0,<br>  "page": 0,<br>  "pages": 0,<br>  "successCode": 0<br>}</pre> | |
| 400 | Media type<br>application/json<br><br>**Example Value** Schema<br><br><pre>{<br>  "data": "string",<br>  "error": true,<br>  "errorCode": [<br>  0<br>  ],<br>  "messages": [<br>  "string"<br>  ],<br>  "total": 0,<br>  "page": 0,<br>  "pages": 0,<br>  "successCode": 0<br>}</pre> | *No links* |

## Chat

POST /api/v1/chats

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema

```
{
  "userId": 0
}
```

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 201 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema<br>`{ "data": { "chatId": "string" }, "error": true, "errorCode": [ 0 ], "messages": [ "string" ],` | *No links* |

| Code | Description | Links |
| --- | --- | --- |


```
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400

*No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


GET /api/v1/chats

**Parameters** Try it out

No parameters

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br><br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "chats": [
      {
        "id": "string",
        "otherUserFirstName": "string",
        "otherUserProfileImage": "string",
        "lastMessage": "string",
        "unreadCount": 0
      }
    ]
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


POST /api/v1/chats/{id}/messages

**Parameters** Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

**Request body** application/json

**Example Value** Schema

```
{
  "chatId": "string",
  "message": "string"
}
```

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 201 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema <br> `{ "data": { "messageId": "string", "message": "string", "createdAt": "2026-04-19T19:53:53.444Z" }, "error": true,` | *No links* |

| Code | Description | Links |
| --- | --- | --- |


```
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400

*No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


GET /api/v1/chats/{id}/messages

**Parameters** Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema | *No links* |


```
{
  "data": {
    "found": true,
    "error": "string",
    "messages": [
      {
        "id": "string",
        "senderId": 0,
        "message": "string",
        "isRead": true,
        "createdAt": "2026-04-19T19:53:53.451Z"
      }
    ]
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
```

| Code | Description | Links |
| --- | --- | --- |


```
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


404 *No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## Notifications

GET `/api/v1/notifications`

**Parameters** Try it out

No parameters

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "notifications": [
      {
        "id": "string",
        "title": "string",
        "message": "string",
        "isRead": true,
        "createdAt": "2026-04-19T19:53:53.456Z"
      }
    ],
    "unreadCount": 0
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**PUT** `/api/v1/notifications/read-all`

**Parameters** Try it out

No parameters

### Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br><br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "message": "string",
    "updated": 0
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


PUT /api/v1/notifications/{id}/read

## Recommendations

GET /api/v1/recommendations

## Parameters

Try it out

No parameters

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "recommendations": [
      {
        "id": "string",
        "item": {
          "id": "string",
          "title": "string",
          "price": 0,
          "image": "string",
          "city": "string"
        },
        "score": 0,
        "reason": "string",
        "algorithm": "string"
      }
    ]
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
```

| Code | Description | Links |
| --- | --- | --- |


```
  "page": 0,
  "pages": 0,
```


**PUT** `/api/v1/recommendations/{id}/click`

### Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `string($guid)` <br> *(path)* | id |

### Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema | *No links* |


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
```

| Code | Description | Links |
| --- | --- | --- |


```
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


404 *No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## Media

**POST** `/api/v1/media`

**Parameters** Try it out

| Name | Description |
| --- | --- |
| entityId<br>**string($guid)**<br>*(query)* | entityId |
| entityType<br>**string**<br>*(query)* | entityType |

Request body **multipart/form-data**

file
**string($binary)**

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 201 | Media type<br>**application/json**<br>Controls `Accept` header.<br>**Example Value** Schema<br>`{ "data": {` | *No links* |

| Code | Description | Links |
| --- | --- | --- |


```
    "id": "string",
    "url": "string",
    "fileName": "string",
    "extension": "string",
    "contentType": "string",
    "fileType": "string",
    "sizeBytes": 0,
    "width": 0,
    "height": 0,
    "createdAt": "2026-04-19T19:53:53.490Z",
    "entityId": "string",
    "entityType": "string"
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400

*No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```

# Categories

GET /api/v1/categories

Parameters

Try it out

| Name | Description |
| --- | --- |
| search<br>string<br>*(query)* | search |
| **page** *<br>integer($int32)<br>*(query)* | page |
| **limit** *<br>integer($int32)<br>*(query)* | limit |
| sortBy<br>string<br>*(query)* | sortBy |
| sortOrder<br>string<br>*(query)* | sortOrder |

Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": [
    {
      "id": 0,
      "nameAr": "string",
      "nameEn": "string",
      "descAr": "string",
      "descEn": "string",
      "logoId": "string",
      "logoUrl": "string",
      "subcategoryCount": 0,
      "created": "2026-04-19T19:53:53.504Z",
      "lastModified": "2026-04-19T19:53:53.504Z"
    }
  ],
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


POST /api/v1/categories

Parameters

Try it out

No parameters

**Request body** application/json

**Example Value** Schema

```
{
  "nameAr": "string",
  "nameEn": "string",
  "descAr": "string",
  "descEn": "string",
  "logoId": "string"
}
```

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 201 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |

```
{
  "data": {
    "id": 0,
    "nameAr": "string",
    "nameEn": "string",
    "descAr": "string",
    "descEn": "string",
    "logoId": "string",
    "logoUrl": "string",
    "subcategoryCount": 0,
    "created": "2026-04-19T19:53:53.512Z",
    "lastModified": "2026-04-19T19:53:53.512Z"
```

| Code | Description | Links |
| --- | --- | --- |


```
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400 *No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


GET /api/v1/categories/{id}

**Parameters** Try it out

| Name | Description |
| --- | --- |
| **id** * <br> integer($int32) <br> *(path)* | id |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls Accept header. <br> **Example Value** Schema | *No links* |


```
{
  "data": {
    "id": 0,
    "nameAr": "string",
    "nameEn": "string",
    "descAr": "string",
    "descEn": "string",
    "logoId": "string",
    "logoUrl": "string",
    "subcategoryCount": 0,
    "created": "2026-04-19T19:53:53.518Z",
    "lastModified": "2026-04-19T19:53:53.518Z"
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
```

| Code | Description | Links |
| --- | --- | --- |


```
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


404

*No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**PUT** `/api/v1/categories/{id}`

**Parameters** Try it out

| Name | Description |
| --- | --- |
| **id** * `integer($int32)` *(path)* | id |

**Request body**

application/json

**Example Value** Schema


```
{
  "id": 0,
  "nameAr": "string",
  "nameEn": "string",
  "descAr": "string",
  "descEn": "string",
  "logoId": "string"
}
```


## Responses

| Code | Description | Links |
|---|---|---|
| 200 | Media type<br>application/json<br>Controls `Accept` header.<br><br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "id": 0,
    "nameAr": "string",
    "nameEn": "string",
    "descAr": "string",
    "descEn": "string",
    "logoId": "string",
    "logoUrl": "string",
    "subcategoryCount": 0,
    "created": "2026-04-19T19:53:53.530Z",
    "lastModified": "2026-04-19T19:53:53.530Z"
  },
  "error": true,
  "errorCode": [
```

| Code | Description | Links |
| --- | --- | --- |


```
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400

*No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**DELETE** `/api/v1/categories/{id}`

**Parameters** Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `integer($int32)` <br> *(path)* | id |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema <br> { "data": "string", "error": true, "errorCode": [ 0 ], "messages": [ "string" ], "total": 0, "page": 0, "pages": 0, "successCode": 0 } | *No links* |
| 400 | Media type <br> application/json <br> **Example Value** Schema | *No links* |

| Code | Description | Links |
| --- | --- | --- |


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## Brands

**GET** `/api/v1/brands`

**Parameters** Try it out

| Name | Description |
| --- | --- |
| search<br>`string`<br>*(query)* | search |
| **page** *<br>`integer($int32)`<br>*(query)* | page |
| **limit** *<br>`integer($int32)`<br>*(query)* | limit |

| Name | Description |
| --- | --- |
| sortBy<br>**string**<br>*(query)* | sortBy |
| sortOrder<br>**string**<br>*(query)* | sortOrder |

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type<br>application/json<br>Controls Accept header.<br>**Example Value** Schema | *No links* |


```
{
  "data": [
    {
      "id": 0,
      "nameAr": "string",
      "nameEn": "string",
      "descAr": "string",
      "descEn": "string",
      "logoId": "string",
      "logoUrl": "string",
      "itemCount": 0
    }
  ],
  "error": true,
  "errorCode": [
    0
  ],
```

| Code | Description | Links |
| --- | --- | --- |


```
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**POST** `/api/v1/brands`

**Parameters** Try it out

No parameters

**Request body** application/json

**Example Value** Schema


```
{
  "nameAr": "string",
  "nameEn": "string",
  "descAr": "string",
  "descEn": "string",
  "logoId": "string"
}
```


**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 201 | Media type<br>application/json<br>Controls `Accept` header.<br>**Example Value** Schema | *No links* |


```
{
  "data": {
    "id": 0,
    "nameAr": "string",
    "nameEn": "string",
    "descAr": "string",
    "descEn": "string",
    "logoId": "string",
    "logoUrl": "string",
    "itemCount": 0
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


| | | |
| --- | --- | --- |
| 400 | Media type<br>application/json<br>**Example Value** Schema | *No links* |


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
```

| Code | Description | Links |
| --- | --- | --- |


```
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


## GET /api/v1/brands/{id}

### Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `integer($int32)` <br> *(path)* | id |

### Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema | *No links* |


```
{
  "data": {
```

| Code | Description | Links |
| --- | --- | --- |


```
    "id": 0,
    "nameAr": "string",
    "nameEn": "string",
    "descAr": "string",
    "descEn": "string",
    "logoId": "string",
    "logoUrl": "string",
    "itemCount": 0
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


404 *No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


**PUT** `/api/v1/brands/{id}`

## Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> `integer($int32)` <br> *(path)* | id |

## Request body

application/json

**Example Value** Schema

```
{
  "id": 0,
  "nameAr": "string",
  "nameEn": "string",
  "descAr": "string",
  "descEn": "string",
  "logoId": "string"
}
```

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls `Accept` header. <br> **Example Value** Schema | *No links* |

| Code | Description | Links |
| --- | --- | --- |


```
{
  "data": {
    "id": 0,
    "nameAr": "string",
    "nameEn": "string",
    "descAr": "string",
    "descEn": "string",
    "logoId": "string",
    "logoUrl": "string",
    "itemCount": 0
  },
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```


400 *No links*

Media type

application/json

**Example Value** Schema


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```

DELETE /api/v1/brands/{id}

Parameters

Try it out

| Name | Description |
| --- | --- |
| **id** * <br> integer($int32) <br> *(path)* | id |

Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | Media type <br> application/json <br> Controls Accept header. <br> **Example Value** Schema | *No links* |


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```

| Code | Description | Links |
| --- | --- | --- |
| 404 | Media type<br>application/json<br>**Example Value** Schema | |


```
{
  "data": "string",
  "error": true,
  "errorCode": [
    0
  ],
  "messages": [
    "string"
  ],
  "total": 0,
  "page": 0,
  "pages": 0,
  "successCode": 0
}
```