

GeeksforGeeks

A computer science portal for geeks

[Android App](#) [GeeksQuiz](#)

[Login/Register](#)

- [Home](#)
- [Algorithms](#)
- [DS](#)
- [GATE](#)
- [Interview Corner](#)
- [Q&A](#)
- [C](#)
- [C++](#)
- [Java](#)
- [Books](#)
- [Contribute](#)
- [Ask a Q](#)
- [About](#)

[Array](#)

[Bit Magic](#)

[C/C++](#)

[Articles](#)

[GFacts](#)

[Linked List](#)

[MCQ](#)

[Misc](#)

[Output](#)

[String](#)

[Tree](#)

[Graph](#)

Pairwise swap elements of a given linked list

Given a singly linked list, write a function to swap elements pairwise. For example, if the linked list is 1->2->3->4->5 then the function should change it to 2->1->4->3->5, and if the linked list is 1->2->3->4->5->6 then the function should change it to 2->1->4->3->6->5.

METHOD 1 (Iterative)

Start from the head node and traverse the list. While traversing swap data of each node with its next node's data.

```
/* Program to pairwise swap elements in a given linked list */  
#include<stdio.h>
```

```
#include<stdlib.h>

/* A linked list node */
struct node
{
    int data;
    struct node *next;
};

/*Function to swap two integers at addresses a and b */
void swap(int *a, int *b);

/* Function to pairwise swap elements of a linked list */
void pairWiseSwap(struct node *head)
{
    struct node *temp = head;

    /* Traverse further only if there are at-least two nodes left */
    while (temp != NULL && temp->next != NULL)
    {
        /* Swap data of node with its next node's data */
        swap(&temp->data, &temp->next->data);

        /* Move temp by 2 for the next pair */
        temp = temp->next->next;
    }
}

/* UTILITY FUNCTIONS */
/* Function to swap two integers */
void swap(int *a, int *b)
{
    int temp;
    temp = *a;
    *a = *b;
    *b = temp;
}

/* Function to add a node at the beginning of Linked List */
void push(struct node** head_ref, int new_data)
{
    /* allocate node */
    struct node* new_node =
        (struct node*) malloc(sizeof(struct node));

    /* put in the data */
    new_node->data = new_data;

    /* link the old list off the new node */
    new_node->next = (*head_ref);

    /* move the head to point to the new node */
    (*head_ref) = new_node;
}
```

```

}

/* Function to print nodes in a given linked list */
void printList(struct node *node)
{
    while (node != NULL)
    {
        printf("%d ", node->data);
        node = node->next;
    }
}

/* Driver program to test above function */
int main()
{
    struct node *start = NULL;

    /* The constructed linked list is:
       1->2->3->4->5 */
    push(&start, 5);
    push(&start, 4);
    push(&start, 3);
    push(&start, 2);
    push(&start, 1);

    printf("\n Linked list before calling pairwiseSwap() ");
    printList(start);

    pairwiseSwap(start);

    printf("\n Linked list after calling pairwiseSwap() ");
    printList(start);

    getchar();
    return 0;
}

```

Time complexity: O(n)

METHOD 2 (Recursive)

If there are 2 or more than 2 nodes in Linked List then swap the first two nodes and recursively call for rest of the list.

```

/* Recursive function to pairwise swap elements of a linked list */
void pairwiseSwap(struct node *head)
{
    /* There must be at-least two nodes in the list */
    if(head != NULL && head->next != NULL)
    {
        /* Swap the node's data with data of next node */
        swap(&head->data, &head->next->data);

        /* Call pairwiseSwap() for rest of the list */
    }
}

```

```

    pairWiseSwap(head->next->next);
}
}

```

Time complexity: $O(n)$

The solution provided there swaps data of nodes. If data contains many fields, there will be many swap operations. See [this](#) for an implementation that changes links rather than swapping data.

Please write comments if you find any bug in above code/algorithm, or find other ways to solve the same problem.

Related Topics:

- [Clone a linked list with next and random pointer | Set 2](#)
- [Given a linked list of line segments, remove middle points](#)
- [Construct a Maximum Sum Linked List out of two Sorted Linked Lists having some Common nodes](#)
- [Given a linked list, reverse alternate nodes and append at the end](#)
- [Pairwise swap elements of a given linked list by changing links](#)
- [Self Organizing List | Set 1 \(Introduction\)](#)
- [Merge a linked list into another linked list at alternate positions](#)
- [QuickSort on Singly Linked List](#)

Like { 4

Tweet { 0

g+1 { 0

Writing code in comment? Please use ideone.com and share the link here.

•

•

•

•

- [Interview Experiences](#)
- [Advanced Data Structures](#)
- [Dynamic Programming](#)
- [Greedy Algorithms](#)
- [Backtracking](#)

- [Pattern Searching](#)
- [Divide & Conquer](#)
- [Mathematical Algorithms](#)
- [Recursion](#)
- [Geometric Algorithms](#)

• Popular Posts

- [All permutations of a given string](#)
- [Memory Layout of C Programs](#)
- [Understanding “extern” keyword in C](#)
- [Median of two sorted arrays](#)
- [Tree traversal without recursion and without stack!](#)
- [Structure Member Alignment, Padding and Data Packing](#)
- [Intersection point of two Linked Lists](#)
- [Lowest Common Ancestor in a BST](#)
- [Check if a binary tree is BST or not](#)
- [Sorted Linked List to Balanced BST](#)

Follow @GeeksforGeeks



[Subscribe](#)

• Recent Comments

- [Bharath Kumar Reddy Janumpally](#)

findsubsets(int [] arr) { int numofsubsets =...

[Power Set](#) · [1 minute ago](#)

- [Siya](#)

We can do it in $O(n \log n)$ i guess by using...

[Myntra Interview Experience | Set 4 \(For Senior Software Engineer \)](#) · [2 minutes ago](#)

- [darkprotocol](#)

Thanks god u didnt selected for SE role. It...

[Amazon Interview | Set 124 \(On-Campus\)](#) · [22 minutes ago](#)

- [Humble_Learner](#)

When the range represented by the node (...)

[Segment Tree | Set 2 \(Range Minimum Query\)](#) · [34 minutes ago](#)

- [Humble_Learner](#)

Learned Something New! :)

[Segment Tree | Set 1 \(Sum of given range\)](#) · [43 minutes ago](#)

- o [tiger](#)

i think efficient solution for the problem in...

[Myntra Interview Experience | Set 4 \(For Senior Software Engineer\)](#) · [44 minutes ago](#)

•

@geeksforgeeks, [Some rights reserved](#) ____ [Contact Us!](#)

Powered by [WordPress](#) & [MooTools](#), customized by geeksforgeeks team