ENERGY BODIES

PROPOSAL FOR DIGITAL EXHIBITION
22 AUG 2025
RENÉE WALKER & CARRIE POWELL

Updated Budget

Item	Description	Cost
iPad Pro 11″	public interaction with Visualization	$0 (team)
Mac mini	running p5.js / PoseNet visualization, outputting directly to the display	$0 (team)
Canon SELPHY CP1500	artifact printout	$281 (team)
OmniMount OWS22 A/V Component Wall Shelf PET2 Adjustable Height, 11.5"L x 16.5"W	shelf for reciept printer	$45 (team)
Display Monitor (65" LG 4K UHD Smart LED TV – 65UF6450.AUS	Visual output	$0 (provided)
Software tools (p5) poseNet	Interactive visualization framework	$0 (creator license)
Audio Headphones (optional, for guided prompt)	Immersive tuning experience	$0 (provided?)
Portrait TV Wall Mount	Safe installation structure, portrait mounting	$62 (team)
Heckler Design – Wall Mount for iPad 10.9/11"	Safe installation structure, secure mounting	$200 (team)
Printed instructional panel	ADA-readable instructions, intro text	$0 (team)
Logitech C920	camera	$0 (team)
raceway kit + Velcro ties.	hide and secure cables	$30-40 (team)
Artist labor (design + setup)	Fabrication, testing, documentation	$0 (team)
Total		**$618**

Final exhibition plan

DISPLAY MONITOR
(65″ LG 4K UHD Smart LED TV – 65UF6450.AUS)

Orientation: Mounted in portrait format (vertical) using a universal VESA wall mount rated for 65″ displays.
Placement: Screen center at approximately 58″ from floor for average viewer eye height.
Bottom edge: ~30″ from floor
Top edge: ~86″ from floor
Mounting Method: Heavy-duty VESA mount (Peerless SF660P, Chief LSM1U, or equivalent) secured directly into wall studs with lag bolts; load capacity ≥ 80 lbs.
Ventilation: Minimum 4–6″ clearance above and below screen to ensure airflow.
Connectivity: HDMI cable routed from laptop/media PC to display, using in-wall or surface cable management channel.
Power: Dedicated wall outlet or power strip rated for continuous use, concealed behind or below the unit.

IPAD CONTROL INTERFACE
(iPad Pro 11″ / (iPad Air 10.9″)

Purpose: Public interaction point for adjusting real-time sliders that control the visualization.
Enclosure: Lockable wall-mounted enclosure sized for iPad Pro 11″ / Air 10.9″ (Heckler Design), with concealed cable pass-through for charging.
Device Size: Approx. 9.75″ wide × 7″ tall; enclosure footprint ~11″ × 8.5″.
Placement: iPad center positioned at 42–48″ from floor for ergonomic standing access.
Orientation: Portrait format to mirror the vertical display orientation.
Security: Enclosure secured to wall studs or backing board; enclosure includes keyed lock or tamper-resistant design.
Power: Continuous charging via concealed in-wall cable kit or surface conduit.

CAMERA
(Logitech C920 HD Pro)

Purpose: Provides live body tracking input for PoseNet.
Placement: Mounted directly above the display, centered, at ~7.2–7.5 ft from floor (just above the TV top edge).
Angle: Tilted downward ~10–15° to capture full body range (floor to head) for participants standing 5–10 ft away.
Mounting: Clip directly to the top bezel of the TV (reinforced with adhesive/Velcro for stability).
Cable Management: USB cable routed down behind the TV with HDMI/power; powered USB extension used if additional length required.

COMPUTER + PRINTER
(Mac mini + Canon SELPHY CP1500)

Mac mini: Dedicated computer running the p5.js / PoseNet visualization, outputting directly to the display.
Printer: Outputs participant “energy body” receipts.
Mounting: Both devices placed on an OmniMount ECS Single AV Wall Shelf (tempered glass, 30 lb capacity).
Arrangement:
— Mac mini secured toward the back of the shelf using HIDEit/HumanCentric Mac mini wall bracket screwed into the OmniMount plate (professional, tamper-proof).
— Canon SELPHY CP1500 positioned at the front for participant access; secured with non-slip mat + Velcro strips to prevent shifting during use.
Placement: Shelf surface at 36–40″ from floor (counter height) for ergonomic reach.
Clearance: Allow 8–10″ overhead clearance above printer for paper cassette access.
Connectivity:
Mac mini → TV via HDMI.
Mac mini → Webcam via USB.
iPad → Mac mini via Wi-Fi (slider data to visualization).
Mac mini → Printer via Wi-Fi (wireless printing).
Power: Both devices powered through shelf’s built-in cable channel, routed with concealed raceway to wall outlet.
Security: All cables secured inside the OmniMount’s cable pass-through; devices fixed with Velcro or brackets to prevent removal.



