

---

# Quantum Generative Adversarial Network with Noise

---

**Project Name:** Quantum Generative Adversarial Network with Noise

**Project member:**

*Yiming Huang*

*Zhili Chen*

*Wanghao Ren*

**Dodument Type:** Report

**Project Start Time:** 11/01/2017

**Sourcecode Version:** 0.0.1

**Keywords:** Variational Quantum Circuit, Machine Learning

**Modify** May 24, 2020

*Submitted by:*

XXX

## Contents


<b>1</b>	<b>Experiment</b>	<b>2</b>
<b>2</b>	<b>Results</b>	<b>2</b>
<b>3</b>	<b>Next Plan</b>	<b>5</b>
<b>4</b>	<b>Appendix</b>	<b>6</b>
A	Source Code . . . . .	6

## 1 Experiment


## 2 Results

1.Condition:  $C(T) = C(G) = C(D) = 1$ , 2qubit, probability of noise: 0.2


According to experiments, bit flip, phase flip and bit and phase flip all have an effect, but depolarizing basically has no effect.




(a) without noise




(b) bit flip



(c) phase flip



(d) bit and phase flip




(e) depolarizing


Figure 1

2.Condition:  $C(T) = C(G) = C(D) = 1$ , 2qubit, probability of noise: 0.4


Increasing the probability of noise, it can be found that noise will have a significant impact.




(a) without noise




(b) bit flip



(c) phase flip




(d) bit and phase flip




(e) depolarizing

Figure 2


3.Condition:  $C(T) = C(G) = C(D) = 1$ , 2qubit, probability of noise: 0.5  
 Bit flip and phase flip will have a great impact under this condition.




(a) without noise




(b) bit flip



(c) phase flip



(d) bit and phase flip



(e) depolarizing

Figure 3

### 3 Next Plan

1.

## 4 Appendix

### A Source Code