Appendix 2

Definition of how YAML objects should be formatted. Version 2. Written 1st April 2019

References to sub-sequences can be done with their names.

The ID of regimens and sequences, which is defined by the FarmBot when it receives it, will be written to internal storage automatically.

Example of a YAML file:

```
111111
other files: ["yaml file1", "yaml file2"] # This field is optional, the program will always look in its own file first.
PIN 1: water pin
                                           # optional labels for pins
                                          # option to set the scale of coordinates
scale : "1=10cm"
default_speed: 50
                                          # option to define a default speed
default z:0
                                          # option to define a default z-coordinate value
default x offset: 0
                                          # option to define a default x-offset value
default v offset: 0
                                          # option to define a default v-offset value
default z offset: 0
                                          # option to define a default z-offset value
# The program assumes every object with a "start_time" field is a Farm Event
my_event:
 start time: date time
 repeat event: {every: <<default 1>>, unit = "minutes/hours/days/weeks/months/years", until: <<date time>>} #optional
 schedule: [{group: [optional], type: [optional], days: [], times: [], actions: <<li>dist of actions or name of sequence>>}]
# Each list of actions can be iterated over a group or plant type, as defined in the CSV file
# The existance of a schedule field means each list of actions is repeated at the set days and times
# The list can be defined as a range. For example, "1,10,2" means every second number starting from 1 and smaller than 10.
# and "23:00,0:00,0:10" means every 10 minutes, starting from 23:00 and ending before 0:00
my_event:
 start time: date time
 group: ["extra_water_group"]
```

```
type: ["radish"]
 schedule: [{group: [optional], type: [optional], every: 4, unit: "minutes/hours/days/weeks/months/years", actions: []}]
# If an item in the schedule list does not have group and doess not have type, it defaults to the option defined above it
# This Farm Event also showcases an alternative way of defining schedules
my_event:
 start time: date time
 group: ["extra_water_group"]
 type: ["radish"]
 actions: [<<actions or name of sequence>>]
# If the object also has a "schedule" field, the "action" field will be ignored
# The program assumes every object without a "start_time" field but with a "schedule" field is a regimen
my_regimen:
 schedule: [{group: [optional], type: [optional], every: 4, unit: "minutes/hours/days/weeks/months/years", actions: []}]
 color: "gray/green/blue/yellow/orange/purple/red" #optional
# The program assumes every object without a "start_time" and without a "schedule" is a sequence
my sequence:
 color: #optional
 actions: []
# Individual actions in a list can also be a string that refers to the name of a sequence
The following are the keywords and formats we defined for single FarmBot commands such as "Move Absolute" and "Write Pin".
MOVE_REL: {x: 0, y: 0, z: <<defualt 0 or as defined>>, speed: <<defualt 50 or as defined>>}
MOVE ABS: {x: 0, y: 0, z: <<defualt 0 or as defined>>, x off: <<default 0 or as defined>>, y off: <<default 0 or as defined>>, z off: <<default 0 or
as defined>>, speed: }
IF : {cond: <<see below>>, then: , else: }
cond: "x = 0 AND y > 0 OR PIN_1 < 0 OR sensor_pin = UNKNOWN"
FIND\_HOME : [x,y,z]
```

```
MESSAGE: {text: <<note: {{x/y/z}} is a special tag>>, type: "success/warning/busy/error/info"}
WAIT: "time in milliseconds"
READ_PIN: {pin: "<<PIN_# or a name you chose>>", label: <<optional, default is pin name>>mode: "D/A"}
WRITE_PIN: {pin: "<<PIN_# or a name you chose>>", value: "ON/OFF", mode: "D"}
WRITE_PIN: {pin: "<<PIN_# or a name you chose>>", value: "0 to 1023", mode: "A"}

TO_SELF # Go to the current plant in a loop
TO_PLANT # go to a plant with this (unique) name, this saves typing in coordinates by hand if you have a special plant. e.g. we can have:
my_sequence:
group: ["water_group"]
actions: [WAIT:"1000", TO_SELF, "water_plant", TO_PLANT:"plant_name"]
```

Appendix 3

Definition of CSV format to be used for Farm Maps (order of the columns does not matter)

name	type	group	X	у	Z
optional	optional	optional	0	0	optional