

other

test runs of other methods

After running Test Bayes, test results will be output to the console (terminal) in the order they were run, or if the command was a parameter modification, no output will be produced. Test Bayes test runs are versioned, in that the output from test runs will be stored in files in the directory the tool is in, making the reordering exist across different machines running the code.

Customizable inputs-

You will be able to customize the following things according to need:

1. **New tests** - You can decide whether tests that have no previous runs will be run first, or just treated like tests with the most average stats out of all. This means that a new test will not be given a 50/50 chance of passing or failing, but instead will be treated as if it were similar to other tests, and will be given the average failure rate of all other tests about to be run. This would be specified with the `-n` flag in the command entered.
2. **Moving average** - You can decide what number of runs you want to include in the calculation of the moving average. While this is not the only parameter our code uses to compute the order of tests, it is certainly a big part of it, and we want to be able to adapt to your needs as much as possible. This can be set in the `pom.xml` file, through the `--avg` flag command, as described above. The default value for this moving average value is 20 test runs.
3. **Test Similarity** - You can finetune an epsilon parameter, which is a decimal value from 0.0 to 1.0, and determines how similar two tests' failure rates can be so as to order by time instead of failure rate. This can be set in the `pom.xml` file, through the `--eps` flag command, as described above. For example, if epsilon was set to 0.01, and two tests had failure rates of 0.94 and 0.95, but the second test was double as long, the first (shorter) test would be run. The default value for epsilon is 0.03.

Building our Project:

Building our project is simple. All dependencies of our project are built into the maven configuration, and will be imported on build, or are existent in the repository already. To run a build and run the tests, enter:

```
git clone https://github.com/avidant/test-bayes  
cd test-bayes
```

mvn clean verify

This will output the success or failure of the build, and success or failure of the tests we've written for our classes.

Further reading -

Much of this work was based off of tutorials given by links 1-5. If the user wants to further understand the workings behind what we are doing a few good places to look at would be:

- (1) <https://junit.org/junit4/javadoc/4.12/org/junit/experimental/max/MaxCore.html>
- (2) <http://automation-webdriver-testng.blogspot.com/2012/07/how-to-call-test-plans-dynamically.html>
- (3) <http://beust.com/weblog/2008/03/29/test-method-priorities-in-testng/>
- (4) <https://arxiv.org/pdf/1801.05917.pdf>
- (5) <https://lib.dr.iastate.edu/cgi/viewcontent.cgi?referer=https://www.google.com/&httpsredir=1&article=6493&context=etd>
- (6) <https://dl.acm.org/citation.cfm?id=1116157>
- (7) <http://spring.io/>