

5_GHZ_Redux

May 31, 2021

1 States with the GHZ symmetries

Initialize the RepLAB toolbox (be in the /replab directory or use run path/replab/replab_init.m)

```
[1]: run ~/w/replab/replab_init
      replab.globals.verbosity(0);
      replab.globals.useReconstruction(1);
```

```
Adding RepLAB to the path
Initializing dependency vpi
Initializing dependency YALMIP
Initializing dependency sdpt3
Adding embedded SDPT3 solver to the path
Initializing dependency MOcov
Initializing dependency MOxUnit
Initializing dependency cyclolab
```

In this notebook, we compute the family of states with the symmetry of the GHZ states, as in [C. Eltschka and J. Siewert, “Entanglement of Three-Qubit Greenberger-Horne-Zeilinger-Symmetric States”](#).

The GHZ state $|\text{GHZ}\rangle = |000\rangle + |111\rangle$ is invariant ($U |\text{GHZ}\rangle = |\text{GHZ}\rangle$) under a family of matrices U

$$U = \begin{pmatrix} a_0 & 0 \\ 0 & a_1 \end{pmatrix} \otimes \begin{pmatrix} b_0 & 0 \\ 0 & b_1 \end{pmatrix} \otimes \begin{pmatrix} c_0 & 0 \\ 0 & c_1 \end{pmatrix} \quad (1)$$

who act on the state space \mathbb{C}^8 . The eight coefficients, in order, are those of $|000\rangle, |001\rangle, |010\rangle, |011\rangle, |100\rangle, |101\rangle, |110\rangle, |111\rangle$.

For the invariance to hold, the unit complex numbers $a_0, a_1, b_0, b_1, c_0, c_1$ obey the equation $a_0 b_0 c_0 = a_1 b_1 c_1 = 1$.

The state is also invariant under permutation of subsystems (a group of order $3! = 6$), and permutation of the levels (a group of order 2).

Let us define the continuous connected group. $T(6)$ is the [torus group](#) with 6 elements, elements that we name according to our scenario.

```
[2]: T6 = replab.T(6);
      T6 = T6.withNames({'a0' 'b0' 'c0' 'a1' 'b1' 'c1'});
```

We then define the subgroup obeying the equation $a_0 b_0 c_0 = a_1 b_1 c_1 = 1$.

```
[3]: T = T6.subgroupWith('a0*b0*c0 = 1', 'a1*b1*c1 = 1')
```

T =

```
Torus group of dimension n=6 and rank r=4
  identity: [0; 0; 0; 0; 0; 0]
  injection: 6 x 4 double
    names: {'a0', 'b0', 'c0', 'a1', 'b1', 'c1'}
  projection: 4 x 6 double
equation(1): 'a0 b0 c0'
equation(2): 'a1 b1 c1'
```

Now, how does that group act on the state space \mathbb{C}^8 ?

We construct the representation whose image is the matrix U above.

```
[4]: Trep = T.diagonalRepWith('a0 b0 c0', ...
                              'a0 b0 c1', ...
                              'a0 b1 c0', ...
                              'a0 b1 c1', ...
                              'a1 b0 c0', ...
                              'a1 b0 c1', ...
                              'a1 b1 c0', ...
                              'a1 b1 c1');
```

We construct now the discrete part, by writing how the subsystem and level permutations affect the elements of the continuous connected part.

This finite group permutes the three subsystems and the two levels, independently, so we write it as a direct product.

```
[5]: S3 = replab.S(3);
      S2 = replab.S(2);
      F = S3.directProduct(S2)
```

F =

```
Direct product group with 2 factors of order 12
generatorNames: {'x1', 'x2', 'x3'}
  identity: {[1, 2, 3], [1, 2]}
    type: Direct product group with 2 factors of order 12
  factor(1): Symmetric group acting on 3 elements
  factor(2): Symmetric group acting on 2 elements
generator(1): {[2, 3, 1], [1, 2]}
```

```

generator(2): {[2, 1, 3], [1, 2]}
generator(3): {[1, 2, 3], [2, 1]}
recognize: AtlasResult (Dihedral group of order 12)

```

Now, we write the action of the generators of this discrete group on the torus elements:

```

[6]: % Permutation of AB
gAB = {[2 1 3] [1 2]};
actAB = T.automorphism('b0', 'a0', 'c0', 'b1', 'a1', 'c1');
% Permutation of AC
gAC = {[3 2 1] [1 2]};
actAC = T.automorphism('c0', 'b0', 'a0', 'c1', 'b1', 'a1');
% Permutation of BC
gBC = {[1 3 2] [1 2]};
actBC = T.automorphism('a0', 'c0', 'b0', 'a1', 'c1', 'b1');
% Permutation of the two levels
gL = {[1 2 3] [2 1]};
actL = T.automorphism('a1', 'b1', 'c1', 'a0', 'b0', 'c0');

```

We check that the generators generate the whole group.

```

[7]: assert(F.subgroup({gAB, gAC, gBC, gL}) == F);

```

The [outer semidirect product construction](#) employs a morphism from a group H to the automorphisms of another group N . This is what we do now.

```

[8]: G = T.semirectProductByFiniteGroup(F, 'preimages', {gAB, gAC, gBC, gL},
    ↪ 'images', {actAB, actAC, actBC, actL});

```

1.1 How does this group act on the state space?

Remember that the integers 1, 2, 3, 4, 5, 6, 7, 8 enumerate $|000\rangle, |001\rangle, |010\rangle, |011\rangle, |100\rangle, |101\rangle, |110\rangle, |111\rangle$.

```

[9]: imgAB = replab.Permutation.toMatrix([1 2 5 6 3 4 7 8]);
imgAC = replab.Permutation.toMatrix([1 5 3 7 2 6 4 8]);
imgBC = replab.Permutation.toMatrix([1 3 2 4 5 7 6 8]);
imgL = replab.Permutation.toMatrix([8 7 6 5 4 3 2 1]);

```

We now construct the representation of the discrete group on the state space.

```

[10]: Frep = F.repByImages('C', 8, 'preimages', {gAB, gAC, gBC, gL}, 'images',
    ↪ {imgAB, imgAC, imgBC, imgL});

```

We had the representation of the torus group Trep , and we now assemble the two.

```

[11]: rep = G.semirectProductRep(Frep, Trep)

```

```
rep =
```

```
Unitary representation
```

```
      Hrep: Unitary representation
      Nrep: Unitary representation
      dimension: 8
divisionAlgebraName: []
      field: 'C'
      group: replab.prods.SemidirectProductGroup_compact
      isUnitary: true
```

... and now it is time to decompose that decomposition.

```
[12]: rep.decomposition
```

```
ans =
```

```
Unitary reducible representation
```

```
      dimension: 8
divisionAlgebraName: []
      field: 'C'
      group: replab.prods.SemidirectProductGroup_compact
injection_internal: 8 x 8 double
      isSimilarRep: true
      isUnitary: true
      mapsAreAdjoint: true
      parent: Unitary representation
projection_internal: 8 x 8 double
  basis(1,'double'): [0.70711; 0; 0; 0; 0; 0; 0; 0.70711]
  basis(2,'double'): [0.70711; 0; 0; 0; 0; 0; 0; -0.70711]
  basis(3,'double'): 8 x 1 double
  basis(4,'double'): 8 x 1 double
  basis(5,'double'): 8 x 1 double
  basis(6,'double'): 8 x 1 double
  basis(7,'double'): 8 x 1 double
  basis(8,'double'): 8 x 1 double
      component(1): Isotypic component C(1) (trivial)
      component(2): Isotypic component C(1) (nontrivial)
      component(3): Isotypic component C(6) (nontrivial)
```

Thus we recover that the states invariant under this type of symmetries are the pure states $|\text{GHZ}_{\pm}\rangle = \frac{|000\rangle \pm |111\rangle}{\sqrt{2}}$ and a mixed state containing all basis elements except $|000\rangle$ and $|111\rangle$ with equal weight $1/6$.

```
[ ]:
```