«interface»
AccountService

getAccounts(Comparator<Account>, UUID, Set<AccountState>, String): List<Account>

«interface»
AuthenticationService

authenticateWithCredentials(String, String, String): Optional<Account>

authenticateWithJwt(String): Optional<Account>

authenticateWithRefreshToken(UUID): Optional<Account>

createAccessToken(UUID): String throws NotFoundException

createRefreshToken(UUID): UUID throws NotFoundException

createAccount(String, String, String, int, boolean, boolea, boolean): Account throws NotUniqueException,
    OperationDisabledException

requestEmailVerification(UUID) throws NotFoundException

validateEmail(UUID): Account throws InvalidTokenException

«interface»
ReplicService

createReplic(URL, MediaMode, String, Instant, String, Account, FileWriterCallback): Replic throws
    ReplicQuotaMetException, ReplicContentWriteException, InvalidExpirationException

getReplics(Comparator<Replic>, UUID, UUID, Set<ReplicState>, String): List<Replic>

setReplicState(UUID, ReplicState): Replic throws NotFoundException

visitReplic(UUID, UUID): ReplicAccess throws NotFoundException

receiveContent(UUID): InputStream throws NotFoundException

«interface»
ReportService

getReports(Comparator<Report>, String): List<Report>

reportReplic(UUID, UUID, String): Report throws NotFoundException, OperationDisabledException

---

«interface»
ServerConfigService

get(): ServerConfig)

save(ServerConfig)