

# Get Entity by Short ID

## Endpoint

**URL:** /:projectId/entities/by-short-id

**Method:** GET

**Authentication Required:** No

## Description

Retrieves a single entity using its `shortId`. Publicly accessible.

## Request

### Query Parameters

Parameter	Type	Required	Description
<code>shortId</code>	string	Yes	The short identifier of the entity.

### Example Request

```
GET /proj1234/entities/by-short-id?shortId=3jh4sK
```

## Response

# Success Response (200 OK)

```
{  
  "id": "entity_xyz",  
  "shortId": "3jh4sK",  
  "title": "Example Post",  
  "content": "This is a sample entity.",  
  "createdAt": "2024-01-01T00:00:00.000Z",  
  ...  
}
```

## Error Responses

### Missing Short ID (400 Bad Request)

```
{  
  "error": "Missing shortId in request query.",  
  "code": "entity/invalid-query-params"  
}
```

### Not Found (404 Not Found)

```
{  
  "error": "Entity not found",  
  "code": "entity/not-found"  
}
```

### Server Error (500 Internal Server Error)

```
{  
  "error": "Internal server error.",  
  "code": "entity/server-error",  
  "details": "<Error message>"  
}
```

## Notes

- No authentication is required.
- The `shortId` is typically used for easily shareable or user-friendly URLs.

Last updated on May 11, 2025