

Delete List

Endpoint

URL: `/:projectId/lists/:listId`

Method: `DELETE`

Authentication Required: Yes

Description

Deletes a sub-list owned by the authenticated user. Root lists cannot be deleted.

Request

Headers

Header	Type	Required	Description
<code>Authorization</code>	<code>string</code>	Yes	Bearer token for authentication.

Path Parameters

Parameter	Type	Required	Description
<code>listId</code>	<code>string</code>	Yes	The ID of the list to delete.

Example Request

```
DELETE /proj1234/lists/list_abc
Authorization: Bearer <ACCESS_TOKEN>
```

Response

Success Response (204 No Content)

(No response body)

Error Responses

Missing List ID (400 Bad Request)

```
{
  "error": "Missing list ID",
  "code": "list/invalid-id"
}
```

List Not Found (404 Not Found)

```
{
  "error": "List not found",
  "code": "list/not-found"
}
```

Root List Deletion Forbidden (403 Forbidden)

```
{
  "error": "Root lists cannot be deleted",
  "code": "list/cannot-delete-root"
}
```

Server Error (500 Internal Server Error)

```
{  
  "error": "Server error",  
  "code": "list/server-error",  
  "details": "<Error message>"  
}
```

Notes

- Only sub-lists (lists with a non-null `parentId`) can be deleted.
- Returns `204 No Content` on successful deletion.
- Root lists are protected and cannot be deleted.

Last updated on May 11, 2025