

User Object

The **User** object is the public-facing user model returned by the Replyke API to client apps. It contains identity, profile, and activity-relevant fields but excludes private or admin-only information.

Properties

Property	Type	Description
<code>id</code>	<code>string</code>	Unique identifier for the user (UUID).
<code>projectId</code>	<code>string</code>	Identifier of the associated project (UUID).
<code>role</code>	<code>"admin" "editor" "visitor"</code>	Role assigned to the user in the project.
<code>name</code>	<code>string null</code>	Display name of the user.
<code>username</code>	<code>string null</code>	Unique username, if set.
<code>avatar</code>	<code>string null</code>	URL to the user's avatar image.
<code>bio</code>	<code>string null</code>	Optional short bio (max 300 characters).
<code>birthdate</code>	<code>Date null</code>	User's birthdate.
<code>location</code>	<code>{ type: "Point", coordinates: [number, number] } null</code>	Optional GeoJSON location ([longitude, latitude]).
<code>metadata</code>	<code>Record<string, any></code>	Public metadata, available in shared content (max size: 10KB).
<code>reputation</code>	<code>number</code>	Activity-based score managed by Replyke.
<code>createdAt</code>	<code>Date</code>	Timestamp when the user was created.

UserFull Object

The **UserFull** object is an internal model used within Replyke's administrative interfaces. It contains the full user record, including sensitive, private, or backoffice-only fields.

Properties

Property	Type	Description
<code>id</code>	<code>string</code>	Unique identifier for the user (UUID).
<code>projectId</code>	<code>string</code>	Identifier of the associated project (UUID).
<code>foreignId</code>	<code>string null</code>	Optional external or static ID for mapping users from another system.
<code>role</code>	<code>"admin" "editor" "visitor"</code>	Role assigned to the user in the project.
<code>email</code>	<code>string null</code>	User's email address.
<code>name</code>	<code>string null</code>	Display name.
<code>username</code>	<code>string null</code>	Unique username.
<code>avatar</code>	<code>string null</code>	Avatar image URL.
<code>bio</code>	<code>string null</code>	Bio (up to 300 characters).
<code>birthdate</code>	<code>Date null</code>	Date of birth.
<code>location</code>	<code>{ type: "Point", coordinates: [number, number] } null</code>	Optional user location in GeoJSON format.
<code>metadata</code>	<code>Record<string, any></code>	Public, sharable metadata (max 10KB).
<code>secureMetadata</code>	<code>Record<string, any></code>	Private metadata, excluded from shared views.
<code>reputation</code>	<code>number</code>	System-managed score based on participation.

Property	Type	Description
isVerified	boolean	Whether the user is verified.
isActive	boolean	Whether the account is currently active.
lastActive	Date	Timestamp of most recent user activity.
suspension	{ isSuspended: boolean, reason: string null, startDate: Date null, endDate: Date null }	Suspension status and duration.
createdAt	Date	Creation timestamp.
updatedAt	Date	Last updated timestamp.
deletedAt	Date null	Deletion timestamp, if applicable.

Summary of Differences

Field	Included in User ?	Included in UserFull ?	Notes
email	✗	✓	Sensitive — excluded from API-facing version.
secureMetadata	✗	✓	Internal use only.
isVerified	✗	✓	Platform-level detail.
isActive	✗	✓	Internal moderation use.
lastActive	✗	✓	Activity tracking — internal analytics.
updatedAt , deletedAt	✗	✓	Full auditing data only shown in admin dashboard.

© Replyke 2025