

# Get Comment

## Endpoint

---

**URL:** `/:projectId/comments/:commentId`

**Method:** `GET`

**Authentication Required:** No

---

## Description

---

Fetches a single comment by its ID. Optionally returns the parent comment if it exists and `withParent=true` is passed.

---

## Request

---

### Path Parameters

Parameter	Type	Required	Description
<code>commentId</code>	<code>string</code>	Yes	The ID of the comment to fetch.

### Query Parameters

Parameter	Type	Required	Description
<code>withParent</code>	<code>string</code>	No	If <code>true</code> , includes the parent comment.

---

# Response

---

## Success Response ( 200 OK )

Returns the requested comment and optionally its parent:

```
{
  "comment": {
    "id": "comment-123",
    "entityId": "entity-456",
    "content": "Nice article!",
    ...
  },
  "parentComment": {
    "id": "comment-001",
    "content": "Original post",
    ...
  }
}
```

If there is no parent or `withParent` is not provided:

```
{
  "comment": { ... },
  "parentComment": null
}
```

---

## Error Responses

### Missing or Invalid ID ( 400 Bad Request )

```
{
  "error": "Missing a valid comment ID in request query",
  "code": "comment/invalid-request"
}
```

### Not Found ( 404 Not Found )

```
{
```

```
"error": "Comment not found",  
"code": "comment/not-found"  
}
```

## Server Error ( 500 Internal Server Error )

```
{  
  "error": "Internal server error.",  
  "code": "comment/server-error",  
  "details": "[error message]"  
}
```

---

## Notes

- Set `withParent=true` to retrieve the parent comment if it exists.
- Returns `parentComment: null` if the comment has no parent or `withParent` is not set.

Last updated on May 11, 2025