UNIVERSAL PROFESSIONAL
Flat Latex

DESCRIPTION:
A 100% premium quality acrylic-based paint that *dries* to a *flat* finish.

This product exhibits high hiding and extended coverage. In addition, it has very low VOC content and low odor and is non-toxic and non-flammable.

RECOMMENDED USES:
Interior and exterior masonry, concrete, stucco, bricks plaster, hollow blocks and properly primed wood.

PRODUCT APPEARANCE	: Liquid
PACKAGE VISCOCITY	: 105-110 kus
DRY FILM THICKNESS	:
DRY SET TO TOUCH	: 30 minutes
DRY HARD	: 2 hours
COATING INTERVAL	: 1-2 hours depending on
room temperature THINNING consistency	: Apply at package
APPLICATION	: brush, roller, spray
COVERAGE	: 30-35 m^2/4L depending on surface porosity or texture
CLEAN-UP	: Water
PACKAGING SIZE	: 1, 4, 16 liters
AVAILABLE COLORS	: White PRO-100 1000's colors with Universal Color Depot. Custom color available. May be tinted with Universal AcriColor Colorant

SURFACE PREPARATION:

New or unpainted surface
Remove dirt, dust, grit, loose mortar, oil, grease and other contaminants. New concrete must be cured at least 28 days before paint application. Please follow manufacturer's recommendation to check use litmus paper test.

Old or previously painted surface
Remove all loose, peeling, chalking or blistering paint, dirt, dust, grease, oil and other contaminants. Treat mold or fungus infestation with bleaching solution (1 part bleach and 3 parts water).

APPLICATION:
Do not thin. Inter-mix all cans of same color to ensure color uniformity and consistency. Always stir paint before and occasionally during application. Apply only when temperature is from 10^o – 35^oC. Do not paint in rain or rain imminent weather. For best results always use high quality roller and brush.

UNIVERSAL PROFESSIONAL
Flat Latex

PAINTING DIRECTIONS: For best results use:
1st coat: Universal Base Coat Acrylic Primer Flat White PRO-50.
                       Allow 1-2 hours drying time.
To remedy surface imperfections:
Putty: Universal Professional Concrete Putty White PRO-10. Allow 4
hours drying time. Spot Prime: Universal Base Coat Acrylic Primer Flat White
PRO-50.

2nd-3rd coat: Universal Professional Flat Latex of desired sheen & color,
                       Allow 1-2 hours drying time between coats.
Apply more coats if higher hiding is desired.