



1. Material: RoHS compliant 12AWG (0.08") Aluminum.
2. Break all sharp edges and mask all threads prior to powder coat.
Inserts should be installed prior to powder coat.
3. Part is to be powder coated with cardinal color C241-BK109.
Thickness must be between 0.05 and 0.12mm unless otherwise indicated.
4. Ink mark in indicated area with company initials.
5. Indicated area to be painted. Grain callout is for cosmetic surface under laser etch (page 2).

Rev.	Date	Description
G	9.22.16	Length of interior flange extended by 5mm (above).
F	8.25.16	Powder coat thickness and 4.0mm hole location changed
E	8.17.16	Coating thickness updated.

MATERIAL:
See Notes

DECIMALS	ANGLES
.X \pm .75	X \pm 1 $^{\circ}$
.XX \pm .25	
.XXX \pm .125	63
.XXXX \pm .050	

BREAK EDGES 0.1/0.5
FILLET RADIUS 0.1/0.5



**ALEPH
OBJECTS**
INCORPORATED

626 West 66th Street
 Loveland, Colorado 80538, USA
 Phone +1-970-377-1111
www.alephobjects.com

Electronics case mini

SIZE A	DWG NO. PP-FP0082_revG
-----------	---------------------------

SCALE	1:3	DO NOT SCALE DRAWING	SHEET	1 of 3
-------	-----	----------------------	-------	--------

REV.
G