



Notes:

1. Part must be RoHS compliant
2. Material: RoHS compliant 12 AWG (0.08") Aluminum
3. Break all sharp edges prior to powder coat
4. Mask all threads prior to powder coat
5. Part is to be powder coated with Cardinal color C241-BK109
Powder coat thickness must be between 0.05 and 0.12mm.
6. Ink mark in area indicated with the first initial of your company name

| Rev | Date | Notes |
|-----|---------|---|
| C | 11.9.17 | Rev for Mini 2 |
| B | 8.17.16 | Coating thickness modified. |
| A | 7.14.16 | FEX-M3 inserts added to bottom plate for better EMI shielding |
| IR | 4.29.16 | Initial release of freeCAD redraw |

| | |
|-------------------------|-------------------------|
| DRAWN BY: bam | DATE: 4/29/16 |
|-------------------------|-------------------------|

MATERIAL:
See Notes

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN MILLIMETERS.
TOLERANCES ARE:

| DECIMALS | ANGLES |
|------------------|---------------------------------|
| .X \pm .75 | X $^{\circ}$ \pm 1 $^{\circ}$ |
| .XX \pm .25 | |
| .XXX \pm .125 | 63 |
| .XXXX \pm .050 | |

BREAK EDGES 0.1/0.5
FILLET RADIUS 0.1/0.5



**ALEPH
OBJECTS**
INCORPORATED

626 West 66th Street
 Loveland, Colorado 80538, USA
 Phone +1-970-377-1111
www.alephobjects.com

5. TITLE

Bottom plate mini

| | |
|------|---------|
| SIZE | DWG NO. |
| A | |

PP-MP0149_revC

REV.
C

SCALE 1:3

DO NOT SCALE DRAWING

SHEET 1 of 2