



## Notes:

1. Material: RoHS compliant 12AWG (0.08") Aluminum
2. Break all sharp edges and mask all threads prior to powder coat.
3. Part is to be powder coated with Cardinal color C241-BK109.  
Thickness of coating must be between 0.05mm and 0.12mm.
4. Ink mark in area indicated with first initial of your company name.

Rev	Date	Description
F	8/16/16	Thickness of powder coat specification changed.
E	7/27/16	Countersink removed from 2 masked holes for manufacturability.
D	7/6/16	FreeCAD redraw. Masking added to countersunk holes (page 2)

DRAWN BY:  
**bam**

DATE:  
**7.6.16**

MATERIAL:  
**See Notes**

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN MILLIMETERS.  
TOLERANCES ARE:

DECIMALS	ANGLES
.X±.75	X°±1°
.XX±.25	
.XXX±.125	
.XXXX±.050	63

BREAK EDGES 0.1/0.5  
FILLET RADIUS 0.1/0.5



**ALEPH  
OBJECTS**  
INCORPORATED

626 West 66th Street  
Loveland, Colorado 80538, USA  
Phone +1-970-377-1111  
www.alephobjects.com

TITLE

**Right side mini**

SIZE  
**A**

DWG NO.

**PP-FP0052**

REV.  
**F**

SCALE  
**1:3**

DO NOT SCALE DRAWING

SHEET  
**1 of 2**