



1. Material: RoHS compliant 12AWG (0.08") Aluminum.
2. Break all sharp edges and mask all threads prior to powder coat.
Inserts should be installed prior to powder coat.
3. Part is to be powder coated with cardinal color C241-BK109.
Thickness must be between 0.05 and 0.12mm unless otherwise indicated.
4. Ink mark in indicated area with company initials.

Rev.	Date	Description
H	8.17.17	Laser etching considerations removed
G	9.22.16	Length of interior flange extended by 5mm (above).
F	8.25.16	Powder coat thickness and 4.0mm hole location changed
E	8.17.16	Coating thickness updated.

DRAWN BY: BAM	DATE: 7.4.16
-------------------------	------------------------

MATERIAL:
See Notes

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN MILLIMETERS.
TOLERANCES ARE:

DECIMALS	ANGLES
.X \pm .75	X° \pm 1°
.XX \pm .25	
.XXX \pm .125	63
.XXXX \pm .050	

BREAK EDGES 0.1/0.5
FILLET RADIUS 0.1/0.5



**ALEPH
OBJECTS**
INCORPORATED

626 West 66th Street
 Loveland, Colorado 80538, USA
 Phone +1-970-377-1111
www.alephobjects.com

6. TITLE

Electronics Case Mini

SIZE A	DWG NO. PP-FP0082
-----------	----------------------

SCALE	1:3	DO NOT SCALE DRAWING	SHEET	1 of 3
-------	-----	----------------------	-------	--------

REV.
H