



Notes:

1. Material: RoHS compliant 12AWG (0.08") Aluminum.
2. Break all sharp edges and mask all threads prior to powder coat.
3. Part is to be powder coated with Cardinal color C241-BK109.
Coating thickness must be between 0.05 and 0.12mm.
4. Ink mark in area indicated with first initial of your company name.

Rev	Date	Description
J	1.22.18	Added Masking for EINSY heatsink
I	11.9.17	Rev for Mini2
H	9.20.16	Dimension of masking modified for clarity
G	8.17.16	Powder coat thickness modified.

DRAWN BY:
bam

DATE:
7.7.16

MATERIAL:
See Notes

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN MILLIMETERS.
TOLERANCES ARE:

DECIMALS	ANGLES
.X±.75	X°±1°
.XX±.25	
.XXX±.125	
.XXXX±.050	

BREAK EDGES 0.1/0.5
FILLET RADIUS 0.1/0.5



**ALEPH
OBJECTS**
INCORPORATED

626 West 66th Street
Loveland, Colorado 80538, USA
Phone +1-970-377-1111
www.alephobjects.com

TITLE

Left side mini

SIZE DWG NO.
A PP-FP0055

SCALE 1:3 DO NOT SCALE DRAWING SHEET 1 of 4

REV.
J