Table 2. Family verdicts in the primary set (protocol §12.3) and the same families in the sensitivity sets (§10.3).

Family	Comparison (with C vs without C)	Cells	Mean D (95% CI)	Share of cells with $D_j > 0$	Direction rule	Conditions failed (§13)	Reported as
Primary set, 158 cases (enters family verdicts)							
P1a	ORACLE vs ORACLE−C	66	1.925 (1.909 to 1.934)	0.98	Supported	None	Verdict: supported
P1b-SITE	SITE vs NV	48	2.198 (2.167 to 2.226)	1.00	Supported	None	Verdict: supported
P1b-FM	FM-P vs FM-P−C	48	0.594 (0.582 to 0.606)	1.00	Supported	E3-site	Not tested (§13)
P2-SITE	SITE vs NV	18	0.052 (0.048 to 0.056)	1.00	Supported	None	Verdict: supported
P2-FM	FM-P vs FM-P−C	12	0.005 (−0.000 to 0.012)	0.50	Inconclusive	E3-site	Not tested (§13)
P2-ORACLE	ORACLE vs ORACLE−C	12	0.042 (0.036 to 0.048)	0.92	Supported	None	Verdict: supported
W = 0 set, 204 cases (sensitivity; reported separately)							
P1b-SITE	SITE vs NV	48	2.181 (2.169 to 2.193)	1.00	Supported	None	Reported separately
P1b-FM	FM-P vs FM-P−C	48	0.671 (0.661 to 0.680)	1.00	Supported	E3-site	Not tested (§13)
P2-SITE	SITE vs NV	6	0.086 (0.083 to 0.090)	1.00	Supported	None	Reported separately
P2-FM	FM-P vs FM-P−C	4	0.018 (0.014 to 0.022)	0.75	Supported	E3-site	Not tested (§13)
P2-ORACLE	ORACLE vs ORACLE−C	4	0.084 (0.081 to 0.087)	1.00	Supported	None	Reported separately
W = 5 set, 201 cases (sensitivity; reported separately)							
P2-SITE	SITE vs NV	6	0.046 (0.043 to 0.048)	1.00	Supported	None	Reported separately
P2-FM	FM-P vs FM-P−C	4	0.006 (−0.003 to 0.014)	0.50	Inconclusive	E3-site	Not tested (§13)
P2-ORACLE	ORACLE vs ORACLE−C	4	0.052 (0.048 to 0.056)	1.00	Supported	None	Reported separately
Single-file set, 123 cases (sensitivity; reported separately)							
P1b-SITE	SITE vs NV	48	2.066 (2.038 to 2.097)	0.96	Supported	None	Reported separately
P1b-FM	FM-P vs FM-P−C	48	0.379 (0.363 to 0.395)	1.00	Supported	E3-site	Not tested (§13)
P2-SITE	SITE vs NV	18	0.053 (0.049 to 0.056)	1.00	Supported	None	Reported separately
P2-FM	FM-P vs FM-P−C	12	0.016 (0.009 to 0.023)	0.75	Supported	E3-site	Not tested (§13)

D_j = (|bias| without C − |bias| with C) / mean truth for P1 families and (|bias| with C − |bias| without C) / mean truth for P2 families (positive = as predicted); |bias| = |mean over the 200 replicates of (estimate − truth)|. Mean D = unweighted mean of D_j over the family's cells ($\bar{D}_F$ in the protocol). D is a dimensionless relative difference in absolute bias.

95% CI: percentile interval of a paired bootstrap (2,000 resamples of the 200 synthetic replicates within each cell, the same indices for both arms and the truth; cells fixed; seed 20261008). It expresses simulation (Monte Carlo) uncertainty, not real-data sampling uncertainty.
Direction rule (§12.3): supported if the lower bound > 0 and $D_j > 0$ in at least 75% of the cells; contradicted if the upper bound < 0 or $D_j > 0$ in at most 25% of the cells; inconclusive otherwise. Only the primary set yields verdicts; a supported verdict is reported as consistent with the theory-motivated direction, not as a confirmation of the theory maps. A family whose §13 conditions fail is not tested and is reported descriptively (FM-P vs FM-P−C families). Sensitivity-set results are reported separately and never enter verdicts.
Family cells and predictions (protocol §12.2): P1a, α = 0, all cells except K = 1, P = 0 (66 cells), predicted ORACLE |bias| < ORACLE−C; P1b-SITE, W = 0, P = 5 or 30, all K, α, γ (48 cells), predicted SITE < NV; P1b-FM, the same 48 cells, predicted FM-P < FM-P−C; P2-SITE, K = 1, P = 0, all W, α, γ (18 cells), predicted SITE ≥ NV; P2-FM, K = 1, P = 0, α > 0 (12 cells), predicted FM-P ≥ FM-P−C; P2-ORACLE, K = 1, P = 0, α > 0 (12 cells), predicted ORACLE ≥ ORACLE−C.
G-SITE (η^2 of S at the window start on C; gate ≤ 0.01): primary set 0.0014, W = 0 set 0.0037, W = 5 set 0.0045; no single-file value exists (the locked code applies the primary value). E3-site failed on the 158-case set for all three representations (Table 3).
The W = 0 set also yields P1a (16 cells) because both arms were run there; P1a is outside the §10.3 scope, is labelled exploratory in the results report and is not shown here.
Abbreviations: C, site (centre); NV, no video; ORACLE, exact content state S and C; ORACLE−C, S without C; FM-P, primary representation; FM-P−C, FM-P after linear site removal.