Table 2. Family verdicts in the primary set (protocol §12.3) and the same families in the sensitivity sets (§10.3).

Family	Comparison (with vs without C)	Cells	Mean D (95% CI)	Share D_j > 0	Direction rule	Failed (§13)	Status
Primary set, 158 cases (enters family verdicts)							
P1a	ORACLE vs ORACLE−C	66	1.925 (1.909 to 1.934)	0.98	Supported	None	Verdict: supported
P1b-SITE	SITE vs NV	48	2.198 (2.167 to 2.226)	1.00	Supported	None	Verdict: supported
P1b-FM	FM-P vs FM-P−C	48	0.594 (0.582 to 0.606)	1.00	Supported	E3-site	Not tested (§13)
P2-SITE	SITE vs NV	18	0.052 (0.048 to 0.056)	1.00	Supported	None	Verdict: supported
P2-FM	FM-P vs FM-P−C	12	0.005 (−0.000 to 0.012)	0.50	Inconclusive	E3-site	Not tested (§13)
P2-ORACLE	ORACLE vs ORACLE−C	12	0.042 (0.036 to 0.048)	0.92	Supported	None	Verdict: supported
W = 0 set, 204 cases (sensitivity; reported separately)							
P1b-SITE	SITE vs NV	48	2.181 (2.169 to 2.193)	1.00	Supported	None	Reported separately
P1b-FM	FM-P vs FM-P−C	48	0.671 (0.661 to 0.680)	1.00	Supported	E3-site	Not tested (§13)
P2-SITE	SITE vs NV	6	0.086 (0.083 to 0.090)	1.00	Supported	None	Reported separately
P2-FM	FM-P vs FM-P−C	4	0.018 (0.014 to 0.022)	0.75	Supported	E3-site	Not tested (§13)
P2-ORACLE	ORACLE vs ORACLE−C	4	0.084 (0.081 to 0.087)	1.00	Supported	None	Reported separately
W = 5 set, 201 cases (sensitivity; reported separately)							
P2-SITE	SITE vs NV	6	0.046 (0.043 to 0.048)	1.00	Supported	None	Reported separately
P2-FM	FM-P vs FM-P−C	4	0.006 (−0.003 to 0.014)	0.50	Inconclusive	E3-site	Not tested (§13)
P2-ORACLE	ORACLE vs ORACLE−C	4	0.052 (0.048 to 0.056)	1.00	Supported	None	Reported separately
Single-file set, 123 cases (sensitivity; reported separately)							
P1b-SITE	SITE vs NV	48	2.066 (2.038 to 2.097)	0.96	Supported	None	Reported separately
P1b-FM	FM-P vs FM-P−C	48	0.379 (0.363 to 0.395)	1.00	Supported	E3-site	Not tested (§13)
P2-SITE	SITE vs NV	18	0.053 (0.049 to 0.056)	1.00	Supported	None	Reported separately
P2-FM	FM-P vs FM-P−C	12	0.016 (0.009 to 0.023)	0.75	Supported	E3-site	Not tested (§13)

D_j = (|bias| without C − |bias| with C)/mean truth (P1) or (|bias| with C − |bias| without C)/mean truth (P2); positive = as predicted; dimensionless. Mean D = unweighted mean over the family's cells ($\bar{D}_F$). 95% CI: paired bootstrap percentile interval (2,000 resamples of the 200 synthetic replicates within each cell, same indices for both arms and the truth; cells fixed): simulation uncertainty, not real-data sampling uncertainty. Direction rule (§12.3): supported if lower bound > 0 and D_j > 0 in ≥ 75% of cells; contradicted if upper bound < 0 or D_j > 0 in ≤ 25%; otherwise inconclusive. Only the primary set yields verdicts (consistent with the theory-motivated direction); families failing §13 (E3-site failed on the 158-case set; Supplementary Table S5) are not tested; sensitivity sets never enter verdicts.

Cells (§12.2): P1a, α = 0, all cells except K = 1, P = 0 (66 cells); P1b-SITE and P1b-FM, W = 0, P = 5 or 30, all K, α, γ (48 cells); P2-SITE, K = 1, P = 0, all W, α, γ (18 cells); P2-FM and P2-ORACLE, K = 1, P = 0, α > 0 (12 cells). G-SITE (≤ 0.01): primary 0.0014, W = 0 0.0037, W = 5 0.0045; none for the single-file set. The W = 0 set's P1a (16 cells; outside §10.3; exploratory) is not shown.

C, site; NV, no video; ORACLE, exact content state and C; ORACLE−C, state without C; FM-P, primary representation; FM-P−C, FM-P after linear site removal.