Information Infrastructure for Life Safety

How Internet Architecture Reveals a Better Structure for Life-Safety Event Meaning

SAFER standardizes life-safety event meaning, not life-safety systems.

Transport moves the message. SAFER defines what the message means.

Version 1.1 • October 2026
Architecture companion to the proposed SAFER Protocol v1.1
Apache License 2.0

Dan Horon and Jeff Horon
Cadgraphics Incorporated / RescueLogic
https://github.com/rescuelogic/SAFER

Contents

Section	Topic
1	Executive Summary — The Problem Is Clarity
2	The Architectural Pattern
3	The SAFER Narrow Waist
4	The Minimal Life-Safety Event Model
5	Payload Only: What SAFER Standardizes
6	Transport Moves the Message; SAFER Defines Meaning
7	Coexist • Wrap • Translate • Reference • Migrate
8	Where Intelligence Belongs
9	Robust Interpretation
10	Requisite Variety
11	Reducing Entropy Through Structure
12	Implementation Example: RescueLogic and Game Plan
13	What This Architecture Enables
14	Principles for Life-Safety Information Infrastructure
15	Related SAFER Documents
References	Selected References

1. Executive Summary — The Problem Is Clarity

Modern life-safety systems are very good at detecting events. The harder problem is preserving the meaning of those events as they pass through panels, networks, databases, drawings, operator interfaces, service workflows, and responder tools.

A panel may report an alarm correctly, but the receiving person or application may still have to ask: Which device? What kind of device? Where is it? What is happening? What should this mean in this building?

That is an information-infrastructure problem. The system detected the condition, but the event meaning may still be scattered across drawings, lookup tables, local memory, and manufacturer-specific message formats.

> **CORE FRAMING** SAFER standardizes life-safety event meaning, not life-safety systems. It is a payload structure for reported events. It does not replace pathway supervision, listed equipment, NFPA 72 compliance, UL evaluation, emergency-response policy, or the authority of the source system.

This paper explains why normalized event meaning can become infrastructure. The devices still detect conditions. Panels still operate according to their design. Existing codes, listings, supervision methods, and response procedures remain authoritative. SAFER simply gives reported events a portable, structured meaning that people and software can understand consistently.

> **PLAIN-LANGUAGE GOAL** Clear alarms. Stable information. Systems that become easier to understand over time.

2. The Architectural Pattern

One reason Internet architecture scales is that many different systems can communicate through shared protocols without requiring identical internal designs.

Life-safety information can use a similar architectural pattern. Different manufacturers may organize points, circuits, panels, loops, nodes, modules, sensors, and events differently. A shared event layer does not require those internal architectures to become the same.

Instead, each source system can present the basic meaning of a reported event at the boundary where other systems and people need to understand it.

Before and after normalization


Before normalization	Device → Panel → Proprietary message	Meaning often depends on local decoding
After normalization	Device → Panel message → Normalized event	ID • Type • Location • Reported condition / reporting code
Infrastructure result	One event meaning	Many uses: operators, technicians, inspectors, responders, analytics, AI

The pattern is not that fire alarm systems should become the Internet. The useful lesson is architectural: a stable translation layer can allow many different systems to exchange meaning without forcing every participant to share the same internal design.

3. The SAFER Narrow Waist

In Internet architecture, the “narrow waist” is the small shared layer that lets many technologies below support many applications above. In life-safety event reporting, the analogous shared layer is normalized event meaning.

THE SAFER NARROW WAIST At the exchange boundary, the reported event can be reduced to a small set of semantic roles: source context, device identity, device type, device location, and reported condition.



The purpose is not to hide manufacturer detail. Manufacturer-specific information remains valuable for installation, service, diagnostics, certification, and product behavior. The shared layer preserves the basic meaning that must survive the handoff. The arrows show reported information flowing toward applications and people, not control commands sent to panels.

4. The Minimal Life-Safety Event Model

The recurring sentence underneath a reported event is simple:

> **This system reports that this device, of this type, at this location, has changed to this state.**

In formal terms, a reported event can be represented as:

e_t = (System, Identity, DeviceType, Location, $Condition_t$)

The conceptual event model describes a known point in its reporting context and the condition it reports at a particular time. A point is identified within that context; device type and location describe it and may be updated or corrected without necessarily changing its identity. A transmitted report can convey a new change, a restoration, a previously reported condition, or a status observation.

KNOWN POINT Relatively stable context	CHANGING PRESENTATION Human-facing states
Identity — which point?	Normal — reported or confirmed normal condition
Device Type — what kind?	Trouble — investigate the reported difficulty
Location — where?	Active — act according to applicable procedures

The reporting system supplies additional source context. Fire alarm panels supervise their own integrity and can report changes to or from Normal. Contact ID can carry a restore report, but that report alone does not establish that every point or the entire system is Normal. Nor does silence establish Normal. These three human-facing categories illustrate a possible presentation; they are not SAFER STATUS values or a required display.

As a conceptual teaching shorthand (not arithmetic or a SAFER field definition):

The three categories simplify human understanding. They do not replace the SAFER STATUS vocabulary, a source's original classification, or RescueLogic's four Logical States.

```
DEVICE = (Identity, DeviceType, Location)
STATE = Normal | Trouble | Active
EVENT = ΔSTATE × DEVICE × TIME
```

IMPORTANT REFINEMENT Normal, Trouble, and Active are useful teaching categories. The SAFER STATUS vocabulary remains explicit and versioned: 1 Active, 2 Supervisory, 3 Restore, 4 Trouble, 5 Status only, and 6 Previously reported.

5. Payload Only: What SAFER Standardizes

A major reason SAFER can be adopted broadly is that it standardizes the payload, not the whole life-safety system.

PAYLOAD ONLY SAFER defines the structure of a reported event payload. It does not define the network architecture, the pathway supervision method, the product listing, the code-compliance basis, the emergency-response policy, or the authority of the source system.

SAFER defines	SAFER does not define
A structured event payload	NFPA 72 compliance
Required and optional field names	UL or ULC listing
SAFER version and report-record identity	Pathway supervision
Numeric STATUS values	Transport security or reliability
A common representation of event meaning	Monitoring-station operations
	Site response policy

This boundary is the adoption path. Manufacturers, integrators, and developers can experiment with the event structure without first redesigning certified products, supervision strategies, or communications pathways.

6. Transport Moves the Message; SAFER Defines Meaning

MQTT, HTTP, AMQP, WebSockets, cellular communicators, IP pathways, and other mechanisms can carry bytes successfully. But a delivered message is not automatically an understood message.

> **TRANSPORT ≠ MEANING** A transport can deliver a message perfectly while leaving the application meaning undefined. SAFER supplies the life-safety event meaning that a transport can carry.

Layer	Question	Examples
Transport	Can the message move?	MQTT, HTTP, AMQP, TCP/IP, cellular, private networks
Payload	What does the message mean?	PANEL_ID, DEVICE_ID, DEVICE_TYPE, DEVICE_LOCATION, STATUS
Application	What should a person or system do?	Display, route, inspect, investigate, respond, analyze

7. Coexist • Wrap • Translate • Reference • Migrate

SAFER is not framed as a demand to abandon legacy reporting. Legacy alarm formats solved real problems and remain widely deployed. SAFER provides a structured event payload that can coexist with those formats and support gradual migration.

Adoption pattern	Practical meaning
Coexist	SAFER payloads can operate alongside existing signaling and monitoring workflows.
Wrap	A SAFER message can include a legacy event code as an optional reference field.
Translate	A gateway or software layer can map known legacy events into the SAFER structure.
Reference	The original source message can be preserved for auditability and troubleshooting.
Migrate	Implementations can move gradually toward richer structured reporting without requiring wholesale replacement.

Example: compact code plus structured payload

A compact legacy message can still be preserved while SAFER carries the meaning more explicitly.

Contact ID translation must consider event code, Q qualifier, and partition-zone/user context together. Contact ID Q=1 means a new event/opening; Q=3 a restore/closing; Q=6 a previously reported condition still present. These are not SAFER STATUS numbers, and the qualifier alone does not establish device type or condition classification. Preserve the source report and identify which values were reported, referenced, or derived.


```
{
  "CUSTOMER": "1234",
  "PANEL_ID": "Node 01",
  "DEVICE_ID": "01-015",
  "DEVICE_TYPE": "Smoke Detector",
  "DEVICE_LOCATION": "Front Lobby",
  "STATUS": 1,
  "SAFER_ID": {"version": "1.1", "unique_id": "123e4567-e89b-42d3-a456-426614174002"},
  "OPTIONAL": {
    "CONTACT_ID": {"version": "SIA DC-05", "code": "1234181101010158"}
  }
}
```


The OPTIONAL.CONTACT_ID object and its nested fields illustrate an adapter-defined way to retain a legacy report; they are not additional SAFER v1.1 baseline requirements. The original Contact ID message format is not designed to carry device type or room description as separate fields. A translator may obtain those details from documented source configuration or maintained customer records, while preserving their origin. A Contact ID restore qualifier reports restoration of a particular condition; it does not by itself prove that an entire system is Normal. Determining SAFER STATUS still requires documented event-code mapping and context.

8. Where Intelligence Belongs

The End-to-End Principle is useful here as an analogy. Networks work best when the network moves information and the endpoints interpret it. Life-safety systems already have their own responsibilities and rules; the analogy is not a substitute for fire alarm code.

SEPARATION OF CONCERNS Detection belongs in listed equipment. Transmission belongs to the approved communications environment. Event meaning belongs in the payload. Interpretation and response belong to applications, operators, responders, and site procedures.

This separation allows each layer to remain accountable for the job it understands best. SAFER does not need to control the detector, redesign the panel, or mandate a network. It needs to preserve the meaning of the reported event as it crosses the boundary into other systems.

8.1 From Event Data to Human Recognition

A structured event provides information software can exchange. At the site where decisions are made, people benefit from recognizing the device type, its reported condition, and its known location.

These three familiar cues help technicians, operators, and responders connect a report to previous experience, the building environment, and applicable procedures. A smoke detector, manual pull station, or supervisory switch gives people a recognizable object to picture, even when the reported condition appears similar.

Human-facing simplification does not replace the full event information model. Reporting context, point identity, original source observations, classification, and message history remain important for accurate interpretation and traceability.

SAFER preserves the information roles. Applications such as RescueLogic may present recognizable device icons, condition cues, and floor-plan locations for the people using them; that presentation is not itself a SAFER reporting code or a mandated response.

A SIMPLE STATE WITH A MEANINGFUL CONDITION

RescueLogic demonstrates how a receiving application can simplify what people see without discarding useful source information.

In its Script Panel Types configuration, the Event Type tab recognizes messages associated with three Base States: Normal, Alarm, and Trouble. The Device tab extracts device type, address, and descriptive Condition text. Device State Images provide recognizable illustrations associated with device type and state.

Two Trouble reports may describe Open Circuit and Ground Fault. The base state helps people recognize the situation; the descriptive condition helps explain what the source reported. Such text can be a symptom or clue without proving the underlying physical cause.

This is a RescueLogic presentation example, not a SAFER requirement. SAFER's six STATUS values do not correspond numerically to RescueLogic's three Base States. Display decisions may use source context and event history; source-to-SAFER translation still requires documented rules and available evidence.

9. Robust Interpretation

Working systems often have imperfect inputs: abbreviated messages, firmware differences, inconsistent labels, partial records, or old documentation. Robust information infrastructure should not break merely because an input is imperfect.

> **DEFENSIVE INTERPRETATION** Be strict and clear in the SAFER payloads you produce. When translating older or manufacturer-specific messages, preserve the event and mark uncertainty rather than manufacturing false certainty.

In practice, distinguish four kinds of information: reported (present in the source), referenced (obtained through known point records), derived (interpreted through stated rules), and unknown or ambiguous (not established). Keep the original source message where practical, and let validation identify disagreement, uncertain location, or unverifiable assumptions.

A source report can be retained for review even when a translator cannot construct a conforming baseline SAFER message because required DEVICE_TYPE or DEVICE_LOCATION information is unavailable. Do not substitute guessed values to make a payload pass validation. A trouble report is not proof that the protected function is completely unavailable, just as missing reports are not proof of NORMAL.

10. Requisite Variety

A life-safety information model must be large enough to represent reality, but not so large that it becomes unusable. Ashby's Law of Requisite Variety is helpful as a design analogy: a system needs enough variety to cope with the variety of the world it manages.

The SAFER model is small, but it captures the recurring variety that matters at the event boundary.

Reality produces	SAFER represents
Many panels and source systems	System / PANEL_ID / CUSTOMER
Many devices and point addresses	DEVICE_ID
Different device purposes	DEVICE_TYPE
Different places in a building	DEVICE_LOCATION and optional owner/location fields
Reporting meaning and descriptive detail	STATUS and optional CONDITION

DESIGN BALANCE Too little structure loses meaning. Too much structure prevents adoption. SAFER keeps the common event layer small enough to implement and explicit enough to be useful.

11. Reducing Entropy Through Structure

Large systems naturally drift toward confusion. Buildings change. Devices are replaced. Location names evolve. Drawings, databases, service notes, and panel text may no longer agree. The system may still operate, but understanding it becomes harder.

MAP AND TERRITORY Floor plans, point lists, databases, event histories, and SAFER messages describe different aspects of an installation. A common structure makes their relationships easier to compare.

Agreement among records supports confidence in those records; discrepancies invite investigation. Neither proves the physical installation is correct. This is not merely administrative cleanliness. In an emergency, a clear representation of the building helps people act with confidence. In maintenance, a clear representation helps technicians fix the right problem. In analytics, a clear representation lets patterns be discovered across buildings and systems.

12. Implementation Example: RescueLogic and Game Plan

RescueLogic already provides ways to organize and present installation information. Game Plan is a planned application exploring additional responder-oriented uses. The possibilities below illustrate how normalized event meaning could help; neither product is required by SAFER.

EXAMPLE, NOT MANDATE SAFER does not require RescueLogic, Game Plan, a particular HMI, a particular database, or a particular floor-plan system. RescueLogic is an existing application example; Game Plan remains in development. These illustrate uses, not SAFER requirements or claims of implemented features.

When event meaning is normalized	Applications can use it for
A panel reports a detector event	Floor-plan highlighting, operator display, event history
A point reports trouble	Service workflow, inspection notes, reliability questions
Two records disagree	Validation review and correction workflow
A responder needs location	Pre-incident planning, navigation, situational awareness

13. What This Architecture Enables

When life-safety event meaning becomes a stable shared layer, the benefits extend beyond a single protocol or product.

Audience	Value
Operators	clearer alarms and faster situational awareness
Technicians	less decoding and more direct troubleshooting
Inspectors and AHJs	more consistent information across records and interfaces
Responders	clearer location and event context before or during response
Owners	better long-term information stewardship across buildings
Developers	a predictable payload for dashboards, validation tools, analytics, digital twins, AI, and integrations

QUIET PROMISE Clarity scales. When information is properly organized, people can recognize what a system reported, compare it with installation records, and see what still needs verification.

14. Principles for Life-Safety Information Infrastructure

These principles summarize the architecture described in this paper.

1. Normalize information once. Translate events at a defined exchange boundary into a shared structure that people can use, while retaining the manufacturer's original information.	**2. Separate hardware from information.** Devices may change, but the structure describing events should remain stable.
3. Standardize the payload, not the system. Preserve event meaning without displacing listed equipment, code requirements, or supervision strategies.	**4. Preserve source truth.** Carry the reported facts and original source detail where useful; do not overwrite observation with interpretation.
5. Accept imperfect inputs. Robust systems can preserve partial information and mark uncertainty instead of breaking.	**6. Match the data model to reality.** **Preserve source context, point identity, device type, location, reported condition, and available time. Distinguish observations from interpretation and qualifiers.**
7. Keep the map aligned with the territory. Floor plans, point lists, databases, histories, and event payloads should reinforce one another.	**8. Place intelligence at the edges.** Detection, transport, interpretation, and response each have their own responsibilities.
9. Reduce entropy through structure. Consistent information models prevent systems from drifting into confusion over time.	**10. Design for evolution.** Applications and tools will change. A stable event structure lets the information survive.

15. Related SAFER Documents

This architecture companion helps explain the purpose of SAFER. It complements, rather than replaces, the protocol, FAQ, and technical information model.

SAFER Common Vocabulary explains source observations, conditions, qualifiers, and presentation. The proposed SAFER Protocol v1.1 remains authoritative for transmitted fields and baseline conformance.

Document	Best use
README.md	GitHub front door; short and developer-friendly.
SAFER Protocol v1.1	Authoritative protocol specification and field definitions.
SAFER Protocol FAQ v1.1	Adoption questions, objections, and boundary clarifications.
What Does Everybody Know?	Plain-language discovery of common information roles through understanding manufacturer differences.
One Architecture. Many Manufacturers. Decades of Continuity.	Firsthand RescueLogic engineering history, manufacturer interoperability, and preservation of installation knowledge.
A Minimal Event Information Model	Research and semantic-interoperability review paper.
What Is an Alarm Event?	One-page teaching handout or poster.
Fire Alarm Panels Speak the Same Language	Visual proof that different manufacturer formats share common event roles.
The Grammar of a Fire Alarm System	Plain-language education for nontechnical readers.

RECOMMENDED GITHUB CONTEXT List this architecture companion in the GitHub document map. Readers should begin with the README, Protocol, and FAQ.

Selected References

Horon, Dan. The SAFER Protocol: Security and Fire Emergency Reports, Version 1.1. RescueLogic, 2026.

Horon, Dan. SAFER Protocol FAQ, Version 1.1. RescueLogic, 2026.

Horon, Dan. A Minimal Event Information Model for Life-Safety Interoperability. RescueLogic, 2026.

Saltzer, J. H., Reed, D. P., and Clark, D. D. “End-to-End Arguments in System Design.” ACM Transactions on Computer Systems, 1984.

Postel, J. Transmission Control Protocol. RFC 793, 1981.

Ashby, W. Ross. An Introduction to Cybernetics. 1956.

Security Industry Association. Contact ID Protocol for Alarm System Communications.

National Fire Protection Association. NFPA 72: National Fire Alarm and Signaling Code.

National Fire Protection Association. NFPA 950: Standard for Data Development and Exchange for the Fire Service.