Continuation Preservation in Boolean-Helper Synthesis for Controller Replacement

Anonymous authors

***Abstract*—Controller replacement after an environment-model change must account for the current state and unfinished obligations. A negative synthesis result may concern an auxiliary encoding rather than the source contract; a positive existence result may still yield an unsuitable controller. We characterize exactly which strict-winning continuations survive a one-way Boolean-helper encoding, including constraints retained during translation. If the helper's first change releases input restrictions before response restrictions, winning requires maintaining the ability to answer every newly legal input. For one unchanged public Vehicle input, a whole-region audit of two saved native strict results finds 1,408 source states that lose strict-winning continuations. Each state is reachable under some initialized cooperative policy; both initial judgments remain positive. In a constructed Patrol update, a reusable source controller coexists with exclusion of its retained entry from the exported encoding. A complete countercertificate and reduced native query establish this temporal loss; the full-helper query remains UNKNOWN. A reconstructed Lift example separately shows why a solved game does not certify a particular extracted graph. Existing cooperative synthesis after normalization to a total arena supplies admitted alternatives for the feasible contracts in our fixed rosters. The results clarify the evidence required to retain a contract and admit a replacement controller.**

***Index Terms*—self-adaptive systems, reactive synthesis, specification repair, non-conflicting strategies, controller verification**

I. Introduction

A revised map does not erase a robot's pending charging request. Its current position and request history constrain replacement: restarting the specification would discard an obligation. Adaptation must decide whether the requirements still admit a continuation and which controller can be installed from that context [1], [2], [3].

A tool translates the contract, solves the encoded game and extracts a controller (Fig. 1). Two decisions follow. First, if the encoding preserves source continuations at the retained entry, a correct strict solver's negative result there rules them out. Second, installation requires auditing the returned graph at that source state and selected private root; an existence result alone does not certify it.

We study a one-way Boolean-helper encoding that releases environmental safety before system safety on its first change. Newly legal inputs can require incompatible responses. Preservation requires answering them throughout a winning continuation, beyond a one-step check at the entry.

Our exact characterization (Theorem 1) extends to retained translation constraints (Proposition 3) and gives a necessary-and-sufficient condition for preserving the entire original strict-winning region. The complete first-flip correction already exists [4]; our contribution characterizes the other encodings.

Vehicle exposes initialization's blind spot: two completed native strict queries preserve both initial judgments but lose source continuations. This public input is outcome-selected; initialized cooperative reachability is existential per target. Patrol exposes the local check's blind spot: a reusable source controller coexists with temporal encoding loss. A countercertificate and reduced native query establish it; the full-helper query remains UNKNOWN. Lift addresses installation: a solved game yields an unsuitable fixed graph. Its selection intervention is a diagnosis, not a general repair.

Existing normalized synthesis supplies admitted alternatives in the fixed rosters; Patrol has an audited reusable controller. Certified source continuations can thus justify retaining requirements despite encoding or output failure, without establishing deployment frequency or superiority.

We define replacement, prove preservation, diagnose both boundaries, and report admission and comparisons in Sections II–VI. The public artifact groups the paper, claim evidence, tool sources and scoped replay instructions by purpose [5].

II. The Replacement Decision and Its Semantics

The update boundary retains the full source state r, including logical history monitors for unfinished obligations. The *original contract* is the candidate after the proposed environment change or repair, before adding synthesis auxiliaries. A replacement graph may select a new private root; it must match r rather than restart the original initializer. Checking assumes a valid holding state until installation. A changing physical state instead needs a verified update bridge or revalidation.

a) Source continuations: Its finite, fully observed Mealy game M has nonempty typed input and response carriers E, Y, with states $D = E \times Y$. A round starts at $s = (e, y)$: ENV supplies the next input e', SYS observes it and chooses y', and the next state is $s' = (e', y')$. Environmental safety is $\rho_e(s, e')$, independent of the next response; system safety $\rho_s(s, e', y')$ includes every system constraint and logical-monitor update. Neither relation need be total. Initial predicates are $\theta_e(e)$ and $\theta_s(e, y)$; invalid type encodings are outside D.

Safety specifies allowed steps. A justice condition must hold infinitely often; the ENV and SYS lists define generalized Büchi objectives A and G. Under *strict* semantics [6], [7], SYS must satisfy safety while the ENV safety prefix, including the current edge, holds, and must satisfy $A \Rightarrow G$ on infinite safety-compliant plays. An ENV safety violation releases the safety duty on that edge and thereafter. Unfairness cannot




Fig. 1. Evidence needed for a state-preserving replacement. An encoded strict refusal transfers to the original contract only with preservation at the same entry. A failed returned graph excludes that graph; it does not exclude every source strategy. Source state and logical obligations are retained, while each candidate binds its own private root.

excuse an earlier required safety violation. Strategies retain private memory and give typed responses even to illegal inputs.

An original-legal prefix follows the declared entry and original safety relations. A fixed strategy is *legal-prefix cooperative* if every such prefix admits an infinite environment-safe continuation satisfying all ENV justices, with that same strategy and reached memory [8], [9]. For a strict strategy, this continuation also satisfies SYS justice. Thus a legal next input is necessary but insufficient: a controller may leave inputs available while preventing a required event forever.

Kind's Definition 3 [7] includes illegal strategy-consistent histories; our positive certificates establish legal-prefix cooperation. Neither resets reached memory. A failure on a legal prefix also refutes the stronger property for that output, but does not exclude every strategy.

Let W contain source states admitting some strict-winning continuation, and K those admitting some strict, legal-prefix cooperative continuation. These regions quantify over strategies and their memory. More generally, $\mathrm{Win}_{\mathrm{str}}(N)$ denotes states with a strategy satisfying the strict duties of game N against every environment strategy. The regions include unreachable typed states and are independent of initialization; W may include environmental dead ends through strict vacuity. An active continuation has already met ENV initialization, prior safety, and required SYS duties.

b) What each result licenses: An entry is *preserved for strict winning* when original winning at r implies winning at its corresponding encoded state. With a correct strict solver, this implication permits a negative encoded result to exclude $r \in W$. Without it, an encoded refusal leaves source feasibility unresolved. A cooperative-core result needs its own sound correspondence; it cannot automatically be read as a strict-game result.

A returned graph fixes private memory q as well as source state s. Its admission check binds a particular (r, q) and verifies every original-legal branch, safety, liveness and cooperation. A passing graph is a constructive feasibility certificate and may be installed under the holding assumption. A failing graph excludes that candidate, not all source strategies. Section VI gives the complete checks.

III. Exact Continuation Preservation

We now characterize the encoding's strict-winning region. The fresh Boolean input b is observed before SYS responds, starts false, and can change to true only once. The added assumption $\mathsf{GF}\neg b$ makes an infinite play after the change unfair, but does not excuse an earlier strict-safety violation. We distinguish a response possible now (C) from maintaining that condition while winning (W_C), then treat retained constraints.

a) The literal reduction: Kind prints each safety assumption as $\rho_n^e \vee \mathrm{next}(\mathit{envHelp})$ and each safety guarantee as $\rho_n^s \vee \mathit{envHelp}$ [7, Sec. 4.1]. Writing $b = \mathit{envHelp}$, conjoining the complete clauses and including helper persistence gives

$$\begin{aligned} \theta_e^R &= \theta_e \wedge \neg b, & \theta_s^R &= \theta_s, \\ \rho_e^R &= (\rho_e \vee b') \wedge (\neg b \vee b'), & \rho_s^R &= \rho_s \vee b, \\ A^R &= A \wedge \mathbf{GF}\neg b, & G^R &= G. \end{aligned} \tag{1}$$

Write $W_R(s, b)$ for the transformed strict-winning predicate. The *complete-relation hypothesis* means that the guards apply to the entire safety relations, including every logical auxiliary constraint. It must be checked for a syntactic route after all translations.

With $b = b' = 0$, both original safety relations apply; with $b = b' = 1$, both are released. A helper-false non-flip input violates transformed ENV safety exactly when it violates original ENV safety. The mismatch occurs on the first flip, $b = 0, b' = 1$: any typed e' is allowed, including one disallowed by ρ_e, while ρ_s still applies. Define

$$C(s) \;\equiv\; \forall e' \in E\ \exists y' \in Y : \rho_s(s, e', y'). \tag{2}$$

There is no environmental-safety antecedent in C. This is a local response test; W_C requires a source strategy that maintains C while satisfying the original strict duties. Let M_C have the original environmental relations and justice objectives, but system safety

$$\rho_s^C(s, e', y') \;\equiv\; C(s) \wedge \rho_s(s, e', y') \wedge C(s'). \tag{3}$$

With $\mathrm{Win}_{\mathrm{str}}$ denoting the strict-winning region of its argument game, define $W_C = C \cap \mathrm{Win}_{\mathrm{str}}(M_C)$ independently of initialization. The outer intersection excludes outside-C states winning vacuously at environmental dead ends.

b) Why a response now is not enough: The patrol update of Section IV-B changes only ENV, so the immediate response condition C is unchanged and holds at the pending entry. The new environment can nevertheless force a later charging state outside C, even though a strict cooperative source controller still exists. Surviving the conversion therefore requires a strategy that maintains C through future legal steps.

Theorem 1 (Exact strict-winning continuation region)**.** *Under the stated Mealy, strict, and complete-relation hypotheses, the reduction* (1) *has, for every $s \in D$,*

$$W_R(s,0) = W_C(s), \qquad W_R(s,1) = \mathit{true}, \tag{4}$$

identifying a region with its characteristic predicate.

Proof. At $b = 1$, legal edges retain the helper, system safety is released, and every infinite legal play violates $\mathsf{GF}\neg b$; hence all states win.

For necessity, a winning strategy at $(s, 0)$ must answer every legal first flip $(e', 1)$ with a ρ_s-safe response, so $s \in C$. Restrict it to original-legal histories with $b = 0$: these have exactly the original obligations. After each such finite prefix its residual strategy still wins, because required safety holds and Büchi conditions are prefix-independent. Repeating the first-flip argument gives C at every reached successor. The restricted strategy therefore wins M_C, so $W_R(\cdot, 0) \subseteq W_C$.

Conversely, start from $s \in W_C$ and follow a winning M_C strategy while $b = 0$ and inputs are original-legal. It maintains C, which supplies a safe response to any first flip. The successor has $b = 1$ and is winning by the first paragraph. Without a flip, original safety and liveness coincide; transformed-illegal inputs release strict duties. Thus $W_C \subseteq W_R(\cdot, 0)$. □

Corollary 2 (Full-region preservation)**.** *The literal reduction preserves the entire original strict-winning region at $b = 0$ if and only if $W \subseteq C$.*

Proof. $W_C \subseteq W \cap C$ and Theorem 1 give necessity. If $W \subseteq C$, every original-legal prefix of an original winning strategy has a winning residual strategy. Every reached state therefore belongs to $W \subseteq C$, so that strategy satisfies (3) and wins M_C. Hence $W \subseteq W_C$, proving sufficiency with the reverse inclusion. □

The exact loss $W \setminus W_C$ can exceed $W \setminus C$: a response possible now may force a later state outside C. The patrol update demonstrates this propagated loss at a reached entry with a genuinely pending request (Section IV-B).

c) Preservation from the original initializer: For initialization of M with a continuation region T, write

$$I_M(T) \;\equiv\; \forall e \in E : \theta_e(e) \Rightarrow \exists y \in Y : \theta_s(e, y) \wedge T(e, y). \tag{5}$$

Original and transformed initial realizability are $I_M(W)$ and $I_M(W_C)$, respectively, by Theorem 1 and initial $b = 0$. Since $W_C \subseteq W$, original unrealizability is preserved. Full-region preservation suffices but is unnecessary for initial preservation, as the initialized/reached-state contrast in Supplement E demonstrates.

d) When syntactic constraints remain: Retained constraints add three questions: where can SYS remain safe after the flip, which states allow safe entry there, and where can a source winning strategy maintain that entry condition?

Let $E_{ij}(s, e')$, $S_{ij}(s, e', y')$ be the safety relations for helper transition $i \to j$. Retain all typed variables and logical monitors; the next helper is observed before the response. Assume $E_{00} = \rho_e$, $S_{00} = \rho_s$, $E_{10} = \mathit{false}$, and no next-response dependencies in E_{ij}. For generalized Büchi objectives A', G', the transformed objectives are $A' \wedge \mathsf{GF}\neg b$ and G' globally, where the corresponding state predicates of A', G' agree with those of A, G at $b = 0$; they may be arbitrary at $b = 1$. For $Z \subseteq D$, $\mathrm{CPre}_{11}(Z)$ contains the states where every typed input satisfying E_{11} admits a typed S_{11}-safe response into Z; states with no legal input qualify vacuously. Define

$$\begin{aligned} U &= \nu Z.\ \mathrm{CPre}_{11}(Z), \\ F &= \{s \mid \forall e' \in E : E_{01}(s, e') \Rightarrow \\ &\qquad \exists y' \in Y : S_{01}(s, e', y') \wedge (e', y') \in U\}. \end{aligned}$$

Let M_F replace system safety by $F(s) \wedge \rho_s(s, e', y') \wedge F(s')$, retaining original environmental relations and justices, and define $W_F = F \cap \mathrm{Win}_{\mathrm{str}}(M_F)$. Thus U requires continued safety after a flip, and F requires safe entry.

Proposition 3 (Preservation with retained constraints)**.** *Under these hypotheses, the strict regions are $W_R(\cdot, 1) = U$ and $W_R(\cdot, 0) = W_F$. Full preservation holds exactly when $W \subseteq F$; unchanged original initialization with $b = 0$ gives $I_M(W_F)$.*

Proof. At $b = 1$, persistence keeps the helper true, so the added assumption fails and only strict safety remains. The fixed point U supplies safe responses back into U; conversely, states with safety-winning residual strategies form a post-fixed point of CPre_{11}. Thus $W_R(\cdot, 1) = U$.

From a winning helper-false state, each legal flip must enter U safely. The same holds after every original-legal non-flip prefix, so all reached states satisfy F. Restriction to those histories wins M_F. Conversely, from $s \in W_F$, a winning M_F strategy maintains F until a flip, then enters U and switches to a uniform safety-winning strategy, available in this finite, fully observed game. Without a flip, original duties hold; afterwards safety holds and the added assumption fails. Illegal inputs release strict duties. This proves $W_R(\cdot, 0) = W_F$.

Finally, $W_F \subseteq W \cap F$ gives necessity for preservation. If $W \subseteq F$, every residual state of an original winning strategy lies in W, hence in F; that strategy wins M_F, proving sufficiency. The unchanged initializer gives $I_M(W_F)$. □

Uniformity follows from $U = \mathrm{CPre}_{11}(U)$: for each $s \in U$ and each E_{11}-legal input e', fix one safe response into U, giving a common memoryless selector.

Safe entry matters even when a flip response exists. With one input value, Boolean response y, true initial and justice predicates, $\rho_e = \mathit{true}$ and $\rho_s = y'$, we have $W = C = D$. Keep $E_{01} = E_{11} = \mathit{true}$ and $S_{01} = y'$, but let $S_{11} = \neg y \wedge \neg y'$. Then $U = \{y = 0\}$ is proper: every flip forces $y' = 1$ outside U, so $F = W_F = \varnothing$. By contrast, complete literal relations give $U = D, F = C$; the complete correction below gives $U = F = D$. Supplement L.1 retains the full example. The Patrol study below applies this general criterion to actual retained constraints. Additional public-input checks and the full scope of each conversion are in Supplement D. Conditions using W do not provide a low-cost runtime precheck.

e) The existing first-transition correction: A released semantic-reduction class ORs b and $\neg b \wedge b'$ into SYS safety when ENV safety is not universally true [4]; otherwise it skips

reduction. This is an existing implementation class, not an established frontend option or default. Our R^+ formalizes this existing rule on complete relations, replacing only system safety by

$$\rho_s^{R^+} = \rho_s \vee b \vee b'. \tag{6}$$

For complete relations under the same hypotheses, the first flip and later helper-true edges release SYS safety: $S_{01} = S_{11} = \mathit{true}$. Proposition 3 gives $U = F = D$, hence $W_F = W$ and $W_{R^+}(s, 0) = W(s)$. Unchanged initializers with initial $b = 0$ preserve initial realizability. Supplement L.6, Proposition L.4 gives the restriction-and-extension proof. This special case does not characterize loss under retained syntactic constraints.

f) Why the exact encoding matters: Guard has Boolean input x, response y, true initial and justice predicates, and $\rho_e = \rho_s = x'$. A constant response is strict-winning; ENV can choose $x' = 1$ forever after any strategy-consistent history, also satisfying Kind's all-history Definition 3. Yet $C = \varnothing$: the first-flip input $(x', b') = (0, 1)$ is legal and has no safe response. Thus the complete printed Section 4.1 relations reject this contract. They differ from the construction in Kind's strict-realizability proof: Appendix A instead writes $\rho_e \vee b$, while the separate semantic implementation uses the preserving correction above [7, Theorem 1, Appendix A]. This is a discrepancy among constructions, not a counterexample to the corrected expression or the separate well-separation theorem.

The selected released syntactic/JTLV route also reports raw-core unrealizability on Guard before extraction. Its saved relations independently show $(0, 1)$ legal and $x' \vee b$ false for both responses at every helper-false initial state [10]. That certifies strict loss without treating the raw cooperative-core verdict as a strict result or claiming a frontend-default execution.

IV. Diagnosing Continuation Loss

Vehicle shows a direct first-flip obstruction with completed native queries; Patrol shows loss propagated back to an entry that passes the immediate check. A *route* is a specific translation, solver and extraction chain. Table I binds each claim to that chain, distinguishing saved relation certificates from executed queries.

A. Vehicle: a public reached-state loss with positive initialization

Unchanged public Vehicle188 supplies a separate, outcome-selected witness. It lies outside the fixed cohorts in Section VI. Let o_i, p_i, g_i be lane-i obstacle, pedestrian and green-light Booleans, x a crosswalk Boolean, $\ell \in \{1, 2, 3\}$ the lane and $v \in \{0, \ldots, 10\}$ the speed. The source has true initial predicates. Three relevant source safety clauses are

$$\begin{aligned} \text{ENV}: \quad & o_2 \Rightarrow (\neg o_1' \vee \neg o_3'), \\ \text{SYS}: \quad & (\ell = 2 \wedge o_2 \wedge o_1') \Rightarrow \ell' = 3, \\ & (\ell = 2 \wedge o_2 \wedge o_3') \Rightarrow \ell' = 1. \end{aligned}$$

These are selected clauses, not the complete safety relations. At $s = (o, p, g, x; \ell, v) = (010, 000, 111, 0; 2, 0)$, the original input rule excludes simultaneous next obstacles in both outer lanes. On the first helper flip, the typed input $(o', p', g', x') = (101, 000, 111, 0)$ becomes legal while both response clauses remain active: they require $\ell' = 3$ and $\ell' = 1$. No choice of next speed can resolve that conflict. The current stopped state is allowed: the positive-speed duty's antecedent includes $\neg o_2$, which is false at s.

The two completed full native strict queries in Table I confirm $s \in W$ and $(s, 0) \notin W_R$, while both actual initializer judgments are true [12]. They use unchanged initializers and no extra transition restriction. Thus positive initialization can coexist with loss at a reached state. The strict queries do not compute cooperative strategies or reachability; those claims use separate source proofs.

a) The complete continuation region: A preregistered audit [13] evaluates all 33,792 typed source states in the saved native winning BDDs. Two independent saved-BDD evaluators agree: $|W| = 8,064$, the helper-false winning slice contains 6,656 source states, and exactly 1,408 source winners are lost, with no gains. *Cooperation from every winning state.* The other ENV safety clauses are $o_1 \Rightarrow \neg o_2'$ and $o_3 \Rightarrow \neg o_2'$; all ENV justices are $g_i \wedge \neg p_i \wedge \neg o_i$. Thus $e_* = (o, p, g, x) = (000, 000, 111, 0)$ is always legal and can repeat fairly, independently of SYS. From any legal prefix of any strict-winning policy, continuing that same policy on e_*^ω gives a compatible fair continuation. Hence every such policy is cooperative and $W = K$.

A safe predecessor for every target. For each $s \in W$, fix $p_s = (e_*; \ell(s), 1)$. The remaining SYS safety clauses require current speed zero for a red light or pedestrian in the occupied lane, positive speed in a free occupied lane, and speed below five at a crosswalk. They also force lane changes from current obstacles and forbid direct jumps between lanes 1 and 3. At p_s, the stop, crosswalk and obstacle guards are false; speed 1 meets the active free-lane duty, and retaining the lane avoids both forbidden jumps. Next speed has only its type bound. The three ENV safety antecedents are also false. Thus $p_s \to s$ is safe for every typed target. The audit separately verifies $p_s \in W$ and its initializer, checking $\theta_e(p_s) \wedge \theta_s(p_s) \wedge W(p_s) \wedge \rho_e(p_s, e(s)) \wedge \rho_s(p_s, e(s), y(s))$ for all 8,064 targets.

An initialized policy for each target. All 1,024 initial ENV assignments have a winning SYS response. Choose p_s at initial input e_*; on next input $e(s)$, take the safe edge and win from s, otherwise follow a winning policy from p_s. For other initial inputs, use winning responses and their winning tails. Every branch wins, so the policy is strict and, by the preceding argument, cooperative. Its legal play p_s, s reaches s at time 1. The policy may depend on s; neither forced reachability nor one policy visiting all targets follows. Supplement X supplies full source checks.

A correct helper controller stays winning along legal executions of its unchanged game. The replacement question concerns a retained state not already guaranteed to lie in the changed candidate's winning region, even when the synthesis route is unchanged. Vehicle proves source-policy reachability, not a model-change execution or a frequency estimate.

TABLE I

BINDING THE PRINCIPAL CLAIMS TO THEIR SOURCE, ENCODING AND QUERY. "NATIVE" NAMES AN EXECUTED TOOL QUERY, NOT A FRONTEND OBSERVATION. THE SELECTED RELEASE IS SPECTRA [11] `1.0.0.202402072123`/JTLV. BINDINGS: SUPPLEMENTS B, E, U, V AND X.

Instance	Source and encoded relations	Calculation or producer	Supported conclusion and limit
Vehicle188	Unchanged public source; full exported syntactic-helper relations match the complete literal encoding (1).	Two completed full `GR1Game` strict queries; independent whole-region evaluation of their saved winning BDDs.	1,408 of 8,064 source strict/cooperative states lost; both initial judgments true. Cooperation and pointwise initialized reachability use source proofs.
Patrol new	Unchanged public source; syntactic helper. $E_{00} = \rho_e$, $S_{00} = S_{01} = \rho_s$; $E_{01} = E_{11} = \top$; S_{11} retains AUX updates.	Full relation checks; complete countercertificate; explicit and native reduced-game queries.	Certified $r \in W \setminus W_F$ with $U = D, F = C$. Direct full-helper native queries remain UNKNOWN.
Lift T	Reconstructed published listing; selected syntactic helper. Original predicates match the helper-false view; no source clause is repaired.	Raw `GR1SeparatedGame` core; generic finite-memory extraction (named in Supplement W.2). One solve, two final selections.	One strict-only graph, one strict cooperative graph. This tests the selected generic extractor, not a historical or default frontend.

The headless route applies the syntactic reduction before default translation and BDD construction, followed by the strict query or the raw, unnormalized cooperative core with generic extraction. Supplements Y.1 and W.2 give the implementation chain. Typed-domain BDD comparisons bind the listed Vehicle/Patrol branches and Lift's helper-false view, including initializers and ordered justices. The chain is statically mapped to public Kind; defaults use ordinary GR(1). GUI execution, historical C-driver identity and a frontend option for the separate semantic correction remain unestablished.

B. Patrol: strict-winning continuation lost from a pending entry

Patrolling (Kind corpus 277 [14]) requires a robot on a 5×5 grid to revisit three fixed checkpoints and the origin, reach charger $(4, 0)$ on low power, and dwell for four states. Closure flags cannot change within one cell; movement avoids blocked checkpoints. The source requires infinitely many visits to each checkpoint and the origin, and infinitely many states with $request = S0$. The three ENV justices require each checkpoint to reopen infinitely often. The logical request monitor, retained at the update, is $S2$ while the charging request is pending. At the retained entry with helper false, the complete literal old/new games give win/loss. For the selected syntactic exports, this comparison is loss/loss with the original old spelling and win/loss with the equivalent-old-spelling control. The initial request clears before the obstruction: the loss concerns full strict continuation. Supplement S gives all source clauses and monitor transitions.

The constructed old model fixes layout $L = (A, B, C) = ((0, 4), (2, 4), (4, 4))$ and permanent checkpoint availability. Removing these additions yields the published new source; coordinate persistence retains the reached layout. SYS requirements, types and monitor equations are identical. Write p, d, z, c, m for position, blocked flags, charged flag, counter and logical monitor, and q for private phase. An old BOOT step stays at the origin and changes $(m, q) = (S0, -1)$ to $(S2, 0)$, reaching the source state

$$r = (L, p, d, z, c, m) = (L, (0, 0), 000, 0, 0, S2).$$

The controller has private phase $q = 0$. The update retains both r and q without reinitialization.

a) Source updates: ENV preserves checkpoint coordinates, freezes a blocked flag within $\|p - t_i\|_\infty \leq 1$, and requires $c = 3 \Rightarrow z'$. SYS moves at most one cardinal step, avoids each currently blocked checkpoint's next position, and stays at $H = (4, 0)$ while $c < 3$. Its counter update is $c' = \min(3, c+1)$ at current $p = H$, and zero otherwise. The complete request-monitor update is

$$m' = \begin{cases} S2, & m = S0,\ \neg z,\ c < 3,\ p \neq H, \\ S1, & m = S2,\ c = 3, \\ S0, & m = S2,\ c < 3,\ p = H, \\ m, & \text{otherwise.} \end{cases}$$

Here $c \in \{0, 1, 2, 3\}$ and every right-hand variable is current. The absorbing $S1$ remains in the typed arena. A policy reaching H with $(c, m) = (0, S2)$ clears the request on the next dwell, giving $(c', m') = (1, S0)$ before c reaches three.

b) A source continuation: Let $O = (0, 0)$, $H = (4, 0)$ and standoffs $s_A = (0, 2), s_B = (2, 2), s_C = (4, 2)$. A handwritten policy expands

$$\begin{aligned} O \to s_A \to A \to s_A \to s_B \to B \to s_B \\ \to s_C \to C \to s_C \to s_A \to O \to H \to s_C \to s_A \end{aligned}$$

into cardinal unit steps, then resumes the approach to A. On each legal input it holds position and phase if $p = H, c < 3$, or if at a standoff before approaching checkpoint i and $d'_i = 1$; otherwise it advances one step and its private phase. Source counter and monitor updates apply even during a hold. Reopening fairness ends each wait; entering the one-cell neighborhood freezes an open flag through the visit and retreat. This policy was designed after diagnosis as a controlled reuse witness.

Complete checks establish $r \in K_{\text{old}} \cap K_{\text{new}}$: the old initialized closure has two roots, 140 nodes and 277 edges; the new closure from r with private phase $q = 0$ has 849 nodes and 12,240 edges. The old closure stays in C. The new one has 62 nodes outside C but remains legal-prefix cooperative: relocating flip inputs are source-illegal. Its all-history Definition 3 status is




Fig. 2. Countercertificate for the new Patrol encoding: avoid H forever and violate SYS justice, or reach H and face the impossible flip after the initial request clears. The flip relocation is source-illegal. The published new source is unchanged; the old restriction, layout and reusable policy are constructed. Evidence bindings: Table I.

TABLE II
EXACT COUNTERCERTIFICATE EXIT (ALL FOURTEEN SOURCE FIELDS) AND CHOSEN NEXT ENV INPUT. THE ADDED HELPER CHANGES $b = 0$ TO $b' = 1$; DASHES DENOTE FIELDS CHOSEN BY SYS.

Fields	Exit state	Flip input
A, B, C coordinates	$(0,4), (2,4), (4,4)$	$(4,0), (2,4), (4,4)$
Blocked flags (A, B, C)	$(1, 0, 0)$	$(1, 0, 0)$
`isCharged`	0	0
Robot position	$(4, 0)$	—
Counter, request (AUX)	$(1, S0)$	—

not established or needed for strict loss. Supplement S retains the complete graphs and all source, monitor, memory and justice checks.

c) A local pass, but an exact continuation loss: Let $N(s)$ count movement/dwell-permitted next robot cells, and $k(s)$ count currently blocked checkpoints. Neither these constraints nor the unique AUX updates depend on next charged/blocked flags. The complete literal flip condition is

$$C(s) \iff N(s) > k(s).$$

A flip can choose arbitrary typed next checkpoint coordinates, so k blocked checkpoints can cover all N cells exactly when $N \leq k$; counter and monitor updates are unique. The old graph stays in C, proving $r \in W_C^{\text{old}}$ for the complete literal relations. The actual old-source export has a different helper-false ENV relation, as detailed below. SYS safety is unchanged, so $C(r)$ is true under both models. Nevertheless, $r \notin W_C^{\text{new}}$.

A 26-node countercertificate covers *every safe response*, independently of that policy or private memory. Its 25 nonexit rows are exactly the states with layout L, any grid position p, and $(d, z, c, m) = (000, 0, 0, S2)$. Away from H, ENV keeps the flags open and power low. Every safe reply has $\|p' - p\|_1 \leq 1$ and the unique update $(c', m') = (0, S2)$, so remains in this set. At H, ENV legally closes distant A; dwell forces $p' = H$ and $(c', m') = (1, S0)$, giving Table II's exit. The saved check of all $5 \cdot 5 \cdot 4 \cdot 3 = 300$ typed SYS outputs per row confirms 103 safe replies. Every infinite nonexit branch satisfies all three ENV justices but violates $\mathsf{GF}(m = S0)$; the exit permits the impossible flip below.

At the exit, charging $1 < 3$ forces $robot' = (4, 0)$, while current $Ablocked = 1$ requires $robot' \neq A' = (4, 0)$. Of 300 typed outputs, 288 violate staying and the remaining 12 violate avoidance: no safe reply exists. Relocation violates source coordinate persistence but is legal on the first helper flip. The monitor is already $S0$ at this exit; the loss concerns *full strict-winning continuation from* r, not failure to discharge its initial request. Theorem 1 therefore excludes r from the new complete literal winning region.

d) Certified loss in the exported arena: The selected Spectra/JTLV syntactic route retains all fourteen source fields and logical monitors. Full-domain export checks establish the helper constraints below, linking the unchanged new source through Proposition 3 to the countercertificate and reduced-game results: $E_{00} = \rho_e$, $S_{00} = S_{01} = \rho_s$, $E_{01} = E_{11} = \mathit{true}$, and $E_{10} = \mathit{false}$. On the typed carrier, S_{11} retains the charging-counter and request-monitor updates. They have no next-ENV dependence. For all 600 assignments to their current support (robot position, charged flag, counter and monitor), each of the 25 typed next robot positions has exactly one AUX update. Every typed input therefore has a response inside D: $U = D$ and $F = C$ on all 75,000,000 source states, with $|F| = 71,812,500$ (Supplement U.1).

For the reached layout, original-legal inputs preserve all six checkpoint coordinates. The resulting closed slice contains 4,800 full source states; no monitor or response is removed. Exact calculations give $|W| = 3,280$ and $|W_F| = 1,104$, with $r \in W \setminus W_F$ despite $r \in F$. A separate explicit solver agrees. The independent native-relation audit checks all 103 replies, nonexit justice values and the zero-response flip. Closure under every legal input and response makes this a certificate for r in the exported arena, not a frontend verdict. Winning counts are slice counts; helper-true states and flip coordinates are unrestricted.

e) A completed native query of the reduced region: A native query of Proposition 3's reduced game uses ρ_e and $\rho_s \wedge F(s')$ in closed layout D_ℓ, retaining all fourteen fields, initializers and three ENV/five SYS justices. It completes in 78.625 s: $|D_\ell \cap W_{\text{raw}}| = 1,152$ and $|F \cap D_\ell \cap W_{\text{raw}}| = 1,104$. An independent audit matches all 4,800 memberships to W_F, excluding r; successor guarding maintains M_F from F. This executes the reduced game, not the full helper or frontend (Supplement U.6).

f) The old model and public initialization: The original old source spelling already loses in its exported helper arena: it allows sixteen inputs at r instead of two. A preregistered

explicit-initial/next spelling preserves every original predicate but changes the converted initializer and helper-false ENV relation. Its unchanged 140-node source graph is certified inside $F = C$, with $U = D$. Supplement W records both source forms and translated clauses.


Saved membership also gives a negative initialized decision for the released syntactic conversion of the unchanged public new source. The legal initial input $e^* = (L, d = 000, z = 0)$ permits all 25 robot positions with $c = 0, m = S0$; every such state lies in $W \cap C$ but outside W_F. Legal helper-false moves preserve L, so Proposition 3, with global $U = D$ and $F = C$, excludes every SYS initial response: $I_M(W_F) = \mathit{false}$. This theorem-derived result needs no full-region solve. Direct full-helper queries, including the unrestricted 150-million-state arena, remain UNKNOWN; neither a frontend refusal nor original-source initialization feasibility follows (Supplement U).

g) Validated reuse and its observed consequence: The handoff changes only the active environment model, retaining the plant/controller objects, source state, monitors and private phase. Across 67 new-mode commits, the request is served at step 30 and clears at 31. Newly legal closures occur at 3, 4 and 31; the last is outside C after service. A repeatable 35-step full-state/private-memory cycle meets all eight source justices. A separate source audit checks every commit, including BOOT; no checkpoint moves.

The passing graph justifies reuse without computing K or weakening the contract. Complete first-flip correction preserves strict continuation by theorem; direct original-game solving is an unrun alternative. The post-diagnosis workload was frozen before execution. Supplements S and U retain source/AST checks, certificates, traces and native controls.

V. A Solved Game Does Not Certify a Returned Graph

Lift tests the second boundary in Fig. 1: a generic extractor's fixed graph. This extractor is not established to implement the prescribed cooperative rank/mode strategy [9, Eq. (18), Theorem 3]. The original contract remains feasible. Changing final selection below is a diagnostic intervention, not a general repair.



The movement disjunct $f'_3 \wedge b_3$ holds.
Next $\mathrm{One}(f)$ fails: **no legal input remains**.

Fig. 3. A reached Lift response disables ENV. Table III gives its original-legal initialized prefix; f, b and m are floor, button and monitor triples (order 1–3); c is cancellation. Here b denotes buttons, not the helper. This edge reuses the bad node; diagnostic selection also acts at first creation.

a) Source mechanism: Lift T copies the trivial replacement listing's Boolean declarations, initializers, safety clauses and response guarantees verbatim [2]. Its only completion appends the same paper's omitted response-pattern definition (Appendix C.2.1), compiled into the logical SYS monitors below. The outputs f_1, f_2, f_3 indicate floors; inputs b_1, b_2, b_3 are buttons and c is cancellation. Here b_i denotes a button, distinct from the helper b. The published listing labels `one_floor` and its three exclusivity clauses as `assumption` [2, Appendix C.3.3, lines 36–46]; their conjunction is $\mathrm{One}(f)$. Under the recorded translation, environment safety is

$$E_L = \mathrm{One}(f) \wedge \bigwedge_{i=1}^{3} \big[(b_i \wedge f_i \Rightarrow \neg b'_i) \wedge (b_i \wedge \neg f_i \wedge \neg c \Rightarrow b'_i)\big],$$

where $\mathrm{One}(f)$ requires exactly one *current* floor. The recorded translator keeps SYS/AUX-dependent invariants as current ENV safety, without an initializer or primed copy. Thus the listing fixes ownership and the translation fixes timing; neither is changed by this reconstruction. System safety conjoins $f_i \Rightarrow D_i$ for all three floors, where

$$\begin{aligned} D_1 &= (f'_1 \wedge (\neg b_2 \wedge \neg b_3 \vee c)) \vee (f'_2 \wedge (b_2 \vee b_3)),\\ D_2 &= (f'_1 \wedge b_1) \vee (f'_2 \wedge \neg b_1 \wedge \neg b_3)\\ &\quad \vee (f'_3 \wedge b_3) \vee (f'_2 \wedge c),\\ D_3 &= (f'_3 \wedge (\neg b_1 \wedge \neg b_2 \vee c)) \vee (f'_2 \wedge (b_1 \vee b_2)). \end{aligned}$$

Every button and cancellation guard uses its current value. Thus D_2 permits both 100 and 011 when $b_1 = b_3 = 1$; no conjunct forbids extra true next floors. For each response obligation, SYS safety also requires

$$m'_i \leftrightarrow (m_i \vee b_i) \wedge \neg(f_i \vee c), \qquad i = 1, 2, 3.$$

These logical monitors are part of the source state; their justices are $\mathsf{GF}\neg m_i$. Initialization sets buttons 000, floors 100 and monitors 000, leaving c free; ENV has no justices. Private selector j belongs only to the returned graph. Supplement H retains the source.

TABLE III
Saved Lift prefix to Fig. 3: native node IDs and private justice selector j. Rows are completed states; the next row's (b, c) supplies the next input. The helper stays false. The last row is the bad node's construction predecessor, outside this prefix.

Node	Buttons b	c	Floors f	Monitors m	j
0	000	0	100	000	0
10	010	1	100	000	0
339	001	1	010	000	0
438	100	0	001	000	1
704	101	0	010	100	2
680	101	0	011	101	0
First-creation predecessor of node 680:					
668	111	0	010	110	2

At node 704 in Table III, repeating the input is legal. Figure 3 shows the returned response $f' = 011$: its $f'_3 \wedge b_3$ disjunct holds and the monitors update $100 \to 101$. No SYS clause forbids the second true floor. In the successor, $\mathrm{One}(f)$ fails, so all next inputs are illegal. The table binds this edge to an original initializer and the graph's actual private

memory. The complete 154-state original-contract graph is strict but non-cooperative. It violates Kind Definition 3 [7, Sec. 4]: an original-legal reachable prefix has no environment-fair continuation. Current SYS variables in ENV safety are allowed by Kind's input syntax [7, Sec. 3.1]. The same contract has the cooperative policy below, yet the transformed game permits the bad node. Thus the failure belongs to the selected extractor's fixed graph, not source infeasibility. The selected raw arena fails the sufficient language-inclusion condition for non-conflictingness [9, Eq. (13c), Theorem 3]: a checked initialized lasso reaches helper true, satisfies all SYS justices and violates the added ENV justice. This is a selected-route output failure, not an abstract-theorem counterexample; Supplement V gives the precise bindings.

b) A positive source policy: Let $\ell \in \{1,2,3\}$ be the unique current floor and let private priority $d \in \{1,3\}$ start at 3, independently of graph selector j. The following policy reads current buttons; the floor-2 tests are ordered:

$$\begin{aligned} \ell = 1: &\quad \ell' \leftarrow 2 \text{ if } b_2 \vee b_3, \text{ else } 1;\\ \ell = 3: &\quad \ell' \leftarrow 2 \text{ if } b_1 \vee b_2, \text{ else } 3;\\ \ell = 2: &\quad \ell' \leftarrow d \text{ if } b_1 \wedge b_3;\ 1 \text{ if } b_1;\\ &\qquad\qquad 3 \text{ if } b_3;\ 2 \text{ otherwise.} \end{aligned}$$

Set $f_i' \leftrightarrow (i = \ell')$, apply the stated monitor equation, and set $d' = 4 - \ell'$ on departure from floor 2, keeping d otherwise. Each move satisfies a displayed movement disjunct. An unanswered button persists until arrival or cancellation. Without cancellation, endpoint priority can be lost at most once, so service occurs within four transitions; arrival or cancellation clears the monitor on the next. The middle floor is reached within one transition when requested. Initialization and legal ENV persistence imply $m_i \Rightarrow b_i$ on every policy prefix. A permanently pending monitor would therefore force a persistent uncancelled button, contradicting the service bound. Thus all monitor justices hold from original initialization.

Every legal policy prefix retains $\mathrm{One}(f)$ and a legal next input. Repeatedly taking $c' = 1$ and $b_i' = b_i \wedge \neg f_i \wedge \neg c$ is one ENV-safe infinite suffix; there are no ENV justices. This proves cooperation under the same reached policy memory, independently of a saved graph report. The complete initialized graph has 128 nodes and 1,020 edges and passes both checks. A separately checked extension also wins the complete transformed game (Supplement H). Neither result claims correctness from arbitrary orphan-monitor states.

c) A matched selection diagnosis: We audit the chain in Table I directly.

One solve supplies the same model and memory objects to both extractors. Saved checks establish equal winning region, stored fixed-point sets X, Y, Z, initializers, transition relations and ordered justices, with unchanged variable order. For a candidate successor t and Boolean helper h, define

$$Q(t) = h(t) \vee \exists e' \in E : \rho_e^{\mathrm{native}}(t, e')[h = 0, h' = 0].$$

After the unchanged progress, goal and existing-node filters produce B, the modified copy substitutes $B \cap Q$ when nonempty, otherwise B, immediately before final response selection. Rank selection and private-memory updates remain unchanged. This tests immediate input availability, retaining helper-true candidates; complete graph audits establish cooperation. Source equations match the helper-false relations on all 1,048,576 original state pairs, initializers and ordered justices; both auditors share compiler exports.

At the first creation of bad node 680, the final candidate floor set is $B = \{011, 100, 101, 110, 111\}$ and $B \cap Q = \{100\}$. The released extractor chooses 011; the diagnostic selection chooses 100, which permits four next inputs. At the later reused edge in Fig. 3, the existing-node filter leaves only 011. Thus the intervention acts during extraction, including first creation, rather than replacing only the displayed reused edge. Supplement W gives the preceding filters and exact predecessor.

The initialized original-contract graphs each have 154 nodes, with 1,170 released and 1,176 preference edges. Both complete checkers classify the released graph as strict-only and the preference graph as strict and cooperative (Table I). The matched output difference is at final selection, but that is not the sole cause: the transformed game already permits the bad node. The intervention is inactive in six successful controls. Counts include two initial nodes and native memory; equal counts do not identify nodes. Supplements H and T retain calls, candidates, traces and certificates.

A separate contract control moves the floor-invariant clauses from ENV/current to SYS/next constraints. Both graphs then coincide and pass the audits. Ownership and timing change together, so this is a contract sensitivity check, not evidence that the original contract needs changing (Supplement W).

d) Why this is a diagnostic contrast: Constructed Polling has the safety assumption $\neg poll \Rightarrow \neg ack'$, ENV justice $\mathsf{GF}ack$, and SYS justice $\mathsf{GF}heartbeat$. An input remains available everywhere. Normalized synthesis on the original nonblocking arena computes exact $K = D$, yet the generic extractor returns a strict graph with terminal cycle $poll = ack = 0$ and no fair ENV continuation. The helper-based released and selection-variant outputs also fail cooperation, with unchanged responses. Hence availability selection and a correct existence region do not certify a fixed graph. All three saved outputs fail the complete cooperation check (Supplement O).

VI. Admission and Existing Comparisons

The distinction in Section II gives a concrete admission rule: keep the source state and logical monitors fixed, bind each candidate's private root, and install the first passing graph. If all candidates fail or remain UNKNOWN, defer replacement without inferring source infeasibility. Holding continues only while valid; otherwise the bridge or revalidation condition in Section II applies. Changing the contract needs a preserving refusal or a separate source argument.

A. Complete fixed-graph checks

The audit checks the selected root or required initial choices, responses to every original-legal input, source safety, logical-monitor and private-memory updates, strict liveness, and legal-prefix cooperation. In the graph of checked legal responses, an

ENV-accepting strongly connected component (SCC) contains a cycle and intersects every ENV justice. Cooperation holds exactly when every reachable node can reach such an SCC. Strict liveness requires that, for each SYS justice, removing the nodes satisfying it from the already reachable graph leaves no ENV-accepting SCC. SCCs need not be bottom components; a singleton needs a self-loop. Even with no ENV justices, a cycle is required.

A model-based audit requires typed predicate correspondence; a direct audit uses source equations. Original-contract views of helper-based graphs keep the helper false and retain every original-legal input. Missing correspondence or exhausted resources leaves the relevant decision UNKNOWN; it does not invalidate an independent source certificate.

B. Existing synthesis as a source of alternatives

Let $V = \nu X.(Alive \wedge \mathrm{CPre}(X))$, where $Alive$ means some original-legal next input exists and $\mathrm{CPre}(X)$ requires a safe SYS response into X for every such input. Every strict cooperative strategy remains in V. If $V = \varnothing$, then $K = \varnothing$; otherwise retain every original-legal input and all safe responses into V, and split rounds into input/response edges to obtain a finite total arena H. The reached states and residual strategies form a post-fixed point of $Alive \wedge \mathrm{CPre}$; restriction retains their legal prefixes and memory. Conversely all original-legal inputs are retained, and $A \Rightarrow (G \wedge A) \equiv A \Rightarrow G$. Thus normalization preserves K (Supplement L.2) and establishes the language premise $L(H, G \wedge A) \subseteq L(H, A)$ [8], [9]. Justice labels occur only on completed states, with empty lists padded by true. The round correspondence identifies final regions, not extracted ranks (Supplements A and L.2).

The cited four-fixed-point theorem supplies a prescribed rank/mode witness inside K and excludes every history-dependent strict cooperative strategy outside it [9, Eq. (18), Theorem 3, Apps. B.1–B.2]. Our generic constructor has no established binding to that strategy; every returned graph is audited separately.

C. A paused replacement and its consequence

Under the constructed old Lift restriction $\mathsf{G}\neg b_1$, inputs $0010, 0010$ in (b_1, b_2, b_3, c) order reach native nodes $0 \to 4 \to 524$. The paused state is

$$(b_1 b_2 b_3, c, f_1 f_2 f_3, m_1 m_2 m_3) = (001, 0, 010, 001),$$

with an unanswered third-floor request. Removing the restriction retains this valuation. Candidate node/selector pairs are native $524/1$, normalized $72/1$, and selection variant $524/1$; IDs are graph-local, and the normalized graph has no helper.

At all three pending boundaries in the old closure, the manager tries native, normalized, then the selection variant until the first complete pass. Coverage, safety, monitor/memory and SCC checks withhold native, admit normalized and leave the third candidate untried. No source field, monitor or runtime state object changes during selection. The displayed case installs normalized root $72/1$ (Supplement U.9).

Separate bounded executions compare all nine candidate/root pairs. All serve the old request at step 1 and clear its monitor at 2. The three retained-native executions later stop after eight commits, with a new first-floor request pending and no legal input. The six alternatives complete twelve commits and reach a fair loop. Later continuity differs; service of the old request does not. Gated native episodes instead remain paused with zero commits. Workloads were fixed after diagnosis and before execution, not held out (Supplement R).

Candidates are prepared beforehand. Gate measurements exclude synthesis: 4.448–5.207 s for Patrol, and 0.039–0.059 s per Lift candidate plus 0.357–0.481 s shared loading/binding. These are bounded software measurements, not latency guarantees (Supplement U.4).

D. What the fixed comparisons establish

Table IV keeps the input sets and their selection rules separate. Existing normalized synthesis supplies admitted graphs for every cooperatively feasible contract in the two fixed rosters: eight of eleven reconstructed listings and twelve of fourteen public inputs. These are separate route runs, not matched extractions, and establish available alternatives rather than selection-variant necessity or comparative superiority.

The eleven listings come from five correlated examples; T and P denote trivial and preferred replacements. For the selected route, Lift T is the only feasible contract with a failed cooperative output. The other unadmitted listings have empty cooperative regions: Arbiter P is strict-only, Minepump P is raw-negative, and Lift P has unknown route correspondence. A raw negative need not be a source refusal. Supplements H (Tables 6–7) and T (Table 25) give the candidate and route results.

The public roster's two strict-only outputs are PCar058, whose cooperative region is empty, and Elevator032, whose nonempty cooperative region fails initialization. Neither is a feasible-contract counterexample. Resource-UNKNOWN SmartHome1 223 is admitted by all three alternatives (Supplement T).

a) Selection, stopping and negative results: The public inventory contains 425 byte-distinct source units, including two pattern libraries. Representative archive-path order with per-input caps of 60 s, 512 MiB heap and 128 MiB direct memory produced 70 completed original models, 107 resource UNKNOWNs, 54 technical UNKNOWNs, one integrity UNKNOWN and 193 unattempted inputs. A BDD-file cap followed by a process-cleanup permission failure stopped the run. Of the 70 completions, two exceeded the checker's 64-variable limit and nine failed array-metadata roster checks; all remaining 59 certified models entered the literal-preservation analysis, without outcome filtering. This is a stopped, resource- and certification-conditioned cohort.

Among its ten strict-preservation losses, all contracts already lack cooperative initialization. Nine exact-loss calculations completed: seven have empty K and two preserve every K state; the tenth remains UNKNOWN. Thus this cohort contains no confirmed cooperative-initialization loss, and it

TABLE IV
EXISTING COMPARISONS, WITH DISTINCT UNITS AND SELECTION RULES. AN ADMITTED GRAPH PASSES STRICTNESS AND LEGAL-PREFIX COOPERATION CHECKS. ALL OUTCOMES, EXCLUSIONS AND UNKNOWNS ARE RETAINED IN SUPPLEMENTS E, H, T AND Y.

Input set and selection	Saved results	What the comparison establishes
All 11 replacement listings in five published examples' appendices; reconstructed.	Selected: 7 admitted, 2 strict-only, 1 raw negative, 1 correspondence UNKNOWN. Normalized: 8 admitted; 3 independently confirmed empty-V stops before solving.	Existing normalized synthesis succeeds on all 8 feasible listings. Correlated reconstructions, not historical executions.
14 unchanged public inputs: all available certified carriers with at most 4,096 states; no region or output filtering.	Selected: 11 admitted, 2 strict-only, 1 resource UNKNOWN. Normalized/cooperative Slugs: 12 admitted and 2 negative each. Original nonblocking strict: 12 admitted, 1 strict-only, 1 negative.	Four routes, 56 recorded input/route outcomes. A bounded certified roster; no population or performance inference.
Stopped public inventory: 425 byte-distinct units, 70 model completions, 59 checker-certified models.	Complete literal relations: 49 satisfy $W \subseteq C$; 10 lose strict states. Exact loss finishes on 9, with no lost K state; 1 remains resource UNKNOWN. All 10 lack cooperative initialization.	An explicit preservation diagnostic with negative results. Counts do not transfer automatically to syntactic exports or estimate incidence.
7 fixed cooperative-positive inputs [15] from the certified inventory; old $W = K$ and literal preservation known.	14 native strict queries and 198,672 typed-state comparisons: source W equals old symbolic $W = K$ and the route source view in all 7; both initial judgments true.	3 helper-active GyroAspect variants; 4 identity/skip controls. No loss or gain in this selected set; no general preservation claim.

supplies no incidence estimate. The separate Vehicle witness and constructed Polling control are outside these denominators. Selected Humanoid044 also has source $V = K = \varnothing$; its guard study does not establish a cooperative rescue (Supplement D).

b) Accessible evidence and shared dependencies: The archives [16], [10], [17], [18], [19] retain sources, graphs, certificates and saved-data replay instructions. Lift's separate decoders and source-equation audits share compiler exports; region and memory checks share a decoder. Patrol combines source, raw-BDD and explicit-set checks. Neither compiler independence nor external reproduction follows. Supplements U–Y distinguish native execution, saved membership, graph audits and source proofs.

VII. SCOPE AND RELATED WORK

a) Scope of the decision: Admission assumes prepared candidates and a valid hold. Changing physical state requires a verified bridge or revalidation. Change detection and automatic candidate generation remain outside this implementation.

Strict preservation alone does not imply cooperation. Source ENV justice may be impossible, and a helper flip itself defeats the added justice. Normalization after conversion need not restore cooperation (Supplement L.2).

b) Relation to prior work: Multi-tier control, exploration, weakening, recovery, interpolation and permissive assumptions [20], [21], [22], [23], [24], [25] construct adaptation choices; our diagnoses test whether retaining the original contract is already justified. Cooperative synthesis [8], [9] certifies its prescribed construction. IROS's middle-fixed-point restrictions block all six priorities [26, author appendix, p. 9]; Lift retains response 100 and localizes the matched difference to final selection. Best-effort GR(1) retains fairness opportunities [27]; acceleration preserves a language-inclusion premise [28, Sections 2.3, 4.1]. The implemented guard's complete form preserves strict winning [4]; our results characterize other encodings. Well-separation classifies targeted assumption violations [29, Section 6.3]. Dynamic-update synthesis constructs bridges [30], [3]; runtime verification retains monitors [31]. Our fixed-entry admission decision precedes any needed changing-state bridge.

VIII. CONCLUSION

At a retained source state, the exact theorem and Vehicle/Patrol identify continuation loss under Boolean-helper encodings. Lift separates fixed-output admission. Existing normalized synthesis and complete graph audits support retaining feasible contracts and admitting qualified candidates. Deployment frequency and general repair effectiveness remain open.

ACKNOWLEDGMENTS

OpenAI Codex [32] assisted with drafting throughout this paper, formal reasoning (Sections II–VI), and experiment design, derivation, implementation, execution, auditing and analysis (Sections IV–VI). Claude (Fable 5.1) and ChatGPT (GPT-6 Pro) reviewed main-paper drafts; Fable also reviewed supplement drafts and a primary paper. The supplement's acknowledgments detail the workflow and limitations.

References

[1] T. Buckworth, D. Alrajeh, J. Kramer, and S. Uchitel, "Adapting specifications for reactive controllers," in *SEAMS*, 2023, pp. 1–12. doi: 10.1109/SEAMS59076.2023.00012.

[2] T.-A. Georgescu, D. Alrajeh, and S. Uchitel, "Learning to adapt GR(1) specifications through degradation," arXiv:2609.12231v1, Sept. 2026. https://arxiv.org/abs/2609.12231v1.

[3] G. Amram, S. Maoz, I. Segall, and M. Yossef, "Dynamic update for synthesized GR(1) controllers," in *ICSE*, 2022, pp. 786–797. doi: 10.1145/3510003.3510054.

[4] Software Modeling Lab, "Spectra Tools: Released Game-Model Bundle," version 1.0.0.202402072123, 2024. Bundled source: `PitermanSemanticReduction`. https://smlab.cs.tau.ac.il/syntech/spectra/tools/update/plugins/tau.smlab.syntech.gamemodel_1.0.0.202402072123.jar.

[5] Anonymous artifact contributors, *Continuation Preservation: Research Artifact*, Oct. 2026. https://github.com/research-artifact-archive/seams2027.Document/layout snapshot: reader-layout-20261024-v1.

[6] R. Bloem, B. Jobstmann, N. Piterman, A. Pnueli, and Y. Sa'ar, "Synthesis of Reactive(1) Designs," *J. Comput. Syst. Sci.*, vol. 78, no. 3, pp. 911–938, 2012. doi: 10.1016/j.jcss.2011.08.007.

[7] A. Gorenstein, S. Maoz, and J. O. Ringert, "Kind controllers and fast heuristics for non-well-separated GR(1) specifications," in *ICSE*, 2024. doi: 10.1145/3597503.3608131.

[8] R. Bloem, R. Ehlers, and R. Könighofer, "Cooperative reactive synthesis," in *ATVA*, 2015, pp. 394–410. doi: 10.1007/978-3-319-24953-7_29.

[9] R. Majumdar, N. Piterman, and A.-K. Schmuck, "Environmentally-friendly GR(1) synthesis," in *TACAS*, 2019, pp. 229–246. doi: 10.1007/978-3-030-17465-1_13. Extended proofs: https://arxiv.org/abs/1902.05629.

[10] Anonymous, *Certificate and Finite-Study Evidence*, version certificate-finite-evidence-20261023-v2, Oct. 2026. https://github.com/research-artifact-archive/seams2027/tree/certificate-finite-evidence-20261023-v2.

[11] S. Maoz and J. O. Ringert, "Spectra: a specification language for reactive systems," *Software and Systems Modeling*, vol. 20, pp. 1553–1586, 2021. doi: 10.1007/s10270-021-00868-z.

[12] Anonymous, *Vehicle188 Native Strict Evidence*, version vehicle188-native-evidence-20261024-v1, Oct. 2026. https://github.com/research-artifact-archive/seams2027/blob/vehicle188-native-evidence-20261024-v1/VEHICLE188_NATIVE_EVIDENCE.md.

[13] Anonymous artifact contributors, *Vehicle188 whole-region saved evidence*, version vehicle188-whole-region-evidence-20261024-v1, Oct. 2026. https://github.com/research-artifact-archive/seams2027/blob/vehicle188-whole-region-evidence-20261024-v1/VEHICLE188_WHOLE_REGION_EVIDENCE.md.

[14] A. Gorenstein, S. Maoz, and J. O. Ringert, "Artifact for ICSE'24 paper: Kind Controllers and Fast Heuristics for Non-Well-Separated GR(1) Specifications," Zenodo, v3, 2024. doi: 10.5281/zenodo.10553249.

[15] Anonymous artifact contributors, *Fixed-seven native saved-data evidence*, version fixed-seven-native-evidence-20261024-v1, Oct. 2026. https://github.com/research-artifact-archive/seams2027/blob/fixed-seven-native-evidence-20261024-v1/FIXED_SEVEN_NATIVE_EVIDENCE.md.

[16] Anonymous, *Saved Controller Evidence*, version intruder-bounded-evidence-20261021-v1, Oct. 2026. https://github.com/research-artifact-archive/seams2027/tree/intruder-bounded-evidence-20261021-v1.

[17] Anonymous, *Pending-Work Native Handoff Evidence*, version pending-native-handoff-evidence-20261023-v2, Oct. 2026. https://github.com/research-artifact-archive/seams2027/tree/pending-native-handoff-evidence-20261023-v2.

[18] Anonymous, *Pending Diagnostic Evidence*, version pending-diagnostic-evidence-20261023-v1, Oct. 2026. https://github.com/research-artifact-archive/seams2027/tree/pending-diagnostic-evidence-20261023-v1.

[19] Anonymous, *Continuation Evidence*, version continuation-evidence-20261024-v1, Oct. 2026. https://github.com/research-artifact-archive/seams2027/blob/continuation-evidence-20261024-v1/CONTINUATION_EVIDENCE.md.

[20] N. D'Ippolito, V. Braberman, J. Kramer, J. Magee, D. Sykes, and S. Uchitel, "Hope for the best, prepare for the worst: Multi-tier control for adaptive systems," in *ICSE*, 2014, pp. 688–699. doi: 10.1145/2568225.2568264.

[21] M. Keegan, V. Braberman, N. D'Ippolito, N. Piterman, and S. Uchitel, "Control and discovery of environment behaviour," *IEEE Transactions on Software Engineering*, vol. 48, no. 6, pp. 1965–1978, 2022. doi: 10.1109/TSE.2020.3044532.

[22] S. Chu, E. Shedden, C. Zhang, R. Meira-Góes, G. A. Moreno, D. Garlan, and E. Kang, "Runtime resolution of feature interactions through adaptive requirement weakening," in *SEAMS*, 2023, pp. 115–125. doi: 10.1109/SEAMS59076.2023.00025.

[23] S. Chu, J. Koe, D. Garlan, and E. Kang, "Integrating graceful degradation and recovery through requirement-driven adaptation," in *SEAMS*, 2024, pp. 122–132. doi: 10.1145/3643915.3644090.

[24] D. G. Cavezza and D. Alrajeh, "Interpolation-based GR(1) assumptions refinement," in *TACAS*, 2017, pp. 281–297. doi: 10.1007/978-3-662-54577-5_16.

[25] A. Anand, K. Mallik, S. P. Nayak, and A.-K. Schmuck, "Computing adequately permissive assumptions for synthesis," in *TACAS*, 2023, pp. 211–228. doi: 10.1007/978-3-031-30820-8_15.

[26] R. Ehlers, R. Könighofer, and R. Bloem, "Synthesizing cooperative reactive mission plans," in *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2015, pp. 3478–3485. doi: 10.1109/IROS.2015.7353862. Author version with appendix: https://www.ruediger-ehlers.de/papers/iros2015.pdf.

[27] S. Liu, Y. Zhang, C. Hu, and W. Dong, "Best-effort GR(1) synthesis: Exploiting environmental cooperation under unrealizability," in *ASE*, 2026, pp. 1806–1818. doi: 10.1145/3832783.3837439.

[28] S. Liu and W. Dong, "Accelerating kind realizability: A multi-stage incremental realizability checking framework," in *FM*, 2026, pp. 240–258. doi: 10.1007/978-3-032-26204-2_13.

[29] S. Maoz and J. O. Ringert, "On well-separation of GR(1) specifications," in *FSE*, 2016, pp. 362–372. doi: 10.1145/2950290.2950300.

[30] L. Nahabedian, V. Braberman, N. D'Ippolito, S. Honiden, J. Kramer, K. Tei, and S. Uchitel, "Dynamic update of discrete event controllers," *IEEE Transactions on Software Engineering*, vol. 46, no. 11, pp. 1220–1240, 2020. doi: 10.1109/TSE.2018.2876843.

[31] M. Carwehl, T. Vogel, G. N. Rodrigues, and L. Grunske, "Runtime verification of self-adaptive systems with changing requirements," in *SEAMS*, 2023, pp. 104–114. doi: 10.1109/SEAMS59076.2023.00024.

[32] OpenAI, *Codex*, 2026. Accessed Oct. 23, 2026. https://openai.com/codex/.