1. Geometric Volume & Net Structural Mass Derivation (Single Bridge)

To establish the exact physical weight added to an accelerator package by a full-flank optical inlay bridge ($L = 5.0\ \text{mm} = 0.50\ \text{cm}$, $W = 15.0\ \text{mm} = 1.50\ \text{cm}$, area $A_{\text{bridge}} = 0.75\ \text{cm}^2 = 75.0\ \text{mm}^2$), the cured volume V_i and net dry mass $m_{i,\text{net}} = \rho_i \cdot V_i$ of each functional layer are derived from first principles.

1.1 Layer-by-Layer Mass Equations

1. **Layer 1 — Cured DVS-BCB Planarization Prime Coat ($t_{\text{BCB}} = 2.00\ \mu\text{m}$, $\rho_{\text{BCB}} = 1.05\ \text{g/cm}^3$):**

$$V_{\text{BCB}} = A_{\text{bridge}} \cdot t_{\text{BCB}} = 0.75\ \text{cm}^2 \times 2.00 \times 10^{-4}\ \text{cm} = 1.50 \times 10^{-4}\ \text{cm}^3 = 0.15000\ \text{mm}^3$$

$$m_{\text{BCB,net}} = V_{\text{BCB}} \cdot \rho_{\text{BCB}} = 1.50 \times 10^{-4}\ \text{cm}^3 \times 1.05\ \text{g/cm}^3 = 1.575 \times 10^{-4}\ \text{g} = 157.50\ \mu\text{g}$$

2. **Layer 2 — Siloxane Elastomer Shear-Buffer ($h_{\text{buf}} = 20.00\ \mu\text{m}$, $\rho_{\text{buf}} = 1.08\ \text{g/cm}^3$):**

$$V_{\text{buf}} = A_{\text{bridge}} \cdot h_{\text{buf}} = 0.75\ \text{cm}^2 \times 2.00 \times 10^{-3}\ \text{cm} = 1.50 \times 10^{-3}\ \text{cm}^3 = 1.50000\ \text{mm}^3$$

$$m_{\text{buf,net}} = V_{\text{buf}} \cdot \rho_{\text{buf}} = 1.50 \times 10^{-3}\ \text{cm}^3 \times 1.08\ \text{g/cm}^3 = 1.620 \times 10^{-3}\ \text{g} = 1620.00\ \mu\text{g}$$

3. **Layer 3 — Bottom VUV-SiO_2 Optical Cladding ($t_{\text{clad,bot}} = 1.50\ \mu\text{m}$, $\rho_{\text{SiO}_2} = 2.20\ \text{g/cm}^3$):**

$$V_{\text{clad,bot}} = 0.75\ \text{cm}^2 \times 1.50 \times 10^{-4}\ \text{cm} = 1.125 \times 10^{-4}\ \text{cm}^3 = 0.11250\ \text{mm}^3$$

$$m_{\text{clad,bot,net}} = 1.125 \times 10^{-4}\ \text{cm}^3 \times 2.20\ \text{g/cm}^3 = 2.475 \times 10^{-4}\ \text{g} = 247.50\ \mu\text{g}$$

4. **Layer 4 — Imprinted a-Si:H Waveguide Cores (3000 Ribs + Imprint Slab, $t_{\text{eff}} = 0.050\ \mu\text{m}$, $\rho_{\text{a-Si:H}} = 2.25\ \text{g/cm}^3$):**

   The 3000 waveguide cores ($w = 450\ \text{nm}$, $h = 220\ \text{nm}$, $L = 0.50\ \text{cm}$) occupy a rib volume of $V_{\text{ribs}} = 3000 \times (4.5 \times 10^{-5}\ \text{cm}) \times (2.2 \times 10^{-5}\ \text{cm}) \times 0.50\ \text{cm} = 1.485 \times 10^{-6}\ \text{cm}^3$, plus the residual nanoimprint stabilization slab outside the etched routing zones ($V_{\text{slab}} = 2.265 \times 10^{-6}\ \text{cm}^3$):

$$V_{\text{a-Si:H,net}} = V_{\text{ribs}} + V_{\text{slab}} = 3.75 \times 10^{-6}\ \text{cm}^3 = 0.00375\ \text{mm}^3$$

$$m_{\text{a-Si:H,net}} = 3.75 \times 10^{-6}\ \text{cm}^3 \times 2.25\ \text{g/cm}^3 = 8.4375 \times 10^{-6}\ \text{g} \approx 8.44\ \mu\text{g}$$

5. **Layer 5 — Top VUV-SiO_2 Passivation Cladding ($t_{\text{clad,top}} = 1.28\ \mu\text{m}$ average, $\rho_{\text{SiO}_2} = 2.20\ \text{g/cm}^3$):**

$$V_{\text{clad,top}} = 0.75\ \text{cm}^2 \times 1.28 \times 10^{-4}\ \text{cm} = 0.960 \times 10^{-4}\ \text{cm}^3 = 0.09600\ \text{mm}^3$$

$$m_{\text{clad,top,net}} = 0.960 \times 10^{-4}\ \text{cm}^3 \times 2.20\ \text{g/cm}^3 = 2.112 \times 10^{-4}\ \text{g} = 211.20\ \mu\text{g}$$

6. **Layer 6 — Dual Index-Matched Silicone Socket Pads ($2 \times 0.15\ \text{mm} \times 15.0\ \text{mm}$, $t_{\text{pad}} = 2.00\ \mu\text{m}$, $\rho_{\text{pad}} = 1.12\ \text{g/cm}^3$):**

   Total pad area $A_{\text{pads}} = 2 \times 0.015\ \text{cm} \times 1.50\ \text{cm} = 0.045\ \text{cm}^2$:

$$V_{\text{pads}} = 0.045\ \text{cm}^2 \times 2.00 \times 10^{-4}\ \text{cm} = 9.00 \times 10^{-6}\ \text{cm}^3 = 0.00900\ \text{mm}^3$$

$$m_{\text{pads,net}} = 9.00 \times 10^{-6}\ \text{cm}^3 \times 1.12\ \text{g/cm}^3 = 1.008 \times 10^{-5}\ \text{g} = 10.08\ \mu\text{g}$$

1.2 Weight & Volume Table (Single $15\ \text{mm} \times 5\ \text{mm}$ Bridge)

Structural Layer	Cured Material	Thickness	Net Volume	Net Dry Mass
1. Base Planarizer	Crosslinked DVS-BCB	$2.00\ \mu\text{m}$	$0.15000\ \text{mm}^3$	$157.50\ \mu\text{g}$
2. Shear Buffer	PDMS-PDPS Elastomer	$20.00\ \mu\text{m}$	$1.50000\ \text{mm}^3$	$1620.00\ \mu\text{g}$
3. Bottom Cladding	VUV-Derived SiO_2	$1.50\ \mu\text{m}$	$0.11250\ \text{mm}^3$	$247.50\ \mu\text{g}$
4. Waveguide Cores	Passivated a-Si:H	$0.22\ \mu\text{m}$	$0.00375\ \text{mm}^3$	$8.44\ \mu\text{g}$
5. Top Cladding	VUV-Derived SiO_2	$1.28\ \mu\text{m}$	$0.09600\ \text{mm}^3$	$211.20\ \mu\text{g}$
6. Socket Interface	Phenyl-Methyl Silicone	$2.00\ \mu\text{m}$	$0.00900\ \text{mm}^3$	$10.08\ \mu\text{g}$
Total Bridge Stack	**Complete 6-Layer Inlay**	$27.00\ \mu\text{m}$	$1.87125\ \text{mm}^3$	$2254.72\ \mu\text{g}$

Explanation of Structural Weight: A complete $15.0\ \text{mm}$ wide optical inlay bridge capable of transporting $192.0\ \text{TB/s}$ bidirectionally adds a total dry weight of only $2.255\ \text{mg}$ ($2.255\ \text{g}$ per $1,000$ bridges). Out of this total mass, 71.8% ($1620.00\ \mu\text{g}$) consists of the $20\ \mu\text{m}$ compliant elastomer buffer, while the active optical $\text{SiO}_2/\text{a-Si:H}/\text{SiO}_2$ waveguide stack weighs just $467.14\ \mu\text{g}$.

---

2. Exact Chemical Mixing Ratios & Stoichiometric Formulations

To achieve reproducible slot-die/inkjet rheology, zero crack formation during VUV curing, and the exact target mechanical and optical constants ($G_{\text{buf}} = 50\ \text{MPa}$, $n_{\text{core}} = 3.48$, $n_{\text{clad}} = 1.444$, $n_{\text{pad}} = 1.500$), the seven process formulations must be prepared according to the following exact mixing ratios.

2.1 Formulation 1: Liquid Silicon Core Ink (Si_5H_{10} in Anhydrous Cyclooctane)

Pure liquid cyclopentasilane (Si_5H_{10}, $\rho_{\text{CPS}} = 0.963\ \text{g/cm}^3$, $M_{\text{CPS}} = 150.505\ \text{g/mol}$) has a low surface tension and oxidizes spontaneously in air. To achieve a slot-die dynamic viscosity of $\eta = 8.0\ \text{mPa} \cdot \text{s}$ and uniform $280\ \text{nm}$ wet-film leveling, it is diluted in anhydrous, deoxygenated cyclooctane (C_8H_{16}, $\rho_{\text{CO}} = 0.834\ \text{g/cm}^3$, $M_{\text{CO}} = 112.216\ \text{g/mol}$).

- **Target Volume Ratio:** $35.0\ \text{vol\%}\ \text{Si}_5\text{H}_{10} : 65.0\ \text{vol\%}\ \text{C}_8\text{H}_{16}$
- **Derivation of Exact Weight Ratio ($\text{wt\%}$):**
  For a $100.0\ \text{cm}^3$ batch of ink:

$$m_{\text{CPS}} = 35.0\ \text{cm}^3 \times 0.963\ \text{g/cm}^3 = 33.705\ \text{g}$$

$$m_{\text{CO}} = 65.0\ \text{cm}^3 \times 0.834\ \text{g/cm}^3 = 54.210\ \text{g}$$

$$m_{\text{ink,total}} = 33.705\ \text{g} + 54.210\ \text{g} = 87.915\ \text{g} \implies \rho_{\text{ink}} = 0.87915\ \text{g/cm}^3$$

$$w_{\text{CPS}} = \frac{33.705\ \text{g}}{87.915\ \text{g}} = 0.38338 \quad (38.34\ \text{wt\%}\ \text{Si}_5\text{H}_{10})$$

$$w_{\text{CO}} = \frac{54.210\ \text{g}}{87.915\ \text{g}} = 0.61662 \quad (61.66\ \text{wt\%}\ \text{C}_8\text{H}_{16})$$

- **Molar Ratio:** $n_{\text{CPS}} = \frac{33.705}{150.505} = 0.22395\ \text{mol}$ to $n_{\text{CO}} = \frac{54.210}{112.216} = 0.48309\ \text{mol}$, giving a molar ratio of $1.000\ \text{mol}\ \text{Si}_5\text{H}_{10} : 2.157\ \text{mol}\ \text{C}_8\text{H}_{16}$ (Mass ratio $1.000 : 1.608$).

2.2 Formulation 2: VUV-Silica Cladding Ink (PHPS in Anhydrous Di-n-butyl Ether)

Perhydropolysilazane (-[SiH_2-NH]-$_n$, $\rho_{\text{PHPS}} = 1.30\ \text{g/cm}^3$, $M_{\text{monomer}} = 45.116\ \text{g/mol}$) is dissolved in anhydrous di-n-butyl ether ($C_8H_{18}O$, $\rho_{\text{DBE}} = 0.764\ \text{g/cm}^3$, $M_{\text{DBE}} = 130.231\ \text{g/mol}$).

- **Target Weight Ratio:** $20.00\ \text{wt\%}$ PHPS polymer : $80.00\ \text{wt\%}$ Di-n-butyl Ether (Mass ratio $1.00 : 4.00$).
- **Derivation of Volume Ratio and Wet Ink Requirement:**
  For $100.0\ \text{g}$ of cladding ink ($20.0\ \text{g}$ PHPS + $80.0\ \text{g}$ DBE):

$$V_{\text{ink}} = \frac{20.0\ \text{g}}{1.30\ \text{g/cm}^3} + \frac{80.0\ \text{g}}{0.764\ \text{g/cm}^3} = 15.385\ \text{cm}^3 + 104.712\ \text{cm}^3 = 120.097\ \text{cm}^3 \implies \rho_{\text{ink}} = 0.8327\ \text{g/cm}^3$$

This corresponds to $12.81\ \text{vol\%}$ **PHPS :** $87.19\ \text{vol\%}$ **Di-n-butyl Ether**.
Since $1.000\ \text{g}$ of dry PHPS yields $1.3318\ \text{g}$ of dense SiO_2, each $1.000\ \text{g}$ of cured SiO_2 cladding requires $\frac{1.000\ \text{g}}{1.3318}$ $= 0.7509\ \text{g}$ of dry PHPS, or $\frac{0.7509\ \text{g}}{0.20} = 3.754\ \text{g}$ of $20\ \text{wt\%}$ PHPS ink.

2.3 Formulation 3: Elastomer Shear-Buffer ($G_{\text{buf}} = 50\ \text{MPa}$ PDMS-PDPS System)

Standard polydimethylsiloxane (PDMS) has a shear modulus of only 0.3–$1.0\ \text{MPa}$, which would allow excessive vertical deflection during wire/die bonding. To raise the shear modulus to exactly $G_{\text{buf}} = 50\ \text{MPa}$ while preserving thermal stability up to $250\ ^\circ\text{C}$, diphenylsiloxane units and surface-treated fumed nanosilica are incorporated into a solventless 3-part addition-cure formulation:

- **Component A (Base Polymer, $75.00\ \text{wt\%}$):** Vinyl-terminated polydimethylsiloxane-co-diphenylsiloxane copolymer containing $35.0\ \text{mol\%}$ diphenylsiloxane units ($M_w \approx 28,000\ \text{g/mol}$, vinyl content $0.18\ \text{mmol/g}$).
- **Component B (Reinforcing Filler & Crosslinker Blend, $24.90\ \text{wt\%}$):** $18.40\ \text{wt\%}$ hexamethyldisilazane-treated fumed silica nanoparticles ($d_{50} = 12\ \text{nm}$, index-matched to prevent scattering) pre-dispersed with $6.50\ \text{wt\%}$ trimethylsilyl-terminated polymethylhydrosiloxane-co-dimethylsiloxane crosslinker (Si-H content $2.40\ \text{mmol/g}$).
- **Component C (Hydrosilylation Catalyst, $0.10\ \text{wt\%}$):** Karstedt's platinum(0)-divinyltetramethyldisiloxane complex diluted in cyclic methylvinylsiloxanes ($1.5\ \text{wt\%}$ Pt solution, yielding $15\ \text{ppm}$ elemental Pt in the total formulation).
- **Stoichiometric Hydride-to-Vinyl Ratio ($r_{\text{H/V}}$):**

$$r_{\text{H/V}} = \frac{m_B \cdot c_{\text{Si-H}}}{m_A \cdot c_{\text{Vinyl}}} = \frac{0.0650\ \text{g} \times 2.40\ \text{mmol/g}}{0.7500\ \text{g} \times 0.18\ \text{mmol/g}} = \frac{0.1560\ \text{mmol}}{0.1350\ \text{mmol}} = 1.156 \quad (\text{Ratio } 1.16 : 1.00)$$

- **Practical Two-Kit Mixing Ratio:** When Component B and Component C are pre-blended as Curing Agent Kit B*, the mixing ratio is exactly* **$3.00\ \text{parts}$ *Base A :* $1.00\ \text{part}$ *Curing Agent B* by weight** ($75.0\ \text{wt\%} : 25.0\ \text{wt\%}$).

2.4 Formulation 4: Reversible Optical Socket Pad ($n_{\text{pad}} = 1.500$, Shore OO 35)

To match the refractive index of the SiO_2 cladding ($n = 1.444$) and expand the nanotaper mode while remaining soft enough to wet the chip interface reversibly under gentle mechanical seating pressure:

- **Part A (Base, $90.91\ \text{wt\%}$):** Vinyl-terminated polyphenylmethylsiloxane ($22.0\ \text{mol\%}$ phenyl groups, tuning refractive index to $n = 1.500$ at $\lambda = 1550\ \text{nm}$) containing $10\ \text{ppm}$ Pt catalyst.
- **Part B (Crosslinker, $9.09\ \text{wt\%}$):** Hydride-terminated polyphenylmethylsiloxane crosslinker formulated at a slightly sub-stoichiometric hydride-to-vinyl molar ratio of $r_{\text{H/V}} = 0.95 : 1.00$ to produce a compliant, tack-free Shore OO 35 elastomer gel.
- **Weight Mixing Ratio:** $10.00 : 1.00$ **(Part A : Part B by weight)**.

2.5 Formulation 5: Cavity Planarizer Ink (DVS-BCB in Mesitylene)

- **Weight Mixing Ratio:** $40.00\ \text{wt}\%$ B-staged Divinylsiloxane-bis-benzocyclobutene (DVS-BCB) oligomer : $60.00\ \text{wt}\%$ high-purity Mesitylene ($1,3,5$-trimethylbenzene, $\rho = 0.864\ \text{g/cm}^3$), equivalent to a $1.00 : 1.50$ **mass ratio**.

2.6 Formulation 6 & 7: Process & Reaction Gas Mixtures

- **Photonic Curing Forming Gas:** $90.00\ \text{vol}\%\ \text{N}_2 + 10.00\ \text{vol}\%\ \text{H}_2$ (molar ratio $9.00 : 1.00$). By molecular weight ($M_{\text{N}_2} = 28.014\ \text{g/mol}$, $M_{\text{H}_2} = 2.016\ \text{g/mol}$), the mass ratio is $99.21\ \text{wt}\%\ \text{N}_2 : 0.79\ \text{wt}\%\ \text{H}_2$.
- **VUV Photo-Oxidation Atmosphere:** $97.00\ \text{vol}\%\ \text{O}_2 + 3.00\ \text{vol}\%\ \text{H}_2\text{O}$ **vapor** at $140\ ^\circ\text{C}$ ($M_{\text{O}_2} = 31.998\ \text{g/mol}$, $M_{\text{H}_2\text{O}} = 18.015\ \text{g/mol}$), corresponding to $98.29\ \text{wt}\%\ \text{O}_2 : 1.71\ \text{wt}\%\ \text{H}_2\text{O}$.

2.7 Summary Table of Mixing Ratios

Formulation Name	Primary Active	Co-Reactant / Solvent	Weight Ratio (wt%)	Volume or Molar Ratio
1. Core Ink	Si_5H_{10}	Anhydrous Cyclooctane	$38.34\% : 61.66\%$	$35.0\% : 65.0\%\ \text{vol}$
2. Cladding Ink	PHPS Polymer	Di-n-butyl Ether	$20.00\% : 80.00\%$	$12.8\% : 87.2\%\ \text{vol}$
3. Shear Buffer	PDMS-PDPS Base	Silica/Crosslinker + Pt	$75.00\% : 25.00\%$	$1.16 : 1.00\ \text{Si-H/Vinyl}$
4. Socket Pad	Phenyl-Vinyl Base	Hydride Crosslinker	$90.91\% : 9.09\%$	$0.95 : 1.00\ \text{Si-H/Vinyl}$
5. Planarizer Ink	DVS-BCB Resin	Mesitylene Solvent	$40.00\% : 60.00\%$	$1.00 : 1.50\ \text{mass}$
6. Forming Gas	Nitrogen (N_2)	Hydrogen (H_2)	$99.21\% : 0.79\%$	$90.0\% : 10.0\%\ \text{mol}$
7. VUV Gas	Oxygen (O_2)	Water Vapor (H_2O)	$98.29\% : 1.71\%$	$97.0\% : 3.0\%\ \text{mol}$

---

3. Bill of Materials & Gross Quantity Table (Per 1,000-Bridge Batch)

In industrial slot-die and inkjet production, dispensing heads require line priming and a 25% overfill allowance ($\eta_{\text{disp}} = 1.25$). Furthermore, for the a-Si:H waveguide layer, a continuous $280\ \text{nm}$ wet Si_5H_{10} film is printed across the full $0.75\ \text{cm}^2$ cavity ($m_{\text{CPS,film}} = 20.22\ \mu\text{g}$ per bridge before UV-NIL and decalin rinse, or $20.22\ \mu\text{g} \times 1.25 = 25.28\ \mu\text{g}$ gross per bridge).

Material / Chemical	Chemical Formula / Spec	Gross Mass (1 Bridge)	Gross Mass (1,000 Bridges)	Batch Volume (1,000 Bridges)
Cyclopentasilane	Si_5H_{10} (99.999% Pure)	$25.28\ \mu\text{g}$	$25.28\ \text{mg}$	$0.0263\ \text{mL}$
Cyclooctane Solvent	C_8H_{16} (Anhydrous)	$40.65\ \mu\text{g}$	$40.65\ \text{mg}$	$0.0487\ \text{mL}$
PHPS Polymer	$\text{-[SiH}_2\text{-NH]-}_n$ (99.99%)	$430.53\ \mu\text{g}$	$430.53\ \text{mg}$	$0.3312\ \text{mL}$
Di-n-butyl Ether	$\text{C}_8\text{H}_{18}\text{O}$ (Anhydrous)	$1722.12\ \mu\text{g}$	$1722.12\ \text{mg}$	$2.2541\ \text{mL}$
PDMS-PDPS Buffer Kit	$3:1$ Base + Crosslinker/SiO_2	$2025.00\ \mu\text{g}$	$2025.00\ \text{mg}$	$1.8750\ \text{mL}$
DVS-BCB Resin	$40\ \text{wt}\%$ Solid fraction	$196.88\ \mu\text{g}$	$196.88\ \text{mg}$	$0.1875\ \text{mL}$
Mesitylene Solvent	C_9H_{12} ($60\ \text{wt}\%$ fraction)	$295.31\ \mu\text{g}$	$295.31\ \text{mg}$	$0.3418\ \text{mL}$
Socket Pad Silicone	Phenyl-Methyl ($10:1$ Kit)	$12.60\ \mu\text{g}$	$12.60\ \text{mg}$	$0.0113\ \text{mL}$
Anhydrous Decalin	$\text{C}_{10}\text{H}_{18}$ (S-Bend Developer)	$15.00\ \text{mg}$	$15.00\ \text{g}$	$16.74\ \text{mL}$
Buffered Oxide Etch	$6:1\ \text{NH}_4\text{F/HF}$ Window Etch	$10.00\ \text{mg}$	$10.00\ \text{g}$	$8.85\ \text{mL}$
Process Gases (6N)	$\text{N}_2/\text{H}_2,\ \text{O}_2/\text{H}_2\text{O},\ \text{CF}_4$	$120.00\ \text{mg}$	$120.00\ \text{g}$	$96.50\ \text{L (STP)}$
Total Gross Inputs	**All Dispensed + Process Media**	$149.75\ \text{mg}$	$149.75\ \text{g}$	—

Explanation of Material Quantities: The combined gross mass of all functional inks dispensed across **1,000 full-flank bridges** (Items 1–8) is just $4.748\ \text{g}$ ($4748.37\ \text{mg}$, or $\sim 5.08\ \text{mL}$ of liquid precursors). Even highly expensive electronic-grade Cyclopentasilane (Si_5H_{10}) requires only $25.28\ \text{mg}$ to manufacture $1,000$ bridges, because the core layer is only $220\ \text{nm}$ thin.

---

4. Complete Cost Breakdown in USD ($) with Total Sum

The economic calculation below is divided into:

- **Part A:** Direct Chemical, Precursor, and Consumable Material Costs.
- **Part B:** Cleanroom Fabrication, Lithography, Laser Micromachining, and Tooling Amortization Costs.
- **Part C:** Optional On-Die Electro-Optic Transceiver & Comb-Laser Overhead (for an end-to-end active comparison against monolithic interposers and pluggable optics).

4.1 Direct Material & Fab Manufacturing Cost Table (Passive Inlay Bridge)

Cost Category / Item	Unit Price Basis	Batch Cost (1,000 Bridges)	Unit Cost (15 mm Bridge)	Unit Cost (1.6 mm Bridge)
1. Si_5H_{10} Core Ink ($65.93\ mg$)	$\$180.00 / g$ Si_5H_{10} + Ampoule	$\$12.50$	$\$0.0125$	$\$0.0013$
2. PHPS Cladding Ink ($2.153\ g$)	$\$24.00 / g$ PHPS Solution	$\$15.50$	$\$0.0155$	$\$0.0017$
3. PDMS-PDPS Shear Buffer ($2.025\ g$)	$\$8.00 / g$ Optical Kit	$\$16.20$	$\$0.0162$	$\$0.0017$
4. DVS-BCB Planarizer ($0.492\ g$)	$\$15.00 / g$ Solution	$\$7.38$	$\$0.0074$	$\$0.0008$
5. Optical Socket Pads ($12.60\ mg$)	$\$45.00 / g$ + Micro-Liner	$\$4.50$	$\$0.0045$	$\$0.0005$
6. Solvents, BOE & 6N Gases	Decalin, BOE, N_2/H_2, O_2	$\$68.92$	$\$0.0689$	$\$0.0140$
Subtotal A: Raw Materials	**All Chemicals & Gases**	$\$125.00$	$\$0.1250$	$\$0.0200$
7. UV Picosecond Cavity Milling	Laser Ablation + Plasma	$\$420.00$	$\$0.4200$	$\$0.1100$
8. Slot-Die & VUV Cladding Cure	3 Coating + 2 VUV Runs	$\$650.00$	$\$0.6500$	$\$0.1800$
9. Adaptive UV-NIL & Direct-Write	Stamp Amortization + $405\ nm$	$\$1,180.00$	$\$1.1800$	$\$0.3100$
10. Xenon Flash Photonic Curing	$80\ \mu s$ Forming-Gas Anneal	$\$310.00$	$\$0.3100$	$\$0.0900$
11. Window Etch, Pad Mate & QC	BOE Thinning + Optical Test	$\$465.00$	$\$0.4650$	$\$0.1300$
Subtotal B: Fab Processing	**All Cleanroom Steps**	$\$3,025.00$	$\$3.0250$	$\$0.8200$
TOTAL SUM (Passive Bridge)	**Complete Inlay Bridge**	$\$3,150.00$	$\$3.1500$	$\$0.8400$

Explanation of Cost Calculation:

- **Raw Material Cost per Bridge:** Even for the largest $15.0\ mm$ full-flank bridge (3000 waveguides), the total chemical and gas consumption costs only $\$0.125$ **(**$12.5\ cents$**)** per bridge ($\$125.00$ per $1,000$ bridges).
- **Fabrication & Lithography Cost per Bridge:** Cleanroom processing—dominated by the high-precision adaptive UV-Nanoimprint step and maskless $405\ nm$ laser direct-writing of the S-bend compensation zones ($\$1.18$ per bridge)—totals $\$3.025$ per $15.0\ mm$ bridge.
- **Total All-In Passive Bridge Sum:** A finished, tested $15.0\ mm$ optical inlay bridge with integrated elastomer shear buffer and reversible optical socket pads costs $\$3.15$ **per unit** ($\$3,150.00$ **per** $1,000$ **units**). For the compact $1.6\ mm$ bridge ($20.48\ TB/s$, exceeding an entire HBM stack), the unit cost drops to $\$0.84$ **per bridge** ($\$840.00$ **per** $1,000$ **units**).

4.2 System-Level Economic Comparison (Active + Passive Link Total Cost for $192\ \mathrm{TB/s}$)

To evaluate the complete system cost of transporting $192.0\ \mathrm{TB/s}$ bidirectionally between two TPU-9 class dies (including the silicon photonics E/O modulator array, Ge-on-Si photodiode array, and shared external CW comb-laser sources at die edges), the table below compares the printed $\mathrm{a\text{-}Si{:}H}$ inlay bridge against conventional packaging technologies:

Interconnect Technology	**Hardware Required for** $192\ \mathrm{TB/s}$	**Power Consumption**	**Total Cost per Link (USD)**	**Cost per** $\mathrm{TB/s}$ **(USD)**
1. Printed $\mathrm{a\text{-}Si{:}H}$ **Inlay (Passive)**	$1\times\ 15\ \mathrm{mm}$ Printed Bridge	$0\ \mathrm{W}$ (Passive Waveguide)	$\$3.15$	$\$0.016\ /\ \mathrm{TB/s}$
2. Printed $\mathrm{a\text{-}Si{:}H}$ **Inlay (Complete)**	Bridge ($\$3.15$) + Die E/O & Comb Laser ($\$28.50$)	$354.0\ \mathrm{W}$ ($0.461\ \mathrm{pJ/bit}$)	$\$31.65$	$\$0.165\ /\ \mathrm{TB/s}$
3. Monolithic Si Interposer (CoWoS)	Full-Reticle Crystalline Si Wafer Slab	$\sim 1,850\ \mathrm{W}$ ($\sim 2.4\ \mathrm{pJ/bit}$)	$\$420.00$	$\$2.188\ /\ \mathrm{TB/s}$
4. Copper Board Traces + Retimers	$6,850$ Diff. Pairs + Active Retimers	$\sim 4,900\ \mathrm{W}$ ($\sim 6.4\ \mathrm{pJ/bit}$)	$\$1,680.00$	$\$8.750\ /\ \mathrm{TB/s}$
5. Pluggable $1.6\mathrm{T}$ **OSFP Optics**	$960\times$ Front-Panel Transceivers	$\sim 10,750\ \mathrm{W}$ ($\sim 14.0\ \mathrm{pJ/bit}$)	$\$1,152,000.00$	$\$6,000.00\ /\ \mathrm{TB/s}$

Summary of Economic Impact: By replacing a $\$420.00$ monolithic silicon interposer slab with a $\$3.15$ localized printed $\mathrm{a\text{-}Si{:}H}$ waveguide inlay ($\$31.65$ including active on-die electro-optics and comb-laser share), packaging interconnect cost drops by 92.5%, while eliminating reticle size limits and cutting interconnect power consumption by more than 80%.