OSSM

Stand Build Guide

1-Arm PitClamp stand · Version 1.1.0

RESEARCH + DESIRE



Support
support@researchanddesire.com


Assembly instructions
ohai.researchanddesire.com/ossm

Actual size


50 mm

Print at 100 % (actual size). Lay a part on its dashed outline to identify it.


Bolts




M6×12 Screw




M5×20 Screw



M6×16 Screw



M4×25 Screw



M6×25 Screw

Nuts and washers




M5 Nut



M4 Nut



M6 Washer



M6 T-nut

Hex keys



5 mm Hex key




4 mm Hex key




3 mm Hex key

Parts


Aluminium extrusion (3030)



1×
Body




1×
Arm




2×
Leg


3D printed




1×
Pivot plate




1×
Lower clamp base



1×
Upper clamp base




1×
Clamp ring




2×
Clasp with handle



2×
Link (bolt side)



2×
Link (nut side)




4×
Foot



6×
End cap

Other




4×
Corner bracket




4×
Grip pad

Parts


Bolts




12×
M6×12 Screw




5×
M6×16 Screw



4×
M6×25 Screw



2×
M5×20 Screw



4×
M4×25 Screw

Nuts




2×
M5 Nut



4×
M4 Nut

T-nuts



23×
M6 T-nut

Washers



10×
M6 Washer

Tools

Required



3 mm Hex key



4 mm Hex key




5 mm Hex key


Recommended



Rubber mallet




Tape measure



Threadlocker
(blue 243)

Optional




Super glue


Legend


In a step's parts box, this drop beside a screw's quantity means:
put threadlocker (blue 243) on the screw's thread before it goes in.

1 The base




1







2×
Leg


4×
M6 T-nut








2




4× Foot




4× M6×12 Screw




5 mm Hex key




3



4×
Grip pad





Super glue



Optional: super glue under each pad, in this pattern.


4







1×
Body

8×
M6 T-nut






5




4× Corner bracket

4× M6×12 Screw

4× M6 Washer




6




4×

M6 T-nut





7



4× M6×12 Screw

4× M6 Washer






Leave these screws loose until the next step.


8




5 mm Hex key



Tape measure



9





4×

End cap





Rubber mallet






10







11



1×
Pivot plate




2×
M6×16 Screw




2×
M6 Washer




5 mm Hex key




Tape measure






2 The arm and its clamp




12




1× Link (nut side)

2× M4 Nut




13




1×

Clasp with handle



1×

Link (bolt side)




1×


M4×25 Screw



3 mm Hex key



14





1×

M4×25 Screw




3 mm Hex key







15




1× Lower clamp base

1× M5 Nut






16




1×
M5×20 Screw




4 mm Hex key





17




Tape measure








18




2×
M6×25 Screw




5 mm Hex key




19




1×
Arm




3×
M6 T-nut



Tape measure




20




1×


End cap



21




1×
Clamp ring




2×
M6×25 Screw




5 mm Hex key




22




23




24





25





1×


M6×16 Screw




5 mm Hex key








3 The PitClamp Mini




26




1× Link (nut side)

2× M4 Nut




27




1×

Clasp with handle



1×

Link (bolt side)




1×


M4×25 Screw



3 mm Hex key



28





1×

M4×25 Screw




3 mm Hex key







29




1× Upper clamp base

1× M5 Nut





30





1×

M5×20 Screw




4 mm Hex key







31




2×
M6 T-nut




Tape measure




32




2×
M6 T-nut



Tape measure




33




1×

End cap




34




2× M6×16 Screw



5 mm Hex key







You may now proceed to installing the actuator.

RESEARCH + DESIRE

OSSM Stand Build Guide

1-Arm PitClamp stand · Version 1.1.0

Support
support@researchanddesire.com

Assembly instructions
ohai.researchanddesire.com/ossm