FieldService Pro Internal Dev Guide

Local development addresses, test credentials, and quick reference. INTERNAL ONLY DO NOT SHARE

CONTENTS

1. Local Development URLs
2. Test Credentials
3. Environment Variables
4. Docker Quick Reference
5. Database Access
6. API Keys & Services
7. Seed Data Summary
8. Useful Commands
9. Architecture Overview

Local Development URLs

Application

ADMIN DASHBOARD (BACK)
`http://localhost:3200`
Next.js 16 — apps/back/

PUBLIC / PORTAL (FRONT)
`http://localhost:3201`
Next.js 16 — apps/front/

CUSTOMER PORTAL LOGIN
`http://localhost:3201/portal/login`
Customer-facing portal

TENANT WEBSITE
`http://localhost:3201`
Public homepage for tenant

Supabase

SUPABASE STUDIO
`http://localhost:54333`
Database GUI, Auth admin, Storage

SUPABASE API
`http://localhost:54331`
REST + Realtime + Auth

INBUCKET (EMAIL TESTING)
`http://localhost:54334`
Catches all auth emails locally

ANALYTICS
`http://localhost:54337`
Supabase Analytics

Database Direct

POSTGRESQL

`localhost:54332`

User: postgres / Pass: postgres / DB: postgres

SHADOW DB (MIGRATIONS)

`localhost:54330`

Used by Drizzle for migration diffs

Test Credentials

Warning: These credentials are for local development only. Never use these in production or share outside the team.

Admin Dashboard Login

Admin User (full access)

Email	`admin@test.com`
Password	`password123`
Role	`admin`
URL	`http://localhost:3200/login`

Other Test Users

All users share the password: `password123`

EMAIL	ROLE	NAME	RATE
`admin@test.com`	Admin	Admin User	—
`jenny.clark@test.com`	Office Manager	Jenny Clark	—
`dave.dispatcher@test.com`	Dispatcher	Dave Dispatcher	—
`mike.johnson@test.com`	Technician	Mike Johnson	$85/hr
`sarah.williams@test.com`	Technician	Sarah Williams	$90/hr
`carlos.rodriguez@test.com`	Technician	Carlos Rodriguez	$80/hr

Test Tenant

Comfort Pro HVAC

Name	`Comfort Pro HVAC`
Slug	`comfort-pro`

Email	info@comfortprohvac.com

Sample Customers (Portal Invites)

These customers exist in the seed data. Invite them via the admin dashboard to test the customer portal.

NAME	EMAIL	TYPE
Robert Anderson	r.anderson@email.com	Residential
Patricia Martinez	p.martinez@email.com	Residential
James Taylor	j.taylor@email.com	Residential
Michael Brown	m.brown@email.com	Residential
Linda Thomas	l.thomas@email.com	Residential
William Garcia	w.garcia@email.com	Residential
Elizabeth Davis	e.davis@email.com	Residential
Barbara Wilson	b.wilson@email.com	Residential
Tom Reynolds	t.reynolds@email.com	Commercial
Susan Chen	s.chen@email.com	Commercial
Frank Mitchell	f.mitchell@email.com	Commercial
Karen Lopez	k.lopez@email.com	Commercial

> **Note:** No pre-created portal passwords exist. Invite a customer from the admin dashboard and check Inbucket (localhost:54334) for the invite email.

Environment Variables

apps/back/.env.local & apps/front/.env.local

```
# Supabase
NEXT_PUBLIC_SUPABASE_URL=http://localhost:54331
NEXT_PUBLIC_SUPABASE_ANON_KEY=sb_publishable_ACJWlzQHlZjBrEguHvfOxg_3BJgxAaH
SUPABASE_SERVICE_ROLE_KEY=sb_secret_N7UND0UgjKTVK-Uodkm0Hg_xSvEMPvz

# Database
DATABASE_URL=postgresql://postgres:postgres@localhost:54332/postgres
```

```
# App URL
NEXT_PUBLIC_APP_URL=http://localhost:3200

# Stripe (replace with real test keys from dashboard.stripe.com)
STRIPE_SECRET_KEY=sk_test_placeholder
STRIPE_WEBHOOK_SECRET=whsec_placeholder
NEXT_PUBLIC_STRIPE_PUBLISHABLE_KEY=pk_test_placeholder

# Email (replace with real key from resend.com)
RESEND_API_KEY=re_placeholder
```

Docker Overrides (.env.docker)

```
# Docker uses host.docker.internal instead of localhost
DATABASE_URL=postgresql://postgres:postgres@host.docker.internal:54332/postgres
NEXT_PUBLIC_BACK_URL=http://host.docker.internal:3200
```

Docker Quick Reference

> **Important:** Node modules are NOT installed on the host. All dev commands (`pnpm dev` , `pnpm typecheck` , etc.) must run inside the Docker container.

```
# Start the container (auto-runs pnpm dev via entrypoint)
docker compose -f /Users/john/WEB/SERVICE/docker-compose.yml up -d

# Check logs
docker logs service-app --tail 20

# Exec into container
docker exec -it service-app zsh

# Restart (fixes EADDRINUSE port conflicts)
docker restart service-app

# Stop
docker compose -f /Users/john/WEB/SERVICE/docker-compose.yml down

# Run Claude Code inside container (sandboxed yolo mode)
claude --dangerously-skip-permissions
```

PROPERTY	VALUE
Container name	`service-app`
Ports exposed	`3200` (back), `3201` (front)

PROPERTY	VALUE
Workdir	`/workspace`
Entrypoint command	`pnpm dev` (Turbo runs both apps)
Node modules	Named Docker volumes (not on host)

Database Access

PostgreSQL (Supabase Local)

Host	`localhost`
Port	`54332`
User	`postgres`
Password	`postgres`
Database	`postgres`
Schema	`fieldservice`
Connection	`postgresql://postgres:postgres@localhost:54332/postgres`

Database Commands (run inside container)

```
# Generate Drizzle migrations
pnpm db:generate

# Push schema to DB (used for dev sync)
pnpm db:push

# Open Drizzle Studio
pnpm db:studio

# Seed database with test data
pnpm db:seed

# Run migrations
pnpm db:migrate
```

Schema Modules (34 tables)

Schema files in `packages/shared/src/db/schema/` :

MODULE	KEY TABLES
tenants	tenants, tenant_settings, tenant_sequences

MODULE	KEY TABLES
users	users
customers	customers, properties, equipment
jobs	jobs, job_line_items, job_photos, job_checklists, timesheets
estimates	estimates, estimate_options, estimate_option_line_items
invoices	invoices, invoice_line_items, payments
pricebook	pricebook_items, pricebook_categories
communications	communication_logs, email_templates
agreements	agreements, agreement_services, agreement_visits
portal	portal_invites
website	website_settings, website_pages, website_services, bookings
system	system config and metadata

API Keys & Services

SERVICE	KEY TYPE	LOCAL VALUE	STATUS
Supabase Anon	Public	`sb_publishable_ACJWlzQHlZjBrEguHvfOxg_3BJgxAaH`	Live (local)
Supabase Service	Secret	`sb_secret_N7UND0UgjKTVK-Uodkm0Hg_xSvEMPvz`	Live (local)
Stripe Secret	Test	`sk_test_placeholder`	Placeholder
Stripe Publishable	Test	`pk_test_placeholder`	Placeholder
Stripe Webhook	Test	`whsec_placeholder`	Placeholder
Resend	API Key	`re_placeholder`	Placeholder

Placeholders: Replace Stripe and Resend keys with real test keys from their dashboards. Supabase keys are real and work with the local Supabase instance.

Seed Data Summary

Run `pnpm db:seed` from inside the container to populate the database.

ENTITY	COUNT	NOTES
Tenant	1	Comfort Pro HVAC
Users	6	1 admin, 1 office mgr, 1 dispatcher, 3 technicians
Customers	12	8 residential, 4 commercial
Properties	14	Springfield, IL addresses
Equipment	10	HVAC units, refrigeration, with serial numbers
Jobs	11	3 completed, 1 in-progress, 2 dispatched, 2 scheduled, 3 new
Estimates	3	1 sent, 1 approved, 1 draft (multi-option)
Invoices	2	1 paid, 1 sent
Sequences	3	JOB, EST, INV prefixes initialized

Useful Commands

Development (inside container)

```
pnpm dev                    # Start all apps (Turbo)
pnpm dev --filter back      # Start only back
pnpm dev --filter front     # Start only front
pnpm typecheck              # TypeScript check all packages
pnpm build                  # Build all
pnpm lint                   # Lint all
```

Supabase (on host machine)

```
cd /Users/john/WEB/SERVICE
supabase start              # Start local Supabase
supabase stop               # Stop local Supabase
supabase status             # Show ports and URLs
supabase db reset           # Reset database to clean state
```

Mobile App (inside container at /workspace/apps/mobile)

```
npx expo start            # Start Expo dev server
npx expo start --clear    # Clear cache and start
```

Architecture Overview

```
SERVICE/
├── apps/
│   ├── back/           # Admin Dashboard — Next.js 16, port 3200
│   │   ├── src/app/(auth)/         # Login, register
│   │   ├── src/app/(dashboard)/    # 35+ admin pages
│   │   ├── src/app/api/v1/         # 50+ REST endpoints (mobile API)
│   │   ├── src/lib/services/       # Business logic layer
│   │   ├── src/lib/auth/           # Auth + RBAC (5 roles)
│   │   └── src/actions/            # Server actions
│   ├── front/          # Public Sites + Portal — Next.js 16, port 3201
│   │   ├── src/app/portal/         # Customer portal (auth, dashboard, jobs, invoices, ...
│   │   ├── src/app/api/portal/     # Portal API routes
│   │   └── src/app/[slug]/         # Tenant websites + booking
│   └── mobile/         # Technician App — React Native / Expo
│       └── src/                    # Offline-first, field mode, voice notes
├── packages/
│   ├── api-types/      # Shared enums, models, constants (zero dependencies)
│   └── shared/         # Drizzle ORM schema, templates, website types
└── supabase/           # Local Supabase config (config.toml)
```

Key Architecture Decisions

ASPECT	APPROACH
Multi-tenancy	Shared DB with `tenant_id` on all tables + RLS
Auth	Supabase Auth — `requireAuth()` / `requireApiAuth()`
Permissions	RBAC with 5 roles: admin, office_manager, dispatcher, csr, technician
Services	Business logic in `src/lib/services/`, shared by server actions + REST API
ORM	Drizzle ORM, schema namespace `fieldservice`
Validation	Zod v4
Payments	Stripe Connect (Checkout for portal payments)
Email	Resend + template engine, Inbucket for local testing
Job Numbers	Tenant-scoped atomic sequences (`tenant_sequences` table)