

# Rajalakshmi Engineering College

Name: Reshma shri.s

Email: 241001194@rajalakshmi.edu.in

Roll no: 241001194

Phone: 8144945959

Branch: REC

Department: IT - Section 2

Batch: 2028

Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 8\_MCQ

Attempt : 1

Total Mark : 15

Marks Obtained : 14

#### Section 1 : MCQ

1. What will be the output for the following code?

```
class InvalidUsernameException extends Exception {  
    public InvalidUsernameException(String message) {  
        super(message);  
    }  
}
```

```
class Test {  
    public static void main(String[] args) {  
        try {  
            String username = "abc";  
            if (username.length() < 5) {  
                throw new InvalidUsernameException("Username must be at  
least 5 characters long");  
            }  
        }  
    }  
}
```

```
    } catch (InvalidUsernameException e) {  
        System.out.println(e.getMessage());  
    }  
}  
}
```

**Answer**

Username must be at least 5 characters long

**Status :** Correct

**Marks :** 1/1

2. What is the purpose of a custom exception in Java?

**Answer**

To create user-defined exceptions for specific scenarios

**Status :** Correct

**Marks :** 1/1

3. what is the output of the following code?

```
class MyException extends Exception {  
    public MyException(String message) {  
        super(message);  
    }  
}  
  
class Test {  
    public static void main(String[] args) {  
        try {  
            throw new MyException("Error occurred");  
        } catch (MyException e) {  
            System.out.println(e);  
        }  
    }  
}
```

**Answer**

MyException: Error occurred

**Status :** Correct

**Marks :** 1/1

4. What will happen if a checked custom exception is thrown inside a method without being caught or declared?

**Answer**

Compilation Error

**Status :** Correct

**Marks :** 1/1

5. How do you create an unchecked custom exception?

**Answer**

By extending RuntimeException

**Status :** Correct

**Marks :** 1/1

6. Which of the following is true about custom exceptions?

**Answer**

Custom exceptions must extend either Exception or RuntimeException

**Status :** Correct

**Marks :** 1/1

7. What will be the output for the following code?

```
import java.io.*;
```

```
class OutOfStockException extends Exception {  
    public OutOfStockException(String message) {  
        super(message);  
    }  
}
```

```
class Test {  
    public static void main(String[] args) {
```

```

try {
    int stock = 0;
    if (stock == 0) {
        throw new OutOfStockException("Item is out of stock");
    }
} catch (OutOfStockException e) {
    System.out.println(e.getMessage());
}
}
}

```

**Answer**

Item is out of stock

**Status :** Correct

**Marks :** 1/1

8. What will be the output for the following code?

```

import java.io.*;

class UnderageException extends Exception {
    public UnderageException(String message) {
        super(message);
    }
}

class Test {
    public static void main(String[] args) {
        try {
            int age = 17;
            if (age < 18) {
                throw new UnderageException("Underage, cannot proceed");
            }
        } catch (UnderageException e) {
            System.out.println(e.getMessage());
        }
    }
}

```

**Answer**

Underage, cannot proceed

**Status :** Correct

**Marks :** 1/1

9. What will be the output for the following code?

```
class NegativeBalanceException extends Exception {  
    public NegativeBalanceException(String message) {  
        super(message);  
    }  
}  
  
class Test {  
    public static void main(String[] args) {  
        try {  
            double balance = -500;  
            if (balance < 0) {  
                throw new NegativeBalanceException("Balance cannot be  
negative");  
            }  
        } catch (NegativeBalanceException e) {  
            System.out.println("Error: " + e.getMessage());  
        }  
    }  
}
```

**Answer**

Error: Balance cannot be negative

**Status :** Correct

**Marks :** 1/1

10. What will be the output for the following code?

```
import java.io.*;
```

```
class NegativeAgeException extends Exception {  
    public NegativeAgeException(String message) {
```

```

        super(message);
    }
}

class Test {
    public static void main(String[] args) {
        try {
            int age = -5;
            if (age < 0) {
                throw new NegativeAgeException("Age cannot be negative");
            }
        } catch (NegativeAgeException e) {
            System.out.println(e.getMessage());
        }
    }
}

```

**Answer**

Age cannot be negative

**Status :** Correct

**Marks :** 1/1

11. What will be the output for the following code?

```

import java.io.*;

class TemperatureTooHighException extends Exception {
    public TemperatureTooHighException(String message) {
        super(message);
    }
}

class Test {
    public static void main(String[] args) {
        try {
            int temperature = 110;
            if (temperature > 100) {
                throw new TemperatureTooHighException("Temperature too
high");
            }
        }
    }
}

```

```

    }
    } catch (TemperatureTooHighException e) {
        System.out.println(e.getMessage());
    }
}

```

**Answer**

Temperature too high

**Status :** Correct

**Marks :** 1/1

12. What will be the output for the following code?

```

class InvalidVotingAgeException extends Exception {
    public InvalidVotingAgeException(String message) {
        super(message);
    }
}

class Test {
    public static void main(String[] args) {
        try {
            int age = 15;
            if (age < 18) {
                throw new InvalidVotingAgeException("You are not eligible to
vote");
            }
            System.out.println("Eligible to vote");
        } catch (InvalidVotingAgeException e) {
            System.out.println(e.getMessage());
        }
    }
}

```

**Answer**

You are not eligible to vote

**Status :** Correct

**Marks :** 1/1

13. What will be the output of the following code?

```
class MyException extends Exception {  
    public MyException() {  
        super("Default Exception Message");  
    }  
}  
  
class Test {  
    public static void main(String[] args) {  
        try {  
            throw new MyException();  
        } catch (MyException e) {  
            System.out.println(e.getMessage());  
        }  
    }  
}
```

**Answer**

Default Exception Message

**Status :** Correct

**Marks :** 1/1

14. what is the output of the following code?

```
class MyException extends Exception {  
    public MyException(String message) {  
        super(message);  
    }  
}  
  
class Test {  
    static void check() throws MyException {  
        throw new MyException("Custom Exception Occurred");  
    }  
  
    public static void main(String[] args) {  
        try {  
            check();  
        }  
    }  
}
```

```
} catch (Exception e) {  
    System.out.println(e.getMessage());  
}  
}  
}
```

**Answer**

Compilation Error

**Status : Wrong**

**Marks : 0/1**

15. Which keyword is used to explicitly throw a custom exception?

**Answer**

throw

**Status : Correct**

**Marks : 1/1**

# Rajalakshmi Engineering College

Name: Reshma shri.s

Email: 241001194@rajalakshmi.edu.in

Roll no: 241001194

Phone: 8144945959

Branch: REC

Department: IT - Section 2

Batch: 2028

Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 8\_Q1

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

Write a program to validate the email address and display suitable exceptions if there is any mistake.

Create 3 custom exception classes as below

DotException AtTheRateException DomainException

A typical email address should have a "." character, and a "@" character, and also the domain name should be valid. Valid domain names for practice be 'in', 'com', 'net', or 'biz'.

Display Invalid Dot usage, Invalid @ usage, or Invalid Domain message based on email id.

Get the email address from the user, validate the email by checking the

above-mentioned criteria, and print the validity status of the input email address.

### ***Input Format***

The first line of input contains the email to be validated.

### ***Output Format***

The output prints a Valid email address or an Invalid email address along with the suitable exception

If email ends with . or contains not exactly one . after @, it throws:

DotException: Invalid Dot usage

Invalid email address

If @ appears not exactly once, it throws:

AtTheRateException: Invalid @ usage

Invalid email address

If the part after the last dot is not among accepted domains:

DomainException: Invalid Domain

Invalid email address

If all conditions satisfied then print:

Valid email address

Refer to the sample input and output for format specifications.

### **Sample Test Case**

Input: sample@gmail.com

Output: Valid email address

### **Answer**

```
// You are using Java
import java.util.Scanner;
class DotException extends Exception
{
    public DotException(String message)
    {
        super(message);
    }
}
class AtTheRateException extends Exception
{
    public AtTheRateException(String message)
    {
        super(message);
    }
}
class DomainException extends Exception
{
    public DomainException(String message)
    {
        super(message);
    }
}
public class Main
{
    public static void validateEmail(String email) throws DotException,
    AtTheRateException, DomainException
    {
        int atIndex=-1;
        int atCount=0;

        for(int i=0;i<email.length();i++)
```

```

    {
        if(email.charAt(i)=='@')
        {
            atCount++;
            atIndex=i;
        }
    }
    if(atCount != 1)
    {
        throw new AtTheRateException("Invalid @ usage");
    }
    if(email.startsWith("@") || email.endsWith("@"))
    {
        throw new AtTheRateException("Invalid @ usage");
    }
    if(email.startsWith(".") || email.endsWith("."))
    {
        throw new DotException("Invalid Dot usage");
    }
    if(email.contains("..") || email.contains(".@") ||email.contains("@."))
    {
        throw new DotException("Invalid Dot usage");
    }
    String domainPart=email.substring(atIndex + 1);
    if(!domainPart.contains("."))
    {
        throw new DotException("Invalid Dot usage");
    }
    int lastDotIndex = email.lastIndexOf('.');
    String domainExtension=email.substring(lastDotIndex+1);

    if(!(domainExtension.equals("in") || domainExtension.equals("com")||
    domainExtension.equals("net") || domainExtension.equals("biz")))
    {
        throw new DomainException("Invalid Domain");
    }
}

public static void main(String[] args)
{
    Scanner sc=new Scanner(System.in);
    String email=sc.nextLine();

```

```
try
{
    validateEmail(email);
    System.out.println("Valid email address");
}
catch(DotException e)
{
    System.out.println(e.getClass().getSimpleName() + ": " + e.getMessage());
    System.out.println("Invalid email address");
}
catch(AtTheRateException e)
{
    System.out.println(e.getClass().getSimpleName() + ": " + e.getMessage());
    System.out.println("Invalid email address");
}
catch(DomainException e)
{
    System.out.println(e.getClass().getSimpleName() + ": " + e.getMessage());
    System.out.println("Invalid email address");
}
finally
{
    sc.close();
}
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Reshma shri.s

Email: 241001194@rajalakshmi.edu.in

Roll no: 241001194

Phone: 8144945959

Branch: REC

Department: IT - Section 2

Batch: 2028

Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 8\_Q2

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

Elsa, a busy professional, is using a scheduling application to plan her meetings efficiently. The application requires users to input meeting durations in minutes, ensuring that the duration is a positive integer and does not exceed 240 minutes (4 hours). Elsa needs a program to assist her in scheduling meetings securely with proper exception handling.

Create a Java class named ElsaMeetingScheduler. Implement a custom exception: InvalidDurationException for invalid meeting duration entries. Implement the main method to interactively take user input for a meeting duration. Implement the validateMeetingDuration method to validate the meeting duration based on the specified rules and throw a custom exception if the validation fails. Print appropriate success or error messages based on the meeting duration.

Implement a custom exception, `InvalidDurationException`, to handle cases where the entered meeting duration does not meet the specified criteria.

### ***Input Format***

The input consists of an integer value 'n', representing the meeting duration.

### ***Output Format***

The output is displayed in the following format:

If the entered meeting duration meets the specified criteria, the program outputs

"Meeting scheduled successfully!"

If the entered meeting duration is invalid, the program outputs an error message indicating the issue.

"Error: Invalid meeting duration. Please enter a positive integer not exceeding 240 minutes (4 hours)."

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 120

Output: Meeting scheduled successfully!

### ***Answer***

```
// You are using Java
import java.util.Scanner;
```

```
class InvalidDurationException extends Exception
{
    public InvalidDurationException(String message)
    {
        super(message);
    }
}

public class Main
```

```

{
    public static void validateMeetingDuration(int duration) throws
    InvalidDurationException
    {
        if(duration <= 0 || duration > 240)
        {
            throw new InvalidDurationException("Invalid meeting duration.");
        }
    }
    public static void main(String[] arg)
    {
        Scanner sc=new Scanner(System.in);
        try
        {
            int duration=sc.nextInt();
            validateMeetingDuration(duration);
            System.out.println("Meeting scheduled successfully!");
        }
        catch(InvalidDurationException e)
        {
            System.out.println("Error: Invalid meeting duration. Please enter a positive
integer not exceeding 240 minutes(4 hours).");
        }
        catch(Exception e)
        {
            System.out.println("Error: Invalid meeting duration. Please enter a positive
integer not exceeding 240 minutes(4 hours).");
        }
        finally
        {
            sc.close();
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Reshma shri.s

Email: 241001194@rajalakshmi.edu.in

Roll no: 241001194

Phone: 8144945959

Branch: REC

Department: IT - Section 2

Batch: 2028

Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 8\_Q3

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

In a user registration system, there is a requirement to implement a username validation module. Users attempting to register must adhere to specific criteria for their usernames to be considered valid.

Your task is to develop a program that takes user input for a desired username and validates it according to the following rules:

The username must not contain any spaces. The username must be at least 5 characters long.

Implement a custom exception, `InvalidUsernameException`, to handle cases where the entered username does not meet the specified criteria.

#### ***Input Format***

The input consists of a string S, representing the desired username.

### **Output Format**

If the username is valid, print "Username is valid: [S]".

If the username is invalid:

1. If the username is short, print "Invalid Username: Username must be at least 5 characters long"
2. If the username contains spaces, print "Invalid Username: Username cannot contain spaces"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: John

Output: Invalid Username: Username must be at least 5 characters long

### **Answer**

```
// You are using Java
import java.util.Scanner;
class InvalidUsernameException extends Exception
{
    public InvalidUsernameException(String message)
    {
        super(message);
    }
}
public class Main
{
    public static void validateUsername(String username) throws
InvalidUsernameException
    {
        if(username.length() < 5)
        {
            throw new InvalidUsernameException("Username must be at least 5
characters long");
        }
        if(username.contains(" "))
```

```
{
    throw new InvalidUsernameException("Username cannot contain
spaces");
}
}
public static void main(String[] arg)
{
    Scanner sc=new Scanner(System.in);
    String username=sc.nextLine();

    try
    {
        validateUsername(username);
        System.out.println("Username is valid: "+username);
    }
    catch(InvalidUsernameException e)
    {
        System.out.println("Invalid Username: "+e.getMessage());
    }
    finally
    {
        sc.close();
    }
}
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: Reshma shri.s

Email: 241001194@rajalakshmi.edu.in

Roll no: 241001194

Phone: 8144945959

Branch: REC

Department: IT - Section 2

Batch: 2028

Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 8\_Q4

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

A local municipality is implementing an online voting system for a community event and wants to ensure that only eligible voters (those aged 18 or older) can participate.

Your task is to develop a program that validates the age of individuals attempting to vote online. If the user's age is below 18, the program should throw a custom exception, `InvalidAgeException`, preventing them from casting their vote. If the input is invalid, catch the appropriate `InputMismatchException` and print the in-built exception message.

#### *Input Format*

The input consists of an integer representing the age.

#### *Output Format*

If the age is 18 or older, print "Eligible to vote"

If the age is below 18, print "Exception occurred: InvalidAgeException: Age is not valid to vote"

If there is any other type of exception, print "An error occurred: " followed by the in-built exception message.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 20

Output: Eligible to vote

### **Answer**

// You are using Java

```
import java.util.Scanner;
```

```
import java.util.InputMismatchException;
```

```
class InvalidAgeException extends Exception  
{
```

```
    public InvalidAgeException(String message)
```

```
    {  
        super(message);  
    }  
}
```

```
public class Main
```

```
{  
    public static void validateAge(int age) throws InvalidAgeException
```

```
    {  
        if(age<18)  
        {  
            throw new InvalidAgeException("Age is not valid to vote");  
        }  
    }  
}
```

```
    public static void main(String[] arg)
```

```
    {  
        Scanner sc= new Scanner(System.in);
```

```
try
{
    int age = sc.nextInt();

    validateAge(age);

    System.out.println("Eligible to vote");
}
catch(InvalidAgeException e)
{
    System.out.println("Exception occurred: "+e.getClass().getSimpleName()
+ ": "+e.getMessage());
}
catch(InputMismatchException e)
{
    System.out.println("An error occurred: "+e.toString());
}
finally
{
    sc.close();
}
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: Reshma shri.s

Email: 241001194@rajalakshmi.edu.in

Roll no: 241001194

Phone: 8144945959

Branch: REC

Department: IT - Section 2

Batch: 2028

Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 8\_Q5

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

In a file management system, users are required to provide a valid file name when creating new files. The system enforces specific rules for file names to maintain consistency and avoid potential issues. Your task is to implement a Java program named FileNameValidator that takes user input for a file name and validates it according to the specified rules.

Rules for Valid File Name:

The file name must consist of alphanumeric characters (letters and digits) only. The file name must have a minimum length of 3 characters.

Implement a custom exception, FileNameValidator, to handle cases where the entered filename does not meet the specified criteria.

***Input Format***

The input consists of a string S, representing the desired filename.

### **Output Format**

The output is displayed in the following format:

If the entered file name meets the specified criteria, the program outputs

"Valid file name"

If the entered file name does not meet the criteria and triggers the InvalidFileNameException, the program outputs

"Error: Invalid file name. It must be alphanumeric and have a minimum length of 3 characters."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: myfile123

Output: Valid file name

### **Answer**

```
// You are using Java
import java.util.Scanner;
```

```
class InvalidFileNameException extends Exception
{
    public InvalidFileNameException(String message)
    {
        super(message);
    }
}

public class Main
{
    public static void validateFileName(String fileName) throws
    InvalidFileNameException
    {
        String errorMessage = "Error: Invalid file name. It must be alphanumeric and
        have a minimum length of 3 characters.";
    }
}
```

```

    if(fileName.length()<3)
    {
        throw new InvalidFileNameException(errorMessage);
    }
    for(char c: fileName.toCharArray())
    {
        if(!Character.isLetterOrDigit(c))
        {
            throw new InvalidFileNameException(errorMessage);
        }
    }
}
public static void main(String[] args)
{
    Scanner sc= new Scanner(System.in);
    String fileName=sc.nextLine();

    try
    {
        validateFileName(fileName);
        System.out.println("Valid file name");
    }
    catch(InvalidFileNameException e)
    {
        System.out.println(e.getMessage());
    }
    finally
    {
        sc.close();
    }
}
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Reshma shri.s

Email: 241001194@rajalakshmi.edu.in

Roll no: 241001194

Phone: 8144945959

Branch: REC

Department: IT - Section 2

Batch: 2028

Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 8\_PAH

Attempt : 1

Total Mark : 40

Marks Obtained : 40

### Section 1 : Coding

#### 1. Problem Statement

Daniel is developing a program to verify the age of users. He wants to ensure that the entered age is within a valid range. Write a program to help Daniel implement this age-checking feature using custom exceptions.

Daniel needs a program that takes an integer input representing a person's age. If the age is between 0 and 150 (inclusive), the program should print "Age is valid!". If the age is less than 0 or greater than 150, the program should throw a custom exception (InvalidAgeException) with the message "Invalid age. Please enter an age between 0 and 150."

Implement a custom exception, InvalidAgeException, to handle cases where the entered age does not meet the specified criteria.

#### ***Input Format***

The input consists of an integer value 'n', representing the age.

### **Output Format**

The output is displayed in the following format:

If the age is valid (between 0 and 150, inclusive), print

"Age is valid!".

If the age is invalid, print

"Error: Invalid age. Please enter an age between 0 and 150."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 45

Output: Age is valid!

### **Answer**

```
// You are using Java
import java.util.Scanner;
class InvalidAgeException extends Exception
{
    public InvalidAgeException(String message)
    {
        super(message);
    }
}
public class Main
{
    public static void main(String[] arg)
    {
        Scanner sc=new Scanner(System.in);
        try
        {
            int age=sc.nextInt();
            if(age<0 || age>150)
            {
```

```

        throw new InvalidAgeException("Invalid age. Please enter an age
between 0 and 150.");
    }
    else
    {
        System.out.println("Age is valid!");
    }
}
catch(InvalidAgeException e)
{
    System.out.println("Error: "+e.getMessage());
}
finally
{
    sc.close();
}
}
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Enigma is developing a simple web application that takes a user-input URL, validates it, and throws a custom exception `InvalidURLFormatException` if the URL does not start with "http://" or "https://".

The main method prompts the user for input, validates the URL, and prints whether it is valid or not.

### ***Input Format***

The input consists of a string, representing the URL entered by the user.

### ***Output Format***

The output displays one of the following results:

If the entered URL is valid according to the specified format, the program prints:

"[URL] is a valid URL"

If the entered URL is not valid according to the specified format, the program prints:

"Invalid URL format: [URL]"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: `http://www.example.com`

Output: `http://www.example.com is a valid URL`

### **Answer**

```
// You are using Java
import java.util.Scanner;
class InvalidURLExceptionFormatException extends Exception
{
    public InvalidURLExceptionFormatException(String message)
    {
        super(message);
    }
}
public class Main
{
    public static void main(String[] arg)
    {
        Scanner sc=new Scanner(System.in);
        String url=sc.nextLine();
        try
        {
            if(url.startsWith("http://")||url.startsWith("https://"))
            {
                System.out.println(url + " is a valid URL");
            }
            else
            {
                throw new InvalidURLExceptionFormatException(url);
            }
        }
    }
}
```

```

    }
}
catch(InvalidURLExceptionFormatException e)
{
    System.out.println("Invalid URL format: "+e.getMessage());
}
finally
{
    sc.close();
}
}
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

You are tasked to create a program that defines a custom exception GradeException. The program should include a Student class with fields for the student's name, age, and grade. Implement a method in the Student class that checks the grade, and if the grade is below 40, it should throw a GradeException. Otherwise, it should display the student's details.

#### **Input Format**

The input consists of three parameters in separate lines:

1. A string representing the student's name.
2. An integer representing the student's age.
3. An integer representing the student's grade.

#### **Output Format**

The output will display the student's details if the grade is valid.

If the grade is below 40, the program will display an error message "Grade is below 40".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: Alice

20

85

Output: Name: Alice

Age: 20

Grade: 85

### **Answer**

// You are using Java

```
import java.util.Scanner;
```

```
class GradeException extends Exception
```

```
{  
    public GradeException(String message)
```

```
{  
        super(message);
```

```
}
```

```
}  
class Student
```

```
{
```

```
    String name;
```

```
    int age;
```

```
    int grade;
```

```
  
    public Student(String name,int age,int grade)
```

```
{
```

```
        this.name=name;
```

```
        this.age=age;
```

```
        this.grade=grade;
```

```
}
```

```
    public void checkGrade() throws GradeException
```

```
{
```

```
        if(this.grade < 40)
```

```
{
```

```
            throw new GradeException("Grade is below 40");
```

```
}
```

```
}
```

```
    public void displayDetails()
```

```
{
```

```
        System.out.println("Name: "+this.name);
```

```

        System.out.println("Age: "+this.age);
        System.out.println("Grade: "+this.grade);
    }
}
public class Main
{
    public static void main(String[] args)
    {
        Scanner sc=new Scanner(System.in);
        try
        {
            String name=sc.nextLine();
            int age=sc.nextInt();
            int grade=sc.nextInt();

            Student student = new Student(name,age,grade);
            student.checkGrade();
            student.displayDetails();
        }
        catch(GradeException e)
        {
            System.out.println(e.getMessage());
        }
        finally
        {
            sc.close();
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

An HR software system is being developed to process employee payrolls. During payroll processing, the system must ensure that no employee has a negative salary and that no employee's salary exceeds 2,00,000. If either condition occurs, the system should throw a custom exception.

Create a custom exception InvalidSalaryException and a class Employee

that processes salary according to the following rules:

If salary < 0, throw `InvalidSalaryException` with the message: "Salary cannot be negative". If salary > 200000, throw `InvalidSalaryException` with the message: "Salary exceeds threshold limit". Otherwise, display: "Salary processed successfully for <empName>: <salary>".

The payroll processing should always display: "Payroll process completed" at the end, regardless of whether an exception occurs.

### ***Input Format***

The first line of input contains an integer representing the employee ID.

The second line contains a string representing the employee's name.

The third line contains a floating-point number representing the salary of the employee.

### ***Output Format***

If the salary is valid: "Salary processed successfully for <empName>: <salary>"

"Payroll process completed"

If the salary is invalid: "<Exception Message>"

"Payroll process completed"

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 101

Rahul

150000.0

Output: Salary processed successfully for Rahul: 150000.0

Payroll process completed

### ***Answer***

// You are using Java

```

import java.util.Scanner;
class InvalidSalaryException extends Exception
{
    public InvalidSalaryException(String message)
    {
        super(message);
    }
}
class Employee
{
    int empId;
    String empName;
    double salary;

    public Employee(int empId, String empName, double salary)
    {
        this.empId=empId;
        this.empName=empName;
        this.salary=salary;
    }
    public void processPayroll() throws InvalidSalaryException
    {
        if(this.salary < 0)
        {
            throw new InvalidSalaryException("Salary cannot be negative");
        }
        if(this.salary > 200000)
        {
            throw new InvalidSalaryException("Salary exceeds threshold limit");
        }
        System.out.println("Salary processed successfully for " + this.empName + ":
"+this.salary);
    }
}
public class Main
{
    public static void main(String[] arg)
    {
        Scanner sc=new Scanner(System.in);
        try
        {

```

```
int id=sc.nextInt();
sc.nextLine();
String name=sc.nextLine();
double salary=sc.nextDouble();

Employee employee = new Employee(id,name,salary);
employee.processPayroll();

}
catch(InvalidSalaryException e)
{
    System.out.println(e.getMessage());
}
finally
{
    System.out.println("Payroll process completed");
    sc.close();
}
}
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Reshma shri.s

Email: 241001194@rajalakshmi.edu.in

Roll no: 241001194

Phone: 8144945959

Branch: REC

Department: IT - Section 2

Batch: 2028

Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 8\_CY

Attempt : 1

Total Mark : 40

Marks Obtained : 40

### Section 1 : Coding

#### 1. Problem Statement

Camila, a user of a social media platform, is looking to change her password to enhance account security. The platform enforces specific rules for password strength to ensure the safety of user accounts. Camila needs a program that prompts her to enter a new password and throws custom exceptions based on the strength of the password.

Password Strength Criteria:

Weak Password:

Length less than 8 characters. Medium Password:

Length 8 or more characters. Missing a mix of uppercase letters, lowercase letters, and digits.

Implement a custom exception, to assist Camila in changing her password

securely. The program should interactively take user input for a new password, categorize its strength, and handle custom exceptions (WeakPasswordException and MediumPasswordException) if the password fails to meet the specified criteria.

### ***Input Format***

The input consists of a string *s*, representing the new password.

### ***Output Format***

The output is displayed in the following format:

If the entered password meets the strength criteria, the program outputs

"Password changed successfully!"

If the entered password is weak, the program outputs

"Error: Weak password. It must be at least 8 characters long."

If the entered password is of medium strength, the program outputs

"Error: Medium password. It must include a mix of uppercase letters, lowercase letters, and digits."

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: ComplexP@ss1

Output: Password changed successfully!

### ***Answer***

```
import java.util.Scanner;
class WeakPasswordException extends Exception
{
    public WeakPasswordException(String message)
    {
        super(message);
    }
}
```

```

}
class MediumPasswordException extends Exception
{
    public MediumPasswordException(String message)
    {
        super(message);
    }
}
public class Main
{
    public static void validatePassword(String password)
        throws WeakPasswordException,MediumPasswordException{
        if(password.length() < 8)
        {
            throw new WeakPasswordException("Error: Weak password. It must be at
least 8 characters long.");
        }
        boolean hasUpper = false;
        boolean hasLower = false;
        boolean hasDigit = false;

        for(char ch : password.toCharArray())
        {
            if(Character.isUpperCase(ch))
            {
                hasUpper=true;
            }
            else if(Character.isLowerCase(ch))
            {
                hasLower = true;
            }
            else if(Character.isDigit(ch))
            {
                hasDigit=true;
            }
        }
        if(!hasUpper || !hasLower || !hasDigit)
        {
            throw new MediumPasswordException("Error: Medium password.It must
include a mix of uppercase letters,lowercase letters, and digits.");
        }
    }
}

```

```

        System.out.println("Password changed successfully!");
    }
    public static void main(String[] args)
    {
        Scanner scanner=new Scanner(System.in);
        String password = scanner.nextLine();
        try
        {
            validatePassword(password);
        }
        catch(WeakPasswordException e)
        {
            System.out.println(e.getMessage());
        }
        catch(MediumPasswordException e)
        {
            System.out.println(e.getMessage());
        }
        finally
        {
            scanner.close();
        }
    }
}

```

**Status :** Correct

**Marks : 10/10**

## 2. Problem Statement

In an online shopping cart system, users can apply coupon codes during checkout to avail of discounts. However, to ensure the validity and security of coupon codes, the system enforces specific rules for their format. Your task is to implement a Java program named `CouponCodeValidator` that takes user input for a coupon code and validates it according to the specified rules.

Rules for Valid Coupon Code:

The coupon code must consist of exactly 10 characters. The coupon code

must contain at least one alphabet (uppercase or lowercase) and at least one digit (0-9). Special characters are not allowed in the coupon code.

Implement a custom exception, `InvalidCouponException`, to handle cases where the entered coupon code does not meet the specified criteria.

### ***Input Format***

The input consists of a string `s`, representing the coupon code.

### ***Output Format***

The output is displayed in the following format:

If the entered coupon code meets the specified criteria, the program outputs

"Coupon code applied successfully!"

If the entered coupon code has less than or more than 10 characters it outputs

"Error: Invalid coupon code length. It must be exactly 10 characters."

If the entered coupon code contains only numeric or only alphabets it outputs

"Error: Invalid coupon code format. It must contain at least one alphabet and one digit."

If the entered coupon code contains special characters it outputs

"Error: Coupon code should not contain special characters."

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: ABCD123456

Output: Coupon code applied successfully!

### ***Answer***

```
// You are using Java
import java.util.Scanner;
```

```

class InvalidCouponException extends Exception
{
    public InvalidCouponException(String message)
    {
        super(message);
    }
}
public class Main
{
    public static void validateCoupon(String code) throws InvalidCouponException
    {
        if(code.length() != 10)
        {
            throw new InvalidCouponException("Error: Invalid coupon code length. It
must be exactly 10 characters.");
        }
        boolean hasLetter=false;
        boolean hasDigit = false;
        for(char c : code.toCharArray())
        {
            if(Character.isLetter(c))
            {
                hasLetter=true;
            }
            else if(Character.isDigit(c))
            {
                hasDigit=true;
            }
            else
            {
                throw new InvalidCouponException("Error: Coupon code should not
contain special characters.");
            }
        }
        if(!hasLetter || !hasDigit)
        {
            throw new InvalidCouponException("Error: Invalid coupon code format. It
must contain at least one alphabet and one digit.");
        }
        System.out.println("Coupon code applied successfully!");
    }
    public static void main(String[] args)

```

```

{
    Scanner scanner=new Scanner(System.in);
    String couponCode=scanner.nextLine();

    try
    {
        validateCoupon(couponCode);
    }
    catch(InvalidCouponException e)
    {
        System.out.println(e.getMessage());
    }
    finally
    {
        scanner.close();
    }
}
}

```

**Status :** Correct

**Marks : 10/10**

### 3. Problem Statement

Theo is trying to update his payment information on a subscription-based streaming service. To proceed, the system requires Theo to provide a valid credit card number consisting of 16 digits. However, Theo wants to make sure that the credit card number he enters meets the specified criteria with proper exception handling.

The credit card number must consist of exactly 16 digits. If the entered credit card number does not meet the specified criteria, the program should throw a custom exception, `InvalidCreditCardException`, and provide Theo with specific error messages: If the length of the credit card number is not 16 digits, the exception message should be: "Invalid credit card number length." If the credit card number contains non-numeric characters, the exception message should be: "Invalid credit card number format."

Implement a custom exception, `InvalidCreditCardException`, to fulfill Theo's requirements and keep his payment information secure.

### ***Input Format***

The input consists of a string value 's', consisting of the 16-digit credit card number.

### ***Output Format***

The output is displayed in the following format:

If the entered credit card number is valid, the program should output a success message:

"Payment information updated successfully!"

If the entered credit card has more than 16 digits or less than 16 digits it displays

"Error: Invalid credit card number length."

If the entered 16-digit credit card has non-integers it displays

"Error: Invalid credit card number format."

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1234567890123456

Output: Payment information updated successfully!

### ***Answer***

```
import java.util.Scanner;

public class Main
{
    public static void main(String[] args)
    {
        Scanner scanner = new Scanner(System.in);
        String s = scanner.nextLine();
        scanner.close();
```

```

    try
    {
        CreditCardValidator.validateCreditCard(s);
        System.out.println("Payment information updated successfully!");
    }
    catch (InvalidCreditCardException e)
    {
        System.out.println("Error: " + e.getMessage());
    }
}
}

```

```

class CreditCardValidator
{
    public static void validateCreditCard(String s) throws
    InvalidCreditCardException {
        if (s.length() != 16)
        {
            throw new InvalidCreditCardException("Invalid credit card number
length.");
        }
        if (!s.matches("\\d{16}"))
        {
            throw new InvalidCreditCardException("Invalid credit card number
format.");
        }
    }
}

```

```

class InvalidCreditCardException extends Exception
{
    public InvalidCreditCardException(String message)
    {
        super(message);
    }
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Tim was tasked with creating a user profile system that validates the user's date of birth input. The system should throw a custom exception, `InvalidDateOfBirthException`, if the date is not in the specified format "dd-mm-yyyy" or if it represents an invalid calendar date.

The main method takes user input, validates the date of birth, and prints whether it is valid or not.

### ***Input Format***

The input consists of a string, representing the date of birth of the user.

### ***Output Format***

The output displays one of the following results:

If the entered date of birth is valid according to the specified format, the program prints:

"[Date] is a valid date of birth"

If the entered date of birth is not valid according to the specified format, the program prints:

"Invalid date: [Date]"

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 01-01-2000

Output: 01-01-2000 is a valid date of birth

### ***Answer***

```
import java.time.LocalDate;
import java.time.format.DateTimeFormatter;
import java.time.format.DateTimeParseException;
import java.time.format.ResolverStyle;
import java.util.Scanner;
```

```
class InvalidDateOfBirthException extends Exception
{
    public InvalidDateOfBirthException(String message)
    {
        super(message);
    }
}
```

```
public class Main
{
    public static void main(String[] args)
    {
        Scanner scanner = new Scanner(System.in);
        String s = scanner.nextLine();
        scanner.close();

        try
        {
            validateDateOfBirth(s);
            System.out.println(s + " is a valid date of birth");
        }
        catch (InvalidDateOfBirthException e)
        {
            System.out.println("Invalid date: " + s);
        }
    }
}
```

```
public static void validateDateOfBirth(String s) throws
InvalidDateOfBirthException
{
```

```
    DateTimeFormatter formatter = DateTimeFormatter.ofPattern("dd-MM-
uuuu")
        .withResolverStyle(ResolverStyle.STRICT);
```

```
    try
    {
        LocalDate date = LocalDate.parse(s, formatter);
    }
    catch (DateTimeParseException e)
```

```
        {  
            throw new InvalidDateOfBirthException("Invalid date of birth");  
        }  
    }  
}
```

**Status :** Correct

**Marks :** 10/10