

MongoDB is a document database that stores records as BSON documents.

A collection is a group of related MongoDB documents.

A document contains field and value pairs and is similar to a JSON object.

MongoDB documents can contain nested objects and arrays.

The `_id` field uniquely identifies a document and MongoDB creates it by default.

MongoDB is schema-flexible, so documents in one collection can have different fields.

A database contains collections, and collections contain documents.

`insertOne` creates one document and `insertMany` creates multiple documents.

`find` returns documents that match a filter and `findOne` returns the first matching document.

`updateOne` and `updateMany` modify matching documents.

`deleteOne` and `deleteMany` remove matching documents.

The `$set` operator changes selected fields without replacing the whole document.

The `$inc` operator increases or decreases a numeric field.

An index helps MongoDB find matching documents more efficiently.

The aggregation pipeline transforms and analyzes documents in multiple stages.

The `$match` stage filters documents and the `$group` stage groups documents.

MongoDB supports sorting, limiting, and projecting selected fields.

Mongoose is an ODM library that provides schemas, models, validation, and middleware for MongoDB in Node.js.

A Mongoose schema describes the shape and rules of application documents.

A Mongoose model provides methods for creating, reading, updating, and deleting documents.

MongoDB drivers allow applications to connect directly to a MongoDB server.