

**Ex.No: 1**

## **BASIC UNIX COMMANDS**

**Date : 27/02/21**

### **Aim**

To understand the basic commands used to work with Unix environment.

### **General Command Structure**

#### **Syntax:**

Command [-options] arguments

#### **Where,**

Command	name of the command
Arguments	file name, user name or some other information that the program needs.
Options	which is a option for a program. So it is put inside square brackets.

### **BASIC COMMANDS**

1. Command : **who**  
Purpose : It is used to get the information about all the users currently working in the system.  
Syntax : who  
Example : \$ who
2. Command : **who am i**  
Purpose : It is used to know in which terminal the user is currently logged on.  
Syntax : who am i  
Example : \$ who am I
3. Command : **date**  
Purpose : It is used to display the system date and time.  
Syntax : date  
Example : \$ date
4. Command : **cal**  
Purpose : It prints the calender for the specified year and month.  
Syntax : cal<month><year>  
Example : \$ cal 05 2003
5. Command : **id**  
Purpose : It is used to display the login name.  
Syntax : id  
Example : \$ id

6. Command : **clear**  
Purpose : It is used to clear the screen.
7. Command : **uname**  
Purpose : It is used to display the details about the OS in which we are working.  
Syntax : `uname [options]`  
Example : `$ uname -n`
8. Command : **tty**  
Purpose : It is used to know the terminal name on which we work.  
Syntax : `tty`  
Example : `$ tty`
9. Command : **pwd**  
Purpose : It is used to display the absolute pathname of current working directory.  
Syntax : `pwd`  
Example : `$ pwd`
10. Command : **bc**  
Purpose : It is used to perform simple mathematical calculations.  
Syntax : `bc filename`  
Example : `$ bcpp`
11. Command : **echo**  
Purpose : It echoes the argument on the standard output textce.  
Syntax : `echo [options] <string>`  
Example : `$ echo 'BOOM'`
12. Command : **man**  
Purpose : It gives details about the unix commands.  
Syntax : `man < command name >`  
Example : `$ man echo`

## FILE MANIPULATION COMMANDS

1. Command : **cat**  
Purpose : It is used to create a new file  
Syntax : cat ><file name>  
Example : \$ cat >  
This is sample File in Unix  
Ctrl – d

To append the content of already existing file.

Example : \$ cat>>

It is also used to display the contents of the files as well as used to create a new file.

Syntax : cat <file name >

Example : \$ cat  
This is sample File in Unix

To display the contents of two or more files, specify the filenames with the cat commands separated by a space in between them.

Example:

```
$cat 1 2 3
1 file
2 file
3 file
```

2. Command : **ls**  
Purpose : It is used to display the files in the current working directory.  
Syntax : ls [options] <arguments>  
Options  
a - to list all directory entries  
d - to list name of directories  
l - to list files in long form  
r - to list file in the reverse order  
t - to list the files sorted by time  
lrt - list content of current directory. Output will be sorted based on modification date & time.

Example : \$ ls -l

3. Command : **tail**  
Purpose : It is used to Print the last several lines of the specified files.  
Syntax : tail [options] <file name>  
Example : \$ tail -5 text

4. Command : **head**  
 Purpose : It is used to display the top portion of the file where top portion represents the no's of lines.  
 Syntax : head [options] <file name>  
 Example : \$ head -5 text
  
5. Command : **cmp**  
 Purpose : Compare two files, and if they differ, tells the first byte and line number where they differ.  
 Syntax : cmp file1 file2  
 Example : \$ cmp a1 a2
  
6. Command : **diff**  
 Purpose : The diff command analyses line by line and displays a list of changes between two files.  
 Syntax : diff file1 file2  
 Example : \$ diff a1 a2
  
7. Command : **wc**  
 Purpose : It is used to count the number of lines, words and characters in a file or group of files.  
 Syntax : wc [options] <file name >  
 Example : \$ wc .txt  
           2    15    95   .txt

The options used with **wc** commands are listed.

Option	Description
-c	Count number of characters in the file
-w	Counts the number of words in the file
-l	Counts number of lines in the file

Example:

```
$ wc -c .txt
95 .txt
$ wc -w .txt
15 .txt
$ wc -l .txt
2 .txt
```

8. Command : **sort**  
 Purpose : Sorts the specified files. The command has many useful arguments..  
 Syntax : sort [options] <file name >  
 Option-r reverse  
 Example : \$ sort .txt

9. Command : **pr**  
Purpose : It is used to display the contents of the file by separating them into pages and each page begins with the header information.  
Syntax : pr [options] <file name >  
Example : \$ pr
10. Command : **cut**  
Purpose : It is used to extract selected fields or columns from each line of one or more files and display them on the standard output textce.  
Syntax : cut [options] <file name >  
Example : \$ cut -c5
11. Command : **paste**  
Purpose : It concatenates the line from each input file column by column with tab characters in between them.  
Syntax : paste [options] <file name >  
Example : \$ paste f1 f2
12. Command : **join**  
Purpose : It is used to extracts common lines from two sorted files and there should be the common field in both file.  
Syntax : join [options] <file name1 ><file name 2>  
Example : \$ join -a1 f1 f2
13. Command : **uniq**  
Purpose : It compares adjacent lines in the file and displays the output by eliminating duplicate adjacent lines in it.  
Syntax : uniq [options] <file name >  
Example : \$ uniq -c text
14. Command : **nl**  
Purpose : It is used to add the line numbers to the file.  
Syntax : nl [options] [filename]  
Example : \$ nl text
15. Command : **tr**  
Purpose : It is used to translate or delete a character or a string from the standard input to produce the required output.  
Syntax : tr [options] <string1><string2>  
Example : \$ tr -s 'a' 'b' < text
16. Command : **tee**  
Purpose : It is used to read the contents from standardinput or from output of another command and reproduces the output to both in standardoutput and direct into output to one or more files.

Syntax :command | tee [options] <file name >  
Example : \$ date | tee dat.txt

17. Command :**grep**  
Purpose : It is used to search the specified pattern from one or more files.  
Syntax :grep [options] <pattern><file name >  
Example : \$ grepwelcometext

## DIRECTORY MANUPULATION COMMANDS

1. Command :**mkdir**  
Purpose : It is used to create new directory or more than one directory.  
Syntax :mkdir<directory name >  
Example :\$ mkdirsudhan
2. Command :**cd**  
Purpose : It is used to change the control from oneworking directory to another specified directory.  
Syntax :cd <directory name >  
Example : \$ cd sudhan
3. Command :**rmdir**  
Purpose : It is used to remove the directory if it is empty.  
Syntax :rmdir<directory name >  
Example : \$ rmdirsudhan

You can use the **-r**(recursive) option with the **rmdir** command so that it deletes the directory even when it is not empty.

For example, \$rmdir -r haran

4. Command :**cp**  
Purpose : It is used to copy one or more files.  
Syntax :cp<source file name ><destination file name>  
Example : \$ cptexttext1
5. Command :**more**  
Purpose : It is used to control the information on the screen from a line to a screen full.  
Syntax : more options <file name >  
Example :\$ more

This command displays one screen full of information from the file. To display the next screen press enter key or space bar. To quit press Q.

6. Command :passwd  
Example : passwd user  
Changes the current user's password, or that of the specified user (requires root privileges).  
The command prompts for the new password.

7. Command : mv  
Purpose : It is used to move a file within a directory with different names and also used to move a file to different directory with its original name.  
Syntax :mv<source file name ><destination directory name>  
Example : \$ mv texttext2

### 8. **chmod command**

You set the access modes of a directory or file by using the chmod command, which has the following pattern:

chmod  
*nnn directory-or-file*

The argument *nnn* is a three-digit number, which gives the access mode for the owner, group, and other users.

For example, the argument 751 is equivalent to rwxr-x--x, which gives the owner every possible permission, gives the group read and execute permission, and gives other users execute permission.

9. Command : write  
Purpose : the write command can be used by any user to write something on someone else's terminal, provided the recipient of the message permits communication  
Syntax : write <user name>  
Example : \$ write user2  
This is sample message.  
Ctrl d

On executing this command the message would be relayed to the user whose login name is user2. He would hear a beep on his terminal, followed by the message.

There are two prerequisites for a smooth write operation:

1. The recipient must be logged in; else an error message is inevitable.
2. The recipient must have given permission for messages to reach his or her terminal.

## 10. wall command

Prints a message to each user except those who've disabled message reception. Type **Ctrl-D** to end the message.

## 11. Command : news

**Purpose** : The system administrator is the sole person who can make news under the Unix OS. He types the information which he wants everyone on the network to know of in different files in /usr/news directory.

**Syntax** : 1) \$news filename  
2) \$news [-options]

**Options :** : 1) -n option only lists the names of the news items from the /usr/news directory that have not yet been read by you.

2) -s option which provides a count of the unread new items in the /usr/news directory.

3) -a shows all the news.

Example 1 : \$ news sample

Where sample is the file name in which the news items are available.

Example 2 : \$news -s

It provides the count of the unread new items.



webminal.org - your linux ~ #

```

- Share files with others, See /common_pool/README.txt
- See 'Root' menu for Webminal Desktop Root and Webminal Root features
- For Teachers/Students, partial sudo (plus C programming) platform ava

fileable - mail us.
[reshmiB@webminal.org ~]$who
[reshmiB@webminal.org ~]$whoami
reshmiB
[reshmiB@webminal.org ~]$date
Mon Mar 1 15:23:14 CET 2021
[reshmiB@webminal.org ~]$cal
March 2021
Su Mo Tu We Th Fr Sa
  1  2  3  4  5  6
 7  8  9 10 11 12 13
14 15 16 17 18 19 20
21 22 23 24 25 26 27
28 29 30 31

[reshmiB@webminal.org ~]$id
uid=246054(reshmiB) gid=246113(reshmiB) groups=246113(reshmiB) context=guest_u:guest_r
:guest_t:s0
[reshmiB@webminal.org ~]$uname
Linux
[reshmiB@webminal.org ~]$tty
/dev/pts/153
[reshmiB@webminal.org ~]$pwd
/home/reshmiB
[reshmiB@webminal.org ~]$echo 'Reshmi'
Reshmi
[reshmiB@webminal.org ~]$man echo

```

Want to use Webminal with other Linux websites? [Launch it](#)

Your terminal login id is: **reshmiB** Please do check your account status under 'Profile'. If that didn't help write to us via email.

Available Lessons: [Select](#)

Just type 'vimtutor', if you want to learn about vim text editor. If you want to change colors, please visit 'play' menu and view first screencast.

ECHO(1) User Commands ECHO(1)

NAME

echo - display a line of text

SYNOPSIS

```

echo [SHORT-OPTION]... [STRING]...
echo LONG-OPTION

```

DESCRIPTION

Echo the STRING(s) to standard output.

```

-n    do not output the trailing newline
-e    enable interpretation of backslash escapes
-E    disable interpretation of backslash escapes (default)

--help display this help and exit
--version
      output version information and exit

```

If -e is in effect, the following sequences are recognized:

```

\\    backslash
\a    alert (BEL)
\b    backspace

```

Manual page echo(1) line 1 (press h for help or q to quit)

Want to use Webminal with other Linux websites? [Launch it](#)

Your terminal login id is: **reshmiB** Please do check your account status under 'Profile'. If that didn't help write to us via email.

Available Lessons: [Select](#)

Just type 'vimtutor', if you want to learn about vim text editor. If you want to change colors, please visit 'play' menu and view first screencast.

The screenshot shows a web browser window with the address bar at `webminal.org/terminal/`. The terminal window displays the following commands and output:

```
[reshmiB@webminal.org ~]$cat >f
reshmi
harshitha[reshmiB@webminal.org ~]$cat >f2
cse
dept
[reshmiB@webminal.org ~]$ls -l
total 8
-rw-rw-r-- 1 reshmiB reshmiB 16 Mar 1 15:25 f
-rw-rw-r-- 1 reshmiB reshmiB 9 Mar 1 15:26 f2
[reshmiB@webminal.org ~]$tail -2 f
reshmi
harshitha[reshmiB@webminal.org ~]$head -1 f
reshmi
[reshmiB@webminal.org ~]$cmp f f2
f f2 differ: byte 1, line 1
[reshmiB@webminal.org ~]$diff f f2
1,2c1,2
< reshmi
< harshitha
\ No newline at end of file
---
> cse
> dept
[reshmiB@webminal.org ~]$wc -w f
2 f
[reshmiB@webminal.org ~]$sort f
harshitha
reshmi
[reshmiB@webminal.org ~]$sort f2
cse
dept
[reshmiB@webminal.org ~]$pr f
```

The sidebar on the right contains navigation links: Home, Play, Profile, FAQ, and Contact Us. Below these links, there is a section titled "Want to use Webminal with other Linux websites?" with a "Launch it" button. Below that, a message states: "Your terminal login id is: **reshmiB** Please do check your account status under 'Profile'. If that didn't help write to us via email." Below this, there is a dropdown menu for "Available Lessons:" and a paragraph of text: "Just type 'vimtutor', if you want to learn about vim text editor. If you want to change colors, please visit 'play' menu and view first screencast."

The screenshot shows a web browser window with the address bar at `webminal.org/terminal/`. The terminal window displays the following commands and output:

```
[reshmiB@webminal.org ~]$sort f2
cse
dept
[reshmiB@webminal.org ~]$pr f
```

The terminal output shows a table with three columns: a date, a file name, and a page number. The table has one row of data:

2021-03-01 15:25	f	Page 1
reshmi		
harshitha		

The sidebar on the right contains navigation links: Home, Play, Profile, FAQ, and Contact Us. Below these links, there is a section titled "Want to use Webminal with other Linux websites?" with a "Launch it" button. Below that, a message states: "Your terminal login id is: **reshmiB** Please do check your account status under 'Profile'. If that didn't help write to us via email." Below this, there is a dropdown menu for "Available Lessons:" and a paragraph of text: "Just type 'vimtutor', if you want to learn about vim text editor. If you want to change colors, please visit 'play' menu and view first screencast."

```
[reshmiB@webminal.org ~]$cut -c1 f
r
h
[reshmiB@webminal.org ~]$paste f f2
reshmi cse
harshitha dept
[reshmiB@webminal.org ~]$join -a1 f f2
reshmi
join: f:2: is not sorted: harshitha
harshitha
[reshmiB@webminal.org ~]$uniq -c f
1 reshmi
1 harshitha
[reshmiB@webminal.org ~]$nl f
1 reshmi
2 harshitha
[reshmiB@webminal.org ~]$tr -s 'h'<f
reshmi
harshitha[reshmiB@webminal.org ~]$date |tee f
Mon Mar 1 15:30:10 CET 2021
[reshmiB@webminal.org ~]$grep andf
[reshmiB@webminal.org ~]$mkdir harahi
[reshmiB@webminal.org ~]$cd harshi
[reshmiB@webminal.org harshi]$cd ~
[reshmiB@webminal.org ~]$rmdir harshi
[reshmiB@webminal.org ~]$cp f f2
[reshmiB@webminal.org ~]$more
Usage: more [options] file...

Options:
-d          display help instead of ring bell
-f          count logical, rather than screen lines
```

```
[reshmiB@webminal.org harshi]$cd ~
[reshmiB@webminal.org ~]$rmdir harshi
[reshmiB@webminal.org ~]$cp f f2
[reshmiB@webminal.org ~]$more
Usage: more [options] file...

Options:
-d          display help instead of ring bell
-f          count logical, rather than screen lines
-l          suppress pause after form feed
-p          do not scroll, clean screen and display text
-c          do not scroll, display text and clean line ends
-u          suppress underlining
-s          squeeze multiple blank lines into one
-NUM        specify the number of lines per screenful
+NUM        display file beginning from line number NUM
+/STRING    display file beginning from search string match
-V          output version information and exit
[reshmiB@webminal.org ~]$mv ff2
mv: missing destination file operand after 'ff2'
Try 'mv --help' for more information.
[reshmiB@webminal.org ~]$chmod
chmod: missing operand
Try 'chmod --help' for more information.
[reshmiB@webminal.org ~]$write reshmi
write: reshmi is not logged in
[reshmiB@webminal.org ~]$wall
[reshmiB@webminal.org ~]$news f
-sh: news: command not found
[reshmiB@webminal.org ~]$news -s
-sh: news: command not found
[reshmiB@webminal.org ~]$
```

**Result:**

Thus the basic Unix commands were executed and outputs were noted.