

ASSIGNMENT-12.1

Name : P.Reshmitha Reddy

Rollno : 2403A510A7

Batch : 05

Course : AI Assisted Coding

Task Description #1 (Sorting – Merge Sort Implementation)

- Task: Use AI to generate a Python program that implements the

Merge Sort algorithm.

- Instructions:

- o Prompt AI to create a function `merge_sort(arr)` that sorts a list in ascending order.

- o Ask AI to include time complexity and space complexity in the function docstring.

- o Verify the generated code with test cases.

- Output:

- o A functional Python script implementing Merge Sort with proper documentation.

Prompt : #generate a Python program that implements the Merge Sort algorithm.

Code :

```

1  def merge_sort(arr):
2      """
3      Sorts a list in ascending order using the Merge Sort algorithm.
4
5      Time Complexity: O(n log n)
6      Space Complexity: O(n)
7      """
8      if len(arr) <= 1:
9          return arr
10
11     mid = len(arr) // 2
12     left = merge_sort(arr[:mid])
13     right = merge_sort(arr[mid:])
14
15     return merge(left, right)
16
17 def merge(left, right):
18     result = []
19     i = j = 0
20
21     while i < len(left) and j < len(right):
22         if left[i] <= right[j]:
23             result.append(left[i])
24             i += 1
25         else:
26             result.append(right[j])
27             j += 1
28
29     result.extend(left[i:])
30     result.extend(right[j:])
31     return result
32
33 # Test cases
34 if __name__ == "__main__":
35     test_cases = [
36         [],
37         [1],
38         [5, 2, 9, 1, 5, 6],
39         [3, 2, 1],
40         [10, -1, 2, 5, 0],
41         [1, 2, 3, 4, 5]
42     ]
43     for arr in test_cases:
44         print(f"Original: {arr} -> Sorted: {merge_sort(arr)}")

```

Output :

```
PS C:\Users\Reshm\Desktop\AIAC> & C:/Users/Reshm/anaconda3/python.exe c:/Users/Reshm/Desktop/
/AIAC/12.1.py
Original: [] -> Sorted: []
Original: [1] -> Sorted: [1]
Original: [5, 2, 9, 1, 5, 6] -> Sorted: [1, 2, 5, 5, 6, 9]
Original: [3, 2, 1] -> Sorted: [1, 2, 3]
Original: [10, -1, 2, 5, 0] -> Sorted: [-1, 0, 2, 5, 10]
Original: [1, 2, 3, 4, 5] -> Sorted: [1, 2, 3, 4, 5]
PS C:\Users\Reshm\Desktop\AIAC>
```

Observation :

The code correctly implements the Merge Sort algorithm using recursion and a helper merge function. The function sorts lists in ascending order and works for empty lists, single-element lists, and lists with duplicate or negative values. The docstring clearly states the time complexity ($O(n \log n)$) and space complexity ($O(n)$). Test cases demonstrate the correctness of the implementation for various input scenarios. The code is readable, modular, and follows good Python practices.

Task Description #2 (Searching – Binary Search with AI Optimization)

- Task: Use AI to create a binary search function that finds a target element in a sorted list.
- Instructions:
 - o Prompt AI to create a function `binary_search(arr, target)` returning the index of the target or -1 if not found.
 - o Include docstrings explaining best, average, and worst-case complexities.
 - o Test with various inputs.

- Expected Output:
- o Python code implementing binary search with AI-generated comments and docstrings.

Prompt : #create a binary search function that finds a target element in a sorted list.

Code :

```
1  def binary_search(arr, target):
2      """
3      Performs binary search to find the index of 'target' in a sorted list 'arr'.
4
5      Best Case Complexity: O(1)    (target is at the middle)
6      Average Case Complexity: O(log n)
7      Worst Case Complexity: O(log n)
8
9      Returns:
10         int: Index of target if found, else -1.
11     """
12     left, right = 0, len(arr) - 1
13
14     # Binary search loop
15     while left <= right:
16         mid = left + (right - left) // 2 # Prevents overflow
17         if arr[mid] == target:
18             return mid # Target found
19         elif arr[mid] < target:
20             left = mid + 1 # Search right half
21         else:
22             right = mid - 1 # Search left half
23     return -1 # Target not found
24
25 # Test cases
26
27 f __name__ == "__main__":
28     test_cases = [
29         ([1, 2, 3, 4, 5], 3),
30         ([10, 20, 30, 40, 50], 25),
31         ([], 1),
32         ([5], 5),
33         ([2, 4, 6, 8, 10], 10),
34         ([1, 3, 5, 7, 9], 1)
35     ]
36     for arr, target in test_cases:
37         print(f"Array: {arr}, Target: {target} -> Index: {binary_search(arr, target)}")
```

Output :

```
PS C:\Users\Reshm\Desktop\AIAC> & C:/Users/Reshm/anaconda3/python.exe c:/Users/Reshm/Desktop/
AIAC/12.1.py
Array: [1, 2, 3, 4, 5], Target: 3 -> Index: 2
Array: [10, 20, 30, 40, 50], Target: 25 -> Index: -1
Array: [], Target: 1 -> Index: -1
Array: [5], Target: 5 -> Index: 0
Array: [2, 4, 6, 8, 10], Target: 10 -> Index: 4
Array: [1, 3, 5, 7, 9], Target: 1 -> Index: 0
PS C:\Users\Reshm\Desktop\AIAC> 
```

Observation :

The code implements binary search efficiently for sorted lists. The docstring clearly explains best ($O(1)$), average, and worst-case ($O(\log n)$) time complexities. The function returns the index of the target if found, or -1 if not found. Test cases cover various scenarios: empty list, single-element list, target present/absent, and edge values. The code is well-commented, readable, and demonstrates correct binary search logic.

Task Description #3 (Real-Time Application – Inventory Management System)

- Scenario: A retail store's inventory system contains thousands of products, each with attributes like product ID, name, price, and stock quantity. Store staff need to:
 1. Quickly search for a product by ID or name.
 2. Sort products by price or quantity for stock analysis.
- Task:
 - o Use AI to suggest the most efficient search and sort

algorithms for this use case.

- o Implement the recommended algorithms in Python.
- o Justify the choice based on dataset size, update frequency, and performance requirements.
- Expected Output:
 - o A table mapping operation → recommended algorithm → justification.
 - o Working Python functions for searching and sorting the inventory.

Prompt :# suggest the most efficient search and sort algorithms for this use case.

Code :

```

1  from typing import List, Dict
2
3  class Product:
4      def __init__(self, product_id: str, name: str, price: float, quantity: int):
5          self.product_id = product_id
6          self.name = name
7          self.price = price
8          self.quantity = quantity
9
10     def __repr__(self):
11         return f"Product(ID={self.product_id}, Name={self.name}, Price={self.price}, Qty={self.quantity})"
12
13     class Inventory:
14         def __init__(self, products: List[Product]):
15             # Hash maps for fast lookup
16             self.id_map: Dict[str, Product] = {p.product_id: p for p in products}
17             self.name_map: Dict[str, Product] = {p.name: p for p in products}
18             self.products = products
19
20         def search_by_id(self, product_id: str):
21             """O(1) average time using hash map."""
22             return self.id_map.get(product_id, None)
23         def search_by_name(self, name: str):
24             """O(1) average time if names are unique."""
25             return self.name_map.get(name, None)
26
27         def sort_by_price(self, reverse=False):
28             """O(n log n) using Timsort."""
29             return sorted(self.products, key=lambda p: p.price, reverse=reverse)
30
31         def sort_by_quantity(self, reverse=False):
32             """O(n log n) using Timsort."""
33             return sorted(self.products, key=lambda p: p.quantity, reverse=reverse)
34
35     # Example usage
36     if __name__ == "__main__":
37         inventory = Inventory([
38             Product("101", "Apple", 0.5, 100),
39             Product("102", "Banana", 0.3, 150),
40             Product("103", "Orange", 0.7, 80),
41             Product("104", "Mango", 1.2, 50)
42         ])
43
44         print("Search by ID '102':", inventory.search_by_id("102"))
45         print("Search by Name 'Mango':", inventory.search_by_name("Mango"))
46         print("Sort by Price:", inventory.sort_by_price())
47         print("Sort by Quantity (descending):", inventory.sort_by_quantity(reverse=True))
48

```

Output :

```
PS C:\Users\Reshm\Desktop\AIAC> & C:/Users/Reshm/anaconda3/python.exe c:/Users/Reshm/Desktop/AIAC/12.1.py
Search by ID '102': Product(ID=102, Name=Banana, Price=0.3, Qty=150)
Search by Name 'Mango': Product(ID=104, Name=Mango, Price=1.2, Qty=50)
Sort by Price: [Product(ID=102, Name=Banana, Price=0.3, Qty=150), Product(ID=101, Name=Apple, Price=0.5, Qty=100), Product
(ID=103, Name=Orange, Price=0.7, Qty=80), Product(ID=104, Name=Mango, Price=1.2, Qty=50)]
Sort by Quantity (descending): [Product(ID=102, Name=Banana, Price=0.3, Qty=150), Product(ID=101, Name=Apple, Price=0.5, Q
ty=100), Product(ID=103, Name=Orange, Price=0.7, Qty=80), Product(ID=104, Name=Mango, Price=1.2, Qty=50)]
PS C:\Users\Reshm\Desktop\AIAC> █
```

Observation :

The code models products with a Product class and manages them in an Inventory class. by product ID or name uses maps (dictionaries), providing fast $O(1)$ average lookup—ideal for large datasets. Sorting by price or quantity uses Python's built-in `sorted()` (Timsort), which is efficient ($O(n \log n)$) and stable. The code is modular, readable, and demonstrates the recommended algorithms for each operation. Test cases show correct search and sort results, validating the implementation for real-world inventory management.