

# Type-guided synthesis for dynamic languages

THOMAS LOGAN

## ACM Reference Format:

Thomas Logan. 2022. Type-guided synthesis for dynamic languages. 1, 1 (October 2022), 1 page. <https://doi.org/10.1145/nnnnnnnn>. nnnnnnnn

## 1 INTRODUCTION

### Background

Some of the most popular programming languages today are dynamic programming languages, which includes Javascript and Python. Javascript is become the language of the web, while Python the most popular for data science and machine learning projects.

Dynamic programming languages can make writing programs quick and easy because they don't require specifying static bounds on behavior. The cost of this efficiency it may be impossible to statically decide if a program is has errors.

Although dynamic languages already offer programming ease and efficiency, it may be possible to increase the ease of writing program by autocompletion, or synthesis of programs from surrounding context.

### Challenge

This article presents a theoretical system that synthesizes terms from context in a dynamic language. In keeping with the spirit of dynamic languages, type annotations are not required, but they are optional.

### Evaluation

---

Author's address: Thomas Logan.

---

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).

© 2022 Association for Computing Machinery.

Manuscript submitted to ACM

Manuscript submitted to ACM