```
// 01-operator.js

// Arithmetic Operator

//Addition
console.log(10+8);

//Sub
console.log(10-8);

// Multiplication
console.log(2*3);

//Division
console.log(10/2); //Return the quotient - 5

//Modulus
console.log(10%3); //Return the reminder - 1

// Assignment operator
// Used to assign values to variables

/*
=
+=
-=
*=
/=
*/

let a = 10
console.log(a+=5); //a = a+5 //10=5 = 15

console.log(a-=10); //a=a-10 //15 -10=5 (as a value is 15 now) //It takes
the previous
//value

console.log(a*=2); //a=a*2 //5*2=10 - a value 5

console.log(a/=4) //a=a/4 //10/4=2.5 - a value 10
console.log(Number(a/=4)); // a=a/4 // 2.5/4 = 0.625

//###Comparison operators
//loose equality (==) => compare only the value
//coercion => convert one datatype to another - type conversion

console.log(2=='2'); //JS convert string datatype into double datatype
and compare the
//value and returns true (It will compare the value, and do coercion -
type conversion)

console.log(2==true); //default value for true is 1, will comapre 2==1,
returns false
console.log(true=='true'); //1==true(as it is boolean string, type
conversion didn't happen)
//(type conversion - true =1), false
console.log(true==true); //1==1
```

```
console.log(1==false); //default value for fales is 0, and it returns
false
console.log(0==false); // false-0, returns true (0==0)

// Mostly we don't use loose equality, we can go for strict equality
//Strict equality (===) => compare both value and datatype, type
conversion will not happen

console.log(2==='2'); //false, as it will compare both value and datatype
console.log(null===undefined); //false, as both are different
console.log(5===5) //true

//###Logical operator - to compare multiple condition
// AND && - all condition should be true (true&&true) => true
// OR || - atleast one condition should be true (true || false) => true
// NOT ! - negative logic (!true) => false

let b = 2, c=6

// &&
console.log(b>c && c>a) //(false && true) = false
console.log(b<c && c>a) //(true && true) = true

// ||
console.log(b>c || c>b) //(false || true) = true
console.log(b<c || c>b) //(true || true) = true

// !
console.log(!(b>c)) //false - but !false = true, true will be printed

//###Unary operator
//Works on single operand, Used for increment or decrement, used for for
loops

//increment => increment the value by 1

//pre increment (++x)

let x =5
// x = 5+1 // first addition operation (increment) happens, just add 1
and then assignment
// happens
console.log(++x) //pre increment, 5+1 = 6

//post increment - x value is 5, it will add the value by 1, it will
// Now x=6 - assignment happens and then increment happens
console.log(x++) //6
console.log(x) //7 // 6+1=7
console.log(x) // 7


// Mostly we use post increment

//pre decrement
let y = 2

console.log(--y) // 1 //2-1 = 1
```

```
//post decrement
console.log(y--) // 1
console.log(y) // 1-1 =0
console.log(y) // 0

output:
6
7
7
1
1
0
0
```