```
//03-looping.js

//loop means - repeat the task until condition become false
// for, while, do while

// for loop - if you know the count or number of iteration, go for, for
loop
//usecase - print the dropdown values (as you know the number of values)
console.log(1)
console.log(2)
console.log(3) // instead of this use for loop to iterate

/* //syntax for loop
for (let index = 0; index < array.length; index++) { //initialization,
condition, iteration
    const element = array[index];

} */

for(let i=0; i<7; i++) {
    console.log(i);
}



//While loop - if you do not know about the number of iterations
//eg: Google, search google, there will be pagination in the bottom,
click next, next etc.,
//usecase: Pagination

//syntax:
/* while (condition) {

} */

let i = 10

while (i<=10) {
    console.log(i);
    i++
}

//do while - not used in automation
// if the condition is not satisfied, it will execute the block of code
atleast once

// login, if yu enter the uname & pwd, then only u will be able to enter

//syntax
/* do {

} while (condition); */

let pin
do {
    pin = 1234 //user enter the pin

    console.log('Please enter your atm pin');
```

```
} while (pin!==1234); //(1234 !== 1234)  // when using !==, we can't use
strict equality

    console.log('pin accepted, welcome!');


/*
Output
1
2
3
0
1
2
3
4
5
6
10
Please enter your atm pin
pin accepted, welcome!
10
*/
```