

A Principled Intermediate Language for JavaScript Verification

Daiva Naudžiūnienė

Imperial College London

Resource Reasoning Meeting

The Team



Philippa
Gardner



Gareth Smith



Thomas
Wood



José Fragoso
Santos



Petar
Maksimović

Running Example: Where is Alice?

```
var Person = function (x) {  
  this.name = x;  
}
```

```
Person.prototype.sayHi = function () {  
  return "Hi! I am " + this.name;  
}
```

```
var alice = new Person("Alice");  
alice.sayHi();
```


Where is Alice?

```
var Person = function (x) {  
  this.name = x;  
}
```

```
Person.prototype.sayHi = function() {  
  return "Hi! I am " + this.name;  
}  
  
var alice = new Person("Alice");  
alice.sayHi();
```

1. Evaluate the function literal and assign to var Person

2. Evaluate the function literal,
and assign to "Person.prototype.sayHi"
3. Create new object
4. Evaluate function body with *this* being an object created in Step 3
5. Assign new object to var alice
6. Call alice.sayHi()



Where is Alice?

```
var Person = function (x) {  
  this.name = x;  
}
```

```
Person.prototype.sayHi = function() {  
  return "Hi! I am " + this.name;  
}
```

```
var alice = new Person("Alice");  
alice.sayHi();
```

1. Evaluate the function literal and assign to var Person


2. Evaluate the function literal,
and assign to "Person.prototype.sayHi"

3. Create new object

4. Evaluate function body with *this* being an object created in Step 3

5. Assign new object to var alice

6. Call `alice.sayHi()`




Where is Alice?

```
var Person = function (x) {  
  this.name = x;  
}  
Person.prototype.sayHi = function() {  
  return "Hi! I am " + this.name;  
}  
var alice = new Person("Alice");  
alice.sayHi();
```

1. Evaluate the function literal and assign to var Person
2. Evaluate the function literal,
and assign to "Person.prototype.sayHi"

3. Create new object

4. Evaluate function body with *this* being an object created in Step 3
5. Assign new object to var alice
6. Call `alice.sayHi()`



Where is Alice?


```
var Person = function (x) {  
  this.name = x;  
}  
  
Person.prototype.sayHi = function() {  
  return "Hi! I am " + this.name;  
}  
  
var alice = new Person("Alice");  
alice.sayHi();
```

1. Evaluate the function literal and assign to var Person
2. Evaluate the function literal,
and assign to "Person.prototype.sayHi"

3. Create new object

4. Evaluate function body with *this* being an object created in Step 3

5. Assign new object to var alice
6. Call alice.sayHi()



Where is Alice?

```
var Person = function (x) {  
  this.name = x;  
}  
Person.prototype.sayHi = function() {  
  return "Hi! I am " + this.name;  
}
```


var alice = new Person("Alice");

alice.sayHi();

1. Evaluate the function literal and assign to var Person
2. Evaluate the function literal,
and assign to "Person.prototype.sayHi"
3. Create new object
4. Evaluate function body with *this* being an object created in Step 3

5. Assign new object to var alice

6. Call alice.sayHi()




Where is Alice?

```
var Person = function (x) {  
  this.name = x;  
}  
Person.prototype.sayHi = function() {  
  return "Hi! I am " + this.name;  
}  
var alice = new Person("Alice");  
alice.sayHi();
```

1. Evaluate the function literal and assign to var Person
2. Evaluate the function literal,
and assign to "Person.prototype.sayHi"
3. Create new object
4. Evaluate function body with *this* being an object created in Step 3
5. Assign new object to var alice

6. Call `alice.sayHi()`



Running Wrong Example: We Cannot Find Alice

```
var Person = function (x) {  
    this.name = x;  
}
```

```
Person.prototype.sayHi = function () {  
    return "Hi! I am " + this.name;  
}
```

```
var alice = Person("Alice");  
alice.sayHi();
```

We cannot find Alice


```
var Person = function (x) {  
  this.name = x;  
}  
  
Person.prototype.sayHi = function() {  
  return "Hi! I am " + this.name;  
}  
  
var alice = Person("Alice");  
alice.sayHi();
```

1. Evaluate the function literal and assign to var Person
2. Evaluate the function literal,
and assign to "Person.prototype.sayHi"

3. Create new object

4. Evaluate function body with *this* being undefined

5. Assign return value to var alice
6. Call alice.sayHi()




Verifying JavaScript Programs

‘Towards a Program Logic for JavaScript’, POPL’12, [Gardner, Maffeis, and Smith](#).

Overall Project

JSVerify: A verification tool for JavaScript programs based on an intermediate language **JSIL**




From ES5 Strict to JSIL - Our choices

We implemented, tested, and proved correct a principled translation from ES5 Strict to JSIL.

JSIL was specifically designed as a **simple** verification language for Javascript:

- ▶ small language;
- ▶ simple semantics;
- ▶ similar memory model to JavaScript's memory model.



Simple goto language:

$$C \in \text{Cmd} \triangleq x := E \\ | \text{skip} | \text{goto } l | \text{goto } [E] \, l_1, l_2$$

l denotes a label and E is an expression with no side effects.

Procedure calls:

$$C \in \text{Cmd} \triangleq \begin{array}{l} x := E \\ | \text{skip} | \text{goto } l | \text{goto } [E] \, l_1, l_2 \\ | x := p(E, \dots, E) \end{array}$$

$$p \in \{E, \text{eval}, \text{built-in-PIId}\}$$

JavaScript heap commands:

$$C \in \text{Cmd} \triangleq \begin{array}{l} x := E \\ | \text{skip} | \text{goto } l | \text{goto } [E] \, l_1, l_2 \\ | x := p(E, \dots, E) \\ | x := \text{new}() | x := \text{hasField}(E, E) \\ | x := [E, E] | [E, E] := E \\ | x := \text{delete}(E, E) \end{array}$$

Prototype-based inheritance:

$$C \in \text{Cmd} \triangleq \begin{array}{l} x := E \\ | \text{skip} | \text{goto } l | \text{goto } [E] \, l_1, l_2 \\ | x := p(E, \dots, E) \\ | x := \text{new}() | x := \text{hasField}(E, E) \\ | x := [E, E] | [E, E] := E \\ | x := \text{delete}(E, E) \\ | x := \text{protoField}(E, E) \\ | x := \text{protoObj}(E, E) \end{array}$$

$C \in \text{Cmd} \triangleq$
 $x := E$
 $| \text{skip} | \text{goto } l | \text{goto } [E] \, l_1, l_2$
 $| x := p(E, \dots, E)$
 $| x := \text{new}() | x := \text{hasField}(E, E)$
 $| x := [E, E] | [E, E] := E$
 $| x := \text{delete}(E, E)$
 $| x := \text{protoField}(E, E)$
 $| x := \text{protoObj}(E, E)$

$\text{Procedure} \triangleq \text{proc } PId(x_1, \dots, x_n) \{$
 $\quad 0: C_0$
 $\quad 1: C_1$
 $\quad \dots$
 $\quad m: C_m$
 $\quad \}$

JSIL Logic versus JS Logic

$$\begin{aligned}
 (1) \mathcal{A}sm \vdash \{P\} \bullet \{R_0 * r \doteq F_I\} \\
 (2) R_0 = \left(S_0 \models \text{This}(F_I, T) \models \gamma(Ls, F_I, F_E) * F_E \neq l_e * \right. \\
 \left. (F_E, @body) \mapsto \lambda X_I, \dots, X_n. e' * (F_E, @scope) \mapsto Ls'_V \right) \\
 (3.1) \mathcal{A}sm \vdash \{R_0\} \bullet \{R_1 * l \doteq Ls_V * r \doteq V_I\} \quad R_1 = S_I * \gamma(Ls_I, V_I, V'_I) \\
 \vdots \\
 (3.m) \mathcal{A}sm \vdash \{R_{m-1}\} \bullet \{R_m * l \doteq Ls_V * r \doteq V_m\} \quad R_m = S_m * \gamma(Ls_m, V_m, V'_m) \\
 (4) \forall j \in \{m+1 \dots n\}. V'_j = \text{undefined} \\
 (5) R'_m = \left(\begin{array}{l} R_m * \exists L. l \doteq L : Ls'_V * \\ (L, X_I) \mapsto V'_I * \\ \vdots \\ (L, X_n) \mapsto V'_n * \\ (L, @this) \mapsto T * \\ (L, @proto) \mapsto \text{null} * \text{defs}(L, e', [X_I, \dots, X_n]) * \\ \text{decls}(e', YS) * \text{newobj}_L(\{ @proto, @this, X_I, \dots, X_n \} \cup YS) \end{array} \right) \\
 (6) \lambda X_1 \dots X_n. \{P_f\} \bullet \{Q_f\} \in \mathcal{A}sm \quad (7) l \notin \text{fv}(Q) \cup \text{fv}(R_m) \\
 (8) \lambda X_1 \dots X_n. \{P_f\} \bullet \{Q_f\} \bullet V'_1 \dots V'_n = \{R'_m\} \bullet \{ \exists L. Q * l \doteq L : Ls'_V \} \\
 \mathcal{A}sm \vdash \{P\} \bullet \{e(e_1, \dots, e_n) \bullet \exists L. Q * l \doteq Ls_V\}
 \end{aligned}$$

JavaScript

**Logic Rules of
Function / Procedure
Call**

JSIL

$$\frac{S(\text{fid}) = \lambda x_1, \dots, x_n. \{P\} m \{Q * \text{ret} \doteq E\} \quad \forall k < j \leq n \ E_j = \text{undefined}}{S \vdash \{P[E_1/x_1, \dots, E_n/x_n]\} x := \text{fid}(E_1, \dots, E_k) \{Q[E_1/x_1, \dots, E_n/x_n] * x \doteq E[E_1/x_1, \dots, E_n/x_n]\}}$$

However...

The complexity of JavaScript does not disappear. It has moved to the code generated by the translation

Back to Example: Where is Alice?

```
var Person = function (x) {  
  this.name = x;  
}
```

```
var alice = new Person("Alice");
```

Translating: Where is Alice in JSIL?

- ▶ The translation generates a top level procedure for each function literal.
- ▶ The translation generates a special procedure `main` for the global code.
- ▶ No nesting of procedures.

JavaScript Code

```
var Person = function (x) { ... }
```

Whole Program

JSIL Code

```
proc PProc(xsc, xthis, x) {...}
```

```
proc main(){...}
```

Translating: Where is Alice in JSIL?

JavaScript Code

```
var Person = function (x) {  
    this.name = x;  
}  
var alice = new Person("Alice");
```

1. Evaluate the function literal

2. Assign function object to var Person
3. Create new object
4. Evaluate function body with
this being an object created in Step 3
5. Assign new object to var alice


JSIL Code

```
xproto := new()  
[xproto, @proto] := lop  
xperson := new()  
[xperson, @code] := "PProc"  
[xperson, @scope] := [lg]  
[xperson, @proto] := lfp  
[xperson, "prototype"] := xproto
```

l_g



x_{person}



Translating: Where is Alice in JSIL?

JavaScript Code

```
var Person = function (x) {  
    this.name = x;  
}
```

```
var alice = new Person("Alice");
```

1. Evaluate the function literal

2. Assign function object to var Person

3. Create new object

4. Evaluate function body with


this being an object created in Step 3

5. Assign new object to var Alice

JSIL Code

$[l_g, \text{"Person"}] := x_{person}$

l_g



Translating: Where is Alice in JSIL?

JavaScript Code

```
var Person = function (x) {  
    this.name = x;  
}  
  
var alice = new Person("Alice");
```


1. Evaluate the function literal
2. Assign function object to var Person

3. Create new object

4. Evaluate function body with
this being an object created in Step 3
5. Assign new object to var alice

JSIL Code

```
 $x_{this} := \text{new}()$   
 $[x_{this}, @proto] := x_{proto}$ 
```




Translating: Where is Alice in JSIL?

JavaScript Code

```
var Person = function (x) {  
    this.name = x;  
}  
  
var alice = new Person("Alice");
```

1. Evaluate the function literal
2. Assign function object to var Person
3. Create new object
4. Evaluate function body with *this* being an object created in Step 3
5. Assign new object to var alice

JSIL Code

$$\begin{aligned}x_{sc} &:= [x_{person}, @scope] \\ x_f &:= [x_{person}, @code] \\ x_{ret} &:= x_f(x_{sc}, x_{this}, \text{"Alice"})\end{aligned}$$


Translating: Where is Alice in JSIL?

JavaScript Code

```
var Person = function (x) {  
    this.name = x;  
}
```

```
var alice = new Person("Alice");
```


1. Evaluate the function literal
2. Assign function object to var Person
3. Create new object
4. Evaluate function body with

this being an object created in Step 3

5. Assign new object to var *alice*

JSIL Code

$[l_g, \text{"alice"}] := x_{this}$



Back to Wrong Example: We Cannot Find Alice

```
var Person = function (name) {  
    this.name = name;  
}
```

```
var alice = Person("Alice");
```

We “forgot” the **new**.

Translating: We Cannot Find Alice

JavaScript Code

```
var Person = function (x) {  
    this.name = x;  
}  
  
var alice = Person("Alice");
```


1. Evaluate the function literal
2. Assign function object to var Person
3. Create new object

4. Evaluate function body with
this being undefined

5. Assign return value to var alice


JSIL Code

```
 $x_{sc} := [x_{person}, @scope]$   
 $x_f := [x_{person}, @code]$   
 $x_{ret} := x_f(x_{sc}, \text{undefined}, \text{"Alice"})$ 
```




Simplifications

Naive translation, but makes soundness proof simple!




Simplifications

Standard **compiler optimizations**, e.g. constant propagation, dead code elimination, algebraic simplifications etc.




Simplifications

Further simplifications using symbolic execution.




Trusted Translation




- ▶ Proven correct with respect to an operational semantics
- ▶ Tested using Test262

Validating the JSIL Compiler

- ▶ We have used ES6 *Test262*
- ▶ Targeted ES5 Strict Subset
Chapters 8-14 except for:
 - ▶ Getters and Setters
 - ▶ Arguments Object
 - ▶ Property attributes
- ▶ We pass **100%** of our targeted ES5 Strict subset



- Program logic for JSIL and a symbolic execution tool based on Separation Logic



JSVerify - Specifying and Verifying the Example

JavaScript Code

```
var Person = function (x) {  
  this.name = x  
}  
var alice = new Person("Alice");
```

JSIL Code

```
{( $x_{this}$ , "name")  $\mapsto$  -}  
PPROC( $x_{sc}$ ,  $x_{this}$ ,  $x$ ) {...}  
{( $x_{this}$ , "name")  $\mapsto$   $x^*$ }  
{ret  $\doteq$  undefined}
```

Specifying and Verifying the Example

Correct Example

$$\left\{ \begin{array}{l} (x_{person}, @scope) \mapsto [l_g]^* \\ (x_{person}, @code) \mapsto \text{"PProc"}^* \\ (x_{this}, \text{"name"}) \mapsto \emptyset \end{array} \right\}$$

$x_{sc} := [x_{person}, @scope]$

$x_f := [x_{person}, @code]$

$x_{ret} := x_f(x_{sc}, x_{this}, \text{"Alice"})$


$$\left\{ \begin{array}{l} (x_{person}, @scope) \mapsto [l_g]^* \\ (x_{person}, @code) \mapsto \text{"PProc"}^* \\ (x_{this}, \text{"name"}) \mapsto \text{"Alice"}^* \\ x_{sc} \doteq [l_g]^* * x_f \doteq \text{"PProc"}^* \\ x_{ret} \doteq \text{undefined} \end{array} \right\}$$

The spec:

$$\{(x_{this}, \text{"name"}) \mapsto _ \}$$

PProc

$$\{(x_{this}, \text{"name"}) \mapsto x * ret \doteq \text{undefined}\}$$



Specifying and Verifying the Wrong Example

Wrong Example

$$\left\{ \begin{array}{l} (x_{person}, @scope) \mapsto [l_g]* \\ (x_{person}, @code) \mapsto \text{"PProc"} \end{array} \right\}$$

$x_{sc} := [x_{person}, @scope]$

$x_f := [x_{person}, @code]$

$x_{ret} := x_f(x_{sc}, \text{undefined}, \text{"Alice"})$


ERROR!

The spec:

$$\{(x_{this}, \text{"name"}) \mapsto -\}$$

PProc

$$\{(x_{this}, \text{"name"}) \mapsto x * ret \doteq \text{undefined}\}$$



Connecting JSIL to other tools

