

# Models on the Peer Models Network

Amin Adibi, Stephanie Harvard, Mohsen Sadatsafavi

2020-06-24



# Contents

<b>1</b>	<b>Introduction</b>	<b>5</b>
<b>2</b>	<b>ACCEPT</b>	<b>7</b>
<b>3</b>	<b>BODE</b>	<b>9</b>
<b>4</b>	<b>CFMortality</b>	<b>11</b>
<b>5</b>	<b>CHDWilson</b>	<b>13</b>
<b>6</b>	<b>CODEXCOPD</b>	<b>15</b>
<b>7</b>	<b>COVIDSEIR</b>	<b>17</b>
<b>8</b>	<b>CVDAnderson</b>	<b>19</b>
<b>9</b>	<b>EPIC</b>	<b>21</b>
<b>10</b>	<b>FEV1</b>	<b>23</b>
<b>11</b>	<b>QRISK3</b>	<b>25</b>
<b>12</b>	<b>API Users' Guide</b>	<b>27</b>
12.1	ACCEPT . . . . .	27
12.2	BODE . . . . .	28
12.3	EPIC . . . . .	28
12.4	FEV1 . . . . .	29

12.5 CVDAnderson . . . . .	29
12.6 CHDWilson . . . . .	30
12.7 CFMortality . . . . .	30
12.8 QRISK3 . . . . .	31
12.9 CODEXCOPD . . . . .	31
12.10COVIDSEIR . . . . .	32

# Chapter 1

## Introduction

This user guide includes information about models hosted on the Peer Models Network.



## Chapter 2

# ACCEPT

Field	Value
Model Name	Acute COPD Exacerbation Prediction Tool (ACCEPT)
Modelling Team	RESP
Publication	doi:10.1016/S2213-2600(19)30397-2
Purpose	Predict probability, rate, and severity of COPD exacerbations
Video	The ACCEPT Model in 90 Seconds
Interviews	Amin Adibi on the ACCEPT Model for COPD: Why and How
Media	COPD exacerbations: finally, a more than ACCEPTable risk score
Web App	ACCEPT web App
R Package	accept
Excel Sheet	PC Version
API User Guide	<a href="#">Link</a>





## Chapter 3

# BODE

Field	Value
Model Name	The Body-Mass Index, Airflow Obstruction, Dyspnea, and Exercise Capacity Index
Modelling Team	Celli et al.
Publication	10.1056/NEJMoa021322
Outcome	Mortality Risk
R Package	bode
API User Guide	<a href="#">Link</a>



## Chapter 4

# CFMortality

Field	Value
Model Name	Mortality prediction models in cystic fibrosis
Modelling Team	Stanojevic et al.
Publication	10.1183/13993003.00224-2019
Outcome	Mortality Risk
Video	
R Package	cfmortality
API User Guide	<a href="#">Link</a>



## Chapter 5

# CHDWilson

Field	Value
Model Name	Prediction of Coronary Heart Disease Using Risk Factor Categories
Modelling Team	Wilson et al.
Publication	10.1161/01.CIR.97.18.1837
Outcome	Coronary Heart Disease
Excel Sheet	PC Version
R Package	chdwilson
API User Guide	<a href="#">Link</a>



## Chapter 6

# CODEXCOPD

Field	Value
Model Name	The CODEX (comorbidity, obstruction, dyspnea, and previous severe exacerbations) Index
Modelling Team	Almagro et al.
Publication	10.1378/chest.13-1328
Outcome	Survival and readmission at both 3 months and 1 year after hospital discharge for a COPD exacerbation
R Package	codexcpd
API User Guide	<a href="#">Link</a>





## Chapter 7

# COVIDSEIR

Field	Value
Model Name	Bayesian SEIR model to estimate physical-distancing effects
Modelling Team	Anderson et al.
Publication	10.1101/2020.04.17.20070086
Outcome	COVID-19 Cases
R Package	covidseir
API User Guide	<a href="#">Link</a>



## Chapter 8

# CVDAnderson

Field	Value
Model Name	Prediction of Coronary Heart Disease Using Risk Factor Categories
Modelling Team	Anderson et al.
Publication	10.1016/0002-8703(91)90861-B
Outcome	CHD, MI, CHD Mortality, Stroke, CVD, CVD Mortalitye
R Package	cvdanderson
API User Guide	<a href="#">Link</a>



## Chapter 9

# EPIC

Field	Value
Model Name	Evaluation Platform in COPD (EPIC)
Modelling Team	RESP
Publication	doi:10.1177%2F0272989X18824098
Outcome	Patient-level outcomes, as well as mortality, prevalence, QALYs, costs, etc.
Video	The EPIC Model in 2 Minutes
Interviews	Mohsen Sadatsafavi on the EPIC Model
R Package	epicR
Excel Sheet	PC Version
API User Guide	Link



## Chapter 10

# FEV1

Field	Value
Model Name	Individualized prediction of lung-function decline in COPD
Modelling Team	RESP
Publication	doi:10.1503/cmaj.151483
Outcome	Lung function over next 11 years
Web App	FEV1 web App
Excel Sheet	PC Version
R Package	fev1
API User Guide	Link





# Chapter 11

## QRISK3

Field	Value
Model Name	10-Year Cardiovascular Disease Risk Calculator
Modelling Team	Hippisley-Cox et al.
Publication	10.1136/bmj.j2099
Outcome	10-yr risk of heart attack/stroke
R Package	QRISK3
API User Guide	<a href="#">Link</a>



## Chapter 12

# API Users' Guide

### 12.1 ACCEPT

#### Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patients provided in the `accept` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("accept", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

#### Cloud Access through Python

```
import json
import requests
url = 'https://prism.peermodelsnetwork.com/route/accept/run'
headers = {'x-prism-auth-user': YOUR_API_KEY}
model_run = requests.post(url, headers=headers,
json = {"func":["prism_model_run"],"model_input":[{"ID": "10001","male": 1,"age": 57,"smoker": 0,
print(model_run)
results = json.loads(model_run.text)
print(results)
```

#### Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: REPLACE_WITH_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"ID": "10001","male": 1,"age": 57,"smo':
https://prism.peermodelsnetwork.com/route/accept/run
```

## 12.2 BODE

### Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `bode` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("bode", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

### Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: REPLACE_WITH_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"FEV1": 40,"mMRC": 3,"BMI": 22,"walk":
https://prism.peermodelsnetwork.com/route/bode/run
```

## 12.3 EPIC

### Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `epicR` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("epic", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

## 12.4 FEV1

### Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `fev1` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("fev1", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

### Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: REPLACE_WITH_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"male":1,"age":70,"smoker":1,"FEV1":2.5,"height":1.75}]}
https://prism.peermodelsnetwork.com/route/fev1/run
```

## 12.5 CVDAnderson

### Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `cvdanderson` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("cvdanderson", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

### Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: REPLACE_WITH_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"age": 33,"gender": 1,"Tchol": 230,"ECG": "Normal"}]}' \
https://prism.peermodelsnetwork.com/route/cvdanderson/run
```

## 12.6 CHDWilson

### Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `chdwilson` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("chdwilson", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

### Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: REPLACE_WITH_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"age": 55,"gender": 1,"Tchol": 250,"LDL": 150}]} \
https://prism.peermodelsnetwork.com/route/chdwilson/run
```

## 12.7 CFMortality

### Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `chdwilson` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("cfmortality", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

## Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: REPLACE_WITH_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"male": 0,"age": 57,"fvc": 66.7,"fev1": 47.4,"fev1_fvc_ratio": 0.7046910804595726}]}'\
https://prism.peermodelsnetwork.com/route/cfmortality/run
```

## 12.8 QRISK3

## Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `QRISK3` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("qrisk3", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

## 12.9 CODEXCOPD

## Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `codexcopd` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("codexcpd", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

## Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: REPLACE_WITH_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"age":40,"charlson":8,"FEV1":40,"mMRC":1}]}'
```

## 12.10 COVIDSEIR

### Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `covidseir` package:

```
library(peermodels)
connect_to_model("covidseir", api_key = YOUR_API_KEY, bypass_router = T)
input <- get_default_input()
names(input)
input$daily_cases
results <- model_run(input)
names(results)
draw_plots()
```

### Cloud Access through Python

```
import json
import requests
api_key = 'YOUR_API_KEY'
url = 'http://model-covidseir.cp.prism-ubc.linaralabs.com/ocpu/library/covidseirPrism/'
headers = {'x-prism-auth-user': 'YDbxcnNHmf4XoteSmCFHKx'}
default_input = requests.post(url, headers=headers, json = {"func":["get_default_input"]})
# json_default_input = json.loads(default_input.json()[0]) # OR:
json_default_input = json.loads(json.loads(default_input.text)[0])
response = requests.post(url, headers=headers, json = {"func":["prism_model_run"], "model_input": json_default_input})
results = json.loads(response.text)
```

### Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: YOUR_API_KEY" \
-d '{"func":["prism_model_run"],"model_input":[{"age":40,"charlson":8,"FEV1":40,"mMRC":1}]}'
```



```
-H "Content-Type: application/json" \  
-d '{"func":["prism_model_run"],"model_input":{"daily_cases":[0,0,1,3,1,8,0,6,5,0,7,7,18,9,22,38,  
} ' \  
http://model-covidseir.cp.prism-ubc.linaralabs.com/ocpu/library/covidseirPrism/R/gateway/json
```