

Models on the Peer Models Network

Amin Adibi, Stephanie Harvard, Mohsen Sadatsafavi

2020-06-24

Contents

1	Introduction	5
2	ACCEPT	7
3	BODE	9
4	CFMortality	11
5	CHDWilson	13
6	CODEXCOPD	15
7	COVIDSEIR	17
8	CVDAnderson	19
9	EPIC	21
10	FEV1	23
11	QRISK3	25
12	API Users' Guide	27
12.1	ACCEPT	27
12.2	BODE	28
12.3	EPIC	28
12.4	FEV1	29

12.5 CVDAnderson	29
12.6 CHDWilson	30
12.7 CFMortality	30
12.8 QRISK3	31
12.9 CODEXCOPD	31
12.10COVIDSEIR	32

Chapter 1

Introduction

This user guide includes information about models hosted on the Peer Models Network.

Chapter 2

ACCEPT

Field	Value
Model Name	Acute COPD Exacerbation Prediction Tool (ACCEPT)
Modelling Team	RESP
Publication	doi:10.1016/S2213-2600(19)30397-2
Purpose	Predict probability, rate, and severity of COPD exacerbations
Video	The ACCEPT Model in 90 Seconds
Interviews	Amin Adibi on the ACCEPT Model for COPD: Why and How
Media	COPD exacerbations: finally, a more than ACCEPTable risk score
Web App	ACCEPT web App
R Package	accept
Excel Sheet	PC Version
API User Guide	Link

Chapter 3

BODE

Field	Value
Model Name	The Body-Mass Index, Airflow Obstruction, Dyspnea, and Exercise Capacity Index
Modelling Team	Celli et al.
Publication	10.1056/NEJMoa021322
Outcome	Mortality Risk
R Package	bode
API User Guide	Link

Chapter 4

CFMortality

Field	Value
Model Name	Mortality prediction models in cystic fibrosis
Modelling Team	Stanojevic et al.
Publication	10.1183/13993003.00224-2019
Outcome	Mortality Risk
Video	
R Package	cfmortality
API User Guide	Link

Chapter 5

CHDWilson

Field	Value
Model Name	Prediction of Coronary Heart Disease Using Risk Factor Categories
Modelling Team	Wilson et al.
Publication	10.1161/01.CIR.97.18.1837
Outcome	Coronary Heart Disease
Excel Sheet	PC Version
R Package	chdwilson
API User Guide	Link

Chapter 6

CODEXCOPD

Field	Value
Model Name	The CODEX (comorbidity, obstruction, dyspnea, and previous severe exacerbations) Index
Modelling Team	Almagro et al.
Publication	10.1378/chest.13-1328
Outcome	Survival and readmission at both 3 months and 1 year after hospital discharge for a COPD exacerbation
R Package	codexcpd
API User Guide	Link

Chapter 7

COVIDSEIR

Field	Value
Model Name	Bayesian SEIR model to estimate physical-distancing effects
Modelling Team	Anderson et al.
Publication	10.1101/2020.04.17.20070086
Outcome	COVID-19 Cases
R Package	covidseir
API User Guide	Link

Chapter 8

CVDAnderson

Field	Value
Model Name	Prediction of Coronary Heart Disease Using Risk Factor Categories
Modelling Team	Anderson et al.
Publication	10.1016/0002-8703(91)90861-B
Outcome	CHD, MI, CHD Mortality, Stroke, CVD, CVD Mortalitye
R Package	cvdanderson
API User Guide	Link

Chapter 9

EPIC

Field	Value
Model Name	Evaluation Platform in COPD (EPIC)
Modelling Team	RESP
Publication	doi:10.1177%2F0272989X18824098
Outcome	Patient-level outcomes, as well as mortality, prevalence, QALYs, costs, etc.
Video	The EPIC Model in 2 Minutes
Interviews	Mohsen Sadatsafavi on the EPIC Model
R Package	epicR
Excel Sheet	PC Version
API User Guide	Link

Chapter 10

FEV1

Field	Value
Model Name	Individualized prediction of lung-function decline in COPD
Modelling Team	RESP
Publication	doi:10.1503/cmaj.151483
Outcome	Lung function over next 11 years
Web App	FEV1 web App
Excel Sheet	PC Version
R Package	fev1
API User Guide	Link

Chapter 11

QRISK3

Field	Value
Model Name	10-Year Cardiovascular Disease Risk Calculator
Modelling Team	Hippisley-Cox et al.
Publication	10.1136/bmj.j2099
Outcome	10-yr risk of heart attack/stroke
R Package	QRISK3
API User Guide	Link

Chapter 12

API Users' Guide

12.1 ACCEPT

Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patients provided in the `accept` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("accept", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

Cloud Access through Python

```
import json
import requests
url = 'https://prism.peermodelsnetwork.com/route/accept/run'
headers = {'x-prism-auth-user': YOUR_API_KEY}
model_run = requests.post(url, headers=headers,
json = {"func":["prism_model_run"],"model_input":[{"ID": "10001","male": 1,"age": 57,"smoker": 0,
print(model_run)
results = json.loads(model_run.text)
print(results)
```

Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: REPLACE_WITH_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"ID": "10001","male": 1,"age": 57,"smo':
https://prism.peermodelsnetwork.com/route/accept/run
```

12.2 BODE

Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `bode` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("bode", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: REPLACE_WITH_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"FEV1": 40,"mMRC": 3,"BMI": 22,"walk":
https://prism.peermodelsnetwork.com/route/bode/run
```

12.3 EPIC

Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `epicR` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("epic", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

12.4 FEV1

Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `fev1` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("fev1", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: REPLACE_WITH_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"male":1,"age":70,"smoker":1,"FEV1":2.5,"height":1.75}]}' \
https://prism.peermodelsnetwork.com/route/fev1/run
```

12.5 CVDAnderson

Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `cvdanderson` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("cvdanderson", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: REPLACE_WITH_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"age": 33,"gender": 1,"Tchol": 230,"ECG": "Normal"}]}' \
https://prism.peermodelsnetwork.com/route/cvdanderson/run
```

12.6 CHDWilson

Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `chdwilson` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("chdwilson", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: REPLACE_WITH_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"age": 55,"gender": 1,"Tchol": 250,"LDL": 150}]} \
https://prism.peermodelsnetwork.com/route/chdwilson/run
```

12.7 CFMortality

Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `chdwilson` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("cfmortality", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: REPLACE_WITH_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"male": 0,"age": 57,"fvc": 66.7,"fev1": 47.4,"fev1_fvc_ratio": 0.7045}]}
https://prism.peermodelsnetwork.com/route/cfmortality/run
```

12.8 QRISK3

Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `QRISK3` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("qrisk3", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

12.9 CODEXCOPD

Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `codexcopd` package:

```
remotes::install_github (resplab/peermodels)
library(peermodels)
connect_to_model("codexcpd", api_key = YOUR_API_KEY)
input <- get_default_input()
results <- model_run(input)
```

Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: REPLACE_WITH_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"age":40,"charlson":8,"FEV1":40,"mMRC":1}]}
https://prism.peermodelsnetwork.com/route/codexcopd/run
```

12.10 COVIDSEIR

Cloud Access through R

Users can access models on the Peer Models Network using the `peermodels` R package, available on GitHub. The following code snippet illustrates how you can run the model for example patient provided in the `covidseir` package:

```
library(peermodels)
connect_to_model("covidseir", api_key = YOUR_API_KEY, bypass_router = T)
input <- get_default_input()
names(input)
input$daily_cases
results <- model_run(input)
names(results)
draw_plots()
```

Cloud Access through Python

```
import json
import requests
url = 'http://model-covidseir.cp.prism-ubc.linaralabs.com/ocpu/library/covidseirPrism/'
headers = {'x-prism-auth-user': 'YOUR_API_KEY'}
default_input = requests.post(url, headers=headers, json = {"func":["get_default_input"]})
# json_default_input = json.loads(default_input.json()[0]) # OR:
json_default_input = json.loads(json.loads(default_input.text)[0])
response = requests.post(url, headers=headers, json = {"func":["prism_model_run"], "model_input": json_default_input})
results = json.loads(response.text)
```

Cloud Access through Linux Bash

In Ubuntu, you can call the API with `curl`:

```
curl \
-X POST \
-H "x-prism-auth-user: YOUR_API_KEY" \
-H "Content-Type: application/json" \
-d '{"func":["prism_model_run"],"model_input":[{"age":40,"charlson":8,"FEV1":40,"mMRC":1}]}
https://prism.peermodelsnetwork.com/route/codexcopd/run
```



```
-d '{"func":["prism_model_run"],"model_input":{"daily_cases":[0,0,1,3,1,8,0,6,5,0,7,7,18,9,22,38,
} ' \
http://model-covidseir.cp.prism-ubc.linaralabs.com/ocpu/library/covidseirPrism/R/gateway/json
```