

STS Aqua-Feed Line

STS PENGUIN



**HVAC
Heat Transfer Fluid
Feed System**

Specified Technical Sales Ltd.

www.specified.ca

Product Brochure PB148 pg.1

STS PENGUIN

Glycol Feed System

Brass Fittings



Features:

- PROPUMPS Pump.
- Manual or Automatic Mode
- Low Level Float Cut Off
- 5-60+ psi Output Pressure
- 4 psi Tight Differential
- Battery Back-up.
- Voltage Meter
- Complete with Accessories
- CE Electronic Adaptor

Benefits:

- Quiet operation with good flow & pressure.
- Precise feed rate control for system size.
- Avoid air injection into system.
- One model covers most pressure ranges.
- No PRV required for installation.
- Portable, runs for many hours w/o AC power.
- Worry free battery condition indication.
- No other installation components required.
- Reliable charge for years of battery life.

DESIGNED FOR HVAC HYDRONIC SYSTEMS

Solar Ready with the addition of your compatible automotive solar charger

Penguin Features

Manufacturer:
Specified Technical Sales Ltd

Tank: Graduated Poly Tank,
20 litre, 5 US gal.

Pump: PROPUMPS
Model FI-2203-1

Capacity 3.1 l/m
0.8 gpm, 5-60+ psi

Controls:
H-O-A, Pressure Demand
with Low Level Cut Off

Optional float for low level
remote alarm contacts

Optional wall mount brackets

Check valve or P.R.V. between
Penguin & hydronic system,
NOT recommended.

Accessories Included



2." Liquid Filled Pressure Gauge



Easy Read Volt Meter



Hand - Off- Auto



Authorized Distributor:



**STS
Aqua-Feed
Line**