

# ProtonDrive Authentication

---

## Overview

---

This application uses **rclone** to authenticate with ProtonDrive. Rclone is a powerful command-line tool that handles the authentication flow securely.

## Authentication Methods

---

ProtonDrive supports two authentication methods through rclone:

### 1. Standard Login (Username + Password)

- Your regular ProtonMail email and password
- Recommended for accounts without 2FA
- Simplest setup process

### 2. Two-Factor Authentication (2FA)

- Required if you have 2FA enabled on your Proton account
- Uses app-specific passwords
- More secure for sensitive data

## Setup Process

---

### First-Time Configuration

The application provides a guided setup wizard:

#### 1. Launch Setup:

```
bash
```

```
./run.sh
```

- The wizard appears automatically on first run
- Or manually trigger via “Configure ProtonDrive” button

#### 2. Rclone Configuration Opens:

- A terminal window launches automatically
- You’ll see the rclone interactive configuration

#### 3. Follow Rclone Prompts:

```
n) New remote
```

```
name> protondrive
```

```
Storage> protondrive
```

#### 4. Enter Credentials:

- **If no 2FA:** Enter username and password
- **If 2FA enabled:** See section below

#### 5. Verify Connection:

- The application will test the connection
- You’ll see a success message when ready

## Authentication with 2FA

If you have Two-Factor Authentication enabled:

### Step 1: Generate App Password

1. **Log into ProtonMail web interface**
2. **Navigate to Settings:**
  - Click on your profile (top-right)
  - Go to "Account" → "Security"
3. **Create App Password:**
  - Find "App passwords" section
  - Click "Create app password"
  - Give it a name (e.g., "Rclone Sync")
  - Copy the generated password
4. **Save Securely:**
  - Store in a password manager
  - You cannot view it again after closing

### Step 2: Use App Password in Rclone

```
Username: your-email@protonmail.com
Password: [paste app password here]
```

**Important:** Use the app password, NOT your regular password!

## Security Considerations

### Password Storage

Rclone stores credentials securely:

#### Location:

```
~/.config/rclone/rclone.conf
```

#### Encryption:

- Passwords are obscured by default
- For additional security, use rclone's password encryption:

```
bash
```

```
rclone config password
```

#### Permissions:

```
chmod 600 ~/.config/rclone/rclone.conf
```

## Best Practices

1. **Use App Passwords:**
  - Even if 2FA is optional, app passwords are more secure

- Allows revocation without changing main password
- Limits scope of access

## 2. **Enable 2FA:**

- Protect your Proton account with 2FA
- Prevents unauthorized access
- Use TOTP apps (Authy, Google Authenticator, etc.)

## 3. **Secure Configuration:**

- Keep rclone.conf file private
- Don't share or commit to version control
- Back up securely (encrypted)

## 4. **Regular Review:**

- Periodically check active app passwords
- Revoke unused passwords
- Update if compromised

## 5. **Network Security:**

- Use trusted networks
- Consider VPN for public Wi-Fi
- All ProtonDrive traffic is encrypted

# Troubleshooting Authentication

---

## Problem: Login fails with correct credentials

### Possible causes:

- 2FA is enabled but using regular password
- App password expired or revoked
- Account locked or suspended

### Solutions:

1. Verify 2FA status in Proton account
2. Generate new app password
3. Check Proton account status
4. Test login on ProtonMail web interface

## Problem: Terminal doesn't open for configuration

### Solutions:

#### 1. Manual configuration:

```
bash
```

```
rclone config
```

#### 2. Check terminal emulator:

```
bash
```

```
which gnome-terminal konsole xterm
```

#### 3. Install terminal:

```
```bash
```

```
# Arch/CachyOS
```

```
sudo pacman -S gnome-terminal
```

```
# Ubuntu/Debian
sudo apt install gnome-terminal
...
```

## Problem: “No remotes found” error

### Solutions:

1. Run configuration wizard again
2. Manually configure rclone:

```
bash
```

```
rclone config
```

3. Verify remote exists:

```
bash
```

```
rclone listremotes
```

## Problem: Authentication works but can't list files

### Possible causes:

- Network connectivity issues
- ProtonDrive API temporary outage
- Rate limiting

### Solutions:

1. Check internet connection
2. Verify ProtonDrive web access
3. Wait a few minutes and retry
4. Check rclone verbose output:

```
bash
```

```
rclone lsd protondrive: -vv
```

## Manual Rclone Configuration

---

If the wizard doesn't work, configure manually:

### Step-by-Step Manual Setup

1. **Open terminal:**

```
bash
```

```
rclone config
```

2. **Create new remote:**

```
n) New remote
```

```
name> protondrive
```

3. **Select ProtonDrive:**

```
Storage> protondrive
```

(Type the number corresponding to ProtonDrive)

4. **Enter username:**

```
username> your-email@protonmail.com
```

5. **Enter password:**

```
password> [your-password-or-app-password]
```

**6. Configure advanced options (optional):**

```
Edit advanced config? (y/n)
n
```

**7. Save configuration:**

```
y) Yes this is OK
q) Quit config
```

**8. Test connection:**

```
bash
rclone lsd protondrive:
```

## Reconfiguring Authentication

---

To update credentials or reconfigure:

### Method 1: Application Interface

1. Open the application
2. Go to “Settings” tab
3. Click “Configure ProtonDrive”
4. Follow the wizard

### Method 2: Command Line

```
rclone config reconnect protondrive:
```

### Method 3: Complete Reconfiguration

```
rclone config delete protondrive
rclone config
```

## Environment Variables

---

For automated setups, you can use environment variables:

```
export RCLONE_CONFIG_PROTODRIVE_TYPE=protondrive
export RCLONE_CONFIG_PROTODRIVE_USERNAME=your-email@protonmail.com
export RCLONE_CONFIG_PROTODRIVE_PASSWORD=your-app-password
```

**Warning:** Be cautious with passwords in environment variables!

## Token Refresh

---

ProtonDrive authentication tokens:

- Are managed automatically by rclone
- Refresh before expiration
- Should not require manual intervention

If you experience frequent authentication prompts:

1. Check system clock accuracy

2. Verify internet stability
3. Consider recreating the remote

## Multi-Account Support

---

To use multiple ProtonDrive accounts:

1. **Create additional remotes:**

```
bash
rclone config
# Create: protondrive-personal, protondrive-work, etc.
```

2. **Configure application:**

- Edit `~/.config/protondrive-sync/config.json`
- Change `remote_name` to desired remote

3. **Or run multiple instances:**

- Use different configuration directories
- Set `XDG_CONFIG_HOME` environment variable

## See Also

---

- [ProtonDrive Setup Guide](#) (`../setup/PROTONDRIVE_SETUP.md`)
- [Selective Sync Documentation](#) (`selective-sync.md`)
- [Rclone Official Documentation](https://rclone.org/protondrive/) (`https://rclone.org/protondrive/`)
- [Proton Account Security Settings](https://account.proton.me/security) (`https://account.proton.me/security`)