

PageRank Algorithm

Guxiao Hu, Puyuan Zhang, Xiu Chen, Zipei Zhu

Saturday 6th December, 2025

Table of Contents

- 1 Introduction
- 2 Algorithm Overview
- 3 Computing PageRank
- 4 Mechanisms
- 5 Applications and Extensions
- 6 Ending

How do search engines work?

*You are an engineer in **Gugloo** designing a search engine in the 1990s.
Consider: how to rank results for each query?*

How do search engines work?

*You are an engineer in **Gugloo** designing a search engine in the 1990s.*
Consider: how to rank results for each query?

- Relevance

How do search engines work?

*You are an engineer in **Gugloo** designing a search engine in the 1990s.*

Consider: how to rank results for each query?

- Relevance
 - NLP-focused approaches. May be discussed at the end of this pre (also linear-algebra heavy!).

How do search engines work?

*You are an engineer in **Gugloo** designing a search engine in the 1990s.*

Consider: how to rank results for each query?

- Relevance
 - NLP-focused approaches. May be discussed at the end of this pre (also linear-algebra heavy!).
- Importance

How do search engines work?

*You are an engineer in **Gugloo** designing a search engine in the 1990s.*

Consider: how to rank results for each query?

- Relevance
 - NLP-focused approaches. May be discussed at the end of this pre (also linear-algebra heavy!).
- Importance
 - Sorting on accessing counts?

How do search engines work?

*You are an engineer in **Gugloo** designing a search engine in the 1990s.*

Consider: how to rank results for each query?

- Relevance
 - NLP-focused approaches. May be discussed at the end of this pre (also linear-algebra heavy!).
- Importance
 - Sorting on accessing counts?

PageRank algorithm focuses on *how important* each webpage is.

The “Random Surfer” Model

The PageRank algorithm

- iterates on a **graph** where webpages are **nodes**, and links are **directed edges**,
- calculates the probability of a “random surfer” visiting each webpage,
- outputs a probability distribution vector.

$$\mathbf{p} = [\text{Pr}(1) \quad \text{Pr}(2) \quad \dots \quad \text{Pr}(n)]^T$$

Algorithm

Notations and Conventions

- Let n denote the number of nodes (i.e. total number of webpages).
- Let $\deg^+(u)$ denote the **out degree** of node u (i.e. number of outreaching links on webpage u).

Definition

Google PageRank^a iteration: Initially, $\Pr(i) := 1/n$ for each webpage $1 \leq i \leq n$. Then iterate by


$$\Pr(v) := (1 - d) \frac{1}{n} + d \sum_{\text{edge } u \rightarrow v} \frac{1}{\deg^+(u)} \Pr(u)$$

where d is the **damping factor** ($0 < d < 1$).

^aTrademark of Google; U.S. patent 6,285,999.

Computing PageRank

- A node is important if important nodes point to it.
- A node contributes part of its importance to the nodes it points to.



A Simplified Model

Let **transition matrix**

$$\mathcal{M}_{ij} := \begin{cases} \frac{1}{\deg^+(j)} & \text{edge } j \rightarrow i \\ 0 & \text{otherwise} \end{cases}$$

i.e., given **adjacent matrix** $A_{ij} = [\text{edge } i \rightarrow j]$ and diagonal matrix K with the outdegrees in the diagonal,

$$\mathcal{M} := (K^{-1}A)^\top$$

Definition

Let **probability distribution vector** of the k -th iteration be

$$\mathbf{p}(k) := [\text{Pr}(1) \quad \text{Pr}(2) \quad \dots \quad \text{Pr}(n)]^T$$

which is initially set to

$$\mathbf{p}(0) := [1/n \quad 1/n \quad \dots \quad 1/n]^T$$

Matrix Algebra III

Definition

The **Google matrix** $\widehat{\mathcal{M}}$ is defined by

$$\widehat{\mathcal{M}} := d\mathcal{M} + \frac{1-d}{n}E$$

where E is $n \times n$ matrix of all ones (so that $E\mathbf{p} = \mathbf{1}$), and $0 < d < 1$ is the damping factor.

The Power Method

Google PageRank can be computed by

$$\mathbf{p}(k+1) = \widehat{\mathcal{M}}\mathbf{p}(k)$$

One may assume PageRank converges after $|\mathbf{p}(t) - \mathbf{p}(t-1)| < \epsilon$.

PageRank and Eigenvectors

Recall the equation

$$\boldsymbol{p}(k+1) = \widehat{\mathcal{M}} \boldsymbol{p}(k)$$

PageRank and Eigenvectors

Recall the equation

$$\begin{aligned} \mathbf{p}(k+1) &= \widehat{\mathcal{M}} \mathbf{p}(k) \\ \Rightarrow \mathbf{p} &= \widehat{\mathcal{M}} \mathbf{p} \quad (\text{when converged}) \end{aligned}$$

PageRank and Eigenvectors

Recall the equation

$$\begin{aligned} p(k+1) &= \widehat{\mathcal{M}} p(k) \\ \Rightarrow p &= \widehat{\mathcal{M}} p \quad (\text{when converged}) \end{aligned}$$

Iteration is “finding a vector that remains unchanged by linear transformation $\widehat{\mathcal{M}}$ ”.

PageRank and Eigenvectors

Recall the equation

$$\begin{aligned} p(k+1) &= \widehat{\mathcal{M}} p(k) \\ \Rightarrow p &= \widehat{\mathcal{M}} p \quad (\text{when converged}) \end{aligned}$$

Iteration is “finding a vector that remains unchanged by linear transformation $\widehat{\mathcal{M}}$ ”.

Definition

v is the **eigenvector**, and λ is the **eigenvalue** of matrix A , if

$$Av = \lambda v$$

PageRank and Eigenvectors

Recall the equation

$$\begin{aligned} p(k+1) &= \widehat{\mathcal{M}} p(k) \\ \Rightarrow p &= \widehat{\mathcal{M}} p \quad (\text{when converged}) \end{aligned}$$

Iteration is “finding a vector that remains unchanged by linear transformation $\widehat{\mathcal{M}}$ ”.

Definition

v is the **eigenvector**, and λ is the **eigenvalue** of matrix A , if

$$Av = \lambda v$$

In fact, p is the **principal eigenvector** of the Google matrix $\widehat{\mathcal{M}}$, and 1 is the corresponding eigenvalue (i.e. the eigenvalue with the largest magnitude).

Properties

Fact

- Both \mathcal{M} and $\widehat{\mathcal{M}}$ are **column-stochastic** (sums of each column are 1), positive.

$$\sum_i \widehat{M}_{ij} = 1 \ (\forall j) \iff \mathbf{1}^\top \widehat{M} = \mathbf{1}^\top$$

($\mathbf{1}^\top$ is a left eigenvector with eigenvalue 1 \Rightarrow 1 is an eigenvalue of $\widehat{\mathcal{M}}$)

- Both \mathcal{M} and $\widehat{\mathcal{M}}$ are positive matrices.

By the **Perron–Frobenius theorem**,

- all other eigenvalues λ_i satisfy $|\lambda_i| < 1$,
- the corresponding eigenvector \mathbf{r} has all positive entries.

A View on Probability

Matrix multiplication \rightarrow updating probability distribution vector.

A View on Probability

Matrix multiplication \rightarrow updating probability distribution vector.

Reason to use the damping factor?

A View on Probability

Matrix multiplication \rightarrow updating probability distribution vector.

Reason to use the damping factor? To avoid trapping (jumping across several pages forever).

A View on Probability

Matrix multiplication \rightarrow updating probability distribution vector.

Reason to use the damping factor? To avoid trapping (jumping across several pages forever).

- With a probability of d , “random surfing” continues;
 - Each u has equal chance $1/\deg^+(u)$ to redirect to v
- with a probability of $1 - d$, surfer redirects to another random page.
 - Each of the n pages has equal chance to redirect to the current page.

A View on Probability

Matrix multiplication \rightarrow updating probability distribution vector.

Reason to use the damping factor? To avoid trapping (jumping across several pages forever).

- With a probability of d , “random surfing” continues;
 - Each u has equal chance $1/\deg^+(u)$ to redirect to v
- with a probability of $1 - d$, surfer redirects to another random page.
 - Each of the n pages has equal chance to redirect to the current page.

$$\mathbb{P}(\text{arriving at } v \mid \text{arriving at } u) := (1 - d) \frac{1}{n} + d \sum_{\text{edge } u \rightarrow v} \frac{1}{\deg^+(u)} \mathbb{P}(\text{arriving at } u)$$

Generalizing *importance*.

Generalizing *importance*.

- Evaluating academic papers based on citations.
- Determine species that are essential to the continuing health of ecosystems.
- Ranking performance of sports teams.
- ...

Further Reading I

Suggested topics for further reading:

Topic

PageRank is actually a variation of **the Markov Chains**.

Fact

Random walk which is

- **irreducible**: with probability of $1/d$, surfer can reach any node with one step \Rightarrow all nodes are reachable ($\Pr > 0$) to the surfer.
- **aperiodic**: with probability of d , surfer stops on their current page \Rightarrow no fixed-length cycles in transition
- **positive recurrent**: expected return time to any node is finite

converges to a stationary distribution.

Question

Will the simplified model $\mathbf{p}(k+1) = \mathcal{M}\mathbf{p}(k)$ we defined before always converge?

Question

Will the simplified model $\mathbf{p}(k+1) = \mathcal{M}\mathbf{p}(k)$ we defined before always converge?

If not, what will happen and why? Construct test-cases to prove.

Topic

Some Easy Ways to Briefly Analyze “Relevance”:

- Word frequency (TF / TF-IDF)
- Proximity scoring (word vectors)
- Matching phrases (bags-of-words)
- ...

Thanks!