JOURNAL OF INFORMATION AND COMMUNICATION TECHNOLOGY
https://e-journal.uum.edu.my/index.php/jict

How to cite this article:
Nagulwar, S., Ansari, I., Bharati, C. R., Zanwar, R., & Raut, U. (202X). AI-driven fraud detection in financial transactions: A comparative study of machine learning, deep learning, and explainable AI techniques. *Journal of Information and Communication Technology, XX*(X), XX-XXX. https://doi.org/10.32890/jict202X.XX.X.X

AI-Driven Fraud Detection in Financial Transactions: A Comparative Study of Machine Learning, Deep Learning, and Explainable AI Techniques

[1]Sahish Nagulwar, [2]Ibrahim Ansari, [3]Chayan Raj Bharati, [4]Raghav Zanwar & [5]Umesh Raut

[1,2,3,4,5]Department of Computer Engineering and Technology, Dr. Vishwanath Karad MIT World Peace University, Pune, India

[1]sahish.nagulwar@mitwpu.edu.in
[2]ibrahim.ansari@mitwpu.edu.in
[3]chayan.bharati@mitwpu.edu.in
[4]raghav.zanwar@mitwpu.edu.in
[*5]umesh.raut@mitwpu.edu.in
*Corresponding author

Received: DD/MM/YYYY Revised: DD/MM/YYYY Accepted: DD/MM/YYYY Published: DD/MM/YYYY

ABSTRACT

Financial fraud has grown with the digitisation of payments, and rule-based controls cannot keep pace with patterns that change faster than rules can be rewritten. This paper surveys twenty-five recent studies on machine learning (ML), deep learning (DL), graph-based, and explainable artificial intelligence (XAI) approaches to fraud detection in financial transactions, and organises them in a five-dimension framework: detection technique, dataset, class-imbalance handling, interpretability, and real-time feasibility. Three gaps recur: the absence of present-day benchmark datasets, weak evaluation of zero-day robustness, and limited cross-institution data sharing. As our proposed solution, we put forward a four-layer hybrid detection architecture that combines a deterministic pre-filter, calibrated boosted scoring, relational graph escalation, and natively interpretable explanation. A preliminary validation on the 2013 European cardholder dataset shows that explanation produced in the same pass as the score costs under 7 ms per transaction, against over 380 ms for a bolted-on model-agnostic explainer, and that layered escalation confines graph inference to under 0.2% of transaction volume. We then extend the architecture with Relational-Anomaly Augmented Boosting (RAAB), which injects time-respecting entity-risk features and autoencoder novelty features into the scoring model. Under a zero-day protocol in which 30% of test fraud follows a pattern absent from training, RAAB raises the area under the precision-recall curve from 0.41 to 0.91 and recall on the unseen pattern from 0% to 44%, at 5.7 ms per transaction. Relational history and novelty are more valuable inside the scoring model than after it, and regulatory auditability need not cost real-time feasibility.

Keywords: class imbalance, explainable AI, financial fraud detection, graph neural networks, zero-day detection

INTRODUCTION

The shift from cash to digital rails (cards, wallets, real-time bank transfers, and UPI-style instant payments) has expanded the attack surface available to fraudsters. Global payment-card fraud losses grew from roughly USD 9.8 billion in 2011 (The Nilson Report, 2013) to USD 32.3 billion in 2021 (The Nilson Report, 2022). At the same time, transaction volumes have reached a scale, millions of transactions per day for a mid-sized processor, that makes manual review of even a small fraction economically infeasible. A bank that once relied on analysts checking flagged cases overnight now has to decide within the few seconds that instant-payment rails allow for funds availability (Federal Reserve, 2023), and within the sub-second window of a card authorisation. That is a different engineering problem from the batch-review workflows of a decade ago.

Traditional fraud controls rely on deterministic rules: velocity limits, blacklists, and fixed spending thresholds. These rules are transparent and cheap to evaluate, but brittle. A rule tuned to last month's fraud pattern is of limited use against this month's, and fraud rings actively probe for the thresholds a rule enforces. Once a threshold becomes known, it stops being a control and becomes a target to route around. This has motivated a large literature on supervised and unsupervised ML for fraud detection, framed as binary classification or anomaly detection over transaction, account, and behavioural features.

Two properties make this a distinctive applied-ML problem. First, fraud is rare: legitimate transactions outnumber fraudulent ones by several hundred to one, so a classifier trained on raw class frequencies collapses to the majority class and reports high accuracy while catching almost nothing. Second, fraud detection is a regulated activity. Supervisory guidance such as SR 11-7 / OCC Bulletin 2011-12 (Board of Governors & OCC, 2011) requires that models used for high-risk financial decisions be validated, auditable, and explainable, which is in direct tension with the black-box nature of the deep models that often achieve the best raw accuracy. A model that cannot explain why it blocked a transaction is, in many regulatory contexts, not a model a bank may deploy.

Both types of classification error carry an immediate, quantifiable business cost. Every point of missed fraud is a reimbursement cost for banks and card networks; every false positive is a legitimate customer declined at the point of sale, which, repeated often enough, drives that customer to a competitor. Fraud detection is therefore one of the few ML problems where the cost matrix is explicit, which is part of why the field has produced such a dense body of applied research.


This paper reviews the literature that has grown around these two tensions: rare-event learning versus standard classification assumptions, and predictive accuracy versus regulatory explainability. Our contributions are: (1) a structured survey of twenty-five recent studies spanning classical ML, deep and graph-based learning, and XAI approaches; (2) a comparison framework that scores each technique family along detection technique, dataset, class-imbalance handling, interpretability, and real-time feasibility; (3) our proposed solution, a four-layer hybrid detection architecture motivated by the open problems the survey surfaces (Figure 3, Table 3); (4) a preliminary validation of our proposal, implemented and evaluated alongside one representative model from each family under a common harness (Table 4, Figures 4 and 5); and (5) Relational-Anomaly Augmented Boosting (RAAB), a proposed extension of that architecture for zero-day detection, which injects relational-risk and novelty features into the scoring model and is evaluated under a zero-day protocol (Tables 5 and 6, Figure 6). The remainder of the paper is organised as follows. The Related Works section surveys the literature. The Research Methodology section describes the review methodology. The Analysis and Discussion section presents the comparative analysis. The Proposed Method section sets out our proposed solution, the hybrid detection architecture. The Evaluation and Results section reports the preliminary validation of our proposal. The RAAB for Zero-Day Detection section extends the proposal with Relational-

Anomaly Augmented Boosting for zero-day detection and evaluates it. The Threats to Validity section discusses threats to validity, and the Conclusion section concludes.

RELATED WORKS

Figure 1 gives the taxonomy that organises this section: four technique families (classical ML, boosted ensembles and deep learning, graph-based methods, and explainable-AI hybrids) with three constraints drawn across all of them (class imbalance, real-time latency, and regulatory auditability). the subsections that follow review each thread in turn, and the Synthesis of the Taxonomy subsection returns to Figure 1 to read the taxonomy as a whole. Table 2 in the Analysis and Discussion section then scores the same families on the five survey dimensions.

Figure 1
Taxonomy of the AI-driven fraud detection technique families covered in this survey



Classical Machine Learning Approaches

The earliest and still most widely deployed fraud-detection models are classical supervised classifiers. Comparative studies have evaluated logistic regression, decision trees, random forest, k-nearest neighbours (KNN), support vector machines, and Naive Bayes on public card-transaction data, generally finding that ensemble tree methods such as random forest outperform single-model baselines on precision and recall (Ganesan et al., 2025; A. Gupta et al., 2022; K. Gupta et al., 2022; Kumar & Iqbal, 2019; Lakshmi et al., 2023; Popat & Chaudhary, 2018; T S et al., 2023). A systematic review found that dimensionality reduction by principal component analysis (PCA) is used both to speed up training and to anonymise cardholder features before public release (Lakshmi et al., 2023). That anonymisation matters for reproducibility: it lets researchers publish comparable results without exposing cardholder data, but it hides the feature semantics that fraudsters exploit from anyone re-training the model. Survey papers position these classical methods as the baseline against which newer deep and graph-based methods must be measured (Ghosh Dastidar et al., 2024; Pathak & Beniwal, 2025): a sophisticated model that cannot beat a well-tuned random forest on the same data is hard to justify in production.

Deep Learning and Ensemble Methods

Beyond classical classifiers, the literature reports gains from gradient-boosted ensembles (XGBoost, LightGBM, CatBoost) and from deep sequence models such as LSTM-based classifiers and CNN detectors that treat a transaction's feature vector as a fixed-size input (Alarfaj et al., 2022; Sariat et al.,

2025). A comparison of CatBoost, XGBoost, and LightGBM under a fixed preprocessing pipeline found CatBoost marginally ahead, with all three within four F1 points of one another (Xiao et al., 2025), which is consistent with the broader observation that data preparation and resampling are a larger lever on final performance than the choice of boosting library (Ghosh Dastidar et al., 2024). Zhao et al. (2024) proposed a modified LightGBM objective tuned for the extreme imbalance ratios of production fraud data, reporting improved minority-class recall without a large precision penalty.

Graph-Based and Relational Approaches

A transaction is rarely an isolated event. Fraud rings reuse devices, IP addresses, shipping addresses, and mule accounts across many transactions, a relational signal that a row-wise classifier cannot see. This has motivated graph neural network (GNN) approaches that model accounts, devices, and merchants as nodes and transactions as edges. Alarfaj and Shahzadi (2025) combined a GNN with a Lambda-architecture streaming pipeline for real-time scoring and an autoencoder for reconstruction-error anomaly scoring, validated on case studies from two banks. A review of graph learning for financial fraud catalogues heterogeneous graph attention networks and dynamic GNNs for anti-money-laundering and cash-out detection, and notes that most published GNN fraud detectors are evaluated on synthetic or single-institution graphs rather than realistic multi-institution networks (Cheng et al., 2025). This is a meaningful limitation, since the coordinated, multi-account rings that GNNs are best suited to catch are exactly the pattern that crosses institutional boundaries.

Explainable AI and Regulatory Compliance

Because regulators require an auditable rationale for any blocked or flagged transaction, a substantial recent strand couples high-accuracy models with post-hoc explanation methods such as SHAP (Lundberg & Lee, 2017) and LIME (Ribeiro et al., 2016). Almalki and Masud (2025) combined a stacking ensemble of XGBoost, LightGBM, and CatBoost with LIME, partial dependence plots, and permutation feature importance, reporting 99% accuracy and 0.99 AUC-ROC on the IEEE-CIS dataset while retaining per-prediction explanations. Shah (2025) proposed a scalable explainable pipeline built on SHAP-style attribution for transaction-level decisions, and a further study frames XAI as a trust-and-transparency layer for financial decision-making rather than a diagnostic tool (Kapale et al., 2024). Aljunaid et al. (2025) combined federated learning, so that no single bank centralises raw customer data, with an XAI layer and hybrid resampling, reporting an F1-score of 0.92 and an AUC-ROC of 1.00 on their evaluation set; an AUC of exactly 1.00 on a held-out set should be read with caution, as it is more often a sign of leakage or an easy split than of a perfect detector. A related line of work maps the interpretability requirement onto named regulatory instruments, arguing that a highly accurate model that cannot explain a specific flagged transaction is, from a compliance standpoint, not deployable (Uddin, 2026).

Handling Class Imbalance

Because fraudulent transactions are a small fraction of the total, nearly every surveyed study reports some form of imbalance handling: SMOTE-family oversampling (Chawla et al., 2002), majority-class undersampling, cost-sensitive loss weighting, or hybrid resampling such as the K-means-SMOTE-ENN scheme used by Aljunaid et al. (Aljunaid et al., 2025). Baisholan et al. (2025) proposed FraudX AI, an interpretable framework designed to remain accurate under severe imbalance without relying heavily on synthetic minority oversampling, which can introduce unrealistic fraud patterns into training. Zhao et al.'s LightGBM variant targets the same problem at the algorithmic level rather than the data level (Zhao et al., 2024). Together these approaches suggest a rough consensus: imbalance is best handled by moderate resampling combined with a loss that already penalises minority-class false negatives, rather than by resampling alone.

Real-Time and Streaming Constraints

A fraud decision that arrives after a payment has settled is of limited value. Streaming architectures that combine a fast deterministic rules layer, a calibrated ML scoring layer, and a slower graph-based layer for organised rings have been proposed to reconcile accuracy with sub-second latency budgets (R. Gupta et al., 2024). Alessi and Fugini (2026) model the stochastic delay in obtaining verified fraud labels, a constraint absent from static benchmarks, and couple it with a dynamic decision-threshold manager that rebalances precision and recall as conditions drift. Ismail and Karaarslan (2026) target the harder zero-day case, where a fraud pattern has no historical precedent, using a generative model of the legitimate-transaction manifold to flag reconstruction-error outliers within a sub-50 ms budget. A recent review of deep learning in financial fraud detection frames real-time capability, auditability, and cross-sector transferability as the three axes on which future infrastructure should be judged (Chen et al., 2026).

Synthesis of the Taxonomy

Figure 1 summarises the six threads above as a single taxonomy. Read left to right, it roughly tracks the order in which the techniques entered the literature: classical models first, boosted ensembles as gradient-boosting libraries matured (Ke et al., 2017), graph methods once relational signals were recognised as under-exploited, and XAI wrappers once regulators began asking hard questions about models already in deployment. The bottom banner (class-imbalance handling, real-time latency, and regulatory auditability) is drawn across every branch because, as the Handling Class Imbalance subsection, the Real-Time and Streaming Constraints subsection, and the Explainable AI and Regulatory Compliance subsection show, none of the four families is exempt from these constraints; they satisfy them to different degrees, which is what Table 2 in the Analysis and Discussion section makes comparable.

RESEARCH METHODOLOGY

This paper follows a systematic literature survey methodology rather than an original implementation as its primary method, consistent with a comparative-study problem selection; the implementation in the Evaluation and Results section is a preliminary check on the survey's conclusions, not the paper's main contribution. Candidate papers were identified by structured keyword search, combining "fraud detection", "financial transactions", "machine learning", "deep learning", "graph neural network", and "explainable AI", across IEEE Xplore, Elsevier ScienceDirect, ACM Digital Library, Springer Link, and arXiv for 2025-2026 work not yet indexed elsewhere. Results were screened first by title and abstract and then, for anything not obviously out of scope, by a full read of the methodology and results sections.

Inclusion required that a paper (i) address fraud, anomaly, or intrusion detection within a financial-transaction context; (ii) describe a concrete ML, DL, graph-based, or XAI technique; and (iii) report at least one empirical metric (accuracy, precision, recall, F1, or AUC-ROC), or a clearly stated architectural contribution if the paper was itself a review. Papers on fraud in non-financial domains (insurance-claims fraud without a transaction-level model, academic fraud) were excluded, as were opinion pieces with no described technique. Applying these criteria to an initial pool of over forty candidates yielded twenty-five papers, published 2018 to 2026, which form the basis of the Related Works section and are all tabulated by family in Table 2.

Each shortlisted study was scored on five dimensions, used consistently in the Analysis and Discussion section: (1) detection technique, the ML/DL/graph/XAI family used; (2) dataset, distinguishing public benchmarks from proprietary bank data; (3) class-imbalance handling, whether and how the skew

between classes was addressed; (4) interpretability, whether the study reports a post-hoc or intrinsic explanation for individual predictions; and (5) real-time feasibility, whether the study reports or discusses inference latency suitable for transaction-time scoring. Two authors scored each study independently and reconciled disagreements by re-reading the relevant section of the source, a lightweight version of the dual-reviewer protocol used in systematic reviews.

Table 1 lists the datasets the surveyed literature evaluates against. The repeated reliance on two public datasets, visible in the "Used by" column, is itself a finding of this survey and is discussed in the Open Gaps subsection.

Table 1
Benchmark datasets used across the surveyed literature

Dataset	Records	Fraud rate	Used by
2013 European cardholder (Dal Pozzolo et al., 2015)	~285,000	~0.17%	(Alarfaj & Shahzadi, 2025; K. Gupta et al., 2022; Lakshmi et al., 2023; T S et al., 2023; Zhao et al., 2024)
IEEE-CIS fraud dataset (IEEE CIS & Vesta, 2019)	~590,000	~3.5%	(Aljunaid et al., 2025; Almalki & Masud, 2025)
Proprietary bank data / synthetic graphs	Varies	Not disclosed	(Alarfaj & Shahzadi, 2025; Alessi & Fugini, 2026; Cheng et al., 2025; Ismail & Karaarslan, 2026)

ANALYSIS AND DISCUSSION

Table 2 summarises the surveyed literature against the five-dimension framework of the Research Methodology section. Studies are grouped by technique family rather than by citation, since papers within a family report broadly similar trade-offs. Figure 2, discussed in the Interpretability-Latency Trade-off subsection, places the same families on the two axes that turn out to be in tension, interpretability and latency.

Table 2
Comparison of AI-driven fraud detection technique families along the five survey dimensions

Technique family	Representative studies	Dataset(s) typically used	Class-imbalance handling	Interpretability	Real-time feasibility	Key limitation
Classical ML (LR, RF, SVM, KNN)	(Ganesan et al., 2025; Ghosh Dastidar et al., 2024; A. Gupta et al., 2022; K. Gupta et al., 2022; Kumar & Iqbal, 2019; Lakshmi et al., 2023; Pathak & Beniwal, 2025; Popat & Chaudhary, 2018; T S et al., 2023)	2013 European cardholder	Undersampling or class weights; often none	High (intrinsic for LR and trees)	High (sub-ms to ms)	Accuracy ceiling on subtle, non-linear fraud patterns
Boosted ensembles (XGBoost, LightGBM, CatBoost)	(Alarfaj et al., 2022; Sariat et al., 2025; Xiao et al., 2025; Zhao et al., 2024)	2013 European cardholder; IEEE-CIS	Cost-sensitive loss; modified objective (Zhao et al., 2024)	Low-Medium	High	Needs a post-hoc XAI layer for compliance
Graph neural networks	(Alarfaj & Shahzadi, 2025; Cheng et al., 2025)	Proprietary bank data; synthetic graphs	Rarely addressed explicitly	Low	Medium	Scales poorly to million-node transaction graphs; single-institution evaluation
Explainable AI / hybrid ensembles	(Aljunaid et al., 2025; Almalki & Masud, 2025; Baisholan et al., 2025; Kapale et al., 2024; Shah, 2025; Uddin, 2026)	IEEE-CIS; 2013 European cardholder	Hybrid resampling (K-means-SMOTE-ENN); stacking	High (post-hoc)	Medium	Explanation methods add inference overhead (quantified in the Evaluation and Results section)
Streaming / real-time architectures	(Alessi & Fugini, 2026; Chen et al., 2026; R. Gupta et al., 2024; Ismail & Karaarslan, 2026)	Proprietary or simulated streams	Dynamic thresholds; label-delay modelling	Varies	Very High	Limited evaluation under realistic label-delay conditions

Accuracy Trends


Reported accuracy and AUC-ROC figures are consistently high; several boosted-ensemble and GNN papers report accuracy or AUC above 0.99 (Alarfaj & Shahzadi, 2025; Almalki & Masud, 2025). However, most of these results come from a small number of public benchmarks, chiefly the 2013 European cardholder dataset and IEEE-CIS (Table 1). Both are now years old and PCA-anonymised, so the raw feature semantics that fraudsters exploit today are not visible in the data the models are trained and benchmarked on. A near-perfect AUC-ROC on a decade-old anonymised dataset says little about how a model would fare against a fraud ring operating this quarter, and accuracy itself is close to uninformative at a 0.17% base rate, where a model that flags nothing scores 99.8%. Precision-recall metrics are the appropriate lens, and only some of the surveyed studies report them.

The Interpretability-Latency Trade-off

A clear tension recurs: the models with the strongest raw performance (deep networks, GNNs, boosted ensembles) are the least interpretable by default, while intrinsically interpretable models such as logistic regression and single decision trees underperform on subtle fraud patterns. Figure 2 plots the technique families along these two axes. They cluster into a fast-but-opaque group (boosted ensembles), a slow-but-opaque group (GNNs), and a group that pays a latency premium specifically to buy back interpretability (SHAP/LIME ensembles, federated XAI).

Figure 2

Interpretability versus latency across the surveyed technique families



Post-hoc explainers bridge this gap at a computational cost that the surveyed papers rarely quantify. Our own measurement in the Evaluation and Results section puts a model-agnostic explainer at over 380 ms per prediction, which by itself exceeds a sub-100 ms authorisation budget several times over, while a tree-specific explainer costs about 6 ms. This suggests that architectures which fuse prediction and explanation into a single lightweight pass matter more in production than marginal gains in raw accuracy.

Regulatory Pressure as a Design Driver

Several of the most recent papers treat compliance as a first-class design constraint, citing SR 11-7 and OCC model-risk guidance (Board of Governors & OCC, 2011) as reasons a model must be auditable before it can be deployed for high-risk decisions (Uddin, 2026). This is a shift from earlier work, which optimised almost exclusively for accuracy on a static benchmark. It also explains the recent pairing of federated learning with XAI: federated training lets institutions collaboratively train a shared detector without centralising sensitive data, addressing a privacy constraint and, indirectly, a compliance one (Aljunaid et al., 2025). The field is converging on the view that a fraud model's regulatory defensibility is a first-order requirement, on par with detection accuracy.

Open Gaps

Three gaps recur. First, there is no standardised, realistic, present-day benchmark for financial fraud research; nearly all reported results trace to one of two aging, heavily anonymised datasets, which limits

comparability and may overstate generalisable accuracy. Second, adversarial and zero-day robustness is rarely evaluated. Most studies assume test-time fraud resembles training-time fraud, an assumption fraud rings actively violate, and only a few recent papers target the zero-day case (Ismail & Karaarslan, 2026). Third, cross-institution collaboration remains nascent: federated learning is proposed as a partial solution, but published evaluations simulate federation across partitions of a single dataset rather than heterogeneous data from real institutions (Aljunaid et al., 2025).

These gaps point toward the solution we propose in the Proposed Method section: an architecture that combines graph-based relational modelling of accounts, devices, and merchants (to catch coordinated rings that row-wise classifiers miss) with a lightweight, natively interpretable scoring head (to avoid the latency penalty of bolted-on explanation) and a federated training protocol (so institutions can share fraud signal without sharing data).


Practical Implications for Financial Institutions

For a practitioner deciding what to build, the survey suggests a pragmatic reading. A classical or boosted-ensemble model remains a reasonable first production deployment, given its low latency and mature tooling, provided it is paired with an explanation layer from day one rather than retrofitted. Graph-based and federated approaches are best reserved for the smaller volume of transactions a first-pass model already flags, both because they cost more to run and because their advantage, seeing relationships across accounts and institutions, only pays off once there is a plausible ring to detect. This escalate-only-when-necessary pattern recurs often enough in the streaming literature (Alessi & Fugini, 2026; R. Gupta et al., 2024) that we treat it as a design principle, and it directly motivates our proposed solution in the Proposed Method section.

THE PROPOSED METHOD: A HYBRID DETECTION ARCHITECTURE

The gaps in the Analysis and Discussion section motivate our proposed solution: a concrete four-layer hybrid detection architecture, shown in Figure 3. The design borrows the three-layer structure implicit across the surveyed literature (a fast deterministic layer, a learned scoring layer, and a relational layer) and adds a fourth, explanation layer designed in from the start rather than bolted on. Figure 3 also shows the escalation that narrows at each stage, so that the expensive layers run on a shrinking fraction of volume. the subsections that follow describe the four layers, and Table 3 maps each one to the literature gap it is proposed to close.

Figure 3
Our proposed four-layer hybrid fraud-detection pipeline, with escalation narrowing at each stage



Escalation narrows with each layer: only ambiguous cases reach Layer 3, and only flagged cases reach Layer 4.

Layer 1: Deterministic Pre-Filter

A lightweight rules layer (velocity checks, geo-mismatch checks, known-bad-payee lists) runs first, at negligible cost, to dispose of the clearest cases, both obvious fraud and clearly legitimate low-risk transactions, before any model inference. This mirrors the rules layer in industry real-time pipelines and keeps average-case latency low, since only ambiguous transactions reach the more expensive layers (Alessi & Fugini, 2026).

Layer 2: Calibrated Ensemble Scoring

Transactions that pass the pre-filter are scored by a boosted-ensemble model in the spirit of the LightGBM and XGBoost approaches of the Deep Learning and Ensemble Methods subsection, chosen over a full deep network for its balance of accuracy and inference cost on tabular features. The model is trained with a cost-sensitive loss and an imbalance-aware resampling strategy such as K-means-SMOTE-ENN (Aljunaid et al., 2025), so that the rare fraud class is not drowned out during training.

Layer 3: Relational Graph Check

Only transactions flagged as suspicious by Layer 2 are escalated to a graph-based relational check, which asks whether the account, device fingerprint, or payee is connected to other recently flagged entities in a rolling transaction graph. Restricting graph inference to escalated transactions directly addresses the scalability limitation of GNN approaches noted in the Open Gaps subsection, since the traversal runs on a small fraction of full volume.

Layer 4: Native Explanation

Rather than attaching a separate explainer after the fact, the scoring model in Layer 2 emits per-feature contributions in the same forward pass as the score, so that a human-readable reason code (for example, "unusual merchant category for this account" or "device seen on three previously flagged accounts") is a direct output of inference rather than a second, costlier pass. For tree ensembles this is available exactly, since the additive structure of the model allows per-leaf contributions to be accumulated during scoring; for a neural scoring head, the equivalent is a jointly trained attention or attribution head. This preserves the auditability that SR 11-7 requires (Board of Governors & OCC, 2011; Uddin, 2026) without the post-hoc explanation overhead measured in the Evaluation and Results section.

Table 3 summarises the proposal by mapping each layer to the gap it addresses; the Evaluation and Results section tests whether the layers behave as Table 3 claims.

Table 3
Mapping of the layers of our proposed architecture to the literature gaps each one addresses

Layer	Gap addressed
1. Deterministic pre-filter	Keeps average latency low for real-time feasibility
2. Calibrated ensemble	Accuracy under extreme class imbalance
3. Relational graph check	Scalable detection of coordinated fraud rings
4. Native explanation	Regulatory auditability without post-hoc latency

EVALUATION AND RESULTS: PRELIMINARY VALIDATION OF OUR PROPOSAL

This section reports a preliminary validation of our proposal. To check that the survey's conclusions hold when the surveyed families are run side by side, and that our proposed architecture is

implementable at the latencies it assumes, we built one representative model from each family and the proposed four-layer pipeline in a single evaluation harness (Python, scikit-learn, LightGBM, XGBoost, SHAP, NetworkX). All models were evaluated on the same stratified 70/30 split of the 2013 European cardholder dataset (Dal Pozzolo et al., 2015), and per-transaction latency was measured the same way for every model: single-row inference on one CPU core of a Google Colab runtime, averaged over 500 transactions. Latencies vary by roughly 20% between runs on shared hardware; we report a single run and draw conclusions only from differences that are far larger than that. The harness, including the notebook that regenerates every table and figure in this section and the next, is released at https://github.com/retrixe/collegework/tree/main/sem7/ics/cca3. Table 4 reports detection performance and latency for every model including the proposed pipeline; Figure 4 reports the explanation overhead that motivates Layer 4; Figure 5 reports the escalation volume that Layer 3 depends on.

Data and Scope

The dataset contains 284,807 card transactions over two days, of which 492 (0.17%) are fraudulent; the split leaves 199,364 transactions (344 fraudulent) for training and 85,443 (148 fraudulent) for testing. Each transaction is described by 30 input dimensions: V1 to V28, the principal components of the original cardholder and transaction fields released in anonymised form, together with Time (seconds from the start of the capture window) and Amount. Only Time and Amount are standardised; V1 to V28 are already on comparable scales. Because the dataset is PCA-anonymised, it carries no account, device, or merchant identifiers, so the relational layer cannot be exercised on it directly. We therefore attach a simulated entity layer in which fraud transactions are grouped into rings that reuse a small number of devices and mule accounts, following the ring structure described in the Graph-Based and Relational Approaches subsection. Detection results for the single models are therefore real; results that depend on the relational layer (the pipeline's Layer 3 and the graph features of the RAAB for Zero-Day Detection section) inherit the simulation, and we say so where it matters.

Detection Performance

Table 4 reports precision, recall, F1, and area under the precision-recall curve (AUC-PR) at a 0.5 decision threshold, together with single-transaction latency. Three of the survey's observations reproduce. Accuracy is uninformative: every model except logistic regression scores 0.999, a figure that carries no information at a 0.17% base rate, which is why Table 4 omits it. Boosted ensembles lead on AUC-PR (0.84 for both XGBoost and LightGBM against 0.70 to 0.80 for the classical models), with logistic regression ranking well (AUC-ROC 0.97) but collapsing at the default threshold (precision 0.07), and KNN competitive on precision at a latency (21 ms) that rules it out for authorisation-time scoring. The imbalance ablation qualifies the consensus of the Handling Class Imbalance subsection rather than confirming it outright: on a fixed LightGBM model, cost-sensitive weighting alone raised recall from 0.76 to 0.80 at a precision of 0.86, whereas SMOTE, with or without weighting, pushed recall to 0.84 only by halving precision (0.59 and 0.46), and the K-means-SMOTE-ENN variant was worse than plain weighting on both counts. On this dataset, which already has 344 training frauds, a weighted loss without resampling is the better operating point; resampling helps most when the minority class is too small to learn from directly.

Table 4

Held-out results on the 2013 European cardholder dataset under a common harness. Latency is single-row inference on one CPU core

Model	Prec.	Rec.	F1	AUC-PR	ms/txn
Logistic regression	0.07	0.88	0.12	0.70	0.41
Random forest (200 trees)	0.86	0.75	0.80	0.79	58.7
KNN (k = 5)	0.93	0.74	0.82	0.80	21.2
Linear SVM (calibrated)	0.85	0.55	0.67	0.70	2.9
XGBoost	0.89	0.78	0.83	0.84	0.69
LightGBM	0.87	0.80	0.83	0.84	1.2
MLP (64-32)	0.76	0.77	0.76	0.78	0.24
Autoencoder (recon. error)	0.39	0.74	0.51	0.43	0.24
Hybrid four-layer pipeline (proposed)	0.91	0.71	0.80	n/a	6.9


Our proposed pipeline, the last row of Table 4, uses the same LightGBM model as its Layer 2 but applies a stricter block threshold (0.80 against 0.50) unless the relational check supplies a ring signal. On this split it traded recall for precision: precision rose from 0.87 to 0.91 and recall fell from 0.80 to 0.71, with 11 false positives and 43 missed frauds among 85,443 transactions. Of the 116 transactions it blocked, 108 were blocked on the ring criterion and 8 on the score alone, and 28 borderline transactions were approved and logged. The threshold pair was fixed before the run and not tuned; a lower block threshold would recover the standalone model's recall at some cost in precision, and the right operating point is a business decision that depends on the relative cost of a missed fraud and a declined customer (the Introduction section). On the simulated entity graph the ring score separated the classes cleanly (mean 6.95 for fraud against 0.25 for legitimate transactions); because that separation is a product of the simulation, we make no claim about the magnitude of the relational gain on real identifiers.

Explanation Overhead

Figure 4 compares the per-transaction cost of the explanation strategies discussed in the Interpretability-Latency Trade-off subsection, all on the same LightGBM model. Scoring alone took 1.2 ms. Emitting per-feature contributions natively in the same pass, as Layer 4 does, brought the full four-layer pipeline, including the pre-filter, the graph check, and reason-code generation, to 6.9 ms. A tree-specific post-hoc explainer (TreeSHAP) added 6.3 ms on top of scoring, about the same as the whole pipeline. A model-agnostic explainer (KernelSHAP with 200 background samples) added 382 ms, more than fifty times the pipeline's total cost, and by itself exceeds a 100 ms authorisation budget nearly four times over. The ranking is what the Interpretability-Latency Trade-off subsection predicts, and the gap is large enough that it will not be closed by hardware: an architecture that requires a model-agnostic explainer on every transaction is not a real-time architecture.

Figure 4

Per-transaction latency of scoring alone, scoring with native contributions (the hybrid pipeline end to end), and scoring with two post-hoc explainers, on the same LightGBM model. Log scale




Escalation Volume

Figure 5 shows how much of the test volume reached each layer of the proposed pipeline. The deterministic pre-filter approved 5.6% of transactions outright; the ensemble approved 94.2% of the remainder below the review threshold; only 144 transactions (0.17%) reached the graph layer; and 116 (0.14%) were blocked. Graph inference therefore ran on roughly one transaction in six hundred, which is the scalability property the Layer 3 subsection relies on. The graph check itself cost 0.07 ms per escalated transaction on a 122,000-node account-device graph, so even a substantially heavier relational model would fit the budget at this escalation rate.

Figure 5

Escalation narrowing across the four layers on the test split (85,443 transactions). Log scale



What the Validation of Our Proposal Does and Does Not Show

The validation supports three claims about our proposal: that the qualitative ordering of technique families in Table 2 holds under a common harness on real data (Table 4); that native explanation removes the latency penalty that makes post-hoc XAI hard to deploy in real time (Figure 4); and that layered escalation confines expensive relational inference to a small fraction of volume (Figure 5). It does not show that the proposed architecture detects more fraud than a well-tuned single model: on this split the pipeline gained precision and lost recall at its fixed thresholds, and the relational gain it is designed to deliver depends on a simulated entity layer. Establishing that gain requires a dataset with real account and device identifiers, which is the first gap identified in the Open Gaps subsection and the reason such a dataset is the priority for future work.

USING RELATIONAL-ANOMALY AUGMENTED BOOSTING FOR ZERO-DAY DETECTION

Our proposed architecture of the Proposed Method section treats the relational signal (Layer 3) and, in the zero-day literature, the unsupervised novelty signal (Ismail & Karaarslan, 2026) as checks applied *after* the scoring model has made its decision. That ordering has a cost: a transaction the row model scores as clearly legitimate never reaches the graph check, however suspicious its device history, and a transaction whose feature vector lies off the manifold of legitimate behaviour is only caught if a separate anomaly detector is consulted. We therefore propose an extension that keeps the four-layer structure but moves both signals into the scoring model itself, and we use it to address the zero-day case that the Open Gaps subsection identified as under-evaluated. We call the extension Relational-Anomaly Augmented Boosting (RAAB). The RAAB Method subsection describes the method and sets it out as Algorithm 1, the Zero-Day Protocol subsection the zero-day protocol used to evaluate it (Table 5), and the RAAB Results subsection the results (Table 6, Figure 6).

Method

The proposed RAAB extension augments the tabular feature vector of each transaction with two small blocks of derived features and trains the Layer-2 boosted model on the augmented vector.

Entity-risk features (four values). For the transaction's device and account, the prior flag rate (flagged transactions divided by total transactions plus one) observed in a rolling account-device graph; and, over all entities within two hops of either, the total flagged count and the flag rate. These are the quantities the Layer-3 check already computes, now exposed to the learner as inputs rather than consulted after the fact. Two details make them safe to learn from. On training rows they are computed out of fold: the graph used to score a row is built from the other four folds of the training period, so no row contributes to its own features. On test rows they are computed from the training-period graph alone, so no test label leaks into any feature. The result is a time-respecting feature in the same sense as a lagged aggregate.

Novelty features (thirty values). An autoencoder with the architecture and legitimate-only training recipe of the Evaluation and Results section, refitted on each training split, emits, for each transaction, the mean and maximum reconstruction residual and the squared residual on each input dimension. Because the autoencoder is trained without fraud labels, these features encode how far a transaction departs from normal behaviour independently of any fraud pattern seen in training, which is the property a zero-day detector needs.

The boosted model is otherwise unchanged (LightGBM, cost-sensitive loss, the regularisation of the Evaluation and Results section). Because the injected features enter the same additive tree model, the native reason codes of Layer 4 extend to them without modification: a blocked transaction can carry the code "reconstruction error far above normal" or "device previously flagged" as a direct output of scoring. Inference cost rises from one model to one model plus one autoencoder forward pass and one graph lookup.

Algorithm 1 sets out the training and inference procedure.

Algorithm 1. Relational-Anomaly Augmented Boosting (RAAB)

Input: training transactions X_tr with labels y_tr and entity identifiers (account, device); incoming transactions X_te with entity identifiers; number of folds K.

1. Train an autoencoder f on the legitimate rows of X_tr only.
2. Novelty features: for a transaction x, let r = f(x) - x and a(x) = [mean(r^2), max|r|, r^2 per input dimension].
3. Out-of-fold entity risk: split X_tr into K folds. For each fold k, build the account-device graph G_k from the other K-1 folds (node counts n and flagged counts c), and for each x in fold k compute e(x) = [c/(n+1) for its device, c/(n+1) for its account, sum of c within two hops, that sum divided by (sum of n within two hops + 1)] from G_k.
4. Build G_full from all of X_tr; compute e(x) for every x in X_te from G_full.
5. Train a cost-sensitive gradient-boosted model g on the augmented vectors [x, a(x), e(x)] with labels y_tr.
6. Inference: for each incoming x, compute a(x) and e(x), obtain the score p = g([x, a(x), e(x)]) together with the per-feature additive contributions, and emit reason codes from the largest positive contributions.

Output: fraud score p and reason codes for x.

Zero-Day Protocol

The Open Gaps subsection identified weak evaluation of zero-day robustness as an open gap. Testing it requires a fraud pattern that is guaranteed absent from training, which no labelled public dataset provides, so this experiment uses a controlled synthetic generator with the schema of the dataset in the Evaluation and Results section: 120,000 transactions at a 0.17% fraud rate, legitimate rows drawn as standard-normal values on V1 to V28, and fraud rows drawn with 1.5 times that spread and displaced on ten dimensions chosen per seed by an offset of 1.0 to 2.2 standard deviations in a random direction, with heavier-tailed amounts and an uninformative Time. The generator was then extended with a second fraud pattern, B, that displaces a set of ten PCA dimensions disjoint from those of the known pattern A. Every B transaction is placed in the test period, so the scoring model has never seen one, and B accounts for 30% of test fraud. B rings reuse devices and accounts in the same way as A rings, as a new fraud pattern run on existing fraud infrastructure would. Recall is reported separately on A and on B. The experiment is repeated over three random seeds, each with a fresh dataset, entity assignment, and split. Table 5 lists the dimensions each pattern displaces under each seed; by construction the two sets never overlap, so a tree model trained on A has no fraud-splitting threshold on any dimension that carries B's signal. Time and Amount are shared by both patterns and are not displaced. With the two injected blocks, the RAAB model sees 64 dimensions in total: the 30 inputs, 4 entity-risk features, and 30 novelty features (mean and maximum residual plus one squared residual per input).

Table 5

Input dimensions displaced by the known pattern A and the zero-day pattern B under each seed

Seed	Pattern A (in training and test)	Pattern B (test only)
42	V10, V11, V13, V15, V16, V18, V20, V21, V25, V27	V1, V3, V6, V9, V12, V17, V19, V23, V24, V28
7	V1, V5, V8, V9, V17, V19, V22, V25, V26, V28	V2, V3, V7, V10, V11, V13, V14, V21, V24, V27
2024	V3, V6, V8, V9, V15, V16, V18, V20, V21, V26	V7, V11, V12, V13, V14, V17, V19, V23, V27, V28

Results

Table 6 reports the ablation numerically and Figure 6 shows it graphically. With neither block of features, the base LightGBM detects none of the zero-day pattern on any seed, which is the expected behaviour of a supervised model asked about the feature directions in the right-hand column of Table 5 that it has never been shown, and its AUC-PR over all test fraud is 0.41. Each block on its own helps the known pattern (recall 0.69 to 0.81 with novelty features, to 0.86 with entity-risk features) but barely touches the zero-day pattern (recall 0.07 and 0.06). Together they lift zero-day recall to 0.44 and AUC-PR to 0.91 with a standard deviation of 0.02 across seeds. The two blocks are complementary rather than additive: the novelty features say that a transaction is unlike anything legitimate, the entity-risk features say that it comes from infrastructure with a history, and the tree model learns that the conjunction is far more diagnostic than either alone. At a 99% precision operating point RAAB recovers 51% of all test fraud against 20% for the base model.


Table 6

RAAB ablation on the zero-day protocol, mean over three seeds (standard deviation in parentheses). Recall at a 0.5 threshold

Model	AUC-PR	Recall, A	Recall, B	Rec. @ P = 0.99
LightGBM (base)	0.41 (0.03)	0.69 (0.03)	0.00 (0.00)	0.20 (0.03)
+ novelty features	0.63 (0.01)	0.81 (0.04)	0.07 (0.03)	0.26 (0.07)
+ entity-risk features	0.67 (0.03)	0.86 (0.04)	0.06 (0.03)	0.37 (0.07)
RAAB (proposed, both)	0.91 (0.02)	0.88 (0.03)	0.44 (0.03)	0.51 (0.15)

Figure 6

Ablation of the proposed RAAB extension under the zero-day protocol. Bars are means over three seeds; whiskers are one standard deviation



As Table 6 does not show latency, we report it here. The end-to-end cost of the RAAB path (autoencoder forward pass, graph lookup, scoring with native contributions) was 5.7 ms per transaction on the same hardware, against 6.9 ms for the full pipeline of the Evaluation and Results section, so the enhancement fits inside the same latency budget. The reason codes produced for zero-day blocks were dominated by the injected features: on the first seed the top contribution for every blocked B transaction was the mean reconstruction error, followed by the device flag rate or the two-hop flag rate.

Relation to Our Proposed Architecture, and Limits

The proposed RAAB extension does not remove Layer 3 of our architecture. The graph check still runs on escalated transactions and can apply richer relational models than four scalar features; what changes is that the scoring model no longer has to be wrong before relational evidence is considered. Nor does

RAAB replace the zero-day detectors of the Real-Time and Streaming Constraints subsection; it is a way of giving their signal to the supervised model, and a stronger generative model than the small autoencoder used here would produce stronger novelty features.

The results carry one limit that the Evaluation and Results section does not: the data are synthetic. The zero-day pattern is synthetic, and its difficulty is set by the generator; a real novel fraud pattern may lie closer to or further from the legitimate manifold than pattern B does. The entity-risk features depend on the simulated ring structure. What is robust to both is the shape of the result: a supervised model with no view of novelty or relational history detects none of a pattern it has not seen, and giving it both views in the same pass recovers a substantial fraction of it at the same precision and almost the same latency. The method is simple to implement on any bank's data that carries account and device identifiers, which is the setting in which it should next be tested.

THREATS TO VALIDITY

As with any literature survey, the conclusions drawn here are shaped by choices made during paper selection. We make explicit where those choices could bias the picture in the Related Works section and the Analysis and Discussion section, and add the limits of the empirical work in the Evaluation and Results section and the RAAB for Zero-Day Detection section.

Publication and Venue Bias

The search favoured IEEE Xplore, ACM, Elsevier, and Springer venues plus arXiv, which skews the sample toward work that is peer-reviewed at a computer-science venue or positioned for one. Practitioner reports, internal bank white papers, and vendor case studies, which may describe production systems quite different from what is published academically, are largely absent, and academic performance figures may not transfer to a live environment with different fraud patterns, latency constraints, and data quality.

Benchmark Dataset Concentration

As Table 1 makes explicit, a large share of the reviewed empirical results are reported on two public datasets. This reflects a real scarcity of realistic, labelled, legally shareable fraud data rather than a flaw in any individual study, but it means the accuracy figures in the Accuracy Trends subsection should be read as statements about those two aging datasets, not as general claims about present-day fraud.

Reviewer and Selection Subjectivity

The five-dimension scoring in the Research Methodology section involved judgement, particularly for the interpretability and real-time columns, where source papers do not always report a clean, comparable number. Where a paper's language was ambiguous, the more conservative rating was chosen, so Table 2 likely understates rather than overstates how favourable the surveyed techniques are on these two dimensions.

Temporal Scope

The twenty-five studies span 2018 to 2026, a window in which both the fraud landscape and the ML tooling changed substantially; GNN-based fraud detection barely appears at the early end of that range. Grouping a 2018 classical-ML paper and a 2026 zero-day paper in the same framework is a simplification, and a reader should weigh the more recent studies more heavily when judging the current state of the art.

Limits of the Empirical Check

The validation of our proposal in the Evaluation and Results section was run on one public dataset with a simulated entity graph, on a single split, without hyperparameter search and without repeated runs. Its single-model detection results, latency results, and escalation results are robust to these limits; the relational gain of its Layer 3 is not, because the ring structure is simulated, and its pipeline thresholds were fixed rather than tuned. The RAAB for Zero-Day Detection section repeats its experiment over three seeds, but its data, its zero-day pattern, and its ring structure are all products of a generator, so the magnitude of the RAAB gain is a property of that benchmark until it is reproduced on data with real identifiers.

CONCLUSION

This paper surveyed twenty-five recent studies on AI-driven fraud detection along five dimensions and found three open problems: reliance on aging, heavily anonymised benchmarks; weak evaluation of zero-day and adversarial robustness; and limited genuine cross-institution collaboration. Building on these gaps, the Proposed Method section set out our proposed solution, a four-layer hybrid detection architecture (Figure 3, Table 3), and the Evaluation and Results section gave a preliminary validation of our proposal, showing on the 2013 European cardholder dataset (Table 4, Figures 4 and 5) that its two structural claims hold: explanation produced in the scoring pass costs under 7 ms per transaction against over 380 ms for a bolted-on model-agnostic explainer, and layered escalation confines graph inference to under 0.2% of volume. The RAAB for Zero-Day Detection section then extended the proposal with RAAB for zero-day detection and showed (Table 6, Figure 6) that the architecture's two deferred signals, relational history and novelty, are more valuable inside the scoring model than after it: injecting both as features raised AUC-PR from 0.41 to 0.91 on a test set in which 30% of fraud followed an unseen pattern, and recovered 44% of that pattern where the base model recovered none, within the same latency budget.

The next step is to evaluate the proposed architecture and its RAAB extension on a dataset with real account and device identifiers, where the relational layer can be tested rather than simulated, and to add a federated training protocol and a drift-aware threshold manager. The released harness (https://github.com/retrixe/collegework/tree/main/sem7/ics/cca3) is intended to make those comparisons possible on equal footing.

ACKNOWLEDGEMENT

This research received no specific grant from any funding agency in the public, commercial, or not-for-profit sectors.

REFERENCES

Alarfaj, F. K., Malik, I., Khan, H. U., Almusallam, N., Ramzan, M., & Ahmed, M. (2022). Credit card fraud detection using state-of-the-art machine learning and deep learning algorithms. *IEEE Access, 10,* 39700-39715. https://doi.org/10.1109/ACCESS.2022.3166891

Alarfaj, F. K., & Shahzadi, S. (2025). Enhancing fraud detection in banking with deep learning: Graph neural networks and autoencoders for real-time credit card fraud prevention. *IEEE Access, 13*, 20633-20646.

Alessi, G., & Fugini, M. (2026). Adaptive real-time financial fraud detection with explainable AI tools. *Digital Threats: Research and Practice, 7*(1). https://doi.org/10.1145/3794859

Aljunaid, S. K., Almheiri, S. J., Dawood, H., & Khan, M. A. (2025). Secure and transparent banking: Explainable AI-driven federated learning model for financial fraud detection. *Journal of Risk and Financial Management, 18*(4), Article 179. https://doi.org/10.3390/jrfm18040179

Almalki, F., & Masud, M. (2025). Financial fraud detection using explainable AI and stacking ensemble methods. *arXiv*. https://arxiv.org/abs/2505.10050

Baisholan, N., Dietz, J. E., Gnatyuk, S., Turdalyuly, M., Matson, E. T., & Baisholanova, K. (2025). FraudX AI: An interpretable machine learning framework for credit card fraud detection on imbalanced datasets. *Computers, 14*(4), Article 120. https://doi.org/10.3390/computers14040120

Board of Governors of the Federal Reserve System, & Office of the Comptroller of the Currency. (2011). *Supervisory guidance on model risk management* (SR Letter 11-7 / OCC Bulletin 2011-12).

Chawla, N. V., Bowyer, K. W., Hall, L. O., & Kegelmeyer, W. P. (2002). SMOTE: Synthetic minority over-sampling technique. *Journal of Artificial Intelligence Research, 16*, 321-357.

Chen, Y., Zhao, C., Xu, Y., Nie, C., & Zhang, Y. (2026). Deep learning in financial fraud detection: Innovations, challenges, and applications. *Data Science and Management, 9*(2), Article 100162. https://doi.org/10.1016/j.dsm.2025.08.002

Cheng, D., Zou, Y., Xiang, S., & Jiang, C. (2025). Graph neural networks for financial fraud detection: A review. *Frontiers of Computer Science*. https://doi.org/10.1007/s11704-024-40474-y

Dal Pozzolo, A., Caelen, O., Johnson, R. A., & Bontempi, G. (2015). Calibrating probability with undersampling for unbalanced classification. In *2015 IEEE Symposium Series on Computational Intelligence (SSCI)* (pp. 159-166). IEEE.

Federal Reserve Financial Services. (2023). *FedNow Service readiness guide: Funds availability*. https://explore.fednow.org/resources/readiness-guide-fund-availability.pdf

Ganesan, Y., et al. (2025). Fraud detection in financial transactions using AI. In *2025 International Conference on Business Intelligence for Technology Innovation (ICBITI)* (pp. 1-7). IEEE. https://doi.org/10.1109/ICBITI65527.2025.11500836

Ghosh Dastidar, K., Caelen, O., & Granitzer, M. (2024). Machine learning methods for credit card fraud detection: A survey. *IEEE Access, 12*, 158939-158965. https://doi.org/10.1109/ACCESS.2024.3487298

Gupta, A., Singh, K., Sharma, N., & Rakhra, M. (2022). Machine learning for detecting credit card fraud. In *2022 IEEE North Karnataka Subsection Flagship International Conference (NKCon)* (pp. 1-6). IEEE. https://doi.org/10.1109/NKCon56289.2022.10126861

Gupta, K., Singh, K., Singh, G. V., Hassan, M., Himani, & Sharma, U. (2022). Machine learning based credit card fraud detection: A review. In *2022 International Conference on Applied Artificial Intelligence and Computing (ICAAIC)* (pp. 362-368). IEEE. https://doi.org/10.1109/ICAAIC53929.2022.9792653

Gupta, R., Goyal, R., Malik, K., & Sahu, I. (2024). AI-enhanced data mining for fraud detection in financial transactions. In *2024 3rd International Conference on Sentiment Analysis and Deep Learning (ICSADL)* (pp. 244-249). IEEE. https://doi.org/10.1109/ICSADL61749.2024.00045

IEEE Computational Intelligence Society, & Vesta Corporation. (2019). *IEEE-CIS fraud detection* [Data set]. Kaggle. https://www.kaggle.com/c/ieee-fraud-detection

Ismail, N. A., & Karaarslan, E. (2026). A dual-path generative framework for zero-day fraud detection in banking systems. *arXiv*. https://arxiv.org/abs/2603.13237

Kapale, R., Deshpande, P., Shukla, S., Kediya, S., Pethe, Y., & Metre, S. (2024). Explainable AI for fraud detection: Enhancing transparency and trust in financial decision-making. In *2024 2nd DMIHER International Conference on Artificial Intelligence in Healthcare, Education and Industry (IDICAIEI)* (pp. 1-6). IEEE. https://doi.org/10.1109/IDICAIEI61867.2024.10842874

Ke, G., Meng, Q., Finley, T., Wang, T., Chen, W., Ma, W., Ye, Q., & Liu, T.-Y. (2017). LightGBM: A highly efficient gradient boosting decision tree. In *Advances in Neural Information Processing Systems 30* (pp. 3146-3154).

Kumar, P., & Iqbal, F. (2019). Credit card fraud identification using machine learning approaches. In *2019 1st International Conference on Innovations in Information and Communication Technology (ICIICT)* (pp. 1-4). IEEE. https://doi.org/10.1109/ICIICT1.2019.8741490

Lakshmi, Y. V., Priyanka, Y. S., Harika, A., Rajitha, N., & Bhargavi, D. (2023). Machine learning based credit card fraud detection. In *2023 International Conference on Sustainable Computing and Data Communication Systems (ICSCDS)* (pp. 299-305). IEEE. https://doi.org/10.1109/ICSCDS56580.2023.10104615

Lundberg, S. M., & Lee, S.-I. (2017). A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems 30* (pp. 4765-4774).

The Nilson Report. (2013, August 19). *Global credit, debit, and prepaid card fraud losses reach $11.27 billion in 2012, up 14.6% over 2011* [Press release]. Business Wire. https://www.businesswire.com/news/home/20130819005953/en/

The Nilson Report. (2022, December 22). *Payment card fraud losses reach $32.34 billion* [Press release]. GlobeNewswire. https://www.globenewswire.com/news-release/2022/12/22/2578877/0/en/

Pathak, M., & Beniwal, R. (2025). A systematic literature survey on credit card fraud detection using machine learning techniques. In *2025 5th International Conference on Pervasive Computing and Social Networking (ICPCSN)* (pp. 149-154). IEEE. https://doi.org/10.1109/ICPCSN65854.2025.11035471

Popat, R. R., & Chaudhary, J. (2018). A survey on credit card fraud detection using machine learning. In *2018 2nd International Conference on Trends in Electronics and Informatics (ICOEI)* (pp. 1120-1125). IEEE. https://doi.org/10.1109/ICOEI.2018.8553963

Ribeiro, M. T., Singh, S., & Guestrin, C. (2016). "Why should I trust you?" Explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining* (pp. 1135-1144). ACM.

Sariat, A. F., Siddique, I. J., Hossain, M., Islam, M. M., & Rahman, T. (2025). AI driven fraud detection in financial ecosystems: A hybrid machine learning framework. In *2025 International Conference on Electrical, Computer and Communication Engineering (ECCE)*. IEEE. https://doi.org/10.1109/ECCE64574.2025.11013808

Shah, S. B. (2025). Advancing financial security with scalable AI: Explainable machine learning models for transaction fraud detection. In *2025 4th International Conference on Distributed Computing and Electrical Circuits and Electronics (ICDCECE)*. IEEE. https://doi.org/10.1109/ICDCECE65353.2025.11034838

T S, A., Fathima, A., Naik, A. D., Goenka, C., Devamane, S. B., & Thimmapurmath, A. R. (2023). Credit card fraud detection using machine learning algorithms. In *2023 International Conference on Computational Intelligence for Information, Security and Communication Applications (CIISCA)* (pp. 419-424). IEEE. https://doi.org/10.1109/CIISCA59740.2023.00085

Uddin, M. N. (2026). A regulatory governance framework for AI-driven financial fraud detection in U.S. banking: Integrating OCC, SR 11-7, CFPB, and FinCEN compliance requirements. *arXiv*. https://arxiv.org/abs/2605.04076

Xiao, Y., Tan, L., & Liu, J. (2025). Application of machine learning model in fraud identification: A comparative study of CatBoost, XGBoost and LightGBM. *Preprints.org*. https://doi.org/10.20944/preprints202503.1199.v1

Zhao, X., Liu, Y., & Zhao, Q. (2024). Improved LightGBM for extremely imbalanced data and application to credit card fraud detection. *IEEE Access, 12*, 159316-159335. https://doi.org/10.1109/ACCESS.2024.3487212