## NetBSD keyboard configuration

## Summary

In this part i'm going to configure my non-us keyboard by changing or adding some system configuration files for keyboard. **US** keyboard users can skip this part.

This part requires you to know basic usage of **vi** program. If you don't know how to use **vi** or **vim** check this website first: <a href="NetBSD">NetBSD</a> vi tutorial</a>

**vi** is almost always pre-installed in every operating system. Learning **vi** is never a bad idea.

## **vi** basic usage cheatsheet:

Command	Meaning
h =	move cursor left
j =	move cursor down
k =	move cursor up
1 =	move cursor right
a =	add after char
i =	add before char
A =	add end of line
I =	add start of line
o =	add below line
0 =	add above line
dd =	delete one line
x =	delete one char
:w =	save
:q =	quit
:wq =	save and quit
:w! =	force save
:q! =	force quit

## **Instructions**

1- Start your system and login.

```
/etc/rc.d/postfix exited with code 1
Starting inetd.
Starting cron.
The following components reported failures:
   /etc/rc.d/postfix
See /var/run/rc.log for more information.
Sun Jan 9 02:38:04 UTC 2022
NetBSD/i386 (Amnesiac) (constty)
login: a
Password:
Jan 9 02:38:28 login: a on tty constty
Last login: Sat Jan 8 17:05:58 2022 on constty
Copyright (c) 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005,
    2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017,
    2018, 2019, 2020 The NetBSD Foundation, Inc. All rights reserved.
Copyright (c) 1982, 1986, 1989, 1991, 1993
    The Regents of the University of California. All rights reserved.
NetBSD 9.2 (GENERIC) #0: Wed May 12 13:15:55 UTC 2021
Welcome to NetBSD!
$
```

2- Changing the system configuration requires privilege. So switch to **root** user with successions of the system configuration requires privilege. So switch to root user with successions of the system configuration is a second contract to the system configuration of the system configuration is a second configuration of the system configuration requires privilege. So switch to root user with the system configuration requires privilege. So switch to root user with the system configuration requires privilege.

```
$ su
Password:
Jan 8 23:43:56 su: a to root on /dev/constty
# ■
```

```
3- Open wscons.conf file with vi editor.
# vi /etc/wscons.conf 📕
4- I'm using tr keyboard. So im going to add encoding tr configuration in this file.
# Screen 0 is already configured as console in most cases.
# Uncomment if a serial console is used.
#screen 0
                        vt 100
        1
                        vt 100
screen
        2
                        vt 100
screen
        3
                        vt 100
screen
screen
        4
                80x25bf vt100
#screen 4
# Note: You must uncomment the 'font
                                         ibm' line above to get a useful
#
        font for any 50 line screens.
#screen 5
                80×50
                        vt 100
#keyboard
                auto
# Select a kernel builtin keyboard map by uncommenting the following line and
```

# Redefine individual keys from a file containing "keysym" and/or "keycode"

# See wsconsctl(8) and /usr/share/wscons/keymaps for more details.

# altering the country code to your requirements. # See wskbd(4) for a full list of supported options.

#mapfile /usr/share/wscons/keymaps/pckbd.sv.svascii

/otc/werone conf: 60 lines 1887 characters

encoding tr

# entries.

#encoding us.swapctrlcaps

5- I'm also going to edit keymaps because my current keyboard doesn't have a less, greater key. (These characters: <, >, |) This requires me to go to /usr/share/wscons/keymaps/ folder.And create a new file named overlay.tr with vieditor.(You can use anything as file name but do not forget it. We're gonna need it)

```
$ cd /usr/share/ыscons/keyмaps/
$ vi overlay.tr
```

6- What i'm going to do in this file that i'm going to set some unusable turkish character buttons to bar | less < and greater > characters. For example there is a ş character in my keyboard. It's unusable in console but i might need | character so i've added keycode 39 = bar line in this file to set şbutton to bar | character. I've also set ö and ç buttons to use less < and greater >. (You can check your full keymap with this command: wsconsctl map | less)

7- Again, open your wscons.conf file with vi editor.

```
# vi /etc/wscons.conf
```

```
# altering the country code to your requirements.
# See wskbd(4) for a full list of supported options.
encoding tr
#encoding us.swapctrlcaps
# Redefine individual keys from a file containing "keysym" and/or "keycode"
# entries.
# See wsconsctl(8) and /usr/share/wscons/keymaps_for more details.
mapfile /usr/share/wscons/keymaps/overlay.tr
# Set arbitrary wscons variable using specified control device
       ctldev
                var
                                value
#setvar ttyE0
                font
                                 ibм
#setvar ttyE1
                                 ibм
                font
# Uncomment for ISO 8859-2 support
#setvar ttvE0
                font
                                 latin2
#setvar ttyE1
                font
                                 latin2
#setvar ttyE2
                                 latin2
                font
#setvar ttyE3
                font
                                 latin2
```

# Change keyboard repeat speed to faster settings.

250

30

repeat.del1

repeat.deln

#setvar wskbd

#setvar wskbd

8- Add mapfile /usr/share/wscons/keymaps/overlay.tr configuration and save it.

9- Restart the system with **shutdown -r now** to load these new keyboard configurations.

```
# shutdown −r now∎
# shutdown -r now
Shutdown NOW!
shutdown: [pid 445]
# wall: You have write permission turned off; no reply possible
*** FINAL System shutdown message from a@ ***
System going down IMMEDIATELY
Mar 2 05:23:08 shutdown: reboot by a:
System shutdown time has arrived
About to run shutdown hooks...
Stopping cron.
Stopping inetd.
Saved entropy to /var/db/entropy-file.
Forcibly unmounting /var/shm
Removing block-type swap devices
swapctl: removing /dev/dk1 as swap device
Wed Mar 2 05:23:11 UTC 2022
Done running shutdown hooks.
```

Mar 2 05:23:16 syslogd[166]: Exiting on signal 15

10- When system starts, login with user and try your configured buttons. If you can see your characters it means that your keyboard configurations are working.

```
/etc/rc.d/postfix exited with code 1
Starting inetd.
Starting cron.
The following components reported failures:
    /etc/rc.d/postfix
See /var/run/rc.log for more information.
Sun Jan 9 04:16:12 UTC 2022
NetBSD/i386 (Ammesiac) (constty)
login: a
Password:
Jan 904:16:18 login: a on tty constty
Last login: Sun Jan 9 01:15:15 2022 on constty
Copyright (c) 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005,
    2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020 The NetBSD Foundation, Inc. All rights reserved.
Copyright (c) 1982, 1986, 1989, 1991, 1993
    The Regents of the University of California. All rights reserved.
NetBSD 9.2 (GENERIC) #0: Wed May 12 13:15:55 UTC 2021
Welcome to NetBSD!
$ :><
```