

Swinburne University Of Technology*Faculty of Science, Engineering and Technology***ASSIGNMENT COVER SHEET**

Subject Code: COS30008
Subject Title: Data Structures & Patterns
Assignment number and title: 6 – List ADT (part A)
Due date: May 6, 2014, 10:30 a.m.
Lecturer: Dr. Markus Lumpe

Your name: _____ **Your student id:** _____

Check Tutorial	Fri 10:30	Fri 12:30	Fri 14:30

Marker's comments:

Problem	Marks	Obtained
constructor	5	
push_back	14	
remove	31	
operator[]	17	
getIterator	3	
Total	70	

Extension certification:

This assignment has been given an extension and is now due on _____

Signature of Convener: _____

Problem Set 6: List ADT (part A)

Preliminaries

Review the solution of problem set 5, the `DoublyLinkedListNode` template class developed in the tutorial in week 6, and the lecture material regarding the construction of an abstract data type.

Start with the header files provided on Blackboard, as they have been fully tested.

Problem 1:

Using the template classes `DoublyLinkedListNode` and `DoublyLinkedListNodeIterator`, implement the template class `List` as specified below:

```
#pragma once

#include "DoublyLinkedListNode.h"
#include "DoublyLinkedListNodeIterator.h"
#include <stdexcept>

template<class T>
class List
{
private:
    // auxiliary definition to simplify node usage
    typedef DoublyLinkedListNode<T> Node;

    Node* fTop;           // the first element in the list
    Node* fLast;          // the last element in the list
    int fCount;           // number of elements in the list

public:
    // auxiliary definition to simplify iterator usage
    typedef DoublyLinkedListNodeIterator<T> Iterator;

    List();               // default constructor - creates empty list
    ~List();              // destructor - frees all nodes

    bool isEmpty() const; // Is list empty?
    int size() const;      // list size

    // adds a node initialized with aElement at front
    void push_front( const T& aElement );

    // adds a node initialized with aElement at back
    void push_back( const T& aElement );

    // removes node that matches aElement from list
    void remove( const T& aElement );

    const T& operator[]( unsigned int aIndex ) const; // list indexer

    // returns an iterator for the nodes of the list
    Iterator getIterator() const;
};
```

The template class `List` defines an "object adapter" for `DoublyLinkedListNode` objects (i.e., the list representation). Somebody else has already started with the implementation, but left the project unfinished. You find a header file for the incomplete `List` class on Blackboard. This header file contains the specification of the template class `List` and the implementations for

- the destructor `~List()`
- the method `bool isEmpty() const`
- the method `int size() const`
- the method `void push_front(const T& aElement)`

You need to implement the remaining member functions. To facilitate this process, apply the following five-step approach:

1. Implement the default constructor and the method `getIterator` first. You can use the following test code for verification (you need to include `<string>` for the program to compile). The default constructor has to create an empty list. The method `getIterator` just returns a value-based `DoublyLinkedListNodeIterator` object properly initialized with the top list node.

```
#include <string>

using namespace std;

List<string> lList;

string s1( "AAAA" );
string s2( "BBBB" );
string s3( "CCCC" );
string s4( "DDDD" );

lList.push_front( s4 );
lList.push_front( s3 );
lList.push_front( s2 );
lList.push_front( s1 );

// iterate from the top
cout << "Top to bottom: " << lList.size() << " elements" << endl;
for ( List<string>::Iterator iter = lList.getIterator();
      iter != iter.rightEnd(); iter++ )
{
    cout << "A list element: " << *iter << endl;
}
```

The result should look like this:

```
Top to bottom: 4 elements
A list element: AAAA
A list element: BBBB
A list element: CCCC
A list element: DDDD
```

2. Implement the method `push_back`, which is just a variant of method `push_front`.

```
string s5( "EEEE" );
string s6( "FFFF" );

lList.push_back( s5 );
```

```

lList.push_back( s6 );

// iterate from the top
cout << "Bottom to top: " << lList.size() << " elements" << endl;
for ( List<string>::Iterator iter = lList.getIterator().last();
      iter != iter.leftEnd(); iter-- )
{
    cout << "A list element: " << *iter << endl;
}

```

The result should look like this:

```

Bottom to top: 6 elements
A list element: FFFF
A list element: EEEE
A list element: DDDD
A list element: CCCC
A list element: BBBB
A list element: AAAA

```

3. Implement the method `remove`. This method has to search for the node that matches `aElement`. If no such node exists, then the list remains unchanged. Otherwise, the corresponding node needs to be taken out of the list and its memory released. Please note that the identified node may coincide with the first or the last node in the list. These boundary conditions need to be address properly. Also, you need to use the cast operator `(Node*)` in this method to convert between `const Node*` and `Node*`. Remember that type `Node` is defined as `typedef DoublyLinkedListNode<T> Node`.

```

lList.remove( s3 );
lList.remove( s1 );
lList.remove( s6 );

// iterate from the top
cout << "Top to bottom: " << lList.size() << " elements" << endl;
for ( List<string>::Iterator iter = lList.getIterator();
      iter != iter.rightEnd(); iter++ )
{
    cout << "A list element: " << *iter << endl;
}

```

The result should look like this:

```

Top to bottom: 3 elements
A list element: BBBB
A list element: DDDD
A list element: EEEE

```

4. Implement `operator[]`. The indexer has to search for the element that corresponds to `aIndex`. Also, `aIndex` may be out of bounds. Hence the indexer has to throw a `range_error` exception. The implementation requires the cast operator `(Node*)` to convert between `const Node*` and `Node*`.

```

cout << "Element at index 2: " << lList[2] << endl;

```

The result should look like this:

```

Element at index 2: EEEE

```

Submission deadline: Tuesday, May 6, 2014, 10:30 a.m.

Submission procedure: on paper, code of class `ListPS6.h`.